Admin lists in the order module

Report of the work done on branch feat/gateway-api, 10 October 2026

Status	Done, verified, committed with this report, merged into `announce-jo-branch` and pushed.
Scope	The list endpoints the admin SPA's trade screens call and the order module lacked: auctions (list and detail with every bid), orders (list), payouts (totals plus lines), and the payment and shipment of an order for staff.
Tests	182 tests pass across db-reactive, cqrs-reactive, its test kit and order; order's end-to-end suite now lists what its scenarios produced.

1. The gap

The admin SPA's auctions, orders and payouts screens run on mocks. They call `GET /api/admin/auctions` (with a detail per auction), `GET /api/admin/orders` (with payment and shipment per order) and `GET /api/admin/payouts` (totals plus lines). The order module had only the single-order read and the staff actions. Two findings shaped the work:

- **The mock types are a sketch, not the backend.** They use cents and names like `announceTitle` and `increment`; the read models hold decimal amounts, `title` and `bid_increment`. The member endpoints already return the read-model rows as they are.
- **Payouts are not a table.** The order row carries the money held for the seller, the fee, the dispute state and every timestamp, and the order context keeps its own copy of the seller's payout readiness. A payout view can be derived from those without crossing contexts.

2. What was built

Endpoints, each context serving its own rows

Endpoint	Context	Filters	Answer
`GET /api/admin/auctions`	auction	status, seller, q	page of auction rows
`GET /api/admin/auctions/{announceId}`	auction		the auction with every bid, cancelled and retracted included
`GET /api/admin/orders`	order	status, seller, buyer, q	page of order rows
`GET /api/admin/orders/{id}/payment`	payment		the payment row
`GET /api/admin/orders/{id}/shipment`	shipping		the shipment row
`GET /api/admin/payouts`	order	status (payout), seller	totals plus a page of payout lines

Pages use the admin envelope `{items, page, size, total}` with a 1-based page and a size capped at 100, newest first. Staff identity as before; a member gets 403. The admin edge already routed all four path families, so it did not change.

The payout derivation

A pure function in the order context turns an order row plus the seller gate into a payout line:

Payout status	Order statuses	Release due
`PENDING_RELEASE`	PAID, SHIPPED, DELIVERED	delivered plus the delivery grace; shipped plus the dispatch grace, or plus the delivery grace when releasing on dispatch; none while only paid
`BLOCKED_DISPUTE`	DISPUTED	none

Payout status	Order statuses	Release due
`RELEASING`	RELEASING	none
`SENT`	SETTLED	none
`REFUNDED`	REFUNDING, REFUNDED	none

The totals cover every live order, not the page: pending, blocked, releasing, sent and refunded amounts with their counts, fees collected on settled deals and fees still pending. They come from one hand-written aggregate query added to the order mapper in `db-reactive`, following the pattern messaging used for its own queries.

Per module

Module	Change
db-reactive	Hand-written `sumByStatus` on the order mapper and its result class; a live-database test that inserts, sums and removes its own rows.
order	`Payouts` (derivation and totals, unit-tested), listing filters on the auction and order services, the six endpoints above, and an end-to-end test that lists what the existing scenarios produced.
Docs	`doc/order-context.md` section 8 and a row in section 11; `doc/frontend-edges.md` section 12 with the field differences the SPA wiring will have to bridge.

3. Verification

One Maven run over db-reactive, cqrs-reactive, cqrs-reactive-test and order:

Module	Tests	Result
db-reactive	71	pass (live MySQL, including the new aggregate test)
cqrs-reactive	59	pass
cqrs-reactive-test	15	pass
order	37	pass
Total	182	no failures

What the new tests prove:

- **Derivation.** Every order status that holds money maps to one payout status and the others to none; the release due date follows the configured windows in both release modes; the totals bucket the sums and ignore statuses that hold no money.
- **Aggregate query.** Fees and payouts are summed per status over live rows only; deleted rows are ignored.
- **End to end.** After the auction, fixed-price, offer and refund scenarios, staff list the closed auction with its two bids, both settled orders, the sent and refunded payouts with a verified seller gate and positive totals, the paid-out payment and delivered shipment of one order; the filters narrow correctly, the paging guard clamps page 0 and size 1000, an unknown payout status is 400, and a member gets 403 on all of it.

4. Left for later

- **Wiring the admin screens.** The SPA's mock types differ from the rows: decimals instead of cents, `title` instead of `announceTitle`, `bidIncrement`, `autoExtendSec`, `CLOSED_SNAGGED`, no timeline, and the payouts answer with the totals defined above. Section 12 of the edge design lists them.
- **No live manual run.** The automated end-to-end suite runs the real module on containers and exercises every new endpoint; no manual pass through the admin edge was made.
- **Roles inside the backends** are still not checked; the edge enforces them.

5. State of the branch

One commit on `feat/gateway-api` on top of `82f3668f`, carrying the change and this report; `announce-jo-branch` fast-forwarded to it and pushed to origin on 2026-10-10.