
Supplementary material for: Multiresolution dictionary learning for conditional distributions

Anonymous Author(s)

Affiliation

Address

email

1 Predictions

Consider the case we want to predict the response y^* for a future observation based on predictors x^* and previous observations $(x^{(n)}, y^{(n)})$ with $x^{(n)} = (x_1, \dots, x_n)$ and $y^{(n)} = (y_1, \dots, y_n)$. Because the partitioning strategy that we adopted lacks an elegant out-of-sample embedding function (unlike other partitioning strategies), we adopt a Voronoi expansion procedure by which the new predictors x^* are allocated to $C_{j,k}$'s having the closest centers with respect to ρ_W . Summaries of the predictive density of y^* will be computed as follows:

(i) allocate predictors x^* to $C_{j,k}$'s having the closest centers with respect to ρ_W

(ii) run the Gibbs sampler for S iterations, and at the s th iteration:

a) sample parameters $\{\sigma_{j,k_j}^{(s)}, \mu_{j,k_j}^{(s)}, \pi_{j,k_j}^{(s)}\}_{j \in \mathbb{Z}, k_j \in \mathcal{K}_j}$ from its posterior, i.e. $p(\cdot | x^{(n)}, y^{(n)})$

b) sample \hat{y}_s^* from the following mixture

$$\sum_{j \in \mathbb{Z}} \pi_{j,k_j(x^*)}^{(s)} \mathcal{N}(\mu_{j,k_j(x^*)}^{(s)}, \sigma_{j,k_j(x^*)}^{(s)})$$

(iii) given sequence $\{\hat{y}_s^*\}_{s=1}^S$, summaries of the predictive density such as mean, variance and quantiles can be computed.

2 Partition Tree Schematic

3 Synthetic examples

3.1 Competitor Algorithms

As we are unaware of other methods, even frequentist, that estimate posteriors with such high-dimensional predictors, we compare point estimates of our approach with other moderately regression algorithms. In particular, we elected to compare against lasso, classification and regression trees (CART), Random Forest (RF) and principal component (PC) regression. In particular, the lasso regularization parameter and the number of principal components for PC regression were chosen based on the Akaike information criterion (AIC). For all algorithms, standard Matlab packages were utilized.

3.2 Additional results

Tables 1, and show mean squared errors and CPU usage under MSB, CART and lasso based on leave-one-out prediction. In particular, table 1 shows results concerning the linear subspace in section 4.4 for different number of factors, i.e. $d = 5$ and $d = 10$. Table 2 shows results concerning the




Figure 1: (i) Multiscale partition of the data. (ii) Path through the tree for $x_i \in \mathbb{R}^p$. (iii) Conditional density of y_i given x_i defined as a convex combination of densities along the path.

Table 1: Linear manifold example 1: Mean and standard deviations of squared errors under multi-scale stick-breaking (MSB), CART and Lasso for sample size 50 and 100 for different simulation scenarios.

p	n		$d = 5$			$d = 10$		
			MSB	CART	LASSO	MSB	CART	LASSO
50k	50	MSE	0.18	0.31	0.25	0.22	0.58	0.22
		STD	0.32	0.30	0.42	0.24	0.54	0.30
		TIME	3	2	1	3	3	1
50k	100	MSE	0.18	0.27	0.26	0.20	0.41	0.52
		STD	0.26	0.42	0.46	0.23	0.46	0.78
		TIME	5	5	2	5	5	1
100k	50	MSE	0.35	0.45	0.89	0.16	0.33	0.20
		STD	0.53	0.77	1.04	0.21	0.46	0.31
		TIME	3	25	2	3	27	2
100k	100	MSE	0.43	0.88	0.52	0.17	0.50	0.31
		STD	0.59	1.29	0.70	0.24	0.75	0.49
		TIME	7	50	5	7	51	5
500k	50	MSE	0.11	0.16	0.15	0.83	2.26	0.92
		STD	0.15	0.24	0.19	1.01	2.60	3.69
		TIME	5	90	11	5	121	10
500k	100	MSE	0.003	0.17	0.08	0.13	1.37	1.06
		STD	0.16	0.23	0.13	1.12	1.81	1.50
		TIME	10	214	43	8	227	42
700k	50	MSE	1.70	1.48	1.47	0.66	1.65	1.07
		STD	2.18	2.47	1.63	0.87	1.49	0.95
		TIME	6	121	12	7	151	13
700k	100	MSE	0.69	1.36	0.82	0.78	1.52	1.43
		STD	0.94	1.47	1.28	1.03	1.34	2.11
		TIME	13	321	41	12	325	44

union of linear subspace in section 4.4. for different number of mixture components, i.e. $G = 5$ and $G = 10$. As shown, in almost all data scenario, our model is able to perform as well as or better than the model associated to the lowest mean squared error and can scale substantially better than others to high dimensional predictors.

Table 2: Non-linear manifold - MFA: Mean and standard deviations of squared errors under multiscale stick-breaking (MSB), CART and Lasso for different sample sizes for different simulations sampled from a mixture of factor analyzers

p	n	SIM	MSB	$G = 10$		$G = 5$		LASSO
				CART	LASSO	MSB	CART	
50k	100	MSE	0.23	0.42	0.36	0.17	0.43	0.22
		STD	0.34	0.59	0.43	0.18	0.69	0.23
		TIME	5	24	3	7	27	3
50k	200	MSE	0.23	0.42	0.27	0.17	0.22	0.20
		STD	0.33	0.56	0.23	0.19	0.38	0.25
		TIME	10	51	8	12	56	7
100k	100	MSE	0.67	1.35	1.32	0.15	0.17	0.22
		STD	1.04	2.26	1.36	0.23	0.19	0.23
		TIME	9	47	6	6	44	5
100k	200	MSE	0.64	1.37	0.85	0.15	0.26	0.15
		STD	0.95	1.77	1.29	0.24	0.42	0.24
		TIME	15	99	15	11	89	15
300k	100	MSE	0.26	0.39	0.31	0.63	1.40	1.01
		STD	0.39	0.51	0.52	0.80	1.24	1.46
		TIME	9.28	125	18	9	145	17
300k	200	MSE	0.25	0.47	0.26	0.63	1.17	0.92
		STD	0.36	0.88	0.43	0.80	2.11	1.04
		TIME	15	262	40	13	283	43
300k	300	MSE	0.25	0.30	0.30	0.62	1.42	0.70
		STD	0.36	0.41	0.48	0.89	1.85	0.94
		TIME	15	463	73	16	465	89

Table 3: Non-linear manifold - Swissroll: Mean and standard deviations of squared errors under multiscale stick-breaking (MSB), CART and Lasso for different sample sizes for different simulation scenarios.

p	n	SWISSROLL			
			MSB	CART	LASSO
10k	100	MSE	0.25	0.46	0.38
		STD	0.24	0.53	0.40
		TIME	5	5	1
100k	50	MSE	0.24	0.44	0.25
		STD	0.24	0.42	0.29
		TIME	3	22	2
100k	100	MSE	0.24	0.43	0.17
		STD	0.26	0.55	0.22
		TIME	6	48	7
200k	50	MSE	0.24	0.67	0.29
		STD	0.23	0.50	0.29
		TIME	4	38	5
200k	100	MSE	0.25	0.78	0.33
		STD	0.26	0.74	0.36
		TIME	6	96	13
500k	50	MSE	0.17	0.47	0.23
		STD	0.23	0.43	0.22
		TIME	5	126	10
500k	100	MSE	0.17	0.33	0.19
		STD	0.21	0.46	0.23
		TIME	11	230	25