

ECL: A Deterministic Cross-Runtime Execution IR with Replayable Semantics and Dependency Interface

Bin Zhang

2026-06-28

Abstract

Agent runtimes increasingly expose traces, tool calls, callbacks, and event streams, but these records are usually tied to a specific framework. This paper presents Execution Compact Layer (ECL), a deterministic execution intermediate representation for agent systems. ECL maps runtime traces into four replayable surfaces: **state**, **intent**, **action**, and **evidence**. The v0.1 system includes a frozen JSON schema, OpenAI Agents SDK and LangChain trace adapters, deterministic validation and replay, an embeddable SDK, a dependency-mode API, and an MCP-shaped local wrapper. Local evaluation shows stable replay hashes, cross-runtime fixture conversion, schema validation, and no drift across the locked v0.1 surfaces. ECL is not a framework, public standard, benchmark, or external adoption claim. It is a local, reproducible system artifact for representing agent execution semantics across runtime boundaries.

1. Introduction

Modern agent systems produce execution traces through framework-specific surfaces: model inputs, tool calls, callback events, run trees, spans, and evidence logs. These records are useful inside their host frameworks, but they are difficult to compare, replay, or cite across runtimes without rewriting the host runtime or assuming a common execution model.

ECL addresses this gap by defining a minimal deterministic representation for agent execution. The goal is not to replace agent frameworks. The goal is to provide a compact execution IR that can be generated from heterogeneous traces and replayed into stable local artifacts.

This paper makes four contributions:

1. A four-surface execution model: **state**, **intent**, **action**, and **evidence**.

2. A deterministic hash and replay contract for local execution records.
3. A cross-runtime mapping surface for OpenAI Agents SDK-style and LangChain-style traces.
4. A dependency interface and MCP-shaped local wrapper that expose ECL without modifying host runtimes.

2. Problem Statement

Agent execution records are fragmented across runtimes. A tool call in one framework may appear as a span, callback, run node, trace event, or tool invocation object in another. Existing traces can preserve rich local detail, but they do not necessarily provide a minimal cross-runtime representation with deterministic replay semantics.

The problem is:

Given a runtime trace `T` from framework `R`,
produce a deterministic execution representation `E`
such that `E` can be validated, replayed, hashed, and cited
without modifying `R` or asserting full-fidelity trace preservation.

The required properties are:

- Minimality: ECL keeps only the execution surfaces needed for state, intent, action, and evidence.
- Determinism: repeated conversion and replay over the same inputs produces identical hashes.
- Replayability: a valid ECL object can generate execution trace, replay result, and evidence bundle artifacts.
- Loss awareness: adapter mappings can record incomplete preservation instead of silently claiming full fidelity.
- Boundary preservation: ECL references host runtime data but does not redefine the host runtime.

3. Related Work

3.1 Runtime Tracing

OpenAI Agents SDK exposes tracing for agent workflows, and LangChain exposes tracing and callback-style observability for chains, tools, and model calls. These systems are runtime-specific trace surfaces. ECL differs by mapping traces into a minimal replayable IR rather than serving as the primary runtime trace system.

3.2 Tool and Protocol Surfaces

The Model Context Protocol (MCP) defines a protocol surface for tools and context exchange. ECL's MCP-shaped local wrapper is not a conformant MCP

implementation, JSON-RPC transport, host-client-server session model, stateful connection, capability negotiation mechanism, authorization layer, published MCP server, or registry integration. It is a local anchor surface that demonstrates how an execution representation can be exposed through tool-shaped functions. It is not a tool-authorization system and does not prove external side effects.

3.3 Observability and Trace Standards

OpenTelemetry defines trace data models for distributed systems. ECL is related in spirit because it treats execution as reviewable trace data, but ECL is narrower: it targets deterministic agent execution representation, replay artifacts, and evidence bundles.

3.4 Provenance and Lineage

Provenance and lineage systems such as W3C PROV and OpenLineage provide broader interchange models for provenance records and data lineage. ECL does not replace those systems. Its v0.1 contribution is limited to a compact representation of agent execution surfaces and deterministic replay artifacts.

Adjacent system	Primary role	ECL v0.1 boundary
OpenAI Agents SDK tracing	Runtime-specific agent workflow tracing	ECL consumes OpenAI-style traces but does not replace the tracing implementation.
LangChain / LangSmith tracing	Runtime observability and debugging	ECL consumes LangChain-style traces but is not a hosted observability system.
OpenTelemetry	Distributed trace telemetry	ECL does not define telemetry semantics or span conventions.
W3C PROV	General provenance interchange	ECL records local execution representation, not general provenance.
OpenLineage	Dataset and job lineage metadata	ECL records agent execution surfaces, not dataset lineage facets.

3.5 Intermediate Representations

Compiler and runtime ecosystems use intermediate representations such as LLVM IR and WebAssembly to separate source-level systems from execution

targets. ECL uses the same separation principle at a smaller scale: host runtimes emit or are mapped into a compact execution representation.

3.6 Canonicalization

ECL's deterministic hash model depends on sorted-key compact JSON serialization and SHA-256 hashing. This local serialization is used for tested hash stability and is not claimed as full RFC 8785/JCS compliance.

4. ECL Model

An ECL record is a tuple:

$E = (S, I, A, V)$

where:

- S is state: lifecycle, actor, persona, runtime, and correlation references.
- I is intent: operation, constraints, expected result, and evidence requirements.
- A is action: tool or operation step, execution mode, side-effect class, and parameters hash.
- V is evidence: result summary, trace references, event chain, policy decisions, and hashes.

The machine-readable binding is:

`schemas/ecl-execution-compact-layer.schema.json`

The local semantic source is:

`SPEC.md`

5. Formal Execution Contract

Let:

- T_r be a source trace from runtime r .
- M_r be a deterministic adapter for runtime r .
- E be an ECL object.
- L be a loss report.
- P be the schema and hash validator.
- R be the replay function.
- H be SHA-256 over deterministic sorted-key compact JSON.

The adapter contract is:

$M_r(T_r) \rightarrow (E, L)$

The validation contract is:

$P(E, \text{schema}) \rightarrow \text{valid} \mid \text{invalid}$

The replay contract is:

$R(E) \rightarrow (\text{execution_trace.json}, \text{evidence_bundle.json}, \text{replay_result.json})$

The determinism invariant is:

If T_r , M_r , schema , checkpoint_ref , and generated_at are unchanged,
then $H(E)$ and $H(R(E))$ remain unchanged.

The boundary invariant is:

ECL records execution representation semantics.

ECL does not prove that an external side effect occurred.

ECL does not make host runtime traces authoritative outside their source systems.

6. System Design

6.1 Schema Layer

The schema layer defines the ECL object model and validates required fields. It is implemented in:

`schemas/ecl-execution-compact-layer.schema.json`
`ecl/validator.py`

6.2 Adapter Layer

The adapter layer maps runtime traces into ECL:

`ecl/adapters/openai_agents.py`
`ecl/adapters/langchain.py`
`external/adoption/ecl_mapper.py`
`external/adoption/trace_loader.py`

The mapping rule is:

Runtime source	ECL surface
runtime metadata, actor, correlation	state
model input, reasoning, requested operation	intent
tool call or run step	action
trace events, outputs, result refs	evidence

6.3 Replay Layer

The replay layer validates an ECL record and emits deterministic artifacts:

`demo/replay_demo.py`
`external/adoption/replay_adapter.py`

6.4 SDK and Dependency Layer

The SDK exposes a minimal embedding surface:

```
sdk/ecl.py
sdk/ecl_dependency.py
```

The dependency API is:

```
import ecl_dependency as ecl

ecl_object = ecl.wrap(trace)
payload = ecl.emit(ecl_object)
result = ecl.verify(ecl_object)
```

6.5 MCP-Shaped Local Wrapper

The MCP-shaped local wrapper exposes the dependency API through tool-shaped functions:

```
mcp/ecl_tool_spec.json
mcp/ecl_server_stub.py
```

This is a local wrapper only. It is not a conformant MCP implementation, JSON-RPC transport, host-client-server session model, stateful connection, capability negotiation mechanism, authorization layer, registry plugin, published MCP server, and not an external adoption signal.

7. Architecture

flowchart LR

```
OA["OpenAI-style trace"] --> MAP["ECL mapping"]
LC["LangChain-style trace"] --> MAP
MAP --> ECL["ECL object: state / intent / action / evidence"]
ECL --> VAL["Validator"]
VAL --> REP["Deterministic replay"]
REP --> ART["execution_trace.json / evidence_bundle.json / replay_result.json"]
ECL --> SDK["SDK dependency API: wrap / emit / verify"]
SDK --> MCP["MCP-shaped local wrapper"]
```

8. Evaluation

8.1 Method

The evaluation is local and fixture-based. It does not use external APIs and does not claim third-party validation. The test suite checks:

- ECL schema validation.
- OpenAI-style fixture mapping.
- LangChain-style fixture mapping.

- Replay determinism.
- SDK API stability.
- Dependency API stability.
- MCP-shaped local wrapper safety.
- Citation reproducibility demo stability.
- No drift in locked core files.
- Synthetic cross-runtime trace-corpus conversion, loss reporting, and replay stability.
- Field-level mapping coverage over the synthetic trace corpus.

8.2 Current Local Results

The latest local validation run reported:

```
python3 -m unittest discover -s tests
Ran 78 tests
OK
```

The synthetic trace-corpus evaluation reported:

```
python3 experiments/evaluate_trace_corpus.py
case_count=12
by_runtime={"langchain": 6, "openai": 6}
valid_count=12
deterministic_count=12
loss_expectation_met_count=12
loss_detected_count=3
surface_coverage={"action": 12, "evidence": 12, "intent": 12, "state": 12}
surface_coverage_by_runtime={"langchain": {"action": 6, "evidence": 6, "intent": 6, "state": 6}, "openai": {"action": 6, "evidence": 6, "intent": 6, "state": 6}}
loss_type_counts={"semantic": 9, "structural": 3}
evaluation_hash=sha256:2434da21056811e7eacf1ffac6944d5420ddeb2aa783f74423326a2b54a33974
```

The corpus contains local synthetic stress cases for complete traces, missing fields, unknown fields, failure status, timestamp drift, nested runs, and implicit tool events. It is not production trace evidence, third-party validation, or a benchmark result.

The trace-corpus counters use case-level units. `case_count`, `valid_count`, `deterministic_count`, `loss_expectation_met_count`, and `loss_detected_count` count synthetic cases. `loss_type_counts` also partitions all 12 synthetic cases by the adapter-level loss type classification, so it is not a subset of the three cases where missing fields were detected.

The negative validation-matrix evaluation reported:

```
python3 experiments/evaluate_validation_matrix.py
baseline_valid=true
case_count=8
expected_invalid_count=8
```

```
invalid_detected_count=8
expectation_met_count=8
evaluation_hash=sha256:00fe0ee8952988f7460280b40554889a890c93f9d181a6c9d8ee8b0194b031c0
```

The validation matrix mutates a valid ECL record to test rejection behavior for missing required surfaces, wrong schema version, tampered canonical hash, source-hash mismatch, empty event chains, additional root properties, invalid action modes, and missing evidence hashes.

The field-level mapping coverage evaluation reported:

```
python3 experiments/evaluate_mapping_coverage.py
case_count=12
total_source_fields=81
direct_mapped_field_count=80
source_hash_only_field_count=1
loss_missing_field_count=4
evaluation_hash=sha256:8a8b820ecbdd1b4e88a2d8e07b05be2d479add0f0c6c3265292cc5a86763e43a
```

This mapping coverage evaluation records whether each top-level source trace field is projected into an ECL surface or retained only through the source trace hash. It is synthetic corpus evidence, not a benchmark or external adoption signal.

The mapping-coverage counters use field-level and label-level units. `total_source_fields`, `direct_mapped_field_count`, and `source_hash_only_field_count` count top-level source trace fields and form a retention accounting over the synthetic corpus. `loss_missing_field_count` counts missing-field labels emitted by the loss report; it is not mutually exclusive with source field retention because a missing expected field may be absent from the source trace and therefore not part of `total_source_fields`.

The citation reproducibility demo reported:

```
python3 examples/citation_repro_demo.py
all_valid=true
all_deterministic=true
result_hash=sha256:8684fa8963ff9ad55c36eed6b89eb15992d1b05566aa1c79ced754fac67e1cdd
```

The MCP-shaped local wrapper self-check reported valid deterministic execution with:

```
verification_hash=sha256:bdcf2ddb30a0e5975782f77fa86415226c46652bbd5490a667a2f2106dd65a5f
```

8.3 Locked Core Surfaces

The current local evaluation keeps these core surfaces unchanged:

```
schemas/ecl-execution-compact-layer.schema.json
sdk/ecl.py
sdk/ecl_dependency.py
```

```
mcp/ecl_tool_spec.json
mcp/ecl_server_stub.py
```

8.4 Interpretation

The results support a narrow claim: ECL v0.1 is locally reproducible over the included fixtures, synthetic trace corpus, and deterministic entrypoints. The results do not support claims of ecosystem adoption, production reliability, third-party validation, or benchmark superiority.

9. Discussion

ECL is most useful when execution records must be compared, replayed, or cited across runtime boundaries. The main design choice is to preserve a small execution surface rather than reproduce every runtime-specific field. This makes the representation compact but requires explicit loss reports when mappings are incomplete.

ECL also separates representation from execution. A host runtime executes. ECL records and replays the execution representation. This separation keeps the dependency interface non-invasive and avoids modifying host frameworks.

The MCP-shaped local wrapper is intentionally conservative. It demonstrates tool-shaped surface readability but does not claim MCP protocol conformance or adoption.

10. Limitations

- The evaluation uses local fixtures, not production traces.
- The system does not prove full-fidelity trace preservation.
- The current adapters target OpenAI-style and LangChain-style traces only.
- The MCP surface is a local stub, not a published MCP server.
- There is no external adoption signal in this version.
- There is no benchmark suite or leaderboard result.

11. Conclusion

ECL v0.1 demonstrates that agent execution traces can be mapped into a deterministic, replayable, hash-stable execution IR with a minimal dependency interface. The system is locally validated and citation-ready, but the paper-level claim remains deliberately narrow: ECL is a reproducible execution representation stack, not a framework, formal standard, production deployment, third-party validation result, or external adoption result.

References

- OpenAI Agents SDK tracing documentation: <https://openai.github.io/openai-agents-python/tracing/>
- LangChain tracing documentation: <https://docs.langchain.com/langsmith/tracing>
- Model Context Protocol specification: <https://modelcontextprotocol.io/specification/>
- OpenTelemetry trace specification: <https://opentelemetry.io/docs/specs/otel/trace/>
- W3C PROV Data Model: <https://www.w3.org/TR/prov-dm/>
- OpenLineage specification: <https://openlineage.io/docs/spec/>
- RFC 8785 JSON Canonicalization Scheme: <https://www.rfc-editor.org/rfc/rfc8785>
- LLVM Language Reference Manual: <https://llvm.org/docs/LangRef.html>
- WebAssembly Core Specification: <https://webassembly.github.io/spec/core/>