

Name: Bernadine Joy N. Algordo

1. Show all database inside your machine.

```
MariaDB [(none)]> SHOW DATABASES;
+-----+
| Database |
+-----+
| chinook  |
| db_faith |
| information_schema |
| mysql    |
| performance_schema |
| phpmyadmin |
| test     |
+-----+
7 rows in set (0.001 sec)
```

2. Create database with database name `db\_faith`

```
MariaDB [(none)]> CREATE DATABASE db_faith;
Query OK, 1 row affected (0.001 sec)
```

3. Use database `db\_faith`;

```
MariaDB [(none)]> USE db_faith;
Database changed
```

4. Create table with table name `tbl\_students`, following fields:

Field Name	Data Type	Length	Extra
id	INT		PRIMARY KEY, AUTO_INCREMENT
lastname	VARCHAR	100	
firstname	VARCHAR	100	
department	VARCHAR	10	
course	VARCHAR	10	
year	INT	2	
status	VARCHAR	10	

```
MariaDB [db_faith]> CREATE TABLE tbl_students (
-> id INT AUTO_INCREMENT PRIMARY KEY,
-> lastname VARCHAR(100),
-> firstname VARCHAR(100),
-> department VARCHAR(10),
-> course VARCHAR(10),
-> year INT(2),
-> status VARCHAR(10)
-> );
ERROR 1050 (42S01): Table 'tbl_students' already exists
```

5. INSERT the following record inside tbl_students in following order:
 - a. Cruz/Jerwin/CCIT/BSIT/2/ACTIVE
 - b. Garcia/John/CCIT/BSCS/2/ACTIVE

c. Mercado/Daniel/CBA/BSA/3/REMOVED

```
MariaDB [db_faith]> INSERT INTO tbl_students (lastname, firstname, department, course, year, status) VALUES
-> ('Cruz', 'Jerwin', 'CCIT', 'BSIT', 2, 'ACTIVE'),
-> ('Garcia', 'John', 'CCIT', 'BSIT', 2, 'ACTIVE'),
-> ('Mercado', 'Daniel', 'CBA', 'BSA', 3, 'REMOVED');
Query OK, 3 rows affected (0.040 sec)
Records: 3 Duplicates: 0 Warnings: 0
```

6. Display all record of 3rd year students.

```
MariaDB [db_faith]> SELECT * FROM tbl_students WHERE year = 3;
+----+-----+-----+-----+-----+-----+-----+
| id | lastname | firstname | department | course | year | status |
+----+-----+-----+-----+-----+-----+-----+
| 3 | Mercado | Daniel | CBA | BSA | 3 | REMOVED |
+----+-----+-----+-----+-----+-----+-----+
1 row in set (0.001 sec)
```

7. Display all record of student/s if the status is equal to 'REMOVED'.

```
MariaDB [db_faith]> SELECT *
-> FROM tbl_students
-> WHERE status = "REMOVED";
+----+-----+-----+-----+-----+-----+-----+
| id | lastname | firstname | department | course | year | status |
+----+-----+-----+-----+-----+-----+-----+
| 3 | Mercado | Daniel | CBA | BSA | 3 | REMOVED |
+----+-----+-----+-----+-----+-----+-----+
1 row in set (0.001 sec)
```

8. Display the firstname of all students under CCIT department.

```
MariaDB [db_faith]> SELECT firstname
-> FROM tbl_students
-> WHERE department = "CCIT";
+-----+
| firstname |
+-----+
| Jerwin |
| John |
+-----+
2 rows in set (0.001 sec)
```

9. Update the lastname to Miranda if the id = 3.

```
MariaDB [db_faith]> UPDATE tbl_students
-> SET lastname = "Mirannda"
-> WHERE id = 3;
Query OK, 1 row affected (0.040 sec)
Rows matched: 1 Changed: 1 Warnings: 0
```

10. Delete Jerwin Cruz data.

```
MariaDB [db_faith]> DELETE FROM tbl_students
-> WHERE id = 1;
Query OK, 1 row affected (0.012 sec)
```