

CS 180 Discussion 1A/1E


Week 2

Haoxin Zheng

10/13/2023

Scheduling

- Class 1,2,...n, each class has starting time $s(i)$ and finishing time $f(i)$.
- Goal: Schedule maximum # of classes that are compatible (no overlap)
- Starting time?
- Finishing time?
- Length of the class?



Scheduling

- Algorithm:
 - Sort classes by finishing time $t_1, t_2 \dots t_n$, s.t. $t_1 \leq t_2 \dots \leq t_n$
 - $A = \emptyset$
 - For $i = 1, 2, \dots n$:
 - If t_i is compatible to the current solution A:
 - $A = A + \{t_i\}$
- Time complexity: $O(n \log n)$
 - Just remember this for sorting right now, will introduce in later lectures.

Scheduling

- Logic – Show the solution from greedy algorithm is optimal
 - Let $\{i_1, i_2, \dots, i_k\}$ be the solution of the greedy algorithm. There can be 3 situations:
 - \exists another compatible set $\{j_1, j_2, \dots, j_b\}$ ($b < k$) \rightarrow Doesn't matter, not optimal since $b < k$.
 - \exists another compatible set $\{j_1, j_2, \dots, j_k\}$. \rightarrow Same number, greedy algorithm gives a tie, still OK.
 - \exists another compatible set $\{j_1, j_2, \dots, j_c\}$. ($c > k$) \rightarrow this is better. **Disprove this by contradiction**
 - We **claim** if $\{j_1, j_2, \dots, j_k\}$ is another compatible set, then $f(i_r) \leq f(j_r), \forall r = 1, 2, \dots, k$
 - Then we can know that, if there exists a compatible $\{j_1, j_2, \dots, j_k\}$, the solution generated from the greedy algorithm ($\{i_1, i_2, \dots, i_k\}$) will also be compatible.
 - Since $f(i_r) \leq f(j_r)$, if \exists another compatible set $\{j_1, j_2, \dots, j_c\}$ ($c > k$), then $\{j_{k+1}, \dots, j_c\}$ can also be appended to the end of $\{i_1, i_2, \dots, i_k\} \rightarrow \{i_1, i_2, \dots, i_k, j_{k+1}, \dots, j_c\}$, length c .
 - However, if we use the greedy algorithm, we cannot forget to include $\{j_{k+1}, \dots, j_c\}$ behind i_k , since they are compatible with $\{i_1, i_2, \dots, i_k\}$. **Contradiction – Disproved.**
 - Next step: prove the **claim**

Scheduling


- We **claim** if $\{j_1, j_2, \dots, j_k\}$ is another compatible set, then $f(i_r) \leq f(j_r), \forall r = 1, 2, \dots, k$
- Proof: by induction
 - Base case: $m=1, f(i_1) \leq f(j_1)$. This is true since the GD algorithm always picks the class with earliest ending time
 - Induction Hypothesis: $f(i_r) \leq f(j_r), \forall r \leq m$
 - Induction step: we want to show $f(i_{m+1}) \leq f(j_{m+1})$
 - $f(i_m) \leq f(j_m) \Rightarrow f(i_m) \leq s(j_{m+1})$
 - \Rightarrow class j_{m+1} is compatible with $\{i_1, i_2, \dots, i_m\}$
 - \Rightarrow GD will always pick i_{m+1} such that $\rightarrow f(i_{m+1}) \leq f(j_{m+1})$
 - Proved.

Stack & Queue

- Stack: Last in First out
- Queue: First in First out
- Priority Queue: Every item pushed is associated with a priority



Stack:

Last in, first out



Queue:

First in, first out




$\text{push}(5, A)$, $\text{push}(8, B)$, $\text{push}(6, C)$
↑ ↑
priority item
 $\text{pop}() \rightarrow (8, B)$, $\text{pop}() \rightarrow (6, C)$, $\text{pop}() \rightarrow (5, A)$

Build a priority Queue - Heap




- Push(a): $O(\log n)$
- Pop(): $O(\log n)$
- Heap sort: $O(n \log n)$
- Heap is a “complete binary tree”. Similar functionalities as a priority queue.
- **Complete binary tree:** Every level, except possibly the last, is completely filled, and all nodes are as far left as possible.

store n elements in a “complete binary tree”




Heap

- Complete binary tree




Heap

- Pop – Method 1:
 - 1) Fill the empty position with one of its children nodes until the bottom of the tree. (Swap with its smaller child in a min-heap, or its larger child in a max-heap.)
 - 2) If it is not a complete tree, fulfill the empty position with the rightmost node.
 - 3) Compare this new node with its new parent node.
 - Min-heap: Swap the new node with its new parent node if the new node is smaller.
 - Max-heap: Swap the new node with its new parent node if the new node is larger.





Heap

- Pop – Method 2:
 - 1) Replace the root of the heap with the last element on the last level
 - 2) Compare the new root with its children; if they are in the correct order, stop.
 - 3) If not, swap the element with one of its children and return to the previous step.
(Swap with its smaller child in a min-heap and its larger child in a max-heap.)
- Example:




Heap – Exercise (Pop)

- Pop:
 - 1) Replace the root of the heap with the last element on the last level
 - 2) Compare the new root with its children; if they are in the correct order, stop.
 - 3) If not, swap the element with one of its children and return to the previous step.
(Swap with its smaller child in a min-heap and its larger child in a max-heap.)
- Q1: Min Heap Pop
- Q2: Max Heap Pop




Heap – Exercise (Pop) – Method 1

- Q1: Min Heap Pop




- Q2: Max Heap Pop




Heap – Exercise (Pop) – Method 2

- Q1: Min Heap Pop



- Q2: Max Heap Pop



Heap

- Push:
 - 1) Add the element to the bottom level of the heap at the leftmost open space
 - 2) Compare the added element with its parent; if they are in the correct order, or become the root node, stop.
 - 3) If not, swap the element with its parent and return to the step 2).

- Example:




Heap – Exercise (Push)

- Push:
 - 1) Add the element to the bottom level of the heap at the leftmost open space
 - 2) Compare the added element with its parent; if they are in the correct order, or become the root node, stop.
 - 3) If not, swap the element with its parent and return to the step 2).
- Q1: [6, 3, 5, 4, 2, 3, 7] – Max Heap?
- Q2: [6, 3, 5, 4, 2, 3, 7] – Min Heap?


Heap – Exercise (Push)

- Q1: [6, 3, 5, 4, 2, 3, 7] – Max Heap?



Heap – Exercise (Push)

- Q1: [6, 3, 5, 4, 2, 3, 7] – Min Heap?




Graph

- Definitions:
 - $G = (V, E)$. V :nodes(vertices), E :edges
 - $n = |V|$, number of nodes
 - $m = |E|$, number of edges

Graph

- Definitions:
 - *Undirected Graph*:
 - $\text{degree}(u)$: number of edges associated with node u



$$V = \{1, 2, 3, 4\}$$

$$E = \{[1, 2], [1, 4], (2, 3), (3, 4)\}$$


$$\begin{matrix} 1 \\ 2 \\ 3 \\ 4 \end{matrix} \begin{bmatrix} 0 & 1 & 0 & 1 \\ 1 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 \\ 1 & 0 & 1 & 0 \end{bmatrix}$$

Graph

- Definitions:

- *Directed Graph:*

- $\text{indegree}(u)$: number of edges pointing to node u
 - $\text{Outdegree}(u)$: number of edges node u pointing to



$$V = \{1, 2, 3, 4\}$$

$$E = \{(1, 2), (1, 4), (2, 3), (4, 3)\}$$

$$\text{indegree}(u) = \# \text{ edges pointing to } u$$

$$\text{indegree}(1) = 0$$

$$\text{indegree}(3) = 2$$

$$\text{outdegree}(1) = 2$$


$$\text{outdegree}(3) = 0$$

$$\text{outdegree}(u) = \# \text{ edges pointing from } u$$

Graph


- Definitions:

- Path*: A path is a sequence of nodes connected by edges
- Connect*: Node u and v are connected $\Leftrightarrow \exists$ a path between u and v
- Connected Graph*: All nodes are connected with each other
- Cycle*: A sequence of nodes $v_1, v_2 \dots v_k$ ($k > 2$), $v_1 = v_k$. No repeat edges, not repeat nodes except v_1 & v_k



Graph

- Definitions:
 - *Tree*: an undirected graph that
 - 1) Connected
 - 2) Don't have any cycles



- *Root a Tree*: Define a node as root.

In rooted, tree :



2 is the parent of 3.

3 is the child of 2.

2 is an ancestor of 5.

5 is a descendant of 2.

- A tree has only one path (distinct edges and distinct nodes) between any two nodes

Data Structure used to store graph

- 1) Adjacency matrix
 - $A[u, v] = 1$ if and only if $(u, v) \in E$


$A =$

	1	2	3	4
1	0	1	0	1
2	0	0	1	0
3	0	0	0	0
4	0	0	1	0

- **Pros:** checking whether $(u, v) \in E$ in $O(1)$ time
- **Cons:** $O(n^2)$ Space complexity
- **Cons:** Slow to list all neighbors of a given node u since you need to traverse all v to check if $(u, v) \in E$

Data Structure used to store graph



- 2) Adjacency list



- **Cons:** checking whether $(u, v) \in E$ in $O(\text{degree}(u))$ time
- **Pros:** $O(|E| + |V|)$ Space complexity.
- **Pros:** $O(\text{degree}(u))$ to list all neighbors of a given node u

Breadth First Search

- s-t connectivity: Is node s and node t connected?




- Implement using Queue



White board

Breadth First Search

- s-t connectivity: whether s and t are connected?
- Breadth First Search (BFS)
 - $\text{visited}[v] = \text{False}, \forall v \in V$
 - $\text{queue} = [s]$
 - while queue is not empty:
 - $u = \text{queue.pop}()$
 - for all v such that $(u, v) \in E$
 - if $\text{visited}[v] == \text{False}$:
 - $\text{visited}[v] = \text{True}$
 - $\text{queue.push}(v)$
 - return visited




- Time complexity: $O(|E| + |V|)$

White board


Breadth First Search

- You may get different BFS Tree depends on the order of traversing

F first:



D first:




Breadth First Search

- The shortest path from starting node (E here) to node X, is the level index i of node X after BFS.



- Proof:

- 1. Prove the shortest path cannot be longer than index i
 - We want to show there is a path with length of i by connecting different nodes between L_k & L_{k+1} .
 - By BFS, we know there has to be an edge between current node and the node in the previous layer.
- 2. Prove the shortest path cannot be shorter than index i
 - By proof by contradiction. If there is such a path, there has to be a link between L_k & L_{k+a} ($a \geq 2$).
 - BFS algorithm doesn't allow such scenario happens. Assume there is an edge (A, B), and node A in L_k and node B in L_{k+a} ($a \geq 2$), then by BFS, B should be at L_{k+1} . Contradiction.



Depth First Search

- DFS(u):
 - visited[u] = True
 - for v s.t. (u, v) ∈ E:
 - If visited[v] = False:
 - DFS(v)



White board

Exercises

2. Give an algorithm to detect whether a given undirected graph contains a cycle. If the graph contains a cycle, then your algorithm should output one. (It should not output all cycles in the graph, just one of them.) The running time of your algorithm should be $O(m + n)$ for a graph with n nodes and m edges.

Exercises

2. Give an algorithm to detect whether a given undirected graph contains a cycle. If the graph contains a cycle, then your algorithm should output one. (It should not output all cycles in the graph, just one of them.) The running time of your algorithm should be $O(m + n)$ for a graph with n nodes and m edges.

- Using BFS. For every visited vertex v , if there is an adjacent u such that u is already visited and u is not a parent of v , then there exists a edge either within the same level of BFS tree, or between the level of BFS tree.
- From the root node, we have at least two paths that can approach v .
- This means there is a cycle in the graph.
- If we don't find such an adjacent for any vertex, we say that there is no cycle.

11. Container With Most Water

Medium

👍 12470

💬 802


♡ Add to List

🔗 Share

Given n non-negative integers a_1, a_2, \dots, a_n , where each represents a point at coordinate (i, a_i) . n vertical lines are drawn such that the two endpoints of the line i is at (i, a_i) and $(i, 0)$. Find two lines, which, together with the x-axis forms a container, such that the container contains the most water.

Notice that you may not slant the container.

Example 1:



Input: height = [1,8,6,2,5,4,8,3,7]

Output: 49

Explanation: The above vertical lines are represented by array [1,8,6,2,5,4,8,3,7]. In this case, the max area of water (blue section) the container can contain is 49.

Example 2:

Input: height = [1,1]

Output: 1

Example 3:

Input: height = [4,3,2,1,4]

Output: 16

Proof – by contradiction

- Suppose the returned result is not the optimal solution. Then there must exist an optimal solution, say a container with a_l and a_r such that it has a greater volume V than the one we got (S). $V > S$. The two pointers didn't point them at the same stage using our algorithm, or we will have the V in our record.
- Since our algorithm stops only if the two pointers meet. So, we must have visited only one of them. Let's say we have visited a_l but not a_r .
- When a pointer stops at a_l , two situations:
 - **Didn't move: The other pointer also points to a_l .**
In this case, iteration ends. But the other pointer must have visited a_r on its way from right end to a_l . Contradiction to the initial discussion.
 - **Moved: The other pointer arrives at a_r' , that is greater than a_l before it reaches a_r .**
In this case, we move a_l . Two situations about current volume $V_{current}$ between a_l & a_r' :
 - a_r is higher than a_l . $V_{current} = h(a_l) \times w(a_l, a_r') > h(a_l) \times w(a_l, a_r) = V$
 - a_r is lower than a_l . $V_{current} = h(a_l) \times w(a_l, a_r') > h(a_r) \times w(a_l, a_r) = V$which means that a_l and a_r is not the optimal solution – Contradiction to the original assumption

Exercises

200. Number of Islands

Medium



10562



276



Add to List



Share

Given an $m \times n$ 2D binary grid `grid` which represents a map of `'1'` s (land) and `'0'` s (water), return *the number of islands*.

An **island** is surrounded by water and is formed by connecting adjacent lands horizontally or vertically. You may assume all four edges of the grid are all surrounded by water.

Example 1:

```
Input: grid = [
  ["1","1","1","1","0"],
  ["1","1","0","1","0"],
  ["1","1","0","0","0"],
  ["0","0","0","0","0"]
]
```

Output: 1

Example 2:

```
Input: grid = [
  ["1","1","0","0","0"],
  ["1","1","0","0","0"],
  ["0","0","1","0","0"],
  ["0","0","0","1","1"]
]
```

Output: 3

Constraints:

- `m == grid.length`
- `n == grid[i].length`
- `1 <= m, n <= 300`
- `grid[i][j]` is `'0'` or `'1'`.

Exercises

```
1 class Solution:
2     def numIslands(self, grid: List[List[str]]) -> int:
3
4     def bfs(i, j, grid):
5
6         q = collections.deque()
7         q.append((i, j))
8         grid[i][j] = "#"
9
10        while q:
11            (curr_i, curr_j) = q.popleft()
12            directions = [(-1, 0), (1, 0), (0, -1), (0, 1)]
13            for direct in directions:
14                temp_i = curr_i + direct[0]
15                temp_j = curr_j + direct[1]
16
17                if temp_i >= 0 and temp_i < len(grid) and temp_j >= 0 and temp_j < len(grid[0]) and grid[temp_i][temp_j] == "1":
18                    q.append((temp_i, temp_j))
19                    grid[temp_i][temp_j] = "#"
20
21        if not grid: return 0
22        count = 0
23
24        for i in range(len(grid)):
25            for j in range(len(grid[0])):
26                if grid[i][j] == "1":
27                    bfs(i, j, grid)
28                    count += 1
29
30        return count
```

Example 2:

```
Input: grid = [
    ["1","1","0","0","0"],
    ["1","1","0","0","0"],
    ["0","0","1","0","0"],
    ["0","0","0","1","1"]
]
```

Output: 3