M. Joyce Meyer
192319032
Batch-8 (10/4/26)

(Placement)

Python Programming

Part-A

1. what is a function? why is it used?

Answers:- A function used in a program. we call it in code. If we use function in code. we can call function when Ever we want.

Example :-

set = ([ ]). set function

2. Difference b/w arguments and parameters?

Answer The Difference b/w arguments & parameters is the parameters are given in the above the code in variable. arguments are mentioned below.

Example :-

Student = (9, 6, 7, 8)

Student1 = ("Student:", (Student1)

3. what is return statement?

Answer:- The return statement is used in the End of the Code. to run and Execute the given parameters.

Example :-

```
print("Hello world")
    return.
```

4. what is a class and object?

Answer:- Class is a "Blue Print". it is used in the main part of the code.

Scanned with OKEN Scanner

and object is an "attribute". and also the Data type.

5. Define Inheritance?

Answer:- Inheritance is a types of mostly used as the "parant class" and the "child class" in Inheritance we are also having the types.

1. single Inheritance
2. Multi Inheritance
3. Multilevel Inheritance
4. hyierachi Inheritance
5. hybride Inheritance.

Example:-
"Parent class"
"child class"

Parent class is handled by the child class.

6. what is method overriding?

Answer:- In a code if Insert and any type of file the method overriding will Read that file multiple time. and giver the output.

Example:-
I/P:- ~~Stdinat~~ = ("/r. Data. txt:, read).
↓
O/P:- "Hellow Python"

what is a answers will gt 8

What is a list? give Example.

Answers :- list is that have data structure and it will store the multiple type of data in one variable. It is in the ordered, and it can be mutable and can change elements in between also.

Example :-

List = [9, 7, 28, 1, 11, 7]

types of list
1. ordered
2. mutable
3. Difference
4. Symmetric Difference
5. Dynamic size

8. Differente b/w append() and Extend()?

Answer :- 1) The append is used in to add and kind of number are word in the End of the variable and produce the output

Example :- append.(40).

if give like

List = [9, 7, 28, 1, 11, 7]

→ and given the append. program in Code the Number will be add in the output it will be added in End of list like

o/p :- [9, 7, 28, 1, 11, 7, 40]

2) The extend is used in to Replace the element in the Code. like numbers. and produce the output.

Example :- Extend.(10).

↳ if o/p : List [9, 4, 7, 2, 1]

It will Replace in any one of the element.

Scanned with OKEN Scanner

9. what is string slicing? give Example..

Answer: String is multiple element can be written in one case de parameter/are variable in " " Double courts.

→ String slicing is also a string, that can be "reversed".

Example

(String[::-1])

↓

This can be taken from the given variables.

Ex:- List = [1, 2, 3, 4 5]
-5 -4 -3 -2 -1

↳ it will be written in "Reverse".

10. Difference b/w upper() & lower()?

Answer:- In the given code if the i/p has given in the normal wording by using upper.() we can change the wordings in ~~no~~ upper case letters.

Example:- o/p = Student = ("Joyce meyer")

⇓

upper.()

o/p = JOYCE MEYER.

Scanned with OKEN Scanner

In the code. If the i/p is give in the Upper case letter. by using lower.() we can change it into the lower case letters.

Example:-

i/p list = ["JUNNU, CHINNI"]

⇓ lower.()

o/p "funny, chimi"

Part-B

1. write a function to find factorial of a number

Answer num = int (input("Enter the number:"))

```
i = 1
fact = i
while (i<n, n+1).
i = i*i
    print ("fact").
```

i/p = 2

o/p = 1
2

2. write program to reverse a string.

Answer:- ~~String = ("9,7,1,28'~~

~~strin = (int~~

```
i/p:- String = int (input ("Enter the Number").
      Reverse = string [::1]
        print ("string reverse:", string)
```

o/p :→ 97
= 79.

3. write a program to find the largest number in a list.

Answer:

```
a = int (input ("Enter the first number:")
b = int (input ("Enter the Second number:")
c = int (input ("Enter the third number:")

if a>b:
if a>c print ("largest number:", a)
Else:
    print ("largest number:", b)

if b>c:
if c>a:
    print ("largest numer:", b)
Else:
    print ("largest number:", c).
```

o/p :- a = 1
b = 2
c = 3

largest Number = 3.

4. Create a class with name & marks, display details.

Answer :-

```
class student
    def __inti__(self, ~~data~~ name, marks).
        self.name = name
        self.marks = marks.
```

Scanned with OKEN Scanner

dent 1 = ("Joyce Meyer": 90)

udent 2 = ("Thola Lokesh": 100).

S = student.

S1 = student 1

S2 = student 2

print(S)

S1.name()

S1.marks()

~~join~~()

S2.name()

S2.marks()

display().

5. write a function to find sum of Element in a list.

Answer:-

list1 = [1, 2, 3, 4, 5]

list2 = [1, 2, 3, 4, 5]

sum = list1 + list2

~~print ("sum", (list1 + list2)~~.

print ("sum").

Scanned with OKEN Scanner