

Cheat sheet — planting the factory into a brand-new monorepo

Plant the factory: step-by-step

- Phase 0 — Prereqs
- Phase 1 — Stamp the base factory
- Phase 2 — Apply the missing upstream patch
- Phase 3 — Vendor the Pocock bootstrap skillset
- Phase 4 — Vendor the `skill_engineering` roster's 8 source skills
- Phase 5 — Build the planner-specific trimmed variants
- Phase 6 — Copy the prompt amendments
- Phase 7 — Drop in the roster wiring
- Phase 8 — Validate before running anything real
- Phase 9 — Bootstrap vocabulary once, interactively
- Phase 10 — First real ticket, end to end
- Version history

Plant the factory: step-by-step

Grounded in the exact steps used to bring up `weather-report` 's extended Pocock+Trail of Bits roster. Every command below is real, not illustrative. See `docs/playbook-adopting-sssf.md` for the full rationale; this is the condensed, print-ready checklist.

Phase 0 — Prereqs

- `uv`, `sqlite3`, `git` (base factory)
- `opencode` CLI on PATH, logged into whichever gateway resolves your chosen model string (the `muse-spark-1.3-contributor-free` id used here is account-specific — substitute your own `opencode models` entry)
- `claude` CLI logged in (reviewer/scout/documenter run on `claude_code` in this roster, not `opencode`)
- API keys for whatever `sssf.config.yaml` actually names

Phase 1 — Stamp the base factory

```
cd /path/to/new-monorepo
git init && git commit --allow-empty -m init
mkdir -p .claude/skills
cp -r /path/to/super-simple-software-factory/.claude/skills/sssf .claude/skills/
uv run .claude/skills/sssf/scripts/install.py
cp .env.sample .env # set your API keys
just demo && just sessions && just obs
```

Green smoke test = config validated, session minted, envelope parsed, events landed in `sssf.db`.

Phase 2 — Apply the missing upstream patch

```
grep -n "OPENCODE_DISABLE" .claude/skills/ssf/templates/adws/adw_modules/
agent_opencode.py
```

Comes up empty — SSSF's shipped template lacks this fix. If any role runs `coding_agent: opencode`, add `_opencode_env()` to `adws/adw_modules/agent_opencode.py`, setting `OPENCODE_DISABLE_CLAUDE_CODE_SKILLS=1` and `OPENCODE_DISABLE_CLAUDE_CODE_PROMPT=1` on the subprocess env `run()` uses, in place of bare `operator_env()`. Without it, opencode auto-discovers skills from `~/.claude/skills/` and injects your global `CLAUDE.md` into every prompt — underneath whatever `skill_engineering:` actually says. Live-confirmed bug, not theoretical: see `weather-report/.scratch/ssf-ops/issues/01-opencode-config-leaks.md`.

Phase 3 — Vendor the Pocock bootstrap skillset

Run `/setup-matt-pocock-skills` inside Claude Code, pointed at the new repo. Vendors `wayfinder` / `grill-with-docs` / `to-spec` / `to-tickets` / `triage` / `domain-modeling` / `grilling` / `improve-codebase-architecture` — the **interactive bootstrap** skills, run by hand, never composed onto a headless role in this roster.

Confirm the label mapping matches the five canonical triage roles (`needs-triage` / `needs-info` / `ready-for-agent` / `ready-for-human` / `wontfix`) — `weather-report/docs/agents/issue-tracker.md` has a working example.

Phase 4 — Vendor the `skill_engineering` roster's 8 source skills

```
# Trail of Bits - clone read-only if you don't have it
git clone https://github.com/trailofbits/skills /tmp/trailofbits-skills
```

Straight Pocock vendors (single file, no flattening):

```
cd /path/to/new-monorepo
uv run /path/to/super-simple-software-factory/.claude/skills/ssf/scripts/
  vendor_skill.py \
  /path/to/super-simple-software-factory/downloads/skills/skills/engineering/
  codebase-design/SKILL.md \
  --dest-dir adws/adw_data/skill_engineering --as codebase-design
# repeat for: tdd, code-review, writing-for-agents, pr
```

ToB skills need hand-flattening first (compatibility check #7 — `compose()` ships one file, ToB splits across `references/*.md`):

```
mkdir -p .scratch/_tob-vendor-staging/flattened
# concatenate SKILL.md + only the reference files your stack needs
# (weather-report kept lang-rust.md, dropped the other 10 — use yours)
# add a CC-BY-SA-4.0 attribution header naming the exact upstream commit
uv run ../vendor_skill.py .scratch/_tob-vendor-staging/flattened/sharp-
  edges.md \
  --dest-dir adws/adw_data/skill_engineering --as sharp-edges
# repeat for: differential-review, property-based-testing
rm -rf .scratch/_tob-vendor-staging
```

Phase 5 — Build the planner-specific trimmed variants

Three files no other role needs — copy directly from `weather-report`, repo-specific trims, not upstream vendors:

```
cp /path/to/weather-report/adws/adw_data/skill_engineering/{codebase-design-
  planner,tdd-planner,sharp-edges-planner}.md \
  adws/adw_data/skill_engineering/
```

Non-Rust stack? Re-check `sharp-edges-planner.md` 's trim — swap `lang-rust.md` for your own language file and re-flatten.

Phase 6 — Copy the prompt amendments

```
cp /path/to/weather-report/adws/adw_data/prompt_engineering/planner/
  {system,user}.md \
  adws/adw_data/prompt_engineering/planner/
cp /path/to/weather-report/adws/adw_data/prompt_engineering/builder/system.md
  \
  adws/adw_data/prompt_engineering/builder/
cp /path/to/weather-report/adws/adw_data/prompt_engineering/reviewer/
  system.md \
  adws/adw_data/prompt_engineering/reviewer/
```

Carries: the already-implemented backstop, the single-phase rule, the seam-naming override, the sharp-edges Phase-4 rewrite, the style-opinions carve-out. Re-read once — some reference `weather-report` -specific conventions (`CONTEXT.md` , `docs/adr/`); verify against your own repo.

Phase 7 — Drop in the roster wiring

Copy `weather-report/adws/adw_sssf_config/sssf.config.yaml` 's `agents:` block wholesale. Adjust only:

- `model:` strings to your own `opencode models / claude` catalog
- `writes:` / `protected_files:` paths if your repo layout differs

Phase 8 — Validate before running anything real

```
just skills      # every skill_engineering file resolves; flags (unused) ones
just quality     # wire to your repo's real test/lint commands first (Rule
                Zero)
```

Phase 9 — Bootstrap vocabulary once, interactively

```
# /grill-with-docs (or /wayfinder), inside Claude Code
# writes CONTEXT.md / docs/adr/ -- planner's system.md expects these
```

Phase 10 — First real ticket, end to end

```
/to-spec          # or let grill-with-docs write it inline
/to-tickets
/triage           # flips Status: to ready-for-agent -- the one human gate
just watch --once # claims it, runs the full chain, resolves it
```

`just watch --once` is the one worth watching closely the first time — the real queue path, not the `just simple-sdlc "<text>"` CLI shortcut, and the one that proves bootstrap→AFK actually works end to end in the new repo.

Version history

Version	Date	Changes
1.0	2026-10-08	Initial cheat sheet, derived from the live <code>weather-report</code> setup (Pocock+ToB extended roster, re-armed planner, opencode harness patch).