

Pandas data with relatively simple commands.

The main idea of Seaborn is that it can create complicated plot types from

**Exploring Seaborn Plots** 

Let's take a look at a few of the datasets and plot types available in Seaborn. Note that all o the following *could* be done using raw matplotlib commands (this is, in fact, what Seaborn does under the hood) but the seaborn API is much more convenient.

# Histograms, KDE, and Densities

Often in statistical data visualization, all you want is to plot histograms and joint distributions of variables. Seaborn provides simple tools to make this happen:

```
data = np.random.multivariate_normal([0, 0], [[5, 2], [2, 2]], size=2000)
data = pd.DataFrame(data, columns=['x', 'y'])

for col in 'xy':
    plt.hist(data[col], normed=True, alpha=0.5)
```

Rather than a histogram, we can get a smooth estimate of the distribution using a kernel density estimation:

```
for col in 'xy':
    sns.kdeplot(data[col], shade=True)
```

Histograms and KDE can be combined using distplot:

```
sns.distplot(data['x']);
```

If we pass the full two-dimensional dataset to kdeplot, we will get a two-dimensional visualization of the data:

```
1 | sns.kdeplot(data);
```

We can see the joint distribution and the marginal distributions together using  ${\tt sns.jointplot}$ . For this plot, we'll set the style to a white background:

```
with sns.axes_style('white'):
sns.jointplot("x", "y", data, kind='kde');
```

There are other parameters which can be passed to <code>jointplot</code>: for example, we can use a hexagonally-based histogram instead:

```
with sns.axes_style('white'):
sns.jointplot("x", "y", data, kind='hex')
```

#### **Pairplots**

When you generalize joint plots to data sets of larger dimensions, you end up with *pair plots*. This is very useful for exploring correlations between multi-dimensional data, when you'd like to plot all pairs of values against each other.

We'll demo this with the well-known *iris* dataset, which lists measurements of petals and sepals of three iris species:

```
iris = sns.load_dataset("iris")
iris.head()
```



Doing Data Science

By Cathy O'Neil and Rachel Schutt



ЕВООК



### Doing Data Science

By Cathy O'Neil and Rachel Schutt



Visualizing the multi-dimensional relationships among the samples is as easy as calling sns.pairplot:

```
sns.pairplot(iris, hue='species', size=2.5);
```

# **Faceted Histograms**

Sometimes the best way to view data is via histograms of subsets.

Seaborn's FacetGrid makes this extremely simple. We'll take a look at some data which shows the amount that restaurant staff receive in tips based on various indicator data:

```
tips = sns.load_dataset('tips')
tips.head()
```

```
tips['tip_pct'] = 100 * tips['tip'] / tips['total_bill']

grid = sns.FacetGrid(tips, row="sex", col="time", margin_titles=True)
grid.map(plt.hist, "tip_pct", bins=np.linspace(0, 40, 15));
```

#### **Factor Plots**

Factor plots can be used to visualize this data as well. This allows you to view the distribution of a parameter within bins defined by any other parameter:

```
with sns.axes_style(style='ticks'):
    g = sns.factorplot("day", "total_bill", "sex", data=tips, kind="box")
    g.set_axis_labels("Day", "Total Bill");
```

# **Joint Distributions**

Similar to the pairplot we saw above, we can use sns.jointplot to show the joint distribution between different datasets, along with the associated marginal distributions:


```
with sns.axes_style('white'):
    sns.jointplot("total_bill", "tip", data=tips, kind='hex')
```

The joint plot can even do some automatic kernel density estimation and regression:

```
sns.jointplot("total_bill", "tip", data=tips, kind='reg');
```

#### **Bar Plots**

Time series can be plotted using sns.factorplot:



We can learn more by looking at the **method** of discovery of each of these planets:


For more information on plotting with Seaborn, see the <u>seaborn</u> documentation, the seaborn gallery, and the official seaborn tutorial.

Article image: Visualizing Data with Seaborn



#### Jake VanderPlas

Jake VanderPlas is a long-time user and developer of the Python scientific stack. He currently works as an interdisciplinary research director at the University of Washington, conducts his own astronomy research, and spends time advising and consulting with local scientists from a wide range of fields.



# Accelerating big data analytics workloads with Tachyon

By Shaoshan Liu

How Baidu combined Tachyon with Spark SOL to increase speed 30-fold



#### Questioning the Lambda Architecture

By Jay Kreps

The Lambda Architecture has its merits, but alternatives are worth exploring.



## Analyzing the world's news: Exploring the GDELT Project through Google BigQuery

By Kalev Leetaru and Felipe Hoffa

What it looks like to analyze, visualize, and even forecast human society using global news coverage.



### Architecting Hadoop Applications

By Mark Grover, Gwen Shapira, Jonathan Seidman and Ted Malaska

In this O'Reilly training video, the "Hadoop Application Architectures" authors present an end-to-end case study of a clickstream analytics engine to provide a concrete example of how to architect and implement a complete solution with Hadoop. In this segment, they provide an overview of the complete architecture. Presenters: Mark Grover, Gwen Shapira, Jonathan Seidman, Ted Malaska

