

# CSCI 112

## Programming with C

### LECTURE: 13

J. L. Pach

# OUTLINE:

- makefile

# OPERATOR

## Overloading in C: Compiler Context Resolution

# THANK

You

# TODAY'S AGENDA

- Compiler
- Makefile

# COMPILER

# THE COMPILATION PROCESS: A TWO-STAGE JOURNEY

Turning source code into a running program happens in two distinct steps:

**Stage 1**: Compilation (`.c` → `.o`)

- **What it does**: Translates your C source code into machine code (binary instructions for the CPU).
- **Command**: `gcc -g -Wall -std=c99 -pedantic -c input.c -o output.o`
- **Output**: An object file (main.o).
- **Key characteristic**: It contains machine code for your file, but it does not yet know where standard library functions (like printf or scanf) are located. References to them remain unresolved.

# THE COMPILATION PROCESS: A TWO-STAGE JOURNEY


**Stage 2**: Linking (.o → Executable)

- **What it does**: Combines your object file(s) with standard libraries and startup code.
- **Command**: `gcc -g output.o -o program.exe`
- **Output**: A final executable file (main.exe or binary).
- **Key characteristic**: The linker resolves all missing references, connects external library functions, and produces a complete, runnable program.

# COMPILER

1. A compiler takes the entire source code and translates it into a machine code file, often called **an executable**.
2. This executable file contains instructions that the computer's processor can directly execute.
3. Once compiled, the program can run independently without the need for the original source code or a compiler.

# EXTENDED DESCRPITION




1. This is the source code you have written in the C/C++ programming language. It forms the basis of your program.
2. During this stage, the preprocessor processes your source code. It includes header files (e.g., stdio.h, math.h) using directives like #include and expands macros defined with #define. The output of this stage is the preprocessed source code.
3. The compiler takes the preprocessed source code and translates it into assembly code. This assembly code is a low-level representation of your program that is specific to the target architecture.
4. The assembler converts the assembly code into object code. Object code is a machine-readable format that contains instructions and data.
5. The linker combines the object code with other necessary libraries (e.g., standard C library) to create the final executable program. This process resolves external references and creates a complete program that can be run.
6. The loader loads the executable program into memory (RAM) so that it can be executed by the CPU. The running program is often referred to as a process.

# PROCESS OF COMPILATION

- Compile main.c into an object file main.o:
- Link the object file main.o into an executable main.exe:

```
gcc -g -Wall -std=c99 -pedantic -c main.c -o main.o
```

```
# 1) Compile main.c into an object file main.o (no linking).
#    Includes debug symbols (-g), enables most warnings (-Wall), uses the C99 standard (-std=c99),
#    and enforces strict standard conformance (-pedantic).
```

```
gcc -g main.o -o main.exe
```

```
# 2) Link the object file into an executable named main.exe.
```

# PROCESS OF COMPILATION

- Compile and link in one step (from main.c directly to main.exe):

```
gcc -g -Wall -std=c99 -pedantic main.c -o main.exe
```

```
# 3) Compile and link in one step: from main.c directly to main.exe,
#    with the same diagnostic/standard flags as in step 1.
```

# ABOUT FLAGS

- The `-g` flag tells the compiler to include debugging information in the output. Without it, setting breakpoints in the compiled file would not be possible. This flag should be disabled in the final compilation of the application after the development process is complete.
- The flags `-Wall`, `-std`, and `-pedantic` are compiler-specific and only necessary during the creation of object files. The `-c` and `-o` flags indicate source and object files, respectively.
- Therefore, if the compilation process is split into two stages — compilation and linking — only the `-g` flag should be repeated during linking.

# MAKEFILE

# What is Make - ? (mingw32-make.exe / make.exe)

**Makefile** is an **automation tool** that manages the compilation and building process for software projects. It primarily serves two main purposes:

- **Dependency Tracking:** Make reads a file called the **Makefile**, which lists all the **dependencies** (input files, like code or headers) needed to create a specific **target** (output file, like a program or object file).
- **Smart Execution:** Make checks the **timestamps** of the target and its dependencies. If any input file is newer than the output file, Make knows the output is **out-of-date** and automatically runs the necessary commands to **rebuild only what has changed**.

## Key Takeaway

> **Make ensures that no unnecessary rebuilding is done, saving time and simplifying complex build steps.** It acts as a smart project manager that only works when work is actually needed.

`

# What Does a Make Rule Look Like

A **Makefile** is just a text file with rules. Each rule has **four key parts**:

1. **Target** – a symbolic name.
2. **Colon :** – separates the target from its dependencies.
3. **Prerequisites (Dependencies):**
   - another file (like utils.o)
   - another target (for example, clean, build, all)
   - mix of both

```
target … : prerequisites …
        recipe
        …
        …
```

4. **Recipe** – one or more shell commands (written exactly as if you typed them in the terminal).
   - Each command **must start with a tab**.
   - Commands run one by one. If one fails (non-zero exit code), make stops.

# SYNTAX OF MAKEFILE

```
target … : prerequisites …
        recipe
        …
        …
```

- Create a file `Makefile`
- And run in cmd: `mingw32-make` or `make`
- The first command **compiles** the source code into an **object file**,
- The second command **links** the object file to produce the final **.exe executable**

```
# The comment preceded by a hashmark
build:
        gcc -g -Wall -std=c99 -pedantic -c main.c -o main.o
        gcc -g main.o -o main.exe
```

# Next improvment 1/2

- Modify to:

```
build_exe:
	gcc -g main.o -o main.exe
build_obj:
	gcc -g -Wall -std=c99 -pedantic -c main.c -o main.o
```

- And run in cmd: `mingw32-make`

> Without any parameters, **make** will only execute the first target. Our first target is linking, so it will create the **.exe** file from the **.o** file. If we wanted to build the **.obj** (object file) alone, we would have to call that target as a program parameter: **'mingw32-make build_obj'**, followed by either **'mingw32-make'** or **'mingw32-make build_exe'**.

# Next improvment 2/2

- ⚒ Modify to:

```
#                <=== HERE
build_exe: build_obj
	gcc -g main.o -o main.exe
build_obj:
	gcc -g -Wall -std=c99 -pedantic -c main.c -o main.o
```

- ⚒ And run in cmd: `mingw32-make`

We can also modify the Makefile where **`build_obj` is a dependency of our `build_exe` target**. This means that **`build_obj` will be executed before `build_exe` runs**.

Consequently, we can then run **make** without any parameters, as it will find the dependencies and execute the entire compilation process.

# Example 2 – main.c other.h other.c

⚒ Modify and create files:

```c
// main.c
#include<stdio.h>
#include "other.h"

int main()
{
  extern_function();
  return 0;
}
```

```c
// other.c
#include <stdio.h>
#include "other.h"
void extern_function()
{
    printf("text from extern_function - other.c\n");
}
```

```c
// other.h
#ifndef _OTHER
#define _OTHER
void extern_function();
#endif  //_OTHER
```

# PROCESS OF COMPILATION

- Compiling:

```
gcc -g -Wall -std=c99 -pedantic -c other.c -o other.o
```

```
gcc -g -Wall -std=c99 -pedantic -c main.c -o main.o
```

- Linking:

```
gcc -g main.o other.o -o main.exe
```

# Headers and the Compilation Process – Key Rules 1/2

- **Including the same header more than once**
  - If the same `header.h` is included in multiple places, the compiler may get confused (errors like *redefinition*). To prevent this, we use *include guards*: `#ifndef` etc.
  - This ensures the header is included only once.
- **How to write `#include`**
  - In source files, we always use **just the filename**:
  - `#include "header.h"`
  - Do not write paths like `../include/header.h`.
  - The compiler, with its options*, decides where to look for headers. This keeps the code clean and independent from the folder structure.

> * If the headers are in a different folder than the source files, pass that folder to the compiler with the `-I` flag: `gcc -Iinc -c src/main.c -o main.o`

# Headers and the Compilation Process – Key Rules 2/2

- **Role of headers in the compilation process**
  - Header files (`.h`) are **not passed directly to the compiler**.
  - The compiler automatically pulls them in if they are included with `#include` in `.c` files.
  - That's why in a Makefile, **we don't compile header files** – instead, we list them as **dependencies**.
  - This way, if a header changes, the correct `.o` files will be rebuilt.

**The key distinction**

> Headers are dependencies in the Makefile, but not arguments for the compiler. That's something students often confuse, so it's worth stressing early.

# Summary

```
gcc -g -Wall -std=c99 -pedantic -c other.c -o other.o
gcc -g -Wall -std=c99 -pedantic -c main.c -o main.o
gcc -g main.o other.o -o main.exe
```

- From just three command-line calls, we can create a **Makefile** that automates the exact same functionality.
- However, at this stage, our Makefile is essentially no different from a simple **batch script** (or a `.bat` file). Every single time we invoke **make**, the entire compilation process is executed from start to finish, regardless of whether any files have actually changed.

```
# makefile
build_exe: build_obj
	gcc -g main.o other.o -o main.exe
build_obj:
	gcc -g -Wall -std=c99 -pedantic -c other.c -o other.o
	gcc -g -Wall -std=c99 -pedantic -c main.c -o main.o
```

# PHONY targets

```
# phony target!
.PHONY: build_exe build_obj
build_exe: build_obj
	gcc -g main.o other.o -o main.exe
build_obj:
	gcc -g -Wall -std=c99 -pedantic -c other.c -o other.o
	gcc -g -Wall -std=c99 -pedantic -c main.c -o main.o
```

- This happens because both of our current targets are essentially **artificial targets** (or `PHONY targets`). Their dependencies don't rely on the existence of any files; they simply establish that one target requires the execution of the other. The line defining this:

```
.PHONY: target1 target2...
```

- should be placed before the first occurrence of the first target. By doing this, **make** will not attempt to search for files with the same name as the target.

# THE NATURE OF MAKE TARGETS

Targets in a Makefile can fall into several categories:

- **Abstract, Symbolic Names:** A target that is purely an artificial name (like clean) and does not correspond to an actual file in the directory.
- **A File Name:** A target that is the name of an existing or yet-to-be-created file (like main.exe or main.o).
- **Both:** A target can often be both a symbolic step *and* a file name, depending on the context.

# How Make Treats Targets (The Decision-Making Process)

If a target is **not listed** in the **.PHONY** directive, make treats the target name as a **file name** and initiates a smart, two-step process:

- **Existence Check:** make first checks if the file named by the target actually exists. If the file **does not exist**, make automatically executes the target's recipe to create it.
- **Timestamp Comparison:** If the file **does exist**, make compares the **modification time** (timestamp) of the target file with the timestamps of all its prerequisites (dependencies).
  - If any of the **prerequisites is newer** (younger) than the target file, the target is considered **out-of-date**, and its recipe is executed. This forces the older file to be recompiled (or otherwise updated) to a newer version.

# WHY THIS STILL MATTERS

- While computational power is high today, this timestamp logic is still crucial, especially in very large projects.
- There is no reason to recompile every single part of a huge system if only a few small source files have changed. **This selective rebuilding is the core reason we use make—it saves enormous amounts of time and makes the build process efficient.**

# Fully Functional Makefile: A Summary 1/3

At this point, we have a **complete and functional Makefile**. If we run it without any parameters, **make** will automatically build the final executable, main.exe.

```
.PHONY: clean

main.exe: main.o other.o
	gcc -g main.o other.o -o main.exe

main.o: main.c
	gcc -g -Wall -std=c99 -pedantic -c main.c -o main.o

other.o: other.h other.c
	gcc -g -Wall -std=c99 -pedantic -c other.c -o other.o
clean:
	del main.o
	del other.o
# we dont have the main.h
```

# Fully Functional Makefile: A Summary 2/3

Make achieves this by generating a **dependency tree** and determining the correct order of execution. We've defined this order as follows:

- The final executable (`main.exe`) depends on both object files: `main.o` and `other.o`.
- These object files, in turn, have their own prerequisites: `main.o` depends only on its source code, `main.c`, while **`other.o` depends on both its source file (`other.c`) AND its header file (`other.h`)**. This last dependency is crucial, ensuring that if the header is modified, other.o will be recompiled.

# Fully Functional Makefile: A Summary 3/3

- We also successfully created a **symbolic target, clean**, for removing temporary object files generated during compilation. This target will **not** be executed automatically; we must explicitly call it by name: make clean.
- Crucially, we only listed clean in the **.PHONY** directive because it's the only truly artificial target. All other targets (main.exe, main.o, other.o) are meant to be treated as actual file names, allowing **make** to use its smart timestamp logic.
- Note that while we needed to list other.h as a dependency for other.o, we **did not** need to define a separate target for it, as headers are only inputs, never outputs.

# Modify and Run

When we execute these commands sequentially in the command prompt (CMD):

- `mingw32-make clean`: The process begins by removing the object files.
- First `mingw32-make`: Because the object files no longer exist, the default target (`main.exe`) is triggered. Since `main.exe` depends on those missing object files, the entire compilation and linking process is executed from scratch to fulfill the dependency chain.
- Second `mingw32-make`: The subsequent invocation will return the message: `mingw32-make: 'main.exe' is up to date.`

This final message confirms that **make** has checked all dependencies and creation dates for every file. It found that the current version of `main.exe` is the newest one, meaning there is no need for **make** to perform any actions or recompilation.

```
mingw32-make clean
mingw32-make
mingw32-make
```

# Variables and Assignment in Makefiles

- In a Makefile, we can greatly enhance flexibility and readability by using **variables**. We've used the `:=` symbol for defining our variables, which denotes **simple assignment**.
- While alternative assignment operators exist (like `=`, `!=`, `?=`, etc.), it's crucial to understand that make operates in **two distinct phases** (reading and execution). Using the simple assignment operator (`:=`) is the safest approach for creating straightforward string variables at this level. You should generally **avoid the `=` operator** for now, as it defines a **recursively expanded variable**, which is reserved for much more complex and advanced scenarios.
- When defining a variable, the content is **not enclosed in quotes**. The variable definition ends either at a newline character `\n` or at the comment symbol `#`. A common pitfall for new users is dealing with whitespace: trailing spaces are often invisible but can be unintentionally included in the variable's value, which may cause build errors.
- To use a variable anywhere in the Makefile, you must enclose its name in parentheses preceded by a dollar sign: `$(VARIABLE_NAME)`.

# EXTENSION 1/2

```
# ================================================>



.PHONY: clean

main.exe: main.o other.o
	gcc -g main.o other.o -o main.exe

main.o: main.c  # we dont have the main.h
	gcc -g -Wall -std=c99 -pedantic -c main.c -o main.o

other.o: other.h other.c
	gcc -g -Wall -std=c99 -pedantic -c other.c -o other.o
clean:
	del main.o
	del other.o
```

```
CC     := gcc
CFLAGS := -g -Wall -std=c99 -pedantic # compiler flags
LFLAG  := -g # linker flag

TARGET := main.exe
OBJS   := main.o other.o
.PHONY: all clean

all: $(TARGET)
$(TARGET): $(OBJS)
	$(CC) $(LFLAG) $(OBJS) -o $(TARGET)
main.o: main.c  # we dont have the main.h
	$(CC) $(CFLAGS) -c main.c -o main.o
other.o: other.h other.c
	$(CC) $(CFLAGS) -c other.c -o other.o
clean:
	del $(OBJS)
```

# extension 2/2

```
CC     := gcc
CFLAGS := -g -Wall -std=c99 -pedantic # compiler flags
LFLAG  := -g # linker flag

TARGET := main.exe
OBJS   := main.o other.o
.PHONY: all clean

all: $(TARGET)
$(TARGET): $(OBJS)
	$(CC) $(LFLAG) $(OBJS) -o $(TARGET)
main.o: main.c  # we dont have the main.h
	$(CC) $(CFLAGS) -c main.c -o main.o
other.o: other.h other.c
	$(CC) $(CFLAGS) -c other.c -o other.o
clean:
	del $(OBJS)
```

- Our script is clearly becoming much smarter and more automated.

- As you can easily observe, **make** inserts the values of our variables wherever we reference them. The commonly accepted **default name for the main build target is all**, which we've defined as a **PHONY** target dependent on our actual **$(TARGET)** variable.

- However, it's essential to remember that this current Makefile is designed exclusively for the **Windows CMD** environment. If we tried to run the clean target in a Linux/Unix environment (such as **Bash**), it would fail because the command **del** is not recognized there.

# Conditional Shell Detection in Make 1/2

```
ifeq ($(SHELL),sh.exe) # without any space!
    DETECTED_SHELL = cmd/powershell
else
    DETECTED_SHELL = bash
endif
```

```
check-shell:
    echo $(SHELL)
    echo Detected: $(DETECTED_SHELL)
```

```
$ mingw32-make check-shell
SHELL=C:/Program Files/Git/usr/bin/sh.exe
Detected: bash
```



```
C:\..> mingw32-make check-shell
SHELL=sh.exe
Detected: cmd/powershell
```



- In Makefiles, we can use **conditional directives** like ifeq and ifneq to create logic that adapts to different environments. This allows us to write more portable build scripts.
- A key built-in variable we can leverage is **$(SHELL)**. This variable stores the path to the shell interpreter that **make** uses internally to execute the commands (recipes).

# CONDITIONAL SHELL DETECTION IN MAKE 2/2

When running `mingw32-make` on Windows:

- **CMD/PowerShell:** `$(SHELL)` typically returns a **relative path** or just the executable name, like `sh.exe`.
- **Git Bash:** `$(SHELL)` often returns the **full, absolute path**, such as `C:/Program Files/Git/usr/bin/sh.exe`.

Therefore, by using a simple conditional statement to check the **length** or the **presence of the absolute path delimiters** (like drive letters and slashes) in the `$(SHELL)` variable, we can reliably distinguish between the "native" Windows environment and the Unix-like Git Bash environment, allowing us to select the appropriate commands for our recipes.

```
CC     := gcc
CFLAGS := -g -Wall -std=c99 -pedantic # compiler flags
LFLAG  := -g # linker flag
TARGET := main.exe
OBJS   := main.o other.o
RM := -rm -f
ifeq ($(SHELL),sh.exe) # without any space!
   # cmd/powershell
   DETECTED_SHELL := cmd/powershell
   RM := del
else
   # bash
   DETECTED_SHELL := bash
endif
.PHONY: all clean check-shell
... # all
clean:
        $(RM) $(OBJS)
check-shell:
        @echo SHELL=$(SHELL)
        @echo Detected: $(DETECTED_SHELL)
```

```
CC     := gcc
CFLAGS := -g -Wall -std=c99 -pedantic # compiler flags
LFLAG  := -g # linker flag

TARGET := main.exe
OBJS   := main.o other.o

RM := -rm -f

ifeq ($(SHELL),sh.exe) # without any space!
   # cmd/powershell
   RM := del
endif

.PHONY: all clean

all: $(TARGET)

$(TARGET): $(OBJS)
        $(CC) $(LFLAG) $(OBJS) -o $(TARGET)

main.o: main.c  # we dont have the main.h
        $(CC) $(CFLAGS) -c main.c -o main.o

other.o: other.h other.c
        $(CC) $(CFLAGS) -c other.c -o other.o
clean:
        $(RM) $(OBJS)
```

# SUMMARY

**Make** offers capabilities far beyond what we've covered so far. This has been merely an introduction to its core principles. We can leverage **Make's conditional logic** to build a fully **automated compilation process** that is aware of the operating environment. Crucially, this includes the ability to dynamically detect the specific shell running on a **Windows system** (be it CMD, PowerShell, or Git Bash) and override the **RM variable** to ensure the correct file deletion command (del or rm) is used, thereby guaranteeing project portability

# THANK YOU!