

Code Book

Juan Aguirre

12/3/2020

Code Book

The run_analysis.R script performs the data preparation and then followed by the 5 steps required as described in the course project's definition.

1. Download the dataset

Dataset downloaded and extracted under the folder called UCI HAR Dataset

2. Assign each data to variables

- features <- features.txt : 561 rows, 2 columns
 - The features selected for this database come from the accelerometer and gyroscope 3-axial raw signals tAcc-XYZ and tGyro-XYZ.
- activities <- activity_labels.txt : 6 rows, 2 columns +List of activities performed when the corresponding measurements were taken and its codes (labels)
- subject_test <- test/subject_test.txt : 2947 rows, 1 column
 - Contains test data of 9/30 volunteer test subjects being observed
- x_test <- test/X_test.txt : 2947 rows, 561 columns
 - Contains recorded features test data
- y_test <- test/y_test.txt : 2947 rows, 1 columns
 - Contains test data of activities'code labels
- subject_train <- test/subject_train.txt : 7352 rows, 1 column
 - Contains train data of 21/30 volunteer subjects being observed
- x_train <- test/X_train.txt : 7352 rows, 561 columns
 - Contains recorded features train data
- y_train <- test/y_train.txt : 7352 rows, 1 columns
 - Contains train data of activities'code labels

3. Merges the training and the test sets to create one data set

- X (10299 rows, 561 columns) is created by merging x_train and x_test using rbind() function
- Y (10299 rows, 1 column) is created by merging y_train and y_test using rbind() function
- Subject (10299 rows, 1 column) is created by merging subject_train and subject_test using rbind() function
- Merged_Data (10299 rows, 563 column) is created by merging Subject, Y and X using cbind() function

4. Extracts only the measurements on the mean and standard deviation for each measurement

- TData (10299 rows, 88 columns) is created by subsetting Merged_Data, selecting only columns: subject, code and the measurements on the mean and standard deviation (std) for each measurement

5. Uses descriptive activity names to name the activities in the data set

- Entire numbers in code column of the TData replaced with corresponding activity taken from second column of the activities variable

6. Appropriately labels the data set with descriptive variable names

- code column in TData renamed into activities
- All Acc in column's name replaced by Accelerometer
- All Gyro in column's name replaced by Gyroscope
- All BodyBody in column's name replaced by Body
- All Mag in column's name replaced by Magnitude
- All start with character f in column's name replaced by Frequency
- All start with character t in column's name replaced by Time

7. From the data set in step 4, creates a second, independent tidy data set with the average of each variable for each activity and each subject

- FData (180 rows, 88 columns) is created by summarizing TData taking the means of each variable for each activity and each subject, after grouped by subject and activity.
- Export FData into FData.txt file.