

CS 525 - ASD

Advanced Software Development

MS.CS Program

Department of Computer Science

Rene de Jong, MsC.



Maharishi University
OF MANAGEMENT

CS 525 - ASD

Advanced Software Development

© 2019 Maharishi University of Management

All course materials are copyright protected by international copyright laws and remain the property of the Maharishi University of Management. The materials are accessible only for the personal use of students enrolled in this course and only for the duration of the course. Any copying and distributing are not allowed and subject to legal action.



Maharishi University
OF MANAGEMENT

Lesson 8 Adapter pattern



L1: ASD Introduction
L2: Strategy, Template method
L3: Observer pattern
L4: Composite pattern, iterator pattern
L5: Command pattern
L6: State pattern
L7: Chain Of Responsibility pattern

Midterm

L8: Proxy, Adapter, Mediator
L9: Factory, Builder, Decorator, Singleton
L10: Framework design
L11: Framework implementation
L12: Framework example: Spring framework
L13: Framework example: Spring framework


Final

Adapter pattern


- Translates the existing interface of a class into an interface that the client requires.
 - (Reusable) wrapper





Design problem



Solution



Better solution: Adapter



Adapter + Adaptee


```
public class DistanceCalculator {  
    public double computeDistance(String origin, String destination) {  
        return (new Random()).nextInt(100);  
    }  
}
```

```
public interface DistanceAdapter {  
    double computeDistanceInKilometers(String origin, String destination);  
    void setDistanceCalculator(DistanceCalculator distanceCalculator);  
}
```


```
public class KilometerDistanceAdapterImpl implements DistanceAdapter {  
    private DistanceCalculator distanceCalculator;  
  
    public double computeDistanceInKilometers(String origin, String destination) {  
        double distanceInMiles = distanceCalculator.computeDistance(origin, destination);  
        return distanceInMiles * 1.609344;  
    }  
  
    public void setDistanceCalculator(DistanceCalculator distanceCalculator) {  
        this.distanceCalculator = distanceCalculator;  
    }  
}
```


Client


```
public class Client {  
  
    public static void main(String[] args) {  
        DistanceCalculator distanceCalculator = new DistanceCalculator();  
        double distanceInMiles = distanceCalculator.computeDistance("city1", "city2");  
        System.out.println("The distance between city1 and city2 =" + distanceInMiles + " miles");  
  
        DistanceAdapter distanceAdapter = new KilometerDistanceAdapterImpl();  
        distanceAdapter.setDistanceCalculator(distanceCalculator);  
  
        double distanceInKilometers = distanceAdapter.computeDistanceInKilometers("city3", "city4");  
        System.out.println("The distance between city3 and city4 =" + distanceInKilometers + " kilometers");  
    }  
}
```




Where are adapters used



Where are adapters used




Where are adapters used




Adapter and Proxy: wrapper

■ Proxy



■ Adapter



Main point

- The Adapter translates an existing interface to a required interface.
- Life is found in layers, from the most abstract transcendental layer (Unified Field) to the most concrete layer.