



Minimum Swaps 2 ☆

[Problem](#)
[Submissions](#)
[Leaderboard](#)
[Editorial](#)

You are given an unordered array consisting of consecutive integers $\in [1, 2, 3, \dots, n]$ without any duplicates. You are allowed to swap any two elements. You need to find the minimum number of swaps required to sort the array in ascending order.

For example, given the array **arr** = [7, 1, 3, 2, 4, 5, 6] we perform the following steps:

i	arr	swap (indices)
0	[7, 1, 3, 2, 4, 5, 6]	swap (0,3)
1	[2, 1, 3, 7, 4, 5, 6]	swap (0,1)
2	[1, 2, 3, 7, 4, 5, 6]	swap (3,4)
3	[1, 2, 3, 4, 7, 5, 6]	swap (4,5)
4	[1, 2, 3, 4, 5, 7, 6]	swap (5,6)
5	[1, 2, 3, 4, 5, 6, 7]	

It took **5** swaps to sort the array.

Function Description

Complete the function `minimumSwaps` in the editor below. It must return an integer representing the minimum number of swaps to sort the array.

`minimumSwaps` has the following parameter(s):

- `arr`: an unordered array of integers

Input Format

The first line contains an integer, **n**, the size of **arr**.

The second line contains **n** space-separated integers **arr[i]**.

Constraints

- $1 \leq n \leq 10^5$
- $1 \leq arr[i] \leq n$

Output Format

Return the minimum number of swaps to sort the given array.

Sample Input 0

```
4
4 3 1 2
```

Sample Output 0

```
3
```

Explanation 0

Given array **arr** : [4, 3, 1, 2]

After swapping (0, 2) we get **arr** : [1, 3, 4, 2]

After swapping (1, 2) we get **arr** : [1, 4, 3, 2]

After swapping (1, 3) we get **arr** : [1, 2, 3, 4]



So, we need a minimum of **3** swaps to sort the array in ascending order.

Sample Input 1

```
5
2 3 4 1 5
```

Sample Output 1

```
3
```

Explanation 1

Given array **arr** : [2, 3, 4, 1, 5]

After swapping (2, 3) we get **arr** : [2, 3, 1, 4, 5]

After swapping (0, 1) we get **arr** : [3, 2, 1, 4, 5]

After swapping (0, 2) we get **arr** : [1, 2, 3, 4, 5]

So, we need a minimum of **3** swaps to sort the array in ascending order.

Sample Input 2

```
7
1 3 5 2 4 6 7
```

Sample Output 2

```
3
```

Explanation 2

Given array **arr** : [1, 3, 5, 2, 4, 6, 7]

After swapping (1, 3) we get **arr** : [1, 2, 5, 3, 4, 6, 7]

After swapping (2, 3) we get **arr** : [1, 2, 3, 5, 4, 6, 7]

After swapping (3, 4) we get **arr** : [1, 2, 3, 4, 5, 6, 7]

So, we need a minimum of **3** swaps to sort the array in ascending order.

[Change Theme](#)

Java 8



```
1  import java.io.*;
2  import java.math.*;
3  import java.security.*;
4  import java.text.*;
5  import java.util.*;
6  import java.util.concurrent.*;
7  import java.util.regex.*;
8
9  public class Solution {
10
11      // Complete the minimumSwaps function below.
12      static int minimumSwaps(int[] arr) {
13
14
15      }
```



```
16
17     private static final Scanner scanner = new Scanner(System.in);
18
19     public static void main(String[] args) throws IOException {
20         BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv
21 ("OUTPUT_PATH")));
22
23         int n = scanner.nextInt();
24         scanner.skip("(\\r\\n|\\[\\n\\r\\u2028\\u2029\\u0085])?");
25
26         int[] arr = new int[n];
27
28         String[] arrItems = scanner.nextLine().split(" ");
29         scanner.skip("(\\r\\n|\\[\\n\\r\\u2028\\u2029\\u0085])?");
30
31         for (int i = 0; i < n; i++) {
32             int arrItem = Integer.parseInt(arrItems[i]);
33             arr[i] = arrItem;
34         }
35     }
36 }
```

Line: 45 Col: 1

[Upload Code as File](#)☐ Test against custom input

Run Code

Submit Code

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)