



ADS-1200

Specifications

ADS-1200



Not your product?

Downloads

FAQs & Troubleshooting

Manuals

Consumables & Accessories

Supported OS

Specifications

United States(English)



Change Countries or Regions (Language)

General Specifications

Memory Capacity	Standard	ADS-1190/ADS-1200: 256 MB ADS-1250W/ADS-1700W: 512 MB
Power Source		100 - 120 V AC 50/60 Hz 220 - 240 V AC 50/60 Hz
Touchscreen LCD (Liquid Crystal Display) ^{*1} (ADS-1700W)		Touchscreen 2.8 in. (71.1 mm) TFT Color LCD
Power Consumption ^{*2}	Scanning ^{*3}	ADS-1190/ADS-1200: Approx. 8 W ADS-1250W: Approx. 9 W ADS-1700W: Approx. 9 W
	Ready ^{*4}	ADS-1190/ADS-1200: Approx. 3.2 W ADS-1250W: Approx. 4.2 W ADS-1700W: Approx. 4.5 W
	Sleep	ADS-1190/ADS-1200: Approx. 1.3 W ADS-1250W: Approx. 1.4 W ADS-1700W: Approx. 1.6 W
	Power Down	ADS-1190/ADS-1200: Approx. 0.1 W ADS-1250W: Approx. 0.1 W ADS-1700W: Approx. 0.1 W
Dimensions		<p>3.28 in. (83 mm)</p> <p>11.81 in. (300 mm)</p> <p>4.06 in. (103 mm)</p> <p>8.15 in. (207.1 mm)</p> <p>11.81 in. (300 mm)</p> <p>8.16 in. (207.2 mm)</p>
Weights		ADS-1190/ADS-1200: Approx. 3 lb (1.36 kg) ADS-1250W: Approx. 3.02 lb (1.37 kg) ADS-1700W: Approx. 3.11 lb (1.41 kg)

Contact Us
Product Registration
Visit www.brother-usa.com

Temperature	Operating	41 °F to 95 °F (5 °C to 35 °C)
	Storage	32 °F to 104 °F (0 °C to 40 °C)
Humidity	Operating	20% to 80%
	Storage	10% to 90%
ADF (Automatic Document Feeder)		Up to 20 pages (Paper: 20 lb (80 g/m ²) Legal size, or less than 0.2 in. (5 mm))

*1 Measured diagonally.

*2 Measured when the machine is connected to your computer.

*3 When using 2-sided (duplex) scanning.

*4 When the USB port is connected.

Document Specifications

Paper Type		Plain Paper, Thin Paper, Thick Paper, Thicker Paper, Recycled Paper, Business Card, Plastic Card
Document Size	Width	2 in. to 8.5 in. (51 mm to 215.9 mm)
	Length	Single Paper: 2 in. to 34 in. (51 mm to 863 mm) Multiple Paper: 2.76 in. to 11.7 in. (70 mm to 297 mm)

Scanner Specifications

Color/Black		Yes/Yes
TWAIN Compliant	Windows	Windows 7 (SP1) / Windows 8 / Windows 8.1 / Windows 10 Windows Server 2008 R2 (SP1) / Windows Server 2012 / Windows Server 2012 R2 / Windows Server 2016
	Mac	macOS v10.11.6 / 10.12.x / 10.13.x
WIA Compliant	Windows	Windows 7 (SP1) / Windows 8 / Windows 8.1 / Windows 10
ICA Compliant	Mac	macOS v10.11.6 / 10.12.x / 10.13.x
Color Depth	Input	48 bit color processing
	Output	24 bit color processing
Resolution	Interpolated	Up to 1200 x 1200 dpi
	Optical	Up to 600 x 600 dpi
Scanning Width		Up to 8.5 in. (215.9 mm)
Gray Scale		256 levels
Max. Speed		For detailed specifications, visit www.brother.com .

Direct Scan Feature (Scan to USB) Specifications

Compatible Media	USB flash drive ^{*1}
Interface	Interface USB 2.0 Hi Speed

*1 USB Mass Storage standard up to 128 GB

Supported formats: FAT12/FAT16/FAT32/exFAT

Interface Specifications

USB	USB 3.0 ^{*1} Use a USB 3.0 cable (Standard A/Micro B) or USB 2.0 interface cable (Standard A/Micro B) ^{*2} that is no more than 6 feet (2.0 meters) long.
Wireless LAN (ADS-1250W/ADS-1700W)	IEEE 802.11b/g/n (Infrastructure Mode) IEEE 802.11g (Wi-Fi Direct or Wireless Direct)

*1 Your machine has a USB 3.0 interface. The machine can also be connected to a computer that has a USB 1.0/1.1/2.0 interface. Third-party USB ports are not supported.

*2 Use of a USB 3.0 (Micro) cable connected to a USB 3.0 port on your computer is recommended to scan in Bus Power Mode (ADS-1190/ADS-1200/ADS-1250W).

Network Specifications (ADS-1250W/ADS-1700W)

Wireless Network Security	WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES)
----------------------------------	--

Setup Support Utility	WPS (ADS-1700W) WLAN Assistant
-----------------------	-----------------------------------

Supported Protocols and Security Features (ADS-1250W/ADS-1700W)

Protocol (IPv4)	ADS-1250W: DHCP, APIPA (Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, SNMPv1/v2c, ICMP, Web Services (Scan) ADS-1700W: DHCP, APIPA (Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLMNR responder, SMTP Client, FTP Client, CIFS Client, SNMPv1/v2c/v3, HTTP/HTTPS server, ICMP, SMTP Client, Web Services (Scan)
Protocol (IPv6) (ADS-1700W)	RA, DNS Resolver, mDNS, LLMNR responder, SMTP Client, FTP Client, CIFS Client, HTTP/HTTPS server, ICMP, SMTP Client, Web Services (Scan)
Network Security (Wireless)	SMTP-AUTH, SSL/TLS (HTTPS/SMTP), SNMP v3, SSH
Network Security (Email)	SMTP-AUTH, SSL/TLS (SMTP)
Wireless Certification	ADS-1250W: Wi-Fi Certification Mark License (WPA™/WPA2™ - Personal) ADS-1700W: Wi-Fi Certification Mark License (WPA™/WPA2™ - Personal), Wi-Fi Protected Setup™ (WPS) Identifier Mark License, Wi-Fi CERTIFIED Wi-Fi Direct®

[Site Map](#) | [Legal](#) | [Privacy Policy](#) | [Global Site](#)

© 2001-2023 Brother Industries, Ltd. All Rights Reserved.
Any trade names and product names of companies appearing on Brother products, related documents and any other materials are all trademarks or registered trademarks of those respective companies.