

T0 Optimization Strategies Compared:
QM-Optimization (Doc. 034) and
Coherent Ising Machine (Doc. 161):
Complementary Levels of the Same Geometric Principle

Johann Pascher

February 2026

Contents

.1	Introduction: Two Optimization Levels in T0	2
	The Starting Problem	2
	The Common Root	2
.2	Document 034: QM-Optimization through Geometric Formalism	3
	The Cylindrical Phase Space	3
	Fractal Damping as Intrinsic Noise	3
	The Three Optimization Strategies from Doc. 034	3
.3	Document 161: T0 Ising Machine – Combinatorial Optimization	4
	The Ising Model as Optimization Language	4
	The T0 Ising Machine: Emergent Couplings	4
	Noise in the CIM: The Annealing Problem	4
.4	Systematic Comparison: Doc. 034 vs. Doc. 161	5
	Overview Table	5
	Parallel 1: Noise – Enemy or Ally?	5
	Parallel 2: Fractal Damping as Universal T0 Mechanism	5
	Parallel 3: Frequency Optimization vs. Topology Optimization	6
	Parallel 4: Determinism and Measurability	6
.5	New Optimization Opportunities through the Connection	7
	Hybrid Optimization: Gate Level + System Level	7
	Noise as a Bridge between Both Levels	7
	Ratio between Gate Error and CIM Residual	7
.6	Summary: Complementary Levels of the Same Principle	8

Abstract

The T0 theory contains two complementary optimization frameworks: Document 034 (*QM-Optimization*) describes how quantum computers can be optimized through geometric transformation in cylindrical phase space and through noise suppression via time-field modulation. Document 161 (*T0 Ising Machine*) shows that combinatorial NP-hard optimization can be solved through geometric relaxation of the mass field $m(x, t)$. This document 162 systematically compares both approaches and demonstrates: they are not competing, but *complementary levels of the same geometric principle* – optimization as physical relaxation into a geometric minimum.

.1 Introduction: Two Optimization Levels in T0

The Starting Problem

Quantum computing struggles with noise and suboptimality on two fundamentally different levels:

1. **Gate level:** Individual quantum gates are disturbed by decoherence, phase noise, and fractal damping. The question: how does one optimize *individual operations*?
2. **Problem level:** Combinatorial optimization problems (NP-hard) are hard to solve even with perfect gates. The question: how does one find *global minima* in vast solution spaces?

The T0 theory addresses **both levels** – but with different tools and at different levels of abstraction. Document 034 [1] solves Problem 1; Document 161 [2] solves Problem 2.

The Common Root

Both approaches share the same geometric origin: the parameter $\xi = 4/30000 \approx 1.333 \times 10^{-4}$ and the time-field binding condition $T \cdot m = 1$. The differences are not conceptual – they are differences in the *scaling level* of application.

.2 Document 034: QM-Optimization through Geometric Formalism

The Cylindrical Phase Space

In Document 034 [1], Hilbert space is replaced by a **cylindrical phase space**. A qubit is not a 2D complex vector, but a point (z, r, θ) :

- $z \in [-1, 1]$: classical basis projection ($z = +1 \equiv |0\rangle$, $z = -1 \equiv |1\rangle$)
- $r \geq 0$: coherence radius (superposition magnitude), with $z^2 + r^2 = 1$
- $\theta \in [0, 2\pi)$: relative phase of the superposition

Gate operations are geometric transformations of this space, not matrix multiplications.

Fractal Damping as Intrinsic Noise

The X-gate (bit-flip) is not an ideal π -rotation in the T0 formalism, but a damped rotation by angle $\alpha = \pi \cdot K_{\text{frak}}$:

$$z' = z \cos(\alpha) - r \sin(\alpha) \quad (1)$$

$$r' = z \sin(\alpha) + r \cos(\alpha) \quad (2)$$

with the fractal damping constant $K_{\text{frak}} = 1 - 100\xi$. A perfect flip ($\alpha = \pi$) is physically impossible – spacetime inherently damps every rotation. This deviation is not directly measurable: it is absorbed into the pulse calibration of real qubits and therefore cannot be tested with current hardware.

The Three Optimization Strategies from Doc. 034

1. **T0-Topology-Compiler**: Qubits are arranged not to minimize SWAP operations, but to minimize the cumulative *fractal path length* of all entangling operations. Critically interacting qubits must be brought physically closer together.
2. **Harmonic resonance frequencies**: Qubit frequencies are calibrated to “magic” frequencies arising from the harmonic structure of the T0 time field:

$$f_n = \left(\frac{E_0}{h} \right) \cdot \xi^2 \cdot (\phi_T^2)^{-n} \quad (3)$$

For superconducting qubits, with $E_0 = 7.398$ MeV sweet spots emerge at approximately **5.50 GHz** ($n = 9$) and **2.10 GHz** ($n = 10$). This calibration intrinsically reduces phase noise.

3. **Active time-field modulation**: A high-frequency *time-field pump* irradiates idle qubits to average out the fundamental ξ -noise and overcome the passive T_2 coherence limit – active decoherence suppression instead of passive waiting.

.3 Document 161: T0 Ising Machine – Combinatorial Optimization

The Ising Model as Optimization Language

In Document 161 [2], it is shown that NP-hard combinatorial problems can be formulated as minimization of the Ising Hamiltonian:

$$H_{\text{Ising}} = -\frac{1}{2} \sum_{i \neq j} J_{ij} \sigma_i \sigma_j - \sum_i h_i \sigma_i \quad (4)$$

A Coherent Ising Machine (CIM) finds the ground state of this Hamiltonian through physical relaxation of laser pulses (spins = phase states 0° or 180°).

The T0 Ising Machine: Emergent Couplings

The T0 theory extends the CIM fundamentally: the couplings J_{ij} are not externally programmable – they geometrically emerge from the time field:

$$J_{ij}^{(T0)} = \int T(x, t)_i \cdot T(x, t)_j \cdot G(x_i, x_j) d^3x \quad (5)$$

The energy functional is:

$$H_{\text{Ising}} \leftrightarrow E_{T0} = \int |\nabla T(x, t)|^2 d^4x \quad (6)$$

Noise in the CIM: The Annealing Problem

In the CIM, noise plays a paradoxical role: it is simultaneously problem and tool. Too little thermal noise leads to local minimum traps; too much noise prevents convergence. The annealing temperature parameter T_{ann} balances this conflict.

In the T0 Ising Machine, $K_{\text{frak}}^{3/2}$ takes this role – not as an external parameter, but as a geometrically determined fractal correction factor.

.4 Systematic Comparison: Doc. 034 vs. Doc. 161

Overview Table

Table 1: Direct comparison of the two T0 optimization frameworks

Aspect	Doc. 034: QM-Optimization	Doc. 161: T0 Ising Machine	Common Root
Target problem	Gate noise, decoherence	NP-hard optimization	Geometric relaxation
Scaling level	Single qubit / gate	Full system (N spins)	$\xi = 4/30000$
Spin representation	(z, r, θ) in cylinder	Phase $0^\circ/180^\circ$ (CIM)	$T \cdot m = 1$ duality
Role of noise	Disturbance (minimize)	Tool (annealing)	K_{frak} correction
Coupling	Gate pulses (external)	J_{ij} (geometrically emergent)	Time field $T(x, t)$
Optimization goal	Maximum gate fidelity	Global minimum of H	Energy minimization
Determinism	Explicit (geometric trafo)	Hidden (OPO equations)	Both deterministic
Prediction	Damped X-flip (not directly measurable)	$\ln(N)$ residual after CIM	ξ signatures

Parallel 1: Noise – Enemy or Ally?

This is the deepest conceptual difference between both documents:

Table 2: The opposing role of noise in both frameworks

Aspect	Doc. 034: QM-Optimization	Doc. 161: T0 Ising Machine
Noise is...	Enemy – disturbs gate fidelity	Tool – enables annealing
T0 cause	Fractal damping K_{frak}	Thermal fluctuations in OPO
Strategy	Actively suppress	Controlledly deploy
Mechanism	Time-field pump modulates $T(x)$	Temperature parameter T_{ann}
Optimum	Noise $\rightarrow 0$	Noise $\rightarrow$ minimum (then $\rightarrow 0$)
T0 analogue	$K_{\text{frak}} \rightarrow 1$ (perfect gates)	$K_{\text{frak}}^{3/2}$ as annealing force

Resolution of the Apparent Contradiction

The apparent contradiction – noise is bad in Doc. 034, good in Doc. 161 – dissolves through the scaling level: at the gate level, any noise is harmful. At the system level, controlled noise is necessary to escape local minima. T0 describes the same physical mechanism (K_{frak}) at both levels.

Parallel 2: Fractal Damping as Universal T0 Mechanism

Table 3: K_{frak} as a universal T0 mechanism at different levels

Context	Doc. 034	Doc. 161	Physical Meaning
K_{frak} definition	$1 - 100\xi$	$K_{\text{frak}}^{3/2}$ (g-2 correction)	Fractal spacetime structure
Acts on...	X-gate rotation (damps)	Annealing dynamics (regulates)	Deviation from ideal
Mathematically	$\alpha = \pi \cdot K_{\text{frak}}$	$\mathcal{D}(N) = e^{-\xi \ln N / D_{\text{frak}}}$	Geometric damping
Measurable via	Residual flip error (masked by calibration)	$\ln(N)$ residual after CIM	ξ signatures
Testable on	Not testable with current hardware	CIM with variable spin count	Gate side currently not testable

Parallel 3: Frequency Optimization vs. Topology Optimization

Both documents propose optimizations of the *system architecture* – at different levels:

Table 4: Architecture optimizations: gate level vs. system level

Optimization type	Doc. 034: QM-Optimization	Doc. 161: T0 Ising Machine
Frequency optimization	Harmonic resonance frequencies f_n	–
Topology optimization	T0-Topology-Compiler (fractal path length)	4D torus topology
Decoherence protection	Active time-field modulation	Toroidal boundary conditions
Coupling structure	Gate pulses pre-compensated	J_{ij} geometrically emergent
Goal	Max. gate fidelity	Min. Ising Hamiltonian

Parallel 4: Determinism and Measurability

Table 5: Determinism and predictions of both documents

Aspect	Doc. 034: QM-Optimization	Doc. 161: T0 Ising Machine
Type of determinism	Explicit: geometric transformations	Hidden: OPO field equations
Source of stochasticity	Fractal spacetime fluctuations	Quantum vacuum initial conditions
Prediction 1	Damped X-flip: $\alpha < \pi$ (not directly measurable)	$\ln(N)$ -scaling residual
Testable prediction 2	Sweet spots at 5.50/2.10 GHz	J_{ij} deviations from free param.
Platform	IBM Brisbane/Sherbrooke	CIM with 1000+ spins
Quantification	$\Delta\alpha = \pi(1 - K_{\text{frak}}) \approx 4.2 \times 10^{-2}$	$\xi \approx 1.3 \times 10^{-4}$

.5 New Optimization Opportunities through the Connection

The systematic comparison of both documents opens optimization opportunities not visible in either document alone:

Hybrid Optimization: Gate Level + System Level

Hybrid T0 Optimization Strategy

A fully T0-optimized quantum architecture combines both levels:

1. **Gate level** (Doc. 034): Harmonic frequency calibration + time-field pump for maximum gate fidelity
2. **System level** (Doc. 161): T0 Ising Machine for combinatorial optimization with geometrically emergent couplings
3. **Linking level**: The T0-Topology-Compiler (Doc. 034) minimizes fractal path lengths – this is the same geometric principle as the torus structure in Doc. 161

Noise as a Bridge between Both Levels

The dualistic role of noise opens a new optimization strategy:

- **Phase 1 (Annealing)**: Controlled noise (K_{frak} regime) – the T0 Ising Machine searches for global minima
- **Phase 2 (Precision)**: Noise suppression (time-field pump) – quantum gates execute the solution with maximum fidelity
- **Transition**: The fractal parameter K_{frak} regulates both phases – as annealing mechanism (Doc. 161) and as gate damping (Doc. 034)

$$\text{Optimization} = \underbrace{K_{\text{frak}}^{3/2} \text{-annealing}}_{\text{Doc. 161: global minimum}} + \underbrace{K_{\text{frak}} \rightarrow 1 \text{-precision}}_{\text{Doc. 034: gate fidelity}} \quad (7)$$

Ratio between Gate Error and CIM Residual

If K_{frak} describes the same universal T0 parameter at both levels, then:

$$\frac{\Delta \alpha_{\text{Gate}}}{\pi} = 1 - K_{\text{frak}} = 100 \xi \approx 1.33 \times 10^{-2}, \quad \frac{1 - \mathcal{D}_{\text{CIM}}(N)}{\ln N} \approx \frac{\xi}{\Delta f} \approx 4.4 \times 10^{-5} \quad (8)$$

Both quantities are fixed by the same ξ , but they are **not equal**: the relative gate flip error on IBM quantum computers ($100 \xi \approx 1.33 \times 10^{-2}$) and the $\ln(N)$ residual in CIM measurements ($\xi/\Delta f \approx 4.4 \times 10^{-5}$) differ by the factor $100 \Delta f \approx 300$; convergence to the same numerical value is not to be expected. This fixed ratio, too, is currently not experimentally testable, because the gate deviation is absorbed into the pulse calibration of real qubits and is not directly measurable.

.6 Summary: Complementary Levels of the Same Principle

Table 6: Full synthesis: both documents as complementary T0 levels

Dimension	Doc. 034	Doc. 161	Connection
Level	Gate / qubit	System / spins	Same ξ
Noise	Enemy (suppress)	Tool (control)	K_{frak} at both levels
Representation	Cylindrical (z, r, θ)	Phase $0^\circ/180^\circ$	$T \cdot m = 1$ states
Topology	Fractal path length	4D torus	Geometric minimization
Coupling	Gate pulses (pre-compensated)	J_{ij} (emergent)	Time field $T(x, t)$
Prediction	$\Delta\alpha \approx 4.2 \times 10^{-2}$	$\ln(N)$ residual	$\xi = 4/30000$

The central insight is:

The Unified T0 Optimization Perspective

Both gate noise (Doc. 034) and combinatorial NP-optimization (Doc. 161) are manifestations of *the same geometric principle*: physical relaxation into the minimum of the T0 energy functional $E_{\text{T0}} = \int |\nabla T(x, t)|^2 d^4x$. The difference is not conceptual – it is the scaling level of observation. The fractal correction K_{frak} appears at both levels as the same universal parameter; the predictions of both levels are fixed by the same ξ but differ by the factor $100 \Delta f \approx 300$.

Bibliography

- [1] J. Pascher, T0 Quantum Mechanics: Geometric Formalism and Optimization Strategies for Quantum Computers, T0 Documentation Series, Document 034 (2025).
- [2] J. Pascher, T0 Theory and Coherent Ising Machines: Structural Parallels, T0 Documentation Series, Document 161 (2026).
- [3] J. Pascher, T0 Theory: Time-Mass Duality as a Fundamental Principle, T0 Documentation Series, Document 003 (2025).
- [4] J. Pascher, Fractal Corrections and the g-2 Anomaly, T0 Documentation Series, Document 018 (2025).
- [5] J. Pascher, T0 Quantum Computing: Qubits and Logic Gates, T0 Documentation Series, Document 147 (2025).
- [6] J. Pascher, T0 Projection onto Scramblon Physics, T0 Documentation Series, Document 148 (2026).
- [7] T. Inagaki et al., A coherent Ising machine for 2000-node optimization problems, *Science* **354**, 603 (2016).