Metadata, cost and accuracy of official statistics served to AI agents: evidence from three MCP servers

João Pedro Azevedo
UNICEF, Office of Strategy and Evidence, Data and Analytics*

27 October 2026

Abstract

AI agents increasingly reach official statistics through Model Context Protocol (MCP) servers rather than through portals or application programming interfaces. A value that reaches an agent without its source, status, uncertainty or release cannot be attributed, dated or interpreted correctly. This paper proposes a minimum metadata standard of fifteen elements for MCP servers that republish official statistics. It scores three public servers against it: the UNICEF SDMX data warehouse MCP, the UN System Data Commons (UN DC) and World Bank Data360. It then measures what answering a question costs on each. Three designs are used: a scripted pilot on two Nigerian series; a pre-registered benchmark of 34 randomly drawn series across 17 sectors and three countries (140 answers, 325 calls); and an agentic benchmark of 96 sessions across seven model and effort settings. The warehouse delivers 46–70% of the standard on every question it answers, against at most 21% for UN DC and 20–29% for Data360. Compliance is cheap, because the metadata travels in the data call, which accounts for 6–22% of characters on UN DC and the warehouse; searching for the series accounts for 67–94%. Across models and effort levels, every reported value for a year the warehouse holds (1,952 of 1,953) matched it, and all 1,953 appeared in the servers' own responses. Higher effort raised cost, not accuracy. In agentic use, the tool definitions a server loads into every request cost more tokens than its data responses. For an official UNICEF MCP, the levers are a compact search, a short tool list, and one data call that carries the fifteen elements.

Keywords: official statistics; metadata; SDMX; Model Context Protocol; AI agents; data dissemination.

1 Introduction

When an analyst asks an AI assistant for Nigeria's under-five mortality rate, the number usually no longer comes from a portal, a PDF or a download. An agent calls a tool exposed by an MCP server, reads the response and writes an answer. Whatever the server leaves out of that response, the answer cannot contain: who produced the estimate, which release it belongs to, whether it was modelled or reported, and how uncertain it is. For official statistics, whose value rests on provenance and method as much as on the number, this is a new and largely unexamined channel.

This paper asks two questions. First, what metadata must a server return with each value for an agent to reproduce, attribute, date and interpret it, and how far do current servers meet that bar? Second, what does it cost, in characters and tokens, to answer a statistical question

*Working draft. Every number, table and figure is generated from the replication package that accompanies this paper; see the Reproducibility section.

through each server, and does that cost depend on the metadata, on the server's design, or on the model that drives the agent?

We answer them for three public MCP servers that republish UNICEF's child-related indicators: the UNICEF SDMX data warehouse MCP (sdmx-mcp 1.2.214), the UN System Data Commons MCP, and the World Bank Data360 MCP. We propose a minimum standard of fifteen elements, each reusing an attribute already defined by SDMX (SDMX Sponsors), the SDG data structure definition (United Nations Statistics Division, 2019) or the UNICEF warehouse. We score the three servers against it, and run three benchmarks of increasing realism.

We find four things.

- **Coverage of the standard ranks the servers consistently.** The warehouse delivers 46–70% of the standard wherever it answers, against at most 21% for UN DC and 20–29% for Data360.
- **Compliance is not a cost problem.** The metadata travels in the data call, the cheap part of any answer; searching for the right series accounts for 67% of the warehouse's characters and 94% of UN DC's.
- **Accuracy did not depend on the model or the effort level.** Every value agents reported for a year the warehouse holds (1,952 of 1,953) matched it, and all 1,953 appeared in the servers' own responses. Higher effort bought more calls, not better answers.
- **The tool definitions a server loads cost more than its data.** In agentic use they are re-sent with every request and add 70,000–80,000 tokens per question on average; all data responses and reasoning together add 17,000–33,000.

Section 2 motivates the problem. Section 3 sets out the standard, the scoring and the cost measures. Section 4 describes the servers, samples and data recorded. Section 5 presents results, Section 6 draws policy implications and Section 7 concludes with limitations.

2 Motivation

An official statistic is a value plus its metadata. The same national under-five mortality rate can be a modelled UN IGME estimate with a 90 per cent uncertainty interval (UN IGME, 2025), or a direct estimate from one survey round. A coverage rate can come from the latest WHO/UNICEF revision or from the one before it. The international statistical system has spent two decades codifying how this information travels between agencies. The SDG data structure definition makes the unit, unit multiplier and observation status mandatory, and defines source detail, time detail, bounds and observation comments (United Nations Statistics Division, 2019). The Statistical Commission's guidelines on data flows and global data reporting set out how data and metadata should pass between national systems and custodian agencies (United Nations Statistical Commission, 2018), and the CCSA principles ask for credit to the original source (Committee for the Coordination of Statistical Activities, 2005). None of this yet reaches the channel through which AI agents now read the data.

Republishing multiplies the risk of loss. A UNICEF value may reach an agent directly from the warehouse, or through a republisher that copied it from the SDG Global Database or from a World Bank collection. At each hop attributes can be dropped, codes re-mapped and releases fall out of date. Our earlier comparisons found concrete cases of each: UN DC attributes every UNICEF facet to "United Nations"; Data360 credits UNICEF on 65 of 117 matched series; and both still served Nigeria's pre-revision DTP3 coverage for 2021–2024 (61, 59, 67, 67), where the warehouse, on the WUENIC 2025 revision, has 50, 55, 63 and 63. An agent cannot detect any of these from the response alone.

Cost shapes what agents can use. Agents are billed and limited by tokens. A server that returns 30,000 characters where 3,000 would do makes every answer slower and dearer, crowds

the model's context, and may push the agent to stop early or to skip a metadata call. A standard that made responses much longer would not be adopted; a server that is cheap only because it drops metadata is not a good server.

There is no standard yet. The MCP specification defines how a tool declares an output schema and returns structured content, but not what a statistical response should contain (Model Context Protocol, 2026). UNICEF is preparing an official MCP server for its data, and the UN system is building shared infrastructure through the UN System Data Commons under UN80 Workstream 16. Both need an agreed minimum and evidence on what it costs.

3 Methodology

3.1 A minimum metadata standard

An element enters the standard only if its absence caused a documented failure in our comparisons of the three servers against the warehouse, and each reuses an attribute that SDMX, the SDG data structure definition or the UNICEF warehouse already defines. Elements attach at three levels: R elements once per response, S elements once per series, and O elements per observation, only when non-empty. Twelve are required in every response; three (marked *) whenever the custodian publishes them (Table 1).

Table 1: The minimum metadata standard

ID	Element	What it must hold	Reuses
R1	Reproducible query	the canonical request that returns the same data	SDMX REST query
R2	Retrieval stamp	server name and version; retrieval time (UTC)	MCP serverInfo; ISO 8601
R3	Completeness statement	every default or filter applied; whether truncated	warehouse MCP appliedDefaults
S1	Identifiers	custodian code unchanged, server id, SDG series code	SDMX INDICATOR; SDG SERIES
S2	Name and definition	name, short definition, link to methodology	SDMX codelists; SDG metadata
S3	Unit	unit code and label, unit multiplier	SDMX UNIT_MEASURE, UNIT_MULT
S4	Breakdown	every dimension coded, explicit totals	SDMX dimensions, _T totals
S5	Custodian and provenance chain	estimating agency and each republisher	SDG custodian role; CCSA principle 4
S6	Release and currency	release, date, ingest date, current or replaced	SDMX dataflow version
S7	Licence and citation	licence and recommended citation	FAIR R1.1
O1	Source	survey round, administrative system or model	SDMX DATA_SOURCE; SDG SOURCE_DETAIL
O2	Reference period*	the period the value refers to, if different	SDG TIME_DETAIL; COVERAGE_TIME
O3	Nature and status	reported, adjusted, modelled, projected; provisional	SDMX OBS_STATUS; SDG NATURE
O4	Uncertainty*	lower and upper bounds, interval type and level	LOWER_BOUND, UPPER_BOUND
O5	Footnote*	the custodian's note, verbatim	SDG COMMENT_OBS; OBS_FOOTNOTE

* Required whenever the custodian publishes it.

Seven carriage rules accompany the elements: (1) pass every element through and never drop one; (2) inline what interpretation needs and link the rest; (3) send header fields once per series and per-observation fields only where they vary; (4) send every coded field as code and label; (5) declare every default the server applied; (6) return values as published, without extra rounding or silent scaling; (7) declare the response schema through MCP's `outputSchema`.

3.2 Scoring

Each answer is scored element by element as *meets* (1 point), *partial* (0.5) or *missing* (0). Partial means incomplete, uneven across flows, or available only through a separate call. Elements the custodian does not publish for that series and country are not applicable. The *share of the standard delivered* is points divided by applicable elements. The automated scoring reproduces all ten hand-scored pilot paths element by element.

3.3 Cost

Cost is measured in characters of every MCP response, counted exactly from the agents' session transcripts (oversized responses from the copy the client saved), and, in the agentic benchmark, in tokens: the usage the API reported for each request. Tokens sent are input plus cache-creation plus cache-read tokens, summed over requests; tokens received are output tokens, thinking included. Tokens sent are decomposed into the *baseline* (the first request, i.e. the client's own instructions and tool list, times the number of requests), *tool definitions* (the jump in context when the server's tools load, times later requests) and the *remainder* (responses and reasoning carried forward). A transcript repeats the usage of one API response on each of its content blocks, so usage is counted once per message identifier.

3.4 Frontier, accuracy and grounding

A way of answering is on the *efficiency frontier* if no other way delivers at least the same share of the standard for fewer characters. A value is *correct* if it is within the larger of 0.5% relative error and the rounding unit of the value reported (0.51 for integers, 0.051 otherwise) of the warehouse value for that year. A number is *grounded* if it appears in the server's responses in that session, verbatim or rounded to the precision reported.

3.5 Three benchmark designs

Table 2: Benchmark designs

Design	Questions	Who chooses the calls	Measures	Purpose
Pilot	2 series, Nigeria; 13 paths	analyst, scripted	characters, share	build and calibrate the scoring; first frontier
Sector and country	34 series × up to 3 countries; 140 answers	fixed path per server, pre-registered	characters by component, share, discovery, agreement	test whether the pilot generalises
Model and effort	4 series, Nigeria × 3 servers × 8 runs; 96 sessions	the agent	tokens sent and received, calls, accuracy, grounding, stability	separate the server from the model

4 Data

Servers. All three servers were queried on 26–27 October 2026 through their public MCP endpoints. The *UNICEF SDMX warehouse MCP* (sdmx-mcp 1.2.214) reads the warehouse's public SDMX REST API (https://sdmx.data.unicef.org), which holds UNICEF's 41 dataflows, through 31 tools for discovery, structure and data. The *UN System Data Commons MCP* serves a knowledge graph of UN-system statistics, including UNICEF series taken from the SDG Global Database and from UNICEF directly, through six tools and an instruction file it asks agents to read first. The *World Bank Data360 MCP* serves World Bank databases (among them WDI, Health, Nutrition and Population, and the Human Capital Project), which republish many UNICEF series under World Bank codes, through 16 tools, with data and metadata in separate calls.

Pilot. Two questions for Nigeria, 2000–2025: the under-five mortality rate (UN IGME) and DTP3 coverage (WUENIC), each answered by every reasonable path on each server, with and without a separate metadata call. Data360 was first queried from 1960 and 1980, which made its responses 2.3 and 1.6 times longer, so it was re-run on the same window; both runs are kept and the first is flagged.

Sector and country sample. The frame is the 210 UNICEF indicator codes in UN DC whose series maps to a warehouse series with Nigerian data. Codes are stratified by UN DC's 17 UNICEF sector groups and, within each, ranked by their number of UN DC variables and split into lower and upper halves. One code is drawn per stratum with a fixed seed (20261027), giving 34 series. All are asked for Nigeria, and twelve drawn at random also for Brazil and data-sparse Somalia: 58 questions on the warehouse and UN DC, and 24 on Data360 for the 14 series it carries. Each server follows one path fixed in advance; discovery uses the custodian's indicator name, with one retry using UN DC's name; the data call always uses the target identifier, so retrieval cost is measured even when discovery fails. Protocol and sample were saved before the first call; agents executed 325 calls used in the analysis, and every response is saved verbatim.

Model and effort panel. Four questions for Nigeria, 2000–2025, chosen because all three servers hold the series and its values agree with the warehouse: the under-five mortality rate (UN IGME), the maternal mortality ratio (MMEIG), the population using at least basic drinking water services (JMP), and women aged 15–49 with four or more antenatal care visits (UNICEF household-survey database). The warehouse values are the reference. Each agent received the same prompt, could use only one server (no web search, files or prior knowledge), and had to answer in a fixed JSON form, returning null for anything the server did not give it. Seven settings were run — Claude Haiku 5.5 at medium effort, and Claude Sonnet 5.5 and Claude Opus 5.5 at low, medium and high effort — plus a repeat of Opus at medium effort: 96 sessions. Claude Fable 5.1 was planned, but all 12 of its sessions were refused because the account had no usage credits for it.

5 Results

5.1 How far the servers meet the standard

The warehouse MCP meets 5 of the 15 elements and partly meets 8; Data360 meets 1 and partly meets 9, mostly through its separate metadata call; UN DC meets 0 and partly meets 4 (Figure 1, Table 3). The ranking follows what each server passes through: the warehouse publishes most of what the standard needs, unevenly across its 41 flows; Data360 holds rich series metadata but keeps it apart from the data; UN DC drops every observation-level attribute, so even where

it copies warehouse values it loses the bounds, status, sources and notes attached to them. No server meets the retrieval stamp (R2) or licence with citation (S7), the two elements any server can add without touching its data.




Figure 1: Elements of the standard met in a data response, by server. Meets: present in the response to a data query; partly: incomplete, uneven across flows, or only via a separate call.

5.2 The pilot frontier

On the two pilot questions the cheapest answer delivers between a quarter and two-thirds of the standard, and a compliant answer would cost about the same (Figure 2). For under-five mortality, the cheapest answer is Data360's data call: 7,937 characters and 27% of the standard. For DTP3, the warehouse's two-call answer (7,350 characters, 67%) is on the frontier. Adding its metadata call lifts Data360 to 46–50% at a cost of 16–19 thousand extra characters, more than half of them lists of countries, regions and years; UN DC stays at 19–21% whether or not it adds its own metadata call.

A standard-compliant response, built from the warehouse's own values and attributes with unpublished fields left as placeholders, takes 2,834 characters for 25 years of under-five mortality (2,929 once the placeholders are filled at typical lengths), fewer than the warehouse's current data response. With the warehouse's discovery call, it costs 9,149 and 4,747 characters for the two questions: about 15% more than the cheapest answer measured today for under-five mortality, and less than any answer measured for DTP3, for 100% of the standard.

5.3 Across sectors and countries

The pre-registered benchmark confirms the ranking on the standard but overturns the ranking on cost (Figure 3). On all 51 questions that both servers answered, the warehouse delivered more of the standard than UN DC: 46–70% against at most 21%. Data360 delivered 20–29%. But UN DC's answer was cheaper than the warehouse's on 43 of 58 questions. Median characters per question were 13.4 thousand for the warehouse, 8.9 thousand for UN DC and 4.2 thousand for Data360. The pilot questions had flattered the warehouse: its search returns a median 9.6 thousand characters for a custodian indicator name.

Search, not metadata, is what costs (Figure 4). Discovery takes 94% of UN DC's characters and 67% of the warehouse's, plus 10% for the warehouse's dimension listing. The data call, which carries the metadata, has a median of 1.9 thousand characters on the warehouse and 0.6 thousand on UN DC. UN DC's search has a long tail, up to 128 thousand characters for migrants in Brazil. Searches cost more for indicators with more breakdowns (Spearman correlation with the number of UN DC variables per code: 0.36 on UN DC, 0.60 on the warehouse). Data360 is cheap partly because its search fails: it found 4 of the 14 series it carries.

Table 3: Element-by-element status (M = meets, P = partly meets, – = missing), with the evidence for the warehouse

Element	Warehouse	UN DC	Data360	Warehouse evidence
R1 Reproducible query	M	P	P	echoes queryURL with flow, key and period
R2 Retrieval stamp	–	–	–	no timestamp or server version in responses
R3 Completeness statement	M	–	P	appliedDefaults, maxObs and the padded key are returned
S1 Identifiers	P	P	P	custodian code and flow key; no SDG series link
S2 Name and definition	P	–	P	definition only from the discovery call; no methodology link
S3 Unit	M	P	M	UNIT_MEASURE code and UNIT_MULTIPLIER; labels on request
S4 Breakdown	M	P	P	full SDMX key with _T totals
S5 Custodian and provenance chain	P	–	P	DATA_SOURCE mixes custodian, survey and pipe; CUSTODIAN only in nutrition
S6 Release and currency	P	–	P	release named inside DATA_SOURCE text for some flows; no date or series status
S7 Licence and citation	–	–	P	no licence or citation in the payload
O1 Source	P	–	P	DATA_SOURCE on 59% of observations; MNCH as bare codes
O2 Reference period	P	–	–	COVERAGE_TIME filled in six flows, nutrition and HIV among them (9% of observations); not in MNCH
O3 Nature and status	P	–	–	OBS_STATUS on 49%; none in WASH, gender, education, economic flows
O4 Uncertainty	P	–	–	bounds on 52% of observations; interval level never stated
O5 Footnote	M	–	–	observation, series and country notes passed through




Figure 2: The pilot frontier: characters returned against share of the standard delivered, Nigeria 2000–2025. Dashed line: measured frontier.




Figure 3: Characters and share of the standard for 140 answers to 58 questions (34 series; Nigeria, Brazil, Somalia). Unanswered questions at 0%; dashed lines are median characters per server.




Figure 4: Share of all characters returned, by component of the answer; sector and country benchmark, fixed paths.

All three servers answered every Nigerian question. The warehouse and UN DC each answered 10 of 12 questions for Brazil and 7 of 12 for Somalia, missing the same ones because UN DC copies the warehouse's gaps. A question with no data costs the warehouse a median 12.6 thousand characters and UN DC 0.6 thousand, because UN DC's search filters by country first. UN DC's values matched the warehouse's in every common year on 41 of 51 answered questions; most of the rest are older releases. Its latest year was the same on 37, earlier on 11 and later on 3. Data360 matched fully on 12 of 19 questions with common years, and its latest year was earlier on 6 of 22. Table 4 gives the medians by sector.

Table 4: Median characters and share of the standard, by sector (unanswered questions included)

Sector	Questions	UNICEF SDMX MCP	UN DC MCP	Data360 MCP
Child mortality	2	7.7k ·58%	9.4k ·17%	4.9k ·23%
Demography	2	16.1k ·60%	5.3k ·19%	7.2k ·29%
Early childhood development	2	15.2k ·68%	11.4k ·18%	–
Economy and aid	6	5.8k ·50%	3.6k ·21%	–
Education	2	13.8k ·52%	10.9k ·20%	4.5k ·25%
Functional difficulty	4	13.8k ·52%	17.4k ·19%	–
Gender	4	12.4k ·52%	6.7k ·21%	–
HIV/AIDS	4	17.6k ·68%	4.7k ·17%	–
Immunization	4	15.5k ·67%	11.7k ·21%	1.4k ·23%
Migration	6	13.8k ·54%	19.2k ·21%	2.9k ·27%
Maternal, newborn and child health	2	15.2k ·60%	11.8k ·19%	4.9k ·25%
Nutrition	2	19.4k ·65%	31.0k ·17%	5.2k ·20%
Child protection	2	14.1k ·64%	13.4k ·18%	1.5k ·21%
Child poverty	4	12.3k ·25%	1.1k ·9%	–
Social policy	4	3.8k ·48%	4.4k ·17%	3.9k ·29%
WASH	6	13.4k ·54%	8.8k ·21%	4.6k ·25%
Adolescents	2	13.5k ·63%	10.1k ·19%	–

5.4 Does the model or the effort level matter?

Every setting answered all 12 questions, and every value reported for a year the warehouse holds was correct (Figure 5, Table 5). Of the 1,953 year-values reported across the 96 sessions, all 1,952 for years the warehouse holds match it within rounding; the other is a year (2000) from a Data360 series the warehouse does not hold. Every reported number, including all 290 uncertainty bounds, appears in the server's own responses. The reference has 246 year-values

per setting; the two missing in every row are a coverage gap in Data360's antenatal care series.




Figure 5: Tokens received per question (median), MCP calls and years correct, by model and effort setting; 12 questions per setting.

Table 5: Cost and accuracy by model and effort setting (12 questions each)

Setting	Tokens sent per question	Tokens received per question	MCP calls	Characters per question	Years correct / reported	Metadata fields
Haiku, medium	655k	2,860	62	27.0k	244 / 244	7.9
Sonnet, low	587k	1,483	47	19.3k	244 / 244	7.9
Sonnet, medium	588k	1,569	46	18.0k	244 / 244	8.2
Sonnet, high	643k	1,805	57	21.9k	244 / 244	8.4
Opus, low	551k	1,308	38	22.5k	244 / 245	7.5
Opus, medium	639k	1,631	51	20.9k	244 / 244	8.1
Opus, high	690k	1,823	57	20.4k	244 / 244	8.1
Opus, medium (repeat)	563k	1,608	47	20.0k	244 / 244	8.1

Medians per question, except MCP calls (total over 12 questions) and metadata fields (mean).

Completeness depended on which series the agent picked. Data360 holds antenatal care in two series: the Human Capital Project series starts in 2010 and misses 2003 and 2008; the Health, Nutrition and Population series ends in 2018 and misses the two latest surveys. Only Opus at low effort picked the second, so its latest value was from 2018.

Higher effort bought more calls, not better answers. For Opus, MCP calls rose from 38 to 51 to 57 across low, medium and high effort, and tokens received from 1,308 to 1,631 to 1,823 per question. Sonnet's tokens received rose in the same way (1,483 to 1,805). Haiku made the most calls (62) and generated the most tokens: 2,860 per question, about 1.8 times Sonnet at medium effort.

The values were stable; the cost and the metadata were not (Table 6). Repeating Opus at medium effort reproduced the series and values in all 12 cells, but tokens sent per question changed by up to 22%, and the median fell 12%: about half the gap between low and high effort for Opus (+25%). The servers behaved deterministically: on UN DC, 11 of 18 repeated calls were byte-different only because JSON keys came back in a different order. One warehouse call, `get_flow_structure` for the child-mortality flow, returned 1.3 million characters; the client refused it and the agent answered without it.

Table 6: Consistency and grounding

Check	Result
Question × server cells where all 8 runs returned identical values	11 of 12
Cells where all 8 runs chose the same series identifier	9 of 12
Largest spread in metadata fields reported within a cell	5 fields
Repeat run: same series and values	12 of 12 cells
Repeat run: same number of MCP calls	9 of 12 cells
Identical calls in different sessions returning identical content	67 of 68
Reported values found in the server's responses	1,953 of 1,953
Reported uncertainty bounds found in the server's responses	290 of 290

Where the tokens go. Tokens sent were about 356 times tokens received. Most are not caused by the server: 84% is the client's own baseline of about 97,000 tokens re-sent with every request, and 88% of all tokens sent were cache reads. Of what the server adds, its tool definitions dominate (Figure 6). Loading a server's tools adds about 15,000 tokens (UN DC, six tools), 20,000 (warehouse, 31 tools) or 22,000 (Data360, 16 tools) to every later request. Over a question of 4 to 6 requests that is 70,000–80,000 tokens on average, against 17,000–33,000 for all responses and reasoning together. Tool count alone does not set the cost: UN DC's six tools weigh almost as much as the warehouse's 31, because their descriptions are long. By characters, the largest items were Data360's `get_metadata` (18,600 per call) and UN DC's instruction file (12,000, read once per session); without it, UN DC needed a median of 8.1 thousand characters per question, against 16.6 thousand for the warehouse and 27.3 thousand for Data360.




Figure 6: Tokens sent per question by component, mean of 32 sessions per server. Definitions: the jump in context when the server's tools load, times later requests.

6 Policy implications

6.1 For an official UNICEF MCP

1. **Return values and the fifteen elements in one data call.** The metadata travels in the cheap part of the answer, and an agent rarely makes a second call. The gaps to close are a retrieval stamp (R2), a structured release and currency field (S6), licence and citation (S7), and status and bounds in the flows where they are empty (O3, O4), with the interval level stated.
2. **Make discovery compact.** Search should return a short ranked list of identifiers and names, filtered by country first, and leave definitions, units and flow lists to the data response; this

is where 67% of the warehouse's characters go, plus 10% for structure.

3. **Keep the tool list short and its descriptions tight.** Tool definitions are re-sent with every request and in agentic use cost more tokens than the data. A small core set with advanced tools behind it would cut the largest server-attributable cost.
4. **Cap and page every response**, so that no single call can return 1.3 million characters.
5. **Declare the response schema** through `outputSchema` and return conforming `structuredContent`.
6. **Test conformance and cost continuously**, with the fixed query sets and scoring scripts used here, reporting share of the standard, characters, tokens sent and received, accuracy and stability across repeated runs.

6.2 For republishers

Pass through, never drop: almost all of UN DC's gaps are attributes the warehouse already publishes. Start with custodian attribution (S5) and release (S6), which answer the attribution concerns custodian agencies have raised and expose stale copies. Mark the canonical series: agents split between duplicate copies of the same series, and where the copies differ in coverage the choice changed the answer.

6.3 For the statistical community

The standard reuses SDMX and SDG attributes, so it asks custodians for nothing new. It can be tabled at the CCS-UN as the minimum any server that republishes custodian data should meet, with S5, S6 and S7 first, and proposed to the UN System Data Commons under UN80 Workstream 16.

6.4 For evaluating agents on official data

Monitor tokens sent and received separately: they differ by two orders of magnitude and respond to different design choices. Do not assume a smaller model is cheaper per answer, or that higher effort improves accuracy on well-specified questions. Repeat runs: run-to-run noise in cost was about half the effect of effort.

7 Final remarks

A modest standard of fifteen elements, built entirely from attributes the statistical system already defines, would let an agent reproduce, attribute, date and interpret every value, at no more than the cost of today's cheapest answers. The servers differ far more in what they pass through than in what they cost; cost is driven by search and by the tool list rather than by the data; and the model or effort level changes the cost but not the values. The design of the server, not the choice of model, decides whether an answer is complete and attributable.

Limitations. The agentic benchmark covers four series for one country with one repeat; the sector benchmark covers three countries; both are snapshots of servers that change. The warehouse is both a server under test and the reference, so a value it has wrong would not be detected. The client's baseline is specific to the agent harness used, although the tool-definition and response components are not. Claude Fable 5.1 and other model families were not tested. The prompt was well specified; open-ended or ambiguous questions may separate models more. Partial scores involve judgement, although the automated rules reproduce the hand scores of the pilot.

Next steps. Run the agentic benchmark with at least three repeats per setting, on more countries and open-ended questions; run all three benchmarks against the prototype of the official UNICEF MCP before and after implementing the standard and a compact search; and publish the query sets and scoring as a conformance test any republishing server can run.

Reproducibility

Every number in the text is a macro written by `paper/code/assets.py` from the analysis outputs, every table is generated and every figure is drawn from the same files; `make all` rebuilds the analysis, the assets and this PDF from the saved server responses and agent transcripts in the repository. Collection (querying live servers with agents) is documented but not re-executed by `make`, since the servers change.

References

Committee for the Coordination of Statistical Activities. Principles governing international statistical activities, 2005. Endorsed 14 September 2005; good practices amended 7 March 2016.

Model Context Protocol. Model context protocol specification, version 2026-07-28: Tools, 2026. outputSchema, structuredContent and resource links.

SDMX Sponsors. Statistical data and metadata exchange (SDMX) standards. Including the REST web-service specification and the cross-domain concepts OBS_STATUS, UNIT_MEASURE and UNIT_MULT.

UN IGME. Levels and trends in child mortality: Report 2025. Technical report, United Nations Inter-agency Group for Child Mortality Estimation, 2025.

United Nations Statistical Commission. Guidelines on data flows and global data reporting for sustainable development goals, 2018. Background document, 49th session.

United Nations Statistics Division. Guidelines for the global data structure definition for sustainable development goals indicators. Technical report, United Nations Statistics Division, 2019. DSD version 1.0.

Mark D. Wilkinson et al. The FAIR guiding principles for scientific data management and stewardship. *Scientific Data*, 3:160018, 2016.