

Lecture 3: Data Representation II — Addresses, Pointers & Arrays

Session 3 · Wed Sep 2, 2026


Contents

Memory Is a Row of Numbered Boxes	1
Pointers Demystified	2
Three Things, Kept Straight	2
Two Pointers, One Object	2
Pointer Arithmetic	3
Run It: the Addresses Step by Four	3
An Array Is Not a Pointer	4
Arrays Decay to Pointers	4
Strings Are Char Arrays	4
Two-Dimensional Arrays	5
Run It: Rows End to End	5
Why the Order Matters	5
The Stack	6
Pointers to Pointers	6
Null Pointers	6
Practice	7
Reading	7

Memory Is a Row of Numbered Boxes

Last time we filled in one byte. Today: where the bytes *live*.

Memory is a row of numbered boxes, one byte each



The small number under each box is its **address**. One box holds one byte.

Every byte your program can touch has a number — its **address**. Nothing more mysterious than house numbers along a street — though they run large, so we write them in hex: `0x7ffd4a08`, not `2147305992`.

Note


This row is your program's own **virtual address space**. Each running program gets one, and the operating system keeps them apart (*Lecture 9*). An optimizing compiler may also keep a value only in a register, where it has no address at all.

Pointers Demystified

A **pointer** is a variable whose value is an address.

```
int x = 42;
int *p = &x;           // &x is "the address of x"
printf("%d\n", *p);    // 42 - *p is "the value at that address"
```

A pointer is a box whose contents is an address



&x is the address of x. ***p** is the value stored there.

Three Things, Kept Straight

Expression	Type	Value
x	int	42
&x	int *	the address of x
*p	int	42

Read the declaration `int *p` as “`*p` is an `int`” — which is exactly what the last row says.

Tip

`&` and `*` undo each other: `*&x` is `x`.

Two Pointers, One Object

Nothing stops two pointers from designating the same object:


```
int x = 42;
int *p = &x;
int *q = &x;           // q points at the same int

*p = 99;
printf("%d\n", *q);    // 99 - q sees the change
printf("%d\n", x);     // 99 - and so does x
```

Two names, one box. This is called **aliasing**. It is why a function handed two pointers may not assume they point at different things — and exactly why `memmove` exists alongside `memcpy`, for the case where the two regions overlap.

Pointer Arithmetic

p + 1 moves one int, not one byte



One int is 4 bytes here, so +1 steps 4 bytes. The compiler does the multiplying.

```
int arr[5] = {10, 20, 30, 40, 50};
int *p = arr;      // p points at arr[0]

*(p + 2) = 99;     // arr[2] becomes 99
```

Rule: $p + i$ moves $i * \text{sizeof}(*p)$ bytes — you count elements, the compiler counts bytes. Subtraction matches: $\&\text{arr}[3] - \&\text{arr}[0]$ is 3, not 12. And $a[i]$ is *defined* as $*(a + i)$, in the standard itself.

Run It: the Addresses Step by Four


```
int arr[5] = {10, 20, 30, 40, 50};
for (int i = 0; i < 5; i++)
    printf("arr[%d] = %-3d  &arr[%d] = %p\n", i, arr[i], i, (void *)&arr[i]);
printf("&arr[3] - &arr[0] = %ld\n", (long)(&arr[3] - &arr[0]));
```

```
arr[0] = 10   &arr[0] = 0x16b106960
arr[1] = 20   &arr[1] = 0x16b106964
arr[2] = 30   &arr[2] = 0x16b106968
arr[3] = 40   &arr[3] = 0x16b10696c
arr[4] = 50   &arr[4] = 0x16b106970
&arr[3] - &arr[0] = 3
```

...960, 964, 968, 96c, 970 — four apart, every time. Your addresses will be different numbers; the spacing will not.

An Array Is Not a Pointer

An array is all the boxes. A pointer is one box.



Both let you write `arr[2]`. Only one of them owns the storage.

```
int arr[5];           // five ints of storage
int *ptr = arr;       // one address, pointing into that storage

sizeof(arr);         // 20 on our teaching systems (5 × 4)
sizeof(ptr);         // 8 on our teaching systems

arr = ptr;           // ERROR: an array name is not assignable
```

Arrays Decay to Pointers

In a parameter declaration, C **adjusts** `int a[]` to `int *a`. These two lines declare the same function:

```
void foo(int a[]);    // what you wrote
void foo(int *a);     // what the compiler sees
```

So the array-ness is gone by the time the function body runs:

```
void foo(int a[]) {
    sizeof(a);        // 8 here – a is a pointer
}
```

The length does not travel with the pointer. Pass it yourself:

```
void foo(int *a, size_t n);
```

Strings Are Char Arrays

C has no string type. A “string” is a `char` array ending in a zero byte, `'\0'` — that terminator is how every library function knows where to stop.

```
#include <string.h>

char    arr[] = "hello"; // 6 bytes: h e l l o \0 – writable
const char *ptr = "hello"; // a pointer to a string literal


sizeof(arr); // 6 – the array, terminator included
strlen(arr); // 5 – characters before the terminator
sizeof(ptr); // 8 – just a pointer
arr[0] = 'H'; // fine
ptr[0] = 'H'; // won't compile – and that is the point
```

Tip

Say `const char *` for a string literal. Plain `char *` compiles too, but then writing through it is undefined behavior your compiler never mentions. `const` turns a crash you might not hit into an error you cannot miss.

Two-Dimensional Arrays

`int a[3][4]` is not a grid in memory. It is three rows of four, stored one row after the next — **row-major** order.

A 2-D array is rows laid end to end

`a[i][j]` is element $i*4 + j$

Stepping `j` moves one slot. Stepping `i` jumps a whole row — four slots.

```
int a[3][4];
sizeof(a);      // 48 — the whole thing
sizeof(a[0]);   // 16 — one row of four ints
```

Run It: Rows End to End

```
int a[3][4];
for (int i = 0; i < 3; i++, printf(" <- row %d\n", i - 1))
    for (int j = 0; j < 4; j++) printf("%p ", (void *)&a[i][j]);
```

```
0x16fac6948 0x16fac694c 0x16fac6950 0x16fac6954 <- row 0
0x16fac6958 0x16fac695c 0x16fac6960 0x16fac6964 <- row 1
0x16fac6968 0x16fac696c 0x16fac6970 0x16fac6974 <- row 2
```

Read across, then down: `...954` ends row 0 and `...958` starts row 1 — the next four bytes. There is no gap between the rows, because there are no rows. It is one run of twelve ints.

Why the Order Matters

Walking a 2-D array along rows touches neighbouring bytes. Walking it down columns jumps a whole row every step:

```
for (i..) for (j..) sum += a[i][j]; // row-major: steps 4 bytes
for (j..) for (i..) sum += a[i][j]; // column-major: jumps 4*ncols bytes
```

Same additions, same answer. In Lecture 1 the column-major version took **26 times longer** on a 4096×4096 array. Now you can see why the two loops are not the same journey through memory — Lecture 16 explains what the hardware does about it.

The Stack

```
void bar(void) {
    int a = 1, b = 2, c = 3;
}
```

Every call gets its own frame



The stack grows downward. Where a, b and c sit **inside** the frame is the compiler's choice.


Warning

The frame is real; the arrangement *inside* it is not. Print `&a`, `&b`, `&c` and compare with your neighbour — then never depend on what you saw.

Pointers to Pointers

```
int x = 42;
int *p1 = &x;    // pointer to int
int **p2 = &p1;  // pointer to pointer to int
int ***p3 = &p2; // and one more
```

Each extra * follows one more arrow



`*p3` is p2 • `**p3` is p1 • `***p3` is 42

You have already used one: `main(int argc, char **argv)` receives a sequence of pointers, each pointing at one command-line argument.

Null Pointers

NULL is the pointer value that means “points at nothing”.

```
int *p = NULL;
*p = 42;      // undefined behavior – on our systems, usually a crash
```

Check before you follow:

```
if (p != NULL) {  
    *p = 42;  
}
```

Note

“Usually a crash” is the *good* case: the failure is loud and immediate. Undefined behavior is not required to crash at all.

Practice

1. Given `int a[10]; int *p = a;` — why does `p + 1` refer to `a[1]` rather than to the next byte?
2. `p` is an `int *` holding `0x1000`. What address is in `p + 2`? What if `p` had been a `char *` instead?
3. Why does `sizeof` report 40 inside `main` but 8 inside a function you passed the array to?
4. `char *s = "hello"; s[0] = 'H';` compiles. What happens when you run it, and why does `char s[] = "hello"; s[0] = 'H';` behave differently?
5. Write a function taking `int **` that swaps which array two pointers refer to.

Reading

- CS:APP §3.8 (Array Allocation and Access)
- The Descent to C — a careful pointer explainer