

Homework 3

Stat 215A, Fall 2020

Due: Push a `homework3.pdf` file to the `lab3/` folder of your `stat-215-a` GitHub repo by Thursday 10/22 at 11:59pm

1 EM Algorithm

Suppose X_1, \dots, X_n are i.i.d. observations from a mixture of two Poisson distributions, $\text{Pois}(\mu_0)$ and $\text{Pois}(\mu_1)$, with mixing probabilities of π and $1 - \pi$, respectively. That is, there is an initial probability π that an observation X_i is drawn from $\text{Pois}(\mu_0)$ and probability $1 - \pi$ from $\text{Pois}(\mu_1)$.

Recall that if $X \sim \text{Pois}(\mu)$, the probability density function is given by

$$p_\mu(x) = \frac{\mu^x e^{-\mu}}{x!}.$$

1. Define the observed data vector, the latent variable vector, and the distribution of the latent variable.
2. Write down the E step for estimating μ_0, μ_1, π .
3. Write down the M step for estimating μ_0, μ_1, π .
4. Give an initial estimator to start the EM algorithm.
5. Write R code to implement the E and M steps.
6. Simulate data from a mixture of two Poisson distributions, where you know the true parameters, and run your EM algorithm on the simulated data. Show the accuracy of EM clustering as you vary the values of μ_0 and μ_1 .
7. Now simulate data from a mixture of two binomial distributions, $\text{Binom}(100, \pi_0)$ and $\text{Binom}(100, \pi_1)$. Show the accuracy of your Poisson EM clustering algorithm as you vary the values of π_0 and π_1 in this misspecified model.