

Proportional Control for Maneuvering Flapping Flight

Jean Pecquet

June 5, 2026

1 Model Description

Table 1 lists the nondimensionalized parameters in the dynamic model. Ranges for the parameters L_w^* , A_w^*/m^* , and ω^* were obtained from the morphological data in [1] and the wingbeat frequency data in [2] for *Anisoptera*.

Table 1: Dimensionless Parameters

Parameter	Description	Range
$L_w^* = \frac{L_w}{L}$	Wing length ratio	[0.65, 0.85]
$A_w^*/m^* = \frac{A_w \rho_{\text{air}} L}{m}$	Inverse wing loading (per wing)	[0.05, 0.25]
$\omega^* = \omega \sqrt{\frac{L}{g}}$	Wing beat frequency	[8, 20]
γ_0	Wing stroke plane angle	[-180°, 180°]
ϕ_1	Wing flapping amplitude	[0°, 60°]
ψ_0	Mean wing pitch angle	[-60°, 60°]
ψ_1	Wing pitch amplitude	[0°, 60°]
δ_0	Wing pitch phase	[-180°, 180°]
σ_0	Fore/hind phase	[-180°, 180°]

Lift and drag coefficients are given by

$$C_L = C_{L,0} \sin 2\alpha$$

$$C_D = C_{D,0} \cos^2 \alpha + C_{D,\frac{\pi}{2}} \sin^2 \alpha$$

with $C_{L,0} = 1.5$, $C_{D,0} = 0.1$, $C_{D,\frac{\pi}{2}} = 2$

2 Equilibrium Solution Space

2.1 Stationary Flight

A good first step might be to identify those parameter values that give an average aerodynamic force over a cycle that is equal to or greater than the weight, i.e. $F_a^* = \frac{F_a}{m_b g} \geq 1$. Outside of this group of solutions, hovering and meaningful manoeuvring flight cannot be achieved. This is independent of the stroke plane angle γ_0 and the fore/hind phase shift σ_0 , which limits us to just 7 parameters. We can further eliminate one parameter by collapsing L_w^* and ϕ_1 into a single wing tip displacement amplitude parameter $s_0^* = \frac{2}{3} L_w^* \phi_1$, resulting in 6 morphological and wingbeat parameters.

As a first, quick verification we compare the $F_a^* = 1$ contour result in the $(A^*/m^*, \omega^*)$ plane to the simplified analytical result of [3] for a translating element with constant 45° pitch through each beat half:

$$(F_a^*)_{\text{constant pitch}} = \frac{C_{L,0}}{4} \frac{A^*}{m^*} (s_0^* \omega^*)^2 \quad (1)$$

Note $A^* = 4A_w^*$. The result is obtained for $s_0^* = 1.5$ (achieved in practice with a small ϕ_1 and a large L_w^*), $\psi_0 = 0^\circ$, $\psi_1 = 45^\circ$, and $\delta_0 = 90^\circ$. Crucially we do this assuming zero body velocity: the velocity of the wings relative to the air is equal to the velocity of the wings relative to the body. Contours are shown in Figure 1. Using a single wing element at the $\frac{2}{3}$ -span station, there is very close agreement, as expected, with a small difference attributable to the sinusoidal wing pitch (as opposed to a square wave). The wing element spends less time at large angle of attack so the mean force is slightly lower. As the number of elements is increased F_a^* converges to a lower value (by about 25%), causing the contour to shift towards higher A^*/m^* and ω^* .




Figure 1: Verification of $F_a^* = 1$ contour at reference condition

The present model allows for more complex wing motions than a simple symmetric stroke: the mean pitching angle ψ_0 may be nonzero, and the phase shift δ_0 between the pitching and flapping motions may be different from 90° . One question we can ask is whether the contribution of the pitch to the force magnitude F_a^* can be represented as a coefficient that would depend on $(\psi_0, \psi_1, \delta_0)$, independent of the other 3 parameters. Looking back to the simple analytical expression for F_a^* for constant pitch, we can extract the dimensionless dynamic pressure

$$q^* = \frac{1}{4} \frac{A^*}{m^*} (s_0^* \omega^*)^2 = \frac{A_w^*}{m^*} (s_0^* \omega^*)^2 \quad (2)$$

We can then evaluate F_a^*/q^* and check whether it is independent of $(\frac{A_w^*}{m^*}, s_0^*, \omega^*)$ over the parameter space, i.e. whether the two groups of variables can be cleanly separated. Again, we do this first assuming zero body velocity, such that $F_a^* = 1$, applied in the right direction, would result in a hover. As can be seen in Figure 2, the separation is clean, with small amounts of scatter associated with the nonlinearity of the flapping motion. The right side of the plot is obtained by picking a reference amplitude ($s_0^* = 0.3$, or $\phi_1 \approx 30^\circ$) to evaluate F_a^* . The sensitivity to the choice of s_0^* is very small, about 1 to 2%. The result is completely independent of A_w^*/m^* and ω^* because they appear purely as multiplicative factors in the analytical expression. It might be clearer to do a purely analytical treatment of this part.

This decomposition appears to be useful because C_ψ provides a measure of the power efficiency of the wingbeat. A given net force can be achieved with a faster or slower wingbeat depending on the wing pitch




Figure 2: Separation of dynamic pressure and wing pitch factors of the aerodynamic force at zero body velocity. (a) Scatter of mean aerodynamic force as a function of dynamic pressure for random sampling of parameter space (b) Collapse of scatter by introduction of C_ψ parameter evaluated as F_a^*/q^* for a reference amplitude value $s_0^* = 0.3$

pattern. If the pattern is such that C_ψ is high, then the wing doesn't have to beat as fast, and less energy is expended (provided any additional energy required to impart that particular pitch motion does not cancel out this benefit, which seems like more of an edge case). Presumably then, values of ψ_0 , ψ_1 , and δ_0 that result in higher C_ψ would be preferred in nature. Looking again at the simplified case from earlier it seems the optimum should sit near $\psi_0 = 0$, $\psi_1 = 45^\circ$, $\delta_0 = 90^\circ$, since a 45° angle of attack maximizes lift (limit case for square wave pitch: $C_\psi = C_{L,0}$).

We show the dependence of C_ψ on the three parameters in Figure 3. Again, C_ψ here is obtained by taking $s_0^* = 0.3$, but this value has little effect on C_ψ as seen in the scatter plot from earlier. The result is what we expect, with ψ_1 slightly larger than 45° to provide a mean angle of attack that is closer to 45° . The dependence of F_a^* on δ_0 is symmetric but the force direction depends on the sign, we highlight $\delta_0 = +90^\circ$ since with our conventions it results in a force in the direction of the leading edge. This optimal value of C_ψ is slightly smaller than $C_{L,0}$. Note that because the optimal pitch pattern is symmetric, the drag coefficient has no effect (drag component cancels out over the two halves of the wingbeat). We notice that with more wing elements, the optimal C_ψ is lower, converging to a value just above unity. This suggests the following approximate criterion for hover feasibility, which may also extend to maneuverability

$$\frac{A_w^*}{m^*} (s_0^* \omega^*)^2 \geq 1 \quad (3)$$

The corresponding 3D surface is shown in Figure 4. The required wingbeat amplitude ϕ_1 for a given $(\frac{A_w^*}{m^*}, \omega^*)$ can be recovered by

$$\phi_1 = \frac{3}{2} \frac{s_0^*}{L_w^*}$$

The very high amplitudes ($\phi_1 \approx 60^\circ$) associated with low values of both $\frac{A_w^*}{m^*}$ and ω^* suggest such combinations probably do not occur, and that the parameter space can be further restricted. The data source for ω^* does not report measurements necessary to obtain $\frac{A_w^*}{m^*}$, but we could maybe find other sources.




Figure 3: Dependence of C_ψ on pitch parameters at zero body velocity. Optimal value shown as white dots.

C_ψ may deviate from its "optimum" value. At this value, the wingbeat is symmetric, meaning the net force vector is normal to the stroke. This means hovering at the optimum C_ψ requires a horizontal stroke plane. Dragonflies however are known to hover with an inclined stroke plane, which could be due to efficiency considerations that we have ignored (picking the maximum C_ψ may not be exactly optimal energy-wise, even if it minimizes s_0 , or our model simply does not capture other real effects that lead to the inclined stroke plane being advantageous). Without going too deep into these energy considerations at least for now, it is interesting at this point to consider the effect of the pitch parameters not just on the force magnitude but on its *direction* relative to the stroke plane. With an inclined stroke (angle γ to the horizontal), hover (or vertical flight) requires the net aerodynamic force vector to be angled by $-\gamma$ to the stroke plane normal.

We denote the force direction angle relative to the stroke plane with β . We find numerically (and could probably show analytically) that β depends only on the mean pitch angle ψ_0 , and on the sign of δ_0 . To be exact, there is a slight variation in $\beta(\psi_0)$ over the range of ψ_1 and $|\delta_0|$ on the order of 0.1° to 1° depending on the wingbeat amplitude. We also find that the (ψ_1, δ_0) that maximizes C_ψ is invariant with ψ_0 . We show $\beta(\psi_0)$ in Figure 5 along with the optimal C_ψ at a given ψ_0 .

Two observations from the plot: (a) β is monotonous in ψ_0 , so ψ_0 can be used conveniently as a control variable for the force direction, in addition to the stroke plane angle γ , and (b) the wing stroke is just as good at producing an in-plane force (when $\psi_0 = 90^\circ$) as it is an out-of-plane force ($\psi_0 = 0$) since $C_\psi^{\max}$ has the same value at both conditions.

Hover Controller

The above insights suggest a few possible ways to achieve hover control. Candidates for control variables can be split into two groups: those that control force magnitude (ϕ_1, ω^* through q^* and ψ_1, δ_0 through C_ψ), and those that control force direction (γ_0, ψ_0). For simplicity, we would rather consider ω^* to be a fixed parameter, so we will exclude it at least for now. We will also consider γ_0 to be fixed for now. In addition, it is beneficial to keep C_ψ at or near its maximum value, which sets ψ_1 and δ_0 . This leaves ϕ_1 (or s_0^*) for magnitude and ψ_0 for direction.




Figure 4: Approximate region of hover feasibility, with boundary surface.

2.2 Moving and Maneuvering Flight

So far we have focused on stationary flight, with at most small amplitude motions about a stationary or slowly drifting position. That is the case where the body velocity relative to the air is much less than the wing velocity relative to the body ($v_b^* \ll s_0^*$). Since we are interested not just in hover but in maneuvering flight, we need to consider the case where $v_b^* \sim s_0^*$, perhaps even $v_b^* \gg s_0^*$.

References

- [1] J. M. Wakeling. Odonatan wing and body morphologies. *Odonatologica*, 26(1):35–52, 1997. URL <https://natuurtijdschriften.nl/pub/592186>.
- [2] C. Aracheloff, R. Garrouste, A. Nel, R. Godoy-Diana, and B. Thiria. Subtle frequency matching reveals resonant phenomenon in the flight of Odonata. *Journal of The Royal Society Interface*, 21(219), 2024. doi: 10.1098/rsif.2024.0401.
- [3] Owen C. Wetherbee and Z. Jane Wang. Stable flapping flight in morphological space: Model, simulation, and explicit stability criteria. *Proceedings of the National Academy of Sciences*, 123(18):e2533138123, 2026. doi: 10.1073/pnas.2533138123. URL <https://www.pnas.org/doi/abs/10.1073/pnas.2533138123>.




Figure 5: Effect of ψ_0 on force direction and wing stroke efficiency.