【资源】NLP多标签文本分类代码实现工具包

专知 2019-11-20

【导读】本文为大家推荐一份多标签文本分类代码实现工具包，希望对大家有所帮助。

原文链接：

https://github.com/RandolphVI/Multi-Label-Text-Classification



2019/11/20 RandolphVI/Multi-Label-Text-Classification: About Muti-Label Text Classification Based on Neural Network.

RandolphVI / **Multi-Label-Text-Classification**

About Muti-Label Text Classification Based on Neural Network.

#text-classification #python3 #tensorflow #sentence-classification #multi-label-classification

2 commits | **1** branch | **0** packages | **0** releases | **1** contributor | Apache-2.0

Branch: master ▾ | New pull request | Create new file | Upload files | Find file | Clone or download ▾

RandolphVI Update README.md — Latest commit `eb9ff3a` on 16 Apr

ANN	Initial commit	8 months ago
CNN	Initial commit	8 months ago
CRNN	Initial commit	8 months ago
FastText	Initial commit	8 months ago
HAN	Initial commit	8 months ago
RCNN	Initial commit	8 months ago
RNN	Initial commit	8 months ago
SANN	Initial commit	8 months ago
data	Initial commit	8 months ago
utils	Initial commit	8 months ago
.gitignore	Initial commit	8 months ago
.travis.yml	Initial commit	8 months ago
LICENSE	Initial commit	8 months ago
README.md	Update README.md	7 months ago
requirements.txt	Initial commit	8 months ago

README.md

Deep Learning for Multi-Label Text Classification

language python3.6 | build passing | code quality A | license Apache-2.0 | issues 11 open

This repository is my research project, and it is also a study of TensorFlow, Deep Learning (Fasttext, CNN, LSTM, etc.).

The main objective of the project is to solve the multi-label text classification problem based on Deep Neural Networks. Thus, the format of the data label is like [0, 1, 0, ..., 1, 1] according to the characteristics of such a problem.

Requirements

- Python 3.6
- Tensorflow 1.1 +
- Numpy
- Gensim

Innovation

Data part

1. Make the data support **Chinese** and English (Which use `jieba` seems easy).
2. Can use **your own pre-trained word vectors** (Which use `gensim` seems easy).

https://github.com/RandolphVI/Multi-Label-Text-Classification 1/6



3. Add embedding visualization based on the **tensorboard**.

Model part

1. Add the correct **L2 loss** calculation operation.
2. Add **gradients clip** operation to prevent gradient explosion.
3. Add **learning rate decay** with exponential decay.
4. Add a new **Highway Layer** (Which is useful according to the model performance).
5. Add **Batch Normalization Layer**.

Code part

1. Can choose to **train** the model directly or **restore** the model from the checkpoint in `train.py` .
2. Can predict the labels via **threshold** and **top-K** in `train.py` and `test.py` .
3. Can calculate the evaluation metrics --- **AUC** & **AUPRC**.
4. Add `test.py` , the **model test code**, it can show the predicted values and predicted labels of the data in Testset when creating the final prediction file.
5. Add other useful data preprocess functions in `data_helpers.py` .
6. Use `logging` for helping to record the whole info (including **parameters display**, **model training info**, etc.).
7. Provide the ability to save the best n checkpoints in `checkmate.py` , whereas the `tf.train.Saver` can only save the last n checkpoints.

Data

See data format in `data` folder which including the data sample files.

Text Segment

You can use `jieba` package if you are going to deal with the Chinese text data.

Data Format

This repository can be used in other datasets (text classification) in two ways:

1. Modify your datasets into the same format of the sample.
2. Modify the data preprocess code in `data_helpers.py` .

Anyway, it should depend on what your data and task are.

🤔**Before you open the new issue about the data format, please check the `data_sample.json` and read the other open issues first, because someone maybe ask me the same question already. For example:**

- 输入文件的格式是什么样子的?
- Where is the dataset for training?
- 在 data_helpers.py 中的 content.txt 与 metadata.tsv 是什么，具体格式是什么，能否提供一个样例?

Pre-trained Word Vectors

You can pre-training your word vectors (based on your corpus) in many ways:

- Use `gensim` package to pre-train data.
- Use `glove` tools to pre-train data.
- Even can use a **fasttext** network to pre-train data.

Network Structure

FastText



References:

- Bag of Tricks for Efficient Text Classification

TextANN



2019/11/20 RandolphVl/Multi-Label-Text-Classification: About Muti-Label Text Classification Based on Neural Network.

sigmoid
dropout
Fully Connected Layer
average
Sentence matrix m x k
A single feature vector k (embedding_dim)
A single feature vector 1024 (fc_hiddent_size)
367 univariate vectors Each element represents the class and the its value represents the probability of this class.
embedding dim = k
函数
VARf
定义域
⋮
值域
TARGET
max_sequence_length = m
height = k (embedding_dim)
height = 1024 (fc_hidden_size)
height = 367 (num_classes)

References:

- Personal ideas 🙃

TextCNN

activation function
Convolution
1-max pooling
sigmoid
dropout
Sentence matrix m x k
3 region sizes: (3, 4, 5) 128 filters(num_filters) for each region size totally 384 filters
128 feature maps (num_filters) for each region size
384 univariate vectors concatenated together to form a single feature vector
367 univariate vectors Each element represents the class and the its value represents the probability of this class.
embedding dim = k
函数
VARf
定义域
⋮
值域
TARGET
max_sequence_length = m
num_filter = n
out_height = m - 5 + 1
out_height = m - 4 + 1
out_height = m - 3 + 1
height = 128 (num_filter)
height = 128 * 3 (num_filter * filter_numbers)
height = 367 (num_classes)

References:

- Convolutional Neural Networks for Sentence Classification

https://github.com/RandolphVI/Multi-Label-Text-Classification 4/6

- A Sensitivity Analysis of (and Practitioners' Guide to) Convolutional Neural Networks for Sentence Classification

TextRNN

Warning: Model can use but not finished yet 🤪!



TODO

1. Add BN-LSTM cell unit.
2. Add attention.

References:

- Recurrent Neural Network for Text Classification with Multi-Task Learning

TextCRNN



References:



2019/11/20 RandolphVI/Multi-Label-Text-Classification: About Muti-Label Text Classification Based on Neural Network.

- Personal ideas 🙃

TextRCNN

activation function
Bi-lstm
Convolution
1-max pooling
concat
sigmoid
dropout
Sentence matrix m x k
Bi-lstm Layer outputs (->): [seq_len, lstm_hidden_size] (<-): [seq_len, lstm_hidden_size]
3 region sizes: (3, 4, 5) 128 filters(num_filters) for each region size totally 384 filters
128 feature maps (num_filters) for each region size
Pooled flat vectors 128 (num_filter)
384 univariate vectors concatenated together to form a single feature vector
367 univariate vectors Each element represents the class and the its value represents the probability of this class.
embedding dim = k
lstm_hidden_size * 2
TARGET

References:

- Personal ideas 🙃

TextHAN

References:

- Hierarchical Attention Networks for Document Classification

TextSANN

Warning: Model can use but not finished yet 🤪!

TODO

1. Add attention penalization loss.
2. Add visualization.

References:

- A STRUCTURED SELF-ATTENTIVE SENTENCE EMBEDDING

About Me

黄威，Randolph

SCU SE Bachelor; USTC CS Master

Email: chinawolfman@hotmail.com

My Blog: randolph.pro

LinkedIn: randolph's linkedin

https://github.com/RandolphVI/Multi-Label-Text-Classification 6/6

-END-

专 · 知