

GNU APL Reference Card

(for GNU APL version 1.8)

Use `C-x gnu-apl` to start GNU APL in Emacs.

Emacs mode

Interaction mode:

beginning of defun	C-M-a
end of defun	C-M-e
find function at point	M-.
apropos symbol	C-c C-a
edit function	C-c C-f
show help for symbol	C-c C-h
finnapl list	C-c TAB
show keyboard	C-c C-k
plot line	C-c RET
edit variable	C-c C-v
trace	C-c C-.

Edit mode:

go to beginning of defun	C-M-a
go to end of defun	C-M-e
find function at point	M-.
apropos symbol	C-c C-a
interactive send current function	C-c C-c
help for symbol	C-c C-h
finnapl list	C-c TAB
show keyboard	C-c C-k
interactive send buffer	C-c C-l
interactive send region	C-c C-s
switch to interactive	C-c C-z
trace	C-c C-.
indent	C-M-q

System

Notation for commands:

F	filename	L	library	P	path
G	logging facility	O	object	S	symbol
W	workspace				

APL standard commands

check workspace integrity)CHECK
clear workspace)CLEAR
save workspace as CONTINUE and exit)CONTINUE
copies objects from given workspace)COPY [L] W [0 ...]
remove W)DROP [L] W
dump W (readable, HTML escaped))DUMP-HTML [[L] W]
dump W (readable APL))DUMP [[L] W]
dump W (readable APL, verbose))DUMPV [[L] W]
erase symbol(s))ERASE S ...
show functions)FNS [from-to]
help)HELP [primitive]
history)HIST [CLEAR]
runs command on host)HOST command ...

loads workspace (IBM .atf format))IN F [0 ...]
show libraries and paths)LIBS [[L] path]
show saved workspaces)LIB [L P] [from-to]
load workspace W)LOAD [L] W
show more error info)MORE
lists symbols matching name)NMS [from-to]
quit APL)OFF
show operators)OPS [from-to]
dump workspace (IBM .atf format))OUT name [0 ...]
protects during copying)PCOPY [L] W [0 ...]
protects during loading)PIN F [0 ...]
quiet load)QLOAD [[L] W]
reset state indicator)RESET
save workspace as W)SAVE [[L] W]
clear suspended functions)SIC
see suspended functions and locals)SINL
see suspended functions)SIS
state indicator)SI
show symbol count)SYMBOLS [count]
show values in use by interpreter)VALUES
show variables)VARS [from-to]
get/set workspace ID)WSID [W]

GNU extension commands (mostly for debugging)

toggles boxing of values when printing]BOXING [OFF num]
toggle colored output]COLOR [ON OFF]
dump W in HTML file]DOXY [path]
expected error count in test suite]EXPECT error_count
help]HELP [primitive]
show keyboard layout]KEYB
as)LIB, but shows fil eextensions]LIB [L P] [from-to]
show/set logging facilities]LOG [G [ON OFF]]
next testcase file]NEXTFILE
performance statistics]PSTAT [CLEAR SAVE]
as)SIS, with more details]SIS
as)SI, with more details]SI
shared variables]SVARS
describe internal details of symbol S]SYMBOL S
define user command]USERCMD [...]
toggle output coloring on console]XTERM [ON OFF]

System variables:

character input/output	<input type="checkbox"/> M
evaluated input/output	<input type="checkbox"/>
account information	<input type="checkbox"/> AI
command line arguments	<input type="checkbox"/> ARG
atomic vector	<input type="checkbox"/> AV
comparison tolerance	<input type="checkbox"/> CT
event message	<input type="checkbox"/> EM
event type	<input type="checkbox"/> ET
format control	<input type="checkbox"/> FC
index origin (indexes start: 1, can be set to 0)	<input type="checkbox"/> IO
left argument	<input type="checkbox"/> L
line counters	<input type="checkbox"/> LC
latent expression (executed when workspace is loaded)	<input type="checkbox"/> LX
print precision (number of digits)	<input type="checkbox"/> PP
print style	<input type="checkbox"/> PS
print width (max characters in each printed line)	<input type="checkbox"/> PW

right argument	<input type="checkbox"/> R
random link	<input type="checkbox"/> RL
shared variable event	<input type="checkbox"/> SVE
system limits	<input type="checkbox"/> SYL
terminal control characters	<input type="checkbox"/> TC
time stamp (current time)	<input type="checkbox"/> TS
time zone (offset from GMT)	<input type="checkbox"/> TZ
user load	<input type="checkbox"/> UL
axis argument	<input type="checkbox"/> X
workspace available (bytes for workspace)	<input type="checkbox"/> WA
dfn axis argument	X
dfn result	λ
dfn left value arg	α
dfn left function arg	α
dfn right value arg	ω
dfn right function arg	ω

System functions:

atomic function	<input type="checkbox"/> AF
attributes	<input type="checkbox"/> AT
char representation	<input type="checkbox"/> CR
delay	<input type="checkbox"/> DL
D. Knuth's dancing links	<input type="checkbox"/> DLX
execute alternate	<input type="checkbox"/> EA
execute both	<input type="checkbox"/> EB
execute controlled	<input type="checkbox"/> EC
environment	<input type="checkbox"/> ENV
event simulate	<input type="checkbox"/> ES
expunge	<input type="checkbox"/> EX
fast Fourier transform	<input type="checkbox"/> FFT
file I/O	<input type="checkbox"/> FIO
FiX (FFI/call native functions)	<input type="checkbox"/> FX
Gtk GUI	<input type="checkbox"/> GTK
MAP ravel elements	<input type="checkbox"/> MAP
input from script	<input type="checkbox"/> INP
name association	<input type="checkbox"/> NA
name class	<input type="checkbox"/> NC
name list	<input type="checkbox"/> NL
plot a graph	<input type="checkbox"/> PLOT
regular expression, regex <input type="checkbox"/> RE string	<input type="checkbox"/> RE
random APL value	<input type="checkbox"/> RVAL
state indicator	<input type="checkbox"/> SI
SQL functions	<input type="checkbox"/> SQL
shared variable control	<input type="checkbox"/> SVC
shared variable offer	<input type="checkbox"/> SVO
shared variable query	<input type="checkbox"/> SVQ
shared variable retraction	<input type="checkbox"/> SVR
shared variable state	<input type="checkbox"/> SVS
STOP vector	<input type="checkbox"/> STOP
transfer form	<input type="checkbox"/> TF
TRACE vector	<input type="checkbox"/> TRACE
unicode character	<input type="checkbox"/> UCS

Notation

comment	⍝
statement separator	◇
assignment	A← ...
assignment	(A B C)←
function definition	▽

zilde (empty vector)	\emptyset
a	$+ a$
a + b	$a + b$
- a	$- a$
a - b	$a - b$
magnitude of a	$ a$
b mod a	$a b$
signal (-1, 0, +1)	$\times a$
ab	$a \times b$
1/a	$\div a$
a/b	$a \div b$
floor of a	$\lfloor a$
min(a,b)	$a \lfloor b$
ceiling of a	$\lceil a$
max(a,b)	$a \lceil b$
e^a	$* a$
a^b	$a * b$
$\log(a)$	$\otimes a$
$\log_b(a)$	$b \otimes a$
first n non-negative integers	ιn
<hr/>	
a = b	$a = b$
a < b	$a < b$
a > b	$a > b$
a ≤ b	$a \leq b$
a ≥ b	$a \geq b$
expression max depth	$\equiv a$
match (value and type)	$a \equiv b$
expression min depth	$\neq a$
not match	$a \neq b$
not a	$\approx a$
a or b	$a \vee b$
a and b	$a \wedge b$
a nor b	$a \nvee b$
a nand b	$a \nwedge b$
a ∈ b ?	$a \in b$
find a in b (binary index)	$a \subseteq b ?$
bitwise a or b	$a \overline{\vee} b$
bitwise a and b	$a \overline{\wedge} b$
bitwise a nor b	$a \overline{\nvee} b$
bitwise a nand b	$a \overline{\nwedge} b$
bitwise a ≠ b	$a \overline{\neq} b$
bitwise a = b	$a \overline{=} b$
<hr/>	
$a! \binom{b}{a}$	$!a$ $a!b$
<hr/>	
$a\pi$	$\otimes a$
circle (trig) function	$a \otimes b$
random integer in [1,a]	$?a$
a distinct random integers in [1,b]	$a?b$
<hr/>	
makes a vector out of A	$, A$
append B to A	A, B
number of components in each dimension of A	ρA
array with shape A and data elements B	$A\rho B$
inverse matrix of A	$\overline{\div} A$

$B^{-1}A$ (solution to $Bx = A$)
reverse elements of A (1^{st} index)
rotate B by A positions
reverse elements of A (last index)
rotate B by A positions (last index)
drop first A elements of B
select first A elements of B
intersection
set (remove duplicates)
union
identity
take right hand side (B)
take left($X_i = 0$) or right($X_i = 1$)
null
take left hand side (A)
i-th element of A
elements of A with indices i, j, k, ...
element of A w/indices i, j, ... in 1^{st} dimension, k, l, ... in second, ...

transpose of A
transpose of B, axes ordered by A
maps A: 1 for $a \in B$, 0 for $a \notin B$
grade up A
grade up B with elements of A as top priority
grade down A
grade down B with elements of A as low priority
enclose A
enclose B with selected elements given the binary vector A
disclose A
recursively pick elements of B given the indices in A

Decode single digits of B with respect to base A
Encode B with respect to bases given by A

line label A
branch to line A

execute APL expression A
format A as chars

user input

system var/function

reduce **op** over array A
compress: select B using A as mask
A/B on last dimension
expand: insert zeros in B using A as mask
 $A \setminus B$ on last dimension
inner product with functions f, g
outer product with function f
for each $b \in B$, apply: Ab

$A \overline{\div} B$
 $\ominus A$
 $A \ominus B$
 $\oplus A$
 $A \oplus B$
 $A \uparrow B$
 $A \cap B$
 $\cup A$
 $A \cup B$
 $\vdash A$
 $A \vdash B$
 $A \vdash [X]B$
 $\neg A$
 $A \neg B$
 $A[i \ j \ k \ \dots]$
 $A[i \ \dots; k \ \dots; \dots]$

$\oslash A$
 $A \oslash B$
 $A \in B$
 $\triangle A$
 $A \triangle B$

∇A
 $A \nabla B$

$\subset A$
 $A \subset B$

$\supset A$
 $A \supset B$

$A \perp B$
 $A \top B$

A:
 $\rightarrow A$

$\underline{\oplus} A$
 $\overline{\oplus} A$

\square

\square

op/A
A/B
 $A \neq B$
 $A \setminus B$

$A \setminus B$
 $A \mathbf{f} . \mathbf{g} B$
 $A \circ . \mathbf{f} B$
 $A \mathbf{\tilde{~}} B$

rank: apply left operand function to A for B
cells specified by array on right
axis: $A \mathbf{f} C$, over Bth axis $A \mathbf{f} [B] C$
commute 1-x over array A $1 - \sim A$

⎕CR, ⎕FIO, ⎕PLOT, ⎕SQL

When called with an empty string as right argument, these will show a table with all their possible uses.

Circle function

A	A∘B	A	A∘B
0	$\sqrt{1-B \times B}$		
$\neg 1$	arcsin B	1	sin B
$\neg 2$	arccos B	2	cos B
$\neg 3$	$\arctan B$	3	tan B
$\neg 4$	$\sqrt{-1+B \times B}$	4	$\sqrt{1+B \times B}$
$\neg 5$	arcsinh B	5	sinh B
$\neg 6$	arccosh B	6	cosh B
$\neg 7$	arctanh B	7	$\tanh B$
$\neg 8$	$\neg(8 \circ B)$	8	$\pm \sqrt{-1+B \times B}$
$\neg 9$	B	9	real part of B
$\neg 10$	+B	10	B
$\neg 11$	$0J1 \times B$	11	imag part of B
$\neg 12$	$*0J1 \times B$ (e^{iB})	12	arc B (phase of B)

For A= 8, the sign before the square root is opposite of B .

Function Definition

Example: $f(d,v) = \left(v_1^d + \dots + v_n^d\right)^{1/d}$

Dynamic function definition (dfn):

α is the left argument, ω is the right argument.

f ← { (+/ $\omega * \alpha$) * ($\div \alpha$) }

Traditional function definition (tradfn):

∇ : begin/end defun. “ $\nabla R \leftarrow A \mathbf{f} B ; U ; V$ ” is “f takes left arg A, right arg B, has local vars U, V, and returns result in R”.

$\nabla \mathbf{res} \leftarrow \mathbf{d} \mathbf{f} \mathbf{v} ; \mathbf{sq} ; \mathbf{sum}$

$\mathbf{sq} \leftarrow \mathbf{v} * \mathbf{d}$

$\mathbf{sum} \leftarrow +/\mathbf{sq}$

$\mathbf{res} \leftarrow \mathbf{sum} * (\div \mathbf{d})$

∇

Copyright © 2020 Jeronimo Pellegrini, Lucas S. Vieira
designed by Jeronimo Pellegrini, Lucas S. Vieira and Stephen Gildea,
for GNU APL

Released under the terms of the GNU General Public License version 3 or later. For more APL documentation, check the GNU APL site. For the \TeX source for this card, see:

<https://www.github.com/jpellegrini/gnu-apl-refcard>