

config.js - clase 4 - Visual Studio Code

EXPLORER

- CLASE 4
 - Ecommerce
 - db
 - carrito_db.js
 - producto_db.js
 - app.js

TERMINAL

```
akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4
$ git config user.name
akurregoh

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4
$ git config user.email
akurregoh@unal.edu.co

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4
$ mkdir Ecommerce

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4
$ cd Ecommerce/

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce
$ touch app.js

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce
$ touch config.js

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce
$ mkdir db
```

main* 0 0 0

Ln 1, Col 1 Spaces: 4 UTF-8 CRLF () JavaScript Go Live

ENG LAA 12:20 AM 2/23/2022

config.js - clase 4 - Visual Studio Code

EXPLORER

- CLASE 4
 - Ecommerce
 - db
 - carrito_db.js
 - producto_db.js
 - app.js

TERMINAL

```
akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce
$ git init
Initialized empty Git repository in D:/clase 4/Ecommerce/.git/

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce (main)
$ git add .

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce (main)
$ git commit -m "Primer Commit"
[main (root-commit) 72b4c6d] Primer Commit
2 files changed, 0 insertions(+), 0 deletions(-)
create mode 100644 app.js
create mode 100644 config.js

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce (main)
$ cd db/

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce/db (main)
$ touch producto_db.js

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce/db (main)
$ touch carrito_db.js
```

main* 0 0 0

Ln 1, Col 1 Spaces: 4 UTF-8 CRLF () JavaScript Go Live

ENG LAA 12:21 AM 2/23/2022

This screenshot shows the first part of a git commit process in Visual Studio Code. The Explorer sidebar on the left shows the project structure: 'CLASE 4' containing 'Ecommerce', which contains a 'db' folder with files 'carrito_db.js', 'producto_db.js', and 'app.js'. The terminal window is active, showing the following commands and output:

```
akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce/db (main)
$ cd ..
akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce (main)
$ nano app.js
akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce (main)
$ git commit -m "Guardando lo importante"
On branch main
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   app.js

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        db/

no changes added to commit (use "git add" and/or "git commit -a")
akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce (main)
$ git add .
warning: LF will be replaced by CRLF in app.js.
```

A 'Select Language Mode' button is visible in the terminal. The status bar at the bottom indicates 'Ln 1, Col 1', 'Spaces: 4', 'UTF-8', 'CRLF', and 'JavaScript'.

This screenshot shows the continuation of the git commit process. The terminal window displays the following commands and output:

```
akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce (main)
$ git add .
warning: LF will be replaced by CRLF in app.js.
The file will have its original line endings in your working directory
akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce (main)
$ git commit -m "Guardando una parte del proyecto"
[main e5a7489] Guardando una parte del proyecto
3 files changed, 1 insertion(+)
create mode 100644 db/carrito_db.js
create mode 100644 db/producto_db.js

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce (main)
$ cd db

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce/db (main)
$ rm producto_db.js

akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce/db (main)
$ git add .
akurr@DESKTOP-MD0G08L MINGW64 /d/clase 4/Ecommerce/db (main)
```

The status bar at the bottom remains the same, showing 'Ln 1, Col 1', 'Spaces: 4', 'UTF-8', 'CRLF', and 'JavaScript'.

