

Lea sobre el resto de métodos de la clase File de Python y cree una tabla donde explique qué hace cada uno.

Method	Description	Example
close()	Closes the file. You should always close your files	<pre>f = open("demofile.txt", "r") print(f.read()) f.close()</pre>
detach()	Returns the separated raw stream from the buffer	<pre>f = open('file.txt', 'r') raw_stream = f.detach() print(raw_stream.read(5))</pre>
fileno()	Returns a number that represents the stream, from the operating system's perspective	<pre>f = open("demofile.txt", "r") print(f.fileno())</pre>
flush()	Cleans out the internal buffer.	<pre>f = open("myfile.txt", "a") f.write("Now the file has one more line!") f.flush() f.write("...and another one!")</pre>
isatty()	This method returns True if the file stream is interactive, example: <u>connected to a terminal device</u> .	<pre>file.isatty()</pre>
read()	Returns the file content	<pre>f = open("demofile.txt", "r") print(f.read())</pre>
readable()	Returns whether the file stream can be read or not. It returns True if the file is readable, False if not.	<pre>f = open("demofile.txt", "r") print(f.readable())</pre>
readline()	Returns one line from the file. You can also specified how many bytes from the line to return, by using the size parameter.	<pre>f = open("demofile.txt", "r") print(f.readline()) print(f.readline())</pre>
readlines()	Returns a list of lines from the file	<pre>f = open("demofile.txt", "r") print(f.readlines())</pre>

seek()	Sets the current file position in a file stream.	f = open("demofile.txt", "r") f.seek(4) print(f.readline())
seekable()	It returns True if the file is seekable, False if not.	f = open("demofile.txt", "r") print(f.seekable())
tell()	It returns the current file position in a file stream. Tip: You can change the current file position with the seek() method.	f = open("demofile.txt", "r") print(f.tell())
truncate()	Resizes the file to a specified size. It resizes the file to the given number of bytes.	f= open("demofile2.txt", "a") f.truncate(20) f.close()
writable()	It returns True if the file is writable, False if not.	f = open("demofile.txt", "a") print(f.writable())
write()	Writes the specified string to the file. "a": The text will be inserted at the current file stream position, default at the end of the file. "w": The file will be emptied before the text will be inserted at the current file stream position, default 0.	f= open("demofile2.txt", "a") f.write("See you soon!") f.close() <i>#open and read the file after the appending:</i> f= open("demofile2.txt", "r") print(f.read())
writelines()	Writes a list of strings to the file	f= open("demofile3.txt", "a") f.writelines(["See you soon!", "Over and out."]) f.close() <i>#open and read the file after the appending:</i> f= open("demofile3.txt", "r") print(f.read())