

NewProject Material List			
		QUANTITY / DEVICE NAMES	
ITEM NO.	EQUIPMENT DESCRIPTION	Total	1
1A	Distance relay Mounting: Horizontal Rack mount, 2 RU Power supply voltage: 48/125V DC or 120V AC Control voltage: 48V DC Current input rating: 5A Voltage input rating: 300V AC Standard I/O: 6 optoisolated inputs, 3 high current outputs, 5 outputs User interface: Hard-wired Pushbuttons Comm. interface: 2 EIA-232 DB9, 1 EIA-485 terminal block, 1 100Base-FX MM LC, 1 BNC IRIG Communications: Standard SEL 0311C10HH3D52X1 See catalog cut	1	1
1B	Distance relay Mounting: Horizontal Rack mount, 3 RU Power supply voltage: 48/125V DC or 120V AC Control voltage: 48V DC Current input rating: 5A Voltage input rating: 300V AC Standard I/O: 6 optoisolated inputs, 3 high current outputs, 5 outputs Additional I/O: 8 inputs, 12 outputs User interface: Hard-wired pushbuttons Comm. interface: 2 EIA-232 DB9, 1 EIA-485 terminal block, 2 10/100Base-T, 1 BNC IRIG, 1 USB B Communications: Standard SEL 0311C11HR3E5221 See catalog cut	1	1

DATE	USER	DESCRIPTION
------	------	-------------