

# Machine Learning Interpretability

## The Good, the Bad, and the Ugly

Patrick Hall

H<sub>2</sub>O.ai

Aug. 1 2018

# Contents

## Front Matter

Notation

Learning Problem

## Surrogate DT

## PD and ICE

## LIME

## Tree Shap

## Recommendations

## Software


## Obligatory Front Matter

- **What is interpretation?** “The ability to explain or to present in understandable terms to a human.” Doshi-Velez and Kim, 2017
- **What is a good interpretation?** "When you can no longer keep asking why." Gilpin et al., 2018
- **Why should you care?**
  - Understanding of an impactful and quickly expanding set of technologies.
  - Addressing accidental or intentional discrimination.
  - Preventing malicious hacking and adversarial attacks.
  - Enabling regulatory compliance and increased financial margins.

## Notation

- **Spaces.**
  - The input features come from a set  $\mathcal{X}$  contained in a  $P$ -dimensional input space (i.e.  $\mathcal{X} \subset \mathbb{R}^P$ ).
  - The output responses come from a set  $\mathcal{Y}$  contained in a  $C$ -dimensional output space (i.e.  $\mathcal{Y} \subset \mathbb{R}^C$ ).
- **Dataset.** A dataset  $\mathbf{D}$  consists of  $N$  tuples of observations:  
 $[(\mathbf{x}^{(0)}, \mathbf{y}^{(0)}), (\mathbf{x}^{(1)}, \mathbf{y}^{(1)}), \dots, (\mathbf{x}^{(N-1)}, \mathbf{y}^{(N-1)})], \mathbf{x}^{(i)} \in \mathcal{X}, \mathbf{y}^{(i)} \in \mathcal{Y}.$ 
  - The input data  $\mathbf{X}$  is composed of the set of row vectors  $\mathbf{x}^{(i)}$ .
    - let  $\mathcal{P}$  be the set of features  $\{X_0, X_1, \dots, X_{P-1}\}$ , where  $X_j = [x_j^{(0)}, x_j^{(1)}, \dots, x_j^{(N-1)}]^T$ .
    - then each  $i$ -th observation denoted as  $\mathbf{x}^{(i)} = [x_0^{(i)}, x_1^{(i)}, \dots, x_{P-1}^{(i)}]$  is an instance of  $\mathcal{P}$ .

# Proposed Updates to the Learning Problem



The learning problem. Adapted from Abu-Mostafa, Magdon-Ismail, and Lin, 2012.

## Surrogate Decision Trees (DT)




Figure:  $h_{\text{tree}}$  for Taiwanese credit card data Lichman, 2013, and for machine-learned GBM response function  $g$ .

- Given a learned function  $g$  and set of predictions,  $g(\mathbf{X}) = \hat{\mathbf{Y}}$ , a surrogate DT can be trained:  $\mathbf{X}, g(\mathbf{X}) \xrightarrow{\mathcal{A}_{\text{surrogate}}} h_{\text{tree}}$ .
- $h_{\text{tree}}$  displays a low-fidelity, highly interpretable flow chart of  $g$ 's decision making process, and important features and interactions in  $g$ .











# Partial Dependence (PD) and Individual Conditional Expectation (ICE)



**Figure:** Surrogate DT, PD, and ICE curves for  $X_j = \text{num}_9$ , for known signal generating function  $f(\mathbf{X}) = \text{num}_1 * \text{num}_4 + |\text{num}_8| * \text{num}_9^2 + e$ , and for machine-learned GBM response function  $g(\mathbf{X})$ .

Combining Surrogate DT models with PD and ICE curves is a convenient method for detecting, confirming, and understanding important interactions.



## Local Interpretable Model-agnostic Explanations (LIME)

- LIME is ideal for creating low-fidelity, highly interpretable explanations for non-DT models and for neural network models trained on unstructured data, e.g. deep learning.
- Always use regression fit measures to assess the trustworthiness of LIME explanations.
- LIME can be difficult to deploy, but there are highly deployable variants. Hu et al., 2018; Hall et al., 2017
- Local feature importance values are offsets from a local intercept.
  - Note that the intercept in LIME can account for the most important local phenomena.
  - Generated LIME samples can contain large proportions of out-of-range data that can lead to unrealistic intercept values.

- Try LIME on discretized input features and on manually constructed interactions.
- Use cross-validation to construct standard deviations or even confidence intervals for reason code values.
- LIME can fail, particularly in the presence of extreme nonlinearity or high-degree interactions.

# Tree Shap - *Description*

# Tree Shap - *Recommendations*

## Closing Recommendations

- Monotonically constrained XGBoost, Surrogate DT, PD and ICE plots, and Tree Shap are a direct and open source way to create an interpretable nonlinear model.
- Global and local explanatory techniques are often necessary to explain a model.
- Use simpler low-fidelity or sparse explanations to understand more accurate and complex high-fidelity explanations.
- Seek consistent results across multiple explanatory techniques.
- Methods relying on generated data are sometimes unpalatable to users. They want to understand *their* data.
- Surrogate models can provide low-fidelity explanations for model mechanisms in original feature spaces if  $g$  is defined to include feature extraction or engineering.
- To increase adoption, production deployment of explanatory methods must be straightforward.



## Software Examples and Resources

### Comparison of Explanatory Techniques on Simulated Data:

[https://github.com/h2oai/mli-resources/tree/master/lime\\_shap\\_treeint\\_compare](https://github.com/h2oai/mli-resources/tree/master/lime_shap_treeint_compare)

### In-depth Explanatory Technique Examples:

[https://github.com/jphall663/interpretable\\_machine\\_learning\\_with\\_python](https://github.com/jphall663/interpretable_machine_learning_with_python)

### "Awesome" Machine Learning Interpretability Resource List:

<https://github.com/jphall663/awesome-machine-learning-interpretability>

## References

- Abu-Mostafa, Yaser S., Malik Magdon-Ismail, and Hsuan-Tien Lin (2012). ***Learning from Data***. New York: AMLBook. URL: <https://work.caltech.edu/textbook.html>.
- Bastani, Osbert, Carolyn Kim, and Hamsa Bastani (2017). "Interpreting blackbox models via model extraction." In: *arXiv preprint arXiv:1705.08504*. URL: <https://arxiv.org/pdf/1705.08504.pdf>.
- Craven, Mark W. and Jude W. Shavlik (1996). "Extracting Tree-Structured Representations of Trained Networks." In: *Advances in Neural Information Processing Systems*. URL: <http://papers.nips.cc/paper/1152-extracting-tree-structured-representations-of-trained-networks.pdf>.
- Doshi-Velez, Finale and Been Kim (2017). "Towards a rigorous science of interpretable machine learning." In: *arXiv preprint arXiv:1702.08608*. URL: <https://arxiv.org/pdf/1702.08608.pdf>.
- Friedman, Jerome, Trevor Hastie, and Robert Tibshirani (2001). ***The Elements of Statistical Learning***. New York: Springer. URL: [https://web.stanford.edu/~hastie/ElemStatLearn/printings/ESLII\\_print12.pdf](https://web.stanford.edu/~hastie/ElemStatLearn/printings/ESLII_print12.pdf).
- Gilpin, Leilani H et al. (2018). "Explaining Explanations: An Approach to Evaluating Interpretability of Machine Learning." In: *arXiv preprint arXiv:1806.00069*. URL: <https://arxiv.org/pdf/1806.00069.pdf>.
- Goldstein, Alex et al. (2015). "Peeking Inside the Black Box: Visualizing Statistical Learning with Plots of Individual Conditional Expectation." In: *Journal of Computational and Graphical Statistics* 24.1.

## References

- Hall, Patrick et al. (2017). *Machine Learning Interpretability with H2O Driverless AI*. URL: <http://docs.h2o.ai/driverless-ai/latest-stable/docs/booklets/MLIBooklet.pdf>.
- Hu, Linwei et al. (2018). “Locally Interpretable Models and Effects based on Supervised Partitioning (LIME-SUP).” In: *arXiv preprint arXiv:1806.00663*. URL: <https://arxiv.org/ftp/arxiv/papers/1806/1806.00663.pdf>.
- Lichman, M. (2013). *UCI Machine Learning Repository*. URL: <http://archive.ics.uci.edu/ml>.
- Ribeiro, Marco Tulio, Sameer Singh, and Carlos Guestrin (2016). “Why should I trust you?: Explaining the predictions of any classifier.” In: *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. ACM, pp. 1135–1144. URL: <http://www.kdd.org/kdd2016/papers/files/rfp0573-ribeiroA.pdf>.