

WAP Manager (HTML Canvas) — Client Guide

What this platform is: a single visual system to design mobile subscription landing pages, connect partner billing APIs, route users by phone / OTP / header enrichment, and run **Priority Chain** checks (status → page) — without deploying a new app for every campaign.

Use this document when explaining the product to clients, ops, or partners.


1. What can you do with this project?

Capability	What the user / admin gets
Campaigns	Create unlimited campaigns by Country + Operator + Service ID on one engine
Visual page designer	Design landing & funnel pages in a drag-and-drop canvas (GrapesJS) — HTML/CSS without coding
Button / hotspot actions	Point any button or invisible hotspot to: signup flow, another page, external URL, scroll, or Priority Chain
Verification modes	Header Enrichment (1-click), OTP-only, hybrid (BOTH), or direct CG redirect
Partner APIs	Configure blocklist, already-subscribed check, charge/subscribe, MSISDN resolve, custom headers
Priority Chain	On click: call partner status URL → match response fields → go to the right page (or website)
Live subscriber link	Share one public URL; engine loads the right campaign + pages dynamically
Analytics & logs	Visits, conversions, OTP stats, API call logs, and per-session journey timeline

End consumer experience: open the campaign link → see branded pages → verify phone (header or OTP) → confirm pack → thank-you / blocked / error / custom pages as configured.

Admin experience: create campaign → design pages → wire buttons → set APIs / Priority rules → publish → monitor logs & analytics.

2. How a campaign works (simple flow)



Typical public link shape:

```
/subscription?country=<Country>&operator=<Operator>&campid=<CampaignId>
```

Optional test params (e.g. `msisdn=`) can be added for QA.

3. Campaign setup (admin)

3.1 Create a campaign

1. Open **Campaigns** in the admin panel.
2. Click **Create Campaign**.
3. Fill:
 - **Name** — e.g. *Jio Games India*
 - **Country / Operator** — routing & audit isolation
 - **Service ID** — partner / carrier billing id
 - **Verification mode** — see section 4

3.2 Design pages (canvas)

Each campaign can include these page types:

Page	Purpose
HOME	Main offer / CTA landing
OTP	Enter mobile + OTP when header is missing
CONFIRM	Pack choice & final confirm
THANKYOU	Success / already subscribed
BLOCKED	DND / not eligible
ERROR	Technical / config failure
LOW_BALANCE	Optional — e.g. parking / insufficient balance
INPROGRESS	Optional — pending / in-progress status

Required for a full funnel: **HOME, OTP, CONFIRM, THANKYOU**. Extra pages are used heavily with **Priority Chain** rules.

3.3 Partner API configuration

Per campaign (API Configuration):

API	Role
Blocklist	Skip billing if number is barred
Subscription check	Detect already active → thank-you / skip recharge
Subscribe / charge	Trigger partner billing
MSISDN resolve	Lookup number when not in header
Headers JSON	Auth tokens for partner calls

URL placeholders (filled automatically at runtime):

- `{{phone}}` / `{{msisdn}}`
- `{{serviceId}}`, `{{country}}`, `{{operator}}`
- `{{planId}}` / `{{pack}}`, `{{subServiceId}}`

4. Verification modes

Mode	Behavior	Best for
HEADER_INJECTION	Read MSISDN from network header → confirm / thank-you; missing → error	Pure WAP / carrier data
OTP_ONLY	Always ask phone + OTP	Wi-Fi / web traffic
BOTH (recommended)	Try header first; if missing → OTP	Mixed cellular + Wi-Fi
NONE	Append click params and redirect to external CG URL	Affiliate / external gateway only

5. Button & hotspot actions (editor)

Select any **button** or **hotspot** in the canvas. In the property panel, **When clicked**:

Option	What happens
Continue signup flow	Normal HE / OTP / confirm path (SUBSCRIBE)
Scroll to a section	Same-page smooth scroll
Go to another page	Jump to OTP, CONFIRM, THANKYOU, etc.
Open a website	External redirect
Try checks in order	Priority Chain (see next section)

No manual HTML coding is required — the editor writes the attributes for you.

6. Priority Chain — full client guide

6.1 What is Priority Chain?

Priority Chain (“Try checks in order”) lets one button run **ordered steps**. Typical use:

1. Call a partner **status / check-subscription** URL.
2. Read fields from the JSON response (e.g. **currentStatus = active**).
3. Send the user to the matching **campaign page** or an **external website**.

4. If nothing matches, either try the next step, open a fallback page, or open a website.

Why clients use it

- Already subscribed → Thank you (no double charge)
- Low balance / parking → Low balance page
- Pending → In progress page
- New user → Confirm / OTP to continue signup
- Custom eligibility, fraud, or CRM checks before billing

Steps run **top → bottom. First matching rule wins**; later steps are skipped once a page/redirect happens.

6.2 How to configure (editor steps)

1. Open the campaign in the **Canvas editor**.
2. Select the CTA button (or draw a hotspot).
3. **When clicked** → choose **Try checks in order**.
4. Open the Priority Chain modal (**Try checks in order**).
5. Add / reorder steps (↑ ↓). Save is applied on the button as you edit.

6.3 Step types

Step type	Meaning
Check a status URL	HTTP call to partner API; evaluate rules
Go to another page	Navigate to a campaign page
Open a website	Full browser redirect
Scroll to a section	Same-page scroll
Continue signup flow	Hand off to normal verification flow

6.4 Status URL + rules (most important part)

For a **Check a status URL** step:

1. Paste the partner URL, e.g.
<https://partner.example.com/sub/checksub?msisdn=>

{{msisdn}}&serviceId=WELLNESS

2. Under **Where to go for each status**, add rules:

Response field	Equals	Then go to
currentStatus	active	Thank you page
currentStatus	parking	Low balance page
currentStatus	pending	In progress page
currentStatus	new	Confirm page

- Field names can be top-level or nested under **data** (e.g. **data.currentStatus** / **subscriptionStatus**).
- Snake_case / camelCase variants are handled where possible.
- Destination can be a **campaign page** or a **website URL**.

If nothing matches

- Try the next step, **or**
- Go to a page (e.g. Confirm / Error), **or**
- Open a website

If the check fails to load (network / HTTP error)

- Same choices: continue, page, or website (often **Error**).

6.5 Example chain (client-ready)

Button on HOME: Subscribe

Priority	Type	Config
1	Status URL	.../checksub?msisdn={{msisdn}}&serviceId=... with rules above
2	Go to page	OTP (only reached if Priority 1 continues / no phone yet)

Runtime behavior

- Phone known + **active** → **THANKYOU** (stop).
- Phone known + **parking** → **LOW_BALANCE** (stop).

- Phone known + **new** / no match → next step or configured miss page (e.g. **CONFIRM**).
- Phone **not** available yet and URL needs **{{msisdn}}** → that API step is **skipped**; chain continues (e.g. to OTP).
- Absolute **https://** partner URLs are called via the **platform proxy** (avoids browser CORS); each call can be logged as a **priority** API call for audit.

6.6 Priority Chain — FAQ

Q: Do I need a developer to change status → page mapping?

No. Change rules in the editor modal.

Q: Can one status go to an external offer URL?

Yes — set rule destination to **A website**.

Q: What if the partner returns an unexpected status?

Use **If nothing matches** (continue / page / website).

Q: Will later priorities still run after a match?

No. First match navigates and stops the chain.

Q: Where do I see what happened for a user?

Session / API logs show **priority** checks (URL, status, which priority step).

7. Public runtime (what the end user sees)

- Campaign HTML/CSS is rendered in an isolated **Shadow DOM** so template styles do not clash with the app shell.
 - Clicks on buttons/hotspots are intercepted — no full page reload for in-campaign navigation.
 - URL updates with **step=** (e.g. **CONFIRM**, **THANKYOU**) so the current funnel step is clear and shareable for debugging.
-

8. Analytics, logs & timelines

Area	What you get
Campaign analytics	Visits, plan views, subscribe success/fail, blocked, etc.
OTP analytics	Delivery / resend / provider performance
Event & API logs	Filter by visit id, MSISDN, click id, vendor / affiliate
Session timeline	Ordered journey: visit → HE → blocklist → priority API → subscribe outcome

9. Client Q&A

Can numbers be international (UAE, KSA, etc.)?

Yes. Non-digits are stripped; no hard-coded 10-digit-only rule. Partner APIs receive the sanitized number.

Wi-Fi user, no header?

In **BOTH** mode the user is sent to **OTP** automatically.

Do we write **data-action** by hand?

No — use the property panel dropdowns / Priority modal.

Already subscribed — double charge?

Subscription check (campaign API and/or Priority status rules) can route to **THANKYOU** / **ALREADY_SUBSCRIBED** and skip charging.

One codebase for many operators?

Yes. One multi-tenant engine; each campaign is data + canvas pages + API config.

10. Go-live checklist

- ☐ Create campaign (country, operator, service id, verification mode — prefer **BOTH**)
- ☐ Configure partner APIs (blocklist, check-sub, subscribe, headers)
- ☐ Design HOME / OTP / CONFIRM / THANKYOU (+ LOW_BALANCE / INPROGRESS if needed)
- ☐ Wire CTA: normal flow **or** Priority Chain with status rules

- ☐ Test public link with cellular + Wi-Fi (and with/without **msisdn** where allowed)
 - ☐ Confirm Priority API rows appear in logs when the CTA is clicked
 - ☐ Review analytics after a small live sample
-

11. One-line summary for the client

HTML Canvas (WAP Manager) lets you design branded subscription funnels once, attach operator APIs, and use **Priority Chain** so a single button can check partner status and send each user to the right page — all without shipping a new website per campaign.