

Network Policies

Networking model

- Containers on the same pod can talk to each other via localhost.
- Pods on the same node communicate via a pod's IP address.
- Pods on different nodes communicate via a pod's IP address.

Advantages

- Allows multi-container design patterns.
- No port coordination between pods is needed.
- Pods on different nodes can easily communicate with each other (unlike Docker networking).

Advantages (cont.)

- If a container within a pod dies and restarts, the IP address that other pods or services use to access it is still valid.
- Pods don't need to be concerned about which node a pod they are accessing is running on.
- **Using services is preferred to direct pod access.**

Network policies

- By default, every pod can communicate directly with every other pod via an IP address.
- However, you might want to restrict how groups of pods can communicate with each other.

Network policies (cont.)

- Network Policies let you group pods together using labels, and define rules between these groups.
- These rules are defined for:
 - *Ingress*: incoming connections to the group of pods
 - *Egress*: outgoing connections made by pods in the group.
- These policies are able to restrict network connections to specific IP ranges and port numbers.

Example

- Run a sample web app.

```
kubectl run hello-web --labels app=hello \  
--image=gcr.io/google-samples/hello-app:1.0 \  
--port 8080 --expose
```

Example (cont.)

```
#hello-allow-from-foo.yaml
```

```
kind: NetworkPolicy
apiVersion: networking.k8s.io/v1
metadata:
  name: hello-allow-from-foo
spec:
  policyTypes:
  - Ingress
  podSelector:
    matchLabels:
      app: hello
  ingress:
  - from:
    - podSelector:
        matchLabels:
          app: foo
```

```
kubectl apply -f hello-allow-from-foo.yaml
```


Example (cont.)

- Now let's validate the ingress policy.
- First, get into a shell of a `foo` pod.

```
kubectl run -l app=foo --image=alpine --restart=Never --  
rm -it test
```

- Make a request to `hello`.

```
wget -qO- --timeout=2 http://hello-web:8080
```

Example (cont.)

- Check that you indeed can't connect to other app.

```
kubectl run -l app=other \  
--image=alpine --restart=Never --rm -it test
```

Once inside the pod

```
wget -q0- --timeout=2 http://hello-web:8080
```

Example (cont.)

```
# - Now Let's try the opposite direction
# foo-allow-to-hello.yaml
kind: NetworkPolicy
apiVersion: networking.k8s.io/v1
metadata:
  name: foo-allow-to-hello
spec:
  policyTypes:
    - Egress
  podSelector:
    matchLabels:
      app: foo
  egress:
    - to:
        - podSelector:
            matchLabels:
              app: hello
    - ports:
        - port: 53
          protocol: TCP
        - port: 53
          protocol: UDP
```

Example (cont.)

- Apply changes

```
kubectl apply -f foo-allow-to-hello.yaml
```

- Create and expose a new application

```
kubectl run hello-again --labels app=hello-again \  
  --image=gcr.io/google-samples/hello-app:1.0 \  
  --port 8080 --expose
```

Example (cont.)

- Run a temporary pod with the `app=foo` label and get a shell inside the container

```
kubectl run -l app=foo --image=alpine --rm -i -t --  
restart=Never tmp
```

- Check whether the pod can establish connections to:
 - `hello-web:8080`
 - `hello-again:8080`
 - `http://www.example.com`

Default policies

- By default, **all** ingress and egress traffic is allowed to/from pods in a namespace.

Deny all ingress traffic

```
apiVersion: networking.k8s.io/v1
kind: NetworkPolicy
metadata:
  name: default-deny
spec:
  podSelector: {}
  policyTypes:
    - Ingress
```

- Pods that aren't selected by any other policy would be isolated.
- All egress traffic is allowed.

Allow all ingress traffic

```
apiVersion: networking.k8s.io/v1
kind: NetworkPolicy
metadata:
  name: allow-all
spec:
  podSelector: {}
  ingress:
  - {}
  policyTypes:
  - Ingress
```


Default deny ingress and egress traffic

```
apiVersion: networking.k8s.io/v1
kind: NetworkPolicy
metadata:
  name: default-deny
spec:
  podSelector: {}
  policyTypes:
    - Ingress
    - Egress
```

Exercise

- Create an `nginx` deployment running on port 80.
- Test the service from another pod (with `alpine` or `busybox` image).
- Set a network policy such that only pods with label `access=true` can access the nginx pod.
- Verify that:
 - If a pod does not have the correct label, it cannot access nginx.
 - If a pod does have the correct label, it can access nginx.

- Solution