

Stored Procedures

Stored Procedures

- A stored procedure contains a set of SQL statements *and* procedural statements.
- Teradata procedures can be of two types:
 - **General Procedure:** Procedure that performs some action in the background.
 - **Dynamic procedure:** Procedures that returns resultset/query result.

Advantages

- Stored procedures reduce the network load between the client and the server.
- Provides better security since the data is accessed through stored procedures instead of accessing them directly.
- Good maintenance since the business logic is tested and stored in the database.

Example

```
CREATE PROCEDURE InsertSalary(  
  IN in_EmployeeNo INTEGER, IN in_Gross INTEGER,  
  IN in_Deduction INTEGER, IN in_NetPay INTEGER  
)  
BEGIN  
  INSERT INTO Salary  
  ( EmployeeNo, Gross, Deduction, NetPay )  
  VALUES  
  (:in_EmployeeNo, :in_Gross, :in_Deduction, :in_NetPay);  
END;
```

```
CALL InsertSalary(105,20000,2000,18000);
```

- The `BEGIN` and `END` statements are required in all Stored Procedures.

SET , IN and OUT Parameters

```
CREATE PROCEDURE CompareValues
(IN var1 BYTEINT, IN var2 BYTEINT, OUT Msg CHAR(20) )
BEGIN
    CASE WHEN var1 = var2 THEN SET Msg = 'They are equal' ;
    WHEN var1 < var2 THEN Set Msg = 'Variable 1 less' ;
    ELSE SET Msg = 'Variable 1 greater' ;
    END CASE;
END;
```

```
CALL Test_Proc (1,2, Msg) ;
```

- This Stored Procedure will take a parameter in and then send something out.

General Syntax

```
REPLACE PROCEDURE [database_name.procedurename]  
[(Input_variable [datatype],Output_variable [datatype])]  
[DYNAMIC RESULT SETS 1]  
BEGIN  
DECLARE var1 [datatype];  
DECLARE var2 [datatype];  
--Error handling block  
DECLARE EXIT HANDLER FOR SQLEXCEPTION  
BEGIN  
    ROLLBACK;  
    -- error handling code  
END;  
  
DECLARE CONTINUE HANDLER FOR SQLSTATE '42000'  
BEGIN  
    -- error handling code  
END;  
  
--Procedure Logic --  
END;
```

Remarks

- `REPLACE` command will create if not present.
- Table does not exist: `SQLSTATE 42000`

IF inside a Stored Procedure

```
CREATE PROCEDURE CompareValuesWithIf
(IN var1 BYTEINT, IN var2 BYTEINT, OUT Msg CHAR(20) )
BEGIN
    IF var1 = var2 THEN SET Msg = 'They are equal';
    END IF;
    IF var1 < var2 THEN SET Msg = 'Variable 1 less';
    END IF;
    IF var1 > var2 THEN SET Msg = 'Variable 1 greater';
    END IF;
END;
```

```
CALL TestIF_Proc (2,2, Msg ) ;
```


Loops

```
CREATE Table My_Log_Tbl  
(  
  cntr Integer  
,eventtime Time  
) Primary Index (cntr);
```

```
CREATE PROCEDURE InsertFiveRecords( )  
LOOPER:BEGIN  
  DECLARE Cntr INTEGER DEFAULT 0;  
  Loopit:LOOP  
    SET Cntr = Cntr + 1;  
    IF Cntr > 5 THEN LEAVE Loopit;  
    END IF;  
    INSERT INTO My_Log_Tbl  
    VALUES (:Cntr);  
  END LOOP Loopit ;  
END LOOPER;
```

- LOOP s require Labeling.
- LEAVE , UNTIL

Multiple `BEGIN/END` statements

- When you have multiple `BEGIN` and `END` statements, you have to label them all (except for the first `BEGIN` and `END` statements).

Cursors

```
DECLARE cname [SCROLL|NOSCROLL] CURSOR FOR sql_select;
```

- `SCROLL` goes to the beginning of results set.

```
OPEN cname [USING parameter,...];
```

```
FETCH [NEXT|FIRST] FROM cname INTO [var|param];
```

```
CLOSE cname;
```

- Without checking for SQLSTATE '02000' (no rows to fetch), we get an infinite loop.

Several examples

- Time to look at the scripts that start with `07` in the `scripts` folder.

Useful links

- [Teradata documentation.](#)
- [Fancy stored procedure from Teradata](#)

Triggers

Why do we need them?

- *Event-driven* operations.
- Useful for data integrity checks and auto updates.

Types

- **Row-level:** Execute once per row modified by the event.
- **Statement-level:** Only once per event.
- `BEFORE` and `AFTER` the triggering event is completed.

What can be an event?

- INSERT
- UPDATE
- DELETE
- INSERT-SELECT

What can be a response?

- INSERT
- UPDATE
- DELETE
- INSERT SELECT
- ABORT/ROLLBACK
- EXEC (macro)