

LP SmartSide — Coverage & Estimating Reference

Reveals, coverage & pieces-per-square · Source: LP SmartSide official Coverage Chart (LPZB0884) & product specifications

Lap Siding — 38 Series (3/8" Cedar Texture / Smooth, 16' boards)

Standard installation: 1" overlap. Reveal = actual face width – 1". Coverage is waste-exclusive — add your own waste factor (typ. 10% for lap) and round up to whole boards.

Coverage per board	$\text{length (ft)} \times \text{reveal (in)} \div 12 = 16 \times \text{reveal} \div 12$
Pieces needed	$\text{wall area (sq ft)} \div \text{coverage per board} \times (1 + \text{waste factor}) \rightarrow \text{round up}$
Pieces per square	$100 \div (16 \times \text{reveal_in} \div 12)$

PROFILE	ACTUAL FACE WIDTH	REVEAL (EXPOSURE)	COVERAGE / 16' BOARD	PIECES / SQUARE*
6" Lap	5-7/8" (5.875")	4-7/8" (4.875")	6.50 sq ft	16 pcs
7" Lap	6-7/8" (6.875")	5-7/8" (5.875")	7.83 sq ft	13 pcs
8" Lap	7-7/8" (7.840")	6-7/8" (6.875")	9.17 sq ft	11 pcs
12" Lap	11-7/8" (11.875")	10-7/8" (10.875")	14.50 sq ft	7 pcs

*Pieces per square = pieces per 100 sq ft, rounded up per LP's published coverage chart (waste not included). Raw 8" lap math: $100 \div 9.17 = 10.9$, rounded to 11. Common estimating error to avoid: the 8" lap face is 7-7/8", not 7-1/4" — use a 6-7/8" reveal.

Soffit — 38 Series (3/8" Cedar Texture / Smooth, vented or solid, 16' boards)

Full-coverage product — no reveal or overlap to subtract. Boards run 16' along the eave with their width spanning the overhang (wall to fascia). Pick the smallest stock width $\geq$ overhang depth; rip to depth. Estimate off actual width. Add a ~10% allowance for channel seating and end cuts.

Soffit area	$\text{eave run (lf)} \times \text{overhang depth (ft)}$
Coverage per panel	$\text{actual width (in)} \div 12 \times \text{length (ft)}$
Pieces (area method)	$\text{soffit area} \div \text{coverage per panel} \times (1 + \text{waste}) \rightarrow \text{round up}$ [exact only when depth = board width]
Boards to order	$\text{eave length (lf)} \div 16 \times \text{courses} \rightarrow \text{round up}$ [courses = $\text{ceil}(\text{depth} \div \text{board width})$]

PANEL WIDTH	ACTUAL WIDTH	LENGTH	COVERAGE / PANEL	BEST FOR OVERHANG DEPTH
12" Soffit	11.94"	16'	15.9 sq ft	Up to ~12" (1:1, no rip)
16" Soffit	15.94"	16'	21.3 sq ft	Up to ~16" (1:1, no rip)
24" Soffit	23.94"	16'	31.9 sq ft	Up to ~24"; rip for odd depths
4' x 8' Panel	47.88"	8'	31.9 sq ft	Wide / open soffit areas

Coverage = full panel width $\times$ length (no lap deduction). Width does NOT change the formula — only the divisor, which scales linearly with width (double width = half the pieces). The catch is matching width to depth: a stock width that equals the overhang depth (e.g. 12" or 24") rips clean 1:1, but an odd depth (e.g. 17") means ripping a 24" board and discarding the ~7" offcut, so the area method underestimates — order by eave length instead (1 board per 16 lf per course) and flag rip waste. For vented soffit, net free area (NFA) for attic ventilation is a separate calculation. 24" actual width follows LP's –1/16" convention; verify against the panel stamp if exact.

Cedar Texture Shakes — Straight or Staggered Edge (4' panels, variable reveal)

Short 4' (48") panels with an installer-selected reveal between min 6-7/8" and max 9-7/8". Piece count scales with the chosen reveal — more overlap = smaller reveal = more panels. Add ~10% waste (a touch more for staggered-edge layouts).

Coverage per panel	$4\text{ ft} \times (\text{reveal in} \div 12)$
Pieces needed	$\text{wall area (sq ft)} \div \text{coverage per panel} \times (1 + \text{waste factor}) \rightarrow \text{round up}$
Pieces per square	$100 \div (4 \times \text{reveal_in} \div 12)$

REVEAL (EXPOSURE)	PANEL LENGTH	COVERAGE / PANEL	PIECES / SQUARE*	NOTE
6-7/8" (6.875") — min	4'	2.29 sq ft	44 pcs	Max coverage rate
7" (7.000")	4'	2.33 sq ft	43 pcs	540 trim range
8" (8.000")	4'	2.67 sq ft	38 pcs	540 trim range
9-7/8" (9.875") — max	4'	3.29 sq ft	31 pcs	Fewest panels

*Pieces per square = pieces per 100 sq ft, before waste, rounded up. Reveal is an installer design choice and scales linearly. LP recommends 540 Series trim when the reveal runs between 7" and 10" — flag the chosen reveal for corner/trim takeoff.

Board & Batten — 38 Series 4' x 10' Panel + Batten Strips

Two-component takeoff: 4'x10' panels form the field, battens are separate vertical trim strips (LP SmartSide trim, typically 2-1/2" or 3-1/2" wide, 16' lengths) run over every panel seam and at the chosen on-center spacing. Keep spacing dividing evenly into 48" so seam battens and field battens stay on one rhythm.

Panel coverage	$4' \times 10' = 40\text{ sq ft (LP nominal)}$
Panels needed	$\text{wall area (sq ft)} \div 40 \times (1 + \text{waste factor}) \rightarrow \text{round up}$
Batten linear feet	$\approx \text{wall area (sq ft)} \div \text{spacing (ft)} + (1 \text{ batten} \times \text{wall height per run})$
Batten pieces	$\text{batten LF} \div 16' \text{ stock length} \rightarrow \text{round up}$

BATTEN SPACING (O.C.)	BATTEN LF / 100 SQ FT	LOOK	DIVIDES INTO 48" SEAM?
12" o.c.	100 LF	Classic narrow	Yes (4 per panel)
16" o.c.	75 LF	Standard	Yes (3 per panel)
24" o.c.	50 LF	Wide / modern	Yes (2 per panel)

Panels: LP estimates off the full 4' width; net shiplap coverage is ~47-7/8". Battens: LF-per-100-sq-ft is a function of spacing only (battens run vertically), so batten LF $\approx$ wall area $\div$ spacing in feet. Battens are mandatory over every 48" panel seam — non-dividing spacings create a double batten at the joint.

Nickel Gap — ExpertFinish / 38 Series (1/2" x 8" nom., fixed 7" reveal, 16' boards)

Tongue-and-groove with a self-spacing locking flange and concealed fasteners. Reveal is fixed at 7" — not installer-adjustable — so the piece count is constant. Installs horizontal or vertical without changing the coverage math. Cedar texture or brushed smooth, ExpertFinish colors or primed.

Coverage per board	$\text{length (ft)} \times \text{reveal (in)} \div 12 = 16 \times 7 \div 12 = 9.33 \text{ sq ft}$
Pieces needed	$\text{wall area (sq ft)} \div 9.33 \times (1 + \text{waste factor}) \rightarrow \text{round up}$
Pieces per square	$100 \div (16 \times 7 \div 12) = 10.7 \rightarrow 11$

PROFILE	THICKNESS	REVEAL (FIXED)	COVERAGE / 16' BOARD	PIECES / SQUARE*
8" Nickel Gap	1/2"	7" (locked)	9.33 sq ft	11 pcs

*Pieces per square = pieces per 100 sq ft, before waste, rounded up (raw 10.7). Reveal is hard-coded by the locking flange — lock this field in the estimator, no reveal input. Concealed fastening; orientation (horizontal/vertical) does not change coverage but should flag trim/J-channel takeoff.

Coverage figures are LP-published and do not include waste — add a jobsite waste factor and round up to whole boards/pieces. Verify against the current LP coverage chart at lpcorp.com before quoting. Additional LP product sections to follow.