Joshua Nelson, u4850020

The Fast Multipole Algorithm vs. the Particle Mesh Ewald Method

Joshua Nelson, u4850020

COMP3006 - Research Project

November 1, 2012

The N body problem

Statement of the problem

Joshua Nelson, u4850020

The N bod

Given N bodies that all interact with each other in some way, how do we efficiently calculate the effect each body has on every other body?

The N body problem History

Joshua Nelson, u4850020

The N body problem

The Fast Multipole Algorithm

Algorithm

Particle Mesl

• First formally specified by Isaac Newton

The N body problem History

- First formally specified by Isaac Newton
- No exact formula solution


The N body problem

Joshua Nelson, u4850020

The N body

- First formally specified by Isaac Newton
- No exact formula solution
- Approximation methods devised

The N body problem $_{\mbox{\scriptsize Applications}}$




The N body problem $_{\mbox{\scriptsize Applications}}$





The N body problem $_{\mbox{\scriptsize Applications}}$



Algorithm

Joshua Nelson, u4850020 • Say that a particle at position r_i with charge q_i gives a potential Q at a particle r_j with charge q_j according to the formula

$$Q = \frac{q_i * q_j}{|r_i - r_j|}$$

Algorithm

Joshua Nelson, u4850020 • Say that a particle at position r_i with charge q_i gives a potential Q at a particle r_i with charge q_i according to the formula

$$Q = \frac{q_i * q_j}{|r_i - r_j|}$$

 For each particle pair, calculate the the interaction according to the above formula

Algorithm

Joshua Nelson,

• Say that a particle at position r_i with charge q_i gives a potential Q at a particle r_i with charge q_i according to the formula

$$Q = \frac{q_i * q_j}{|r_i - r_j|}$$

- For each particle pair, calculate the the interaction according to the above formula
- Use the potential at each particle to calculate the force, and move the particle according to this force.

Algorithm

Joshua Nelson, u4850020 • Say that a particle at position r_i with charge q_i gives a potential Q at a particle r_i with charge q_i according to the formula

$$Q = \frac{q_i * q_j}{|r_i - r_j|}$$

- For each particle pair, calculate the the interaction according to the above formula
- Use the potential at each particle to calculate the force, and move the particle according to this force.
- Order $O(n^2)$ complexity.

Key components to the Fast Multipole Algorithm

Joshua Nelson, u4850020

Key components to the Fast Multipole Algorithm

The Mesh



Key components to the Fast Multipole Algorithm

Joshua Nelson, u4850020

Key components to the Fast Multipole Algorithm

- The Mesh
- Multipole Expansions

The Fast Multipole Algorithm The Mesh

Joshua Nelson, u4850020 The Particle Mesh

Level 0


Level o			
Level 1 Level 2			
Level 2			
l			
l			
l			

The Fast Multipole Algorithm The Mesh

Joshua Nelson, u4850020

The Fast Multipole

Well separated cells



The Fast Multipole Algorithm Expansions

Joshua Nelson, u4850020

> Multipole Expansions: A series, centered on a particular cell, which can approximate the potential from the cell's particles near that cell

The Fast Multipole Algorithm Expansions

- Multipole Expansions: A series, centered on a particular cell, which can approximate the potential from the cell's particles near that cell
- Local Expansions: A series, centered on a particular cell, formed from a Multipole Expansion, which approximates the potential from within the cell at some distance away from that cell.

The Fast Multipole Algorithm vs. the Particle Mesh Ewald Method

Joshua Nelson, u4850020

problem The basi

The Dask solution

Multipol Algorithr

Particle Me

• Form Multipole Expansions at the lowest mesh level

- Form Multipole Expansions at the lowest mesh level
- Translate them to their parent's cells, combining the four children by summing them to form the parent's Multipole Expansion

- Form Multipole Expansions at the lowest mesh level
- Translate them to their parent's cells, combining the four children by summing them to form the parent's Multipole Expansion
- Repeat the above for each level



- Form Multipole Expansions at the lowest mesh level
- Translate them to their parent's cells, combining the four children by summing them to form the parent's Multipole Expansion
- Repeat the above for each level
- At the highest level, from the Multipole Expansion, form a Local Expansion.


- Form Multipole Expansions at the lowest mesh level
- Translate them to their parent's cells, combining the four children by summing them to form the parent's Multipole Expansion
- Repeat the above for each level
- At the highest level, from the Multipole Expansion, form a Local Expansion.
- Translate this to children nodes, repeat to the lowest mesh level.



Basic structure of the Particle Mesh Ewald Method

Basic structure of the Particle Mesh Ewald Method

• Interpolate particles to a grid





Basic structure of the Particle Mesh Ewald Method

Joshua Nelson, u4850020

- Interpolate particles to a grid
- Perform a fourier transformation on the grid

Basic structure of the Particle Mesh Ewald Method

Joshua Nelson, u4850020

- Interpolate particles to a grid
- Perform a fourier transformation on the grid
- Calculate long range potential in reciprocal space using this grid

Basic structure of the Particle Mesh Ewald Method

Joshua Nelson,

- Interpolate particles to a grid
- Perform a fourier transformation on the grid
- Calculate long range potential in reciprocal space using this grid
- Return to real space using another fourier transformation

Basic structure of the Particle Mesh Ewald Method

Joshua Nelson,

- Interpolate particles to a grid
- Perform a fourier transformation on the grid
- Calculate long range potential in reciprocal space using this grid
- Return to real space using another fourier transformation
- Calculate in real space directly for near particles, and use interpolated grid values for the long range potential.



Characteristics of the Particle Mesh Ewald Method

Joshua Nelson, u4850020

Characteristics of the Particle Mesh Ewald Method


• Complexity of $O(n\log(n))$

Characteristics of the Particle Mesh Ewald Method


Joshua Nelson, u4850020

Characteristics of the Particle Mesh Ewald Method


- Complexity of O(nlog(n))
- Fourier transformation technique leads to Periodic Boundary Conditions



Results Basic Algorithm




Results Fast Multipole Algorithm




Results Particle Mesh Ewald Algorithm


Joshua Nelson, u4850020



Results Comparison



Results Comparison



Conclusion Methods

Joshua Nelson, u4850020

• Fast Multipole Algorithm is the fastest with the lowest run times over most cases

Conclusion Methods

- Fast Multipole Algorithm is the fastest with the lowest run times over most cases
- Particle Mesh Ewald has desriable features and more potential for paralellisation and optimisation

Conclusion Methods

- Fast Multipole Algorithm is the fastest with the lowest run times over most cases
- Particle Mesh Ewald has desriable features and more potential for paralellisation and optimisation
- The Basic solution is not feasible for very large system sizes

Joshua Nelson, u4850020

 Created fucntional implementations of the Basic, Particle Mesh Ewald, and Fast Multipole algorithms in Java.

- Created fucntional implementations of the Basic, Particle Mesh Ewald, and Fast Multipole algorithms in Java.
- Well documented and coded with readability in mind

- Created fucntional implementations of the Basic, Particle Mesh Ewald, and Fast Multipole algorithms in Java.
- Well documented and coded with readability in mind
- Actualization of often abstractly defined algorithms

- Created fucntional implementations of the Basic, Particle Mesh Ewald, and Fast Multipole algorithms in Java.
 - Well documented and coded with readability in mind
- Actualization of often abstractly defined algorithms
- Complexity analysis of algorithms, crossover points found.

Conclusion

- Created fucntional implementations of the Basic, Particle Mesh Ewald, and Fast Multipole algorithms in Java.
- Well documented and coded with readability in mind
- Actualization of often abstractly defined algorithms
- Complexity analysis of algorithms, crossover points found.
- Bridged the gap between mathematicians, computer scientists, and computational chemists.