

Some Important Subtleties of Inheritance and Constructors in Java

(Not necessarily an all-inclusive list.)

(Please let me know if you see any errors.)

Contents

Constructors Are Not Inherited

Constructor Chaining

No No-Arg Superclass Constructor

super() Must Be First

Initialization Order

Overridden Methods in Constructors

this() vs super()

Each Class Initializes Its Own Fields

Default Constructors

Abstract Class Constructors

Constructors Are Not Polymorphic

Static and Instance Initializers

Calling super in a Chain of Inheritance

Exception Handling

Object Creation Sequence

Constructors Are Not Inherited

- Subclasses do not inherit constructors from their parent class.
- Subclasses can call a superclass constructor using .

`super(...)`

[↑ Back to Top](#)

Constructor Chaining Happens Automatically

- All ancestor constructors execute when a subclass is instantiated.
- They are executed from the topmost superclass down to the subclass
- If not specified, Java inserts an implicit `super()`.

```
class A {
    A() {
        System.out.println("A");
    }
}

class B extends A {
    B() {
        System.out.println("B");
    }
}
```

Output:

```
A
B
```

[↑ Back to Top](#)

If the Superclass Has No No-Arg Constructor

- The subclass must explicitly call `super(args)`.
- Otherwise, compilation fails.

[↑ Back to Top](#)

The `super()` Call Must Be the First Statement

- No statements may appear before `super()`.
- If omitted, Java inserts it automatically (if possible).
- Java 24 introduces a preview feature allowing pre-constructor code.

[↑ Back to Top](#)

Instance Variable Initialization Order

1. Memory allocated for all fields.
2. Superclass initialization occurs first.
3. Subclass initialization follows.

[↑ Back to Top](#)

Avoid Calling Overridden Methods in Constructors

- Overridden methods may run before subclass fields initialize.
- This can cause inconsistent or unsafe behavior.

A superclass constructor should not invoke non-final, non-static methods that may be overridden in subclasses. Because of polymorphism, such a call can execute the subclass's overridden method before the subclass's instance variables have been initialized, potentially leading to inconsistent or erroneous behavior.

[↑ Back to Top](#)

`this()` vs `super()`

- `this()` calls another constructor in the same class.
- `super()` calls a superclass constructor.
- You may use one or the other — not both.

[↑ Back to Top](#)

Each Class Has Responsibility for Its Own Fields

- Each constructor initializes only its own class's fields.
- Superclass fields must be initialized via `super()` for proper initialization.

[↑ Back to Top](#)

Default Constructors and Inheritance

- No constructors → Java supplies a default no-arg constructor.
- Defining any constructor suppresses the default.
- Constructors are not inherited, but initialization behavior is.

[↑ Back to Top](#)

Abstract Classes Still Have Constructors

- Abstract classes cannot be instantiated.
- Their constructors still run during subclass creation.

[↑ Back to Top](#)

Constructors Are Not Polymorphic

- Constructors cannot be overridden.
- Execution depends on the instantiated class.

[↑ Back to Top](#)

Static and Instance Initializers

1. Static initializers (only once, when the class loads)
2. Instance variable initializers (superclass → subclass)

3. Constructors (superclass → subclass)

[↑ Back to Top](#)

Calling super in a Chain of Inheritance

1. Each level can call a specific superclass constructor
2. Each level can pass arguments upward, possibly modifying/validating them at each level
3. This provides a clear chain of responsibility for setting up the object state.

[↑ Back to Top](#)

Exception Handling in Constructors

- Checked exceptions must be declared or handled.
- If a superclass constructor throws a checked exception, the subclass constructor must throw it or handle it.
- This ensures all parts of the hierarchy honor exception contracts.

[↑ Back to Top](#)

Object Creation Sequence Summary

Example: Class C that extends B that extends A

1. Memory allocated for all fields.
2. Static initializers: A → B → C
3. Constructors: A → B → C

[↑ Back to Top](#)