

A Factor Model with Paired Comparison Indicators

Joshua N. Pritikin

Virginia Institute for Psychiatric and Behavioral Genetics
Virginia Commonwealth University

May 2019



Acknowledgment



Friday, Shutterstock

Some mentors and collaborators

- ▶ Mike Neale
- ▶ Rob Kirkpatrick

Funded in part by NIDA R25 DA-26119



How to plan a study



A pre-registered analysis plan

- ▶ Model chosen
- ▶ Fake data simulated
- ▶ Analyses scripts written



Not pre-registered but



- ▶ Model chosen
- ▶ Fake data simulated
- ▶ Analyses scripts **somewhat** written




Thorough and complete mental plan



Delegated to an expert



Vague Plan



- Collect data
- Figure out the model **later**



Magical thinking



Reality sets in




Ranking skill

Chess, Go, shogi, etc

$$i, j \in \{1, 2, \dots, N\} \quad (1)$$

$$\pi(i > j) = \frac{\theta_i}{\theta_i + \theta_j} \quad (2)$$



where N is the number of players and θ is some measure of skill¹

Also similar to Thurstone (1927)

¹Bradley and Terry (1952); Luce (1959)

A factor model

RESEARCH

COMPUTER SCIENCE

A general reinforcement learning algorithm that masters chess, shogi, and Go through self-play

David Silver^{1,2*,†}, Thomas Hubert^{1*}, Julian Schrittwieser^{1*}, Ioannis Antonoglou¹, Matthew Lai¹, Arthur Guez¹, Marc Lanctot¹, Laurent Sifre¹, Dhharshan Kumaran¹, Thore Graepel¹, Timothy Lillicrap¹, Karen Simonyan¹, Demis Hassabis^{1†}

The game of chess is the longest-studied domain in the history of artificial intelligence. The strongest programs are based on a combination of sophisticated search techniques, domain-specific adaptations, and handcrafted evaluation functions that have been refined by human experts over several decades. By contrast, the AlphaGo Zero program recently achieved superhuman performance in the game of Go by reinforcement learning from self-play. In this paper, we generalize this approach into a single AlphaZero algorithm that can achieve superhuman performance in many challenging games. Starting from random play and given no domain knowledge except the game rules, AlphaZero convincingly defeated a world champion program in the games of chess and shogi (Japanese chess), as well as Go.



Prior work is mostly univariate

Thurstone (1927) \approx 6000 citations

Bradley and Terry (1952) \approx 2500 citations

Luce (1959) \approx 6500 citations



Association/correlational model (not a factor model)


- ▶ Bockenholt (1988) \approx 15 citations
- ▶ Dittrich, Francis, Hatzinger, and Katzenbeisser (2006) \approx 15 citations



Ship's manifest

- ▶ Bayes
- ▶ Item response model
- ▶ Posterior predictive check †
- ▶ Scale recovery
- ▶ Simulation-based Calibration †
- ▶ Validation
- ▶ Close


† Two prominent methods for Bayesian model validation




Ship's manifest

- ▶ Bayes
- ▶ Item response model
- ▶ Posterior predictive check †
- ▶ Scale recovery
- ▶ Simulation-based Calibration †
- ▶ Validation
- ▶ Close

† Two prominent methods for Bayesian model validation



Bayes' Theorem



$$P(A|B) \cdot P(B) = P(A \cap B) = P(B|A) \cdot P(A)$$



Bayesian Inference

$$\pi(\theta|y) = \frac{\pi(y|\theta)\pi(\theta)}{\pi(y)} \quad (3)$$

- ▶ y is the observed data
- ▶ θ is the parameter vector
- ▶ $\pi(\theta)$ is the prior
- ▶ $\pi(y|\theta)$ is the likelihood
- ▶ $\pi(\theta|y)$ is the **posterior**



Bayesian Inference

$$\pi(\theta|y) \propto \pi(y|\theta)\pi(\theta) \quad (4)$$


- ▶ y is the observed data
- ▶ θ is the parameter vector
- ▶ $\pi(\theta)$ is the prior
- ▶ $\pi(y|\theta)$ is the likelihood
- ▶ $\pi(\theta|y)$ is the **posterior**



Ship's manifest

- ▶ Bayes
- ▶ Item response model
- ▶ Posterior predictive check †
- ▶ Scale recovery
- ▶ Simulation-based Calibration †
- ▶ Validation
- ▶ Close

† Two prominent methods for Bayesian model validation



A tournament



Item Response Model

```



1 softmax <- function(y) exp(y) / sum(exp(y))
2 cmp_probs <- function(scale, pa1, pa2, thRaw) {
3   th <- cumsum(thRaw)
4   diff <- scale * (pa1 - pa2);
5   unsummed <- c(0, c(diff - rev(th)), c(diff + th),
6     use.names = FALSE)
7   softmax(cumsum(unsummed))
8 }

```


- ▶ `scale` is a scalar number
- ▶ `pa1`, `pa2` are latent scores for two different objects
- ▶ `thRaw` is a vector of thresholds
- ▶ Similar to the partial credit model²

²Masters (1982)

Which is more efficient?



Parameter recovery by connectivity



More than win/lose

Participant picks: running, golf

How predictable is the action?

- ▶ golf is much more predictable than running.
- ▶ golf is somewhat more predictable than running.
- ▶ Both offer roughly equal predictability.
- ▶ running is somewhat more predictable than golf.
- ▶ running is much more predictable than golf.




Item Parameters

Item model explorer demo

- ▶ Can regard **scale** as arbitrary
- ▶ For any **scale**, thresholds can be correspondingly scaled
- ▶ Object variance and item discrimination are **confounded**




Response curve for simulations



Ship's manifest

- ▶ Bayes
- ▶ Item response model
- ▶ Posterior predictive check †
- ▶ Scale recovery
- ▶ Simulation-based Calibration †
- ▶ Validation
- ▶ Close

† Two prominent methods for Bayesian model validation



Posterior predictive check



Define

$$\pi(y^{\text{rep}}|y) = \int d\theta \pi(y^{\text{rep}}|\theta) \pi(\theta|y) \pi(\theta). \quad (5)$$

A good likelihood satisfies³

$$\pi(y^{\text{rep}}|\theta) = \pi(y^{\text{rep}}|\theta, y) \quad (6)$$

³Gelman et al. (2013, p. 146)



Method


- ▶ 2 thresholds
- ▶ 5 objects with round-robin connectivity
- ▶ 1000 observations (100 per object pair)
- ▶ $\chi^2 = \frac{(O-E)^2}{E}$
- ▶ Minimum frequency of 5 per expected cell

For each object pair i, j where $i < j$, collect statistics

$$\int dy^{\text{rep}} \chi_{ij}^2(y, y^{\text{rep}}) \pi(y^{\text{rep}}|y) \quad (7)$$




Object connectivity



Note: Can't check datasets with sparse, tree-like connectivity




Results




Ship's manifest

- ▶ Bayes
- ▶ Item response model
- ▶ Posterior predictive check †
- ▶ Scale recovery
- ▶ Simulation-based Calibration †
- ▶ Validation
- ▶ Close

† Two prominent methods for Bayesian model validation



Distribution of objects



- ▶ Nice if objects are standard normally distributed
- ▶ How to find the best scaling constant?



Intuition

```
9  cmp_probs <- function(scale, pa1, pa2, thRaw) {  
10    th <- cumsum(thRaw)  
11    diff <- scale * (pa1 - pa2); # <—————  
12    unsummed <- c(0, c(diff - rev(th)), c(diff + th),  
13      use.names = FALSE)  
14    softmax(cumsum(unsummed))  
15  }
```

- ▶ The scale of `diff` is **fixed**; thresholds have prior $\mathcal{N}(0, 2)$
- ▶ If scale **increases** then $(pa1 - pa2)$ **decreases** to keep the product (`diff`) constant; Object variance is **reduced**
- ▶ If scale **decreases** then $(pa1 - pa2)$ **increases** to keep the product (`diff`) constant; Object variance is **increased**




Negative feedback loop

```
16 transformed parameters {  
17   real scale = (sigma * sigma) ^ varCorrection;  
18 }  
19 model {  
20   sigma ~ lognormal(1, 1);  
21   theta ~ normal(0, sigma);  
22   ...    // remaining lines omitted  
23 }
```


- ▶ `sigma` is an estimate of object standard deviation
- ▶ `theta` is a vector of object locations
- ▶ `varCorrection` is some constant ≥ 1
- ▶ Model fails if object variance is too small




Illustration




Scale correction



Boosted scale correction



RMSE with true scores




Excessive measurement error signaled by model failure



Ship's manifest

- ▶ Bayes
- ▶ Item response model
- ▶ Posterior predictive check †
- ▶ Scale recovery
- ▶ Simulation-based Calibration †
- ▶ Validation
- ▶ Close

† Two prominent methods for Bayesian model validation



Simulation-Based Calibration (SBC)

Procedure

1. $\tilde{\theta} \sim \pi(\theta)$
2. $\tilde{y} \sim \pi(y|\tilde{\theta})$
3. $\{\theta_1, \dots, \theta_L\} \sim \pi(\theta|\tilde{y})$ or $\pi(\tilde{y}|\theta) \pi(\theta)$
4. $\sum_{l=1}^L \mathcal{I}(\theta_l < \tilde{\theta})$ is uniformly distributed in $[0, L]$

Integrating the posteriors over the joint distribution returns the prior,⁴

$$\pi(\theta) = \int d\tilde{y}d\tilde{\theta} \pi(\theta|\tilde{y}) \pi(\tilde{y}|\tilde{\theta}) \pi(\tilde{\theta}) \quad (8)$$

⁴Talts, Betancourt, Simpson, Vehtari, and Gelman (2018) 







Example #1


```
24 data {  
25   int<lower=1> N; // number of observations  
26 }  
27 transformed data {  
28   real loading_ = normal_rng(0,3); // sim prior  
29   vector[N] obs;  
30   for (n in 1:N) obs[n] = normal_rng(loadings_, 1); // sim data  
31 }  
32 parameters {  
33   real loading; // theta  
34 }  
35 model {  
36   loading ~ normal(0, 3); // prior  
37   for (n in 1:N) {  
38     obs[n] ~ normal(loadings_, 1.0); // likelihood  
39   }  
40 }
```




Examples of bad histograms



Results



Support compatibility




Example #2

```
41 data {  
42   int<lower=1> N; // number of observations  
43 }  
44 transformed data {  
45   real loading_ = (lognormal_rng(0,1) *  
46     (bernoulli_rng(0.5) * 2 - 1));  
47   vector[N] obs;  
48   for (n in 1:N) obs[n] = normal_rng(loadings_, 1); // sim data  
49 }  
50 parameters {  
51   real loading; // theta  
52 }  
53 model {  
54   loading ~ normal(0, 3); // prior  
55   for (n in 1:N) {  
56     obs[n] ~ normal(loadings_, 1.0); // likelihood  
57   }  
58 }
```



Results



Huh?




Validated a **subset** of the parameter space



Ship's manifest

- ▶ Bayes
- ▶ Item response model
- ▶ Posterior predictive check †
- ▶ Scale recovery
- ▶ Simulation-based Calibration †
- ▶ **Validation**
- ▶ Close

† Two prominent methods for Bayesian model validation




Univariate model

SBC

- ▶ $\tau_1, \tau_2 \sim \mathcal{N}(0, 2)$
- ▶ 25 objects $\sim \mathcal{N}(0, 1)$
- ▶ 375 pairwise comparisons
- ▶ random tree connectivity
- ▶ 1000 draws from the prior, with 1023 draws per prior



Worst univariate histograms



Multivariate workflow




Screen indicators for good behavior,

- ▶ Fit univariate models
- ▶ Discard items with extreme scaling factors
- ▶ Fix model-wise scale at the mean item scale



Covariance, sample size




Method

SBC


- ▶ 3 items
- ▶ 50 objects $\sim \mathcal{N}(0, 1)$
- ▶ $\tau_1 \sim \mathcal{N}(-0.8, 0.2), \tau_2 \sim \mathcal{N}(-1.7, 0.2)$
- ▶ Variances $\sim \log \mathcal{N}(0.3^2, 0.3)$
- ▶ Correlations $\sim \text{lkj}(2.0)$
- ▶ 700 pairwise comparisons
- ▶ Random tree connectivity
- ▶ 500 draws from the prior, with 1535 draws per prior



Worst covariance model histograms



Factor model, sample size




Method

SBC


- ▶ 4 items
- ▶ 50 objects $\sim \mathcal{N}(0, 1)$
- ▶ $\tau_1 \sim \mathcal{N}(-0.8, 0.2)$, $\tau_2 \sim \mathcal{N}(-1.7, 0.2)$
- ▶ Proportions $\sim \text{Beta}(4.0, 3.0)$
- ▶ 800 pairwise comparisons
- ▶ Random tree connectivity
- ▶ 500 draws from the prior, with 1535 draws per prior



Beta(4.0, 3.0)



Worst factor model histograms




Note: 68 chains had divergent transitions after warm-up. There were a total of 127 divergent transitions across all chains.



Ship's manifest

- ▶ Bayes
- ▶ Item response model
- ▶ Posterior predictive check †
- ▶ Scale recovery
- ▶ Simulation-based Calibration †
- ▶ Validation
- ▶ Close

† Two prominent methods for Bayesian model validation



Caveat emptor



- ▶ Figure out your analysis plan before data collection
- ▶ Simulate data and write the analyses scripts
- ▶ Preregister it



Future work

CRAN package

- ▶ Stan models are tricky
- ▶ Connections are exogenous, non-stochastic; Need SBC



Submit manuscript



Questions?



- Bockenholt, U. (1988). A logistic representation of multivariate paired-comparison models. *Journal of Mathematical Psychology*, 32(1), 44–63. doi: 10.1016/0022-2496(88)90037-5
- Bradley, R. A., & Terry, M. E. (1952). Rank analysis of incomplete block designs: I. The method of paired comparisons. *Biometrika*, 39(3/4), 324–345. doi: 10.2307/2334029
- Dittrich, R., Francis, B., Hatzinger, R., & Katzenbeisser, W. (2006). Modelling dependency in multivariate paired comparisons: A log-linear approach. *Mathematical Social Sciences*, 52(2), 197–209. doi: 10.1016/j.mathsocsci.2006.06.001
- Gelman, A., Carlin, J. B., Stern, H. S., Dunson, D. B., Vehtari, A., & Rubin, D. B. (2013). *Bayesian data analysis* (3rd ed. ed.). CRC press.
- Luce, R. D. (1959). *Individual choice behaviour: A theoretical analysis*. New York: Wiley.
- Masters, G. N. (1982). A Rasch model for partial credit scoring. *Psychometrika*, 47, 149–174. doi: 10.1007/BF02296272
- Silver, D., Hubert, T., Schrittwieser, J., Antonoglou, I., Lai, M., Guez, A., ... others (2018). A general reinforcement learning



algorithm that masters chess, shogi, and Go through self-play.

Science, 362(6419), 1140–1144. doi: 10.1126/science.aar6404

Talts, S., Betancourt, M., Simpson, D., Vehtari, A., & Gelman, A. (2018). Validating bayesian inference algorithms with simulation-based calibration.

Thurstone, L. L. (1927). A law of comparative judgment.

Psychological review, 34(4), 273. doi: 10.1037/h0070288

