

Network Creation Games

Fall 2020

1 General model

2 Sum Game

Network creation games

- Creation and maintenance of a network is modeled as a game

Network creation games

- Creation and maintenance of a network is modeled as a game
- n players, think of them as vertices $V = \{1, \dots, n\}$ in an undirected graph

Network creation games

- Creation and maintenance of a network is modeled as a game
- n players, think of them as vertices $V = \{1, \dots, n\}$ in an undirected graph
- Each player can buy/create edges to other players paying a price $\alpha > 0$ per edge

Network creation games

- Creation and maintenance of a network is modeled as a game
- n players, think of them as vertices $V = \{1, \dots, n\}$ in an undirected graph
- Each player can buy/create edges to other players paying a price $\alpha > 0$ per edge
- A strategy s_u of player u is a subset $s_u \in V - \{u\}$ that represents the set of nodes for which u pays for a link.

Network creation games

- Creation and maintenance of a network is modeled as a game
- n players, think of them as vertices $V = \{1, \dots, n\}$ in an undirected graph
- Each player can buy/create edges to other players paying a price $\alpha > 0$ per edge
- A strategy s_u of player u is a subset $s_u \in V - \{u\}$ that represents the set of nodes for which u pays for a link.
- As a result of a strategy profile $s = (s_1, \dots, s_n)$ a graph $G(s) = (V, E)$ is created so that $E = \{(u, v) | u \in s_v \vee v \in s_u\}$

Network creation games

- Creation and maintenance of a network is modeled as a game
- n players, think of them as vertices $V = \{1, \dots, n\}$ in an undirected graph
- Each player can buy/create edges to other players paying a price $\alpha > 0$ per edge
- A strategy s_u of player u is a subset $s_u \in V - \{u\}$ that represents the set of nodes for which u pays for a link.
- As a result of a strategy profile $s = (s_1, \dots, s_n)$ a graph $G(s) = (V, E)$ is created so that $E = \{(u, v) | u \in s_v \vee v \in s_u\}$
- The goal of the player u is to minimize a cost function:

$$c_u(s) = \text{creation cost} + \text{usage cost}$$

Individual cost

Let $s = (s_1, \dots, s_n)$ and $G = G(s)$. The cost for player u :

$$c_u(s) = \text{creation cost} + \text{usage cost}$$

- Creation cost: $\alpha|s_u|$
- Usage cost:
 - SumGame (Fabrikant et al. PODC 2003)
Sum over all distances: $\sum_{v \in V} d_G(u, v)$
This is an average-case approach to the usage cost
 - MaxGame (Demaine et al. PODC 2007)
Maximum over all distances: $\max_{v \in V} d_G(u, v)$
A worst-case approach to the usage cost

$$\text{SumGame} : c_u(s) = \alpha|s_u| + \sum_{v \in V} d_G(u, v)$$


Social cost

- Creation cost: $\alpha|E(G)|$
- Usage cost:
 - SumGame: $\sum_{u,v \in V} d_G(u, v)$
 - MaxGame: $\max_{u,v \in V} d_G(u, v)$

$$\text{SumGame: } C(s) = \alpha|E| + \sum_{u,v \in V} d_G(u, v)$$

$$\text{MaxGame: } C(s) = \alpha|E| + \max_{u,v \in V} d_G(u, v)$$

An example




An example

$$s = (\{3, 4\}, \{1, 3\}, \{5\}, \{3\}, \{3\}, \{3\})$$

An example


$$s = (\{3, 4\}, \{1, 3\}, \{5\}, \{3\}, \{3\}, \{3\})$$



An arrow indicates who bought the edge


An example

$s = (\{3, 4\}, \{1, 3\}, \{5\}, \{3\}, \{3\}, \{3\})$ and $G(s)$




An example: SumGame

$s = (\{3, 4\}, \{1, 3\}, \{5\}, \{3\}, \{3\}, \{3\})$ and $G(s)$



An example: SumGame


$s = (\{3, 4\}, \{1, 3\}, \{5\}, \{3\}, \{3\}, \{3\})$ and $G(s)$



$$c_1(s) = 2\alpha + 1 + 1 + 1 + 2 + 2 = 2\alpha + 7 \dots$$

An example: SumGame

$s = (\{3, 4\}, \{1, 3\}, \{5\}, \{3\}, \{3\}, \{3\})$ and $G(s)$




$$c_1(s) = 2\alpha + 1 + 1 + 1 + 2 + 2 = 2\alpha + 7 \dots$$

$$c(s) = 7\alpha + (7 + 8 + 5 + 8 + 9 + 9) = 7\alpha + 56$$


An example: MaxGame

$s = (\{3, 4\}, \{1, 3\}, \{5\}, \{3\}, \{3\}, \{3\})$ and $G(s)$



An example: MaxGame


$s = (\{3, 4\}, \{1, 3\}, \{5\}, \{3\}, \{3\}, \{3\})$ and $G(s)$



$$c_1(s) = 2\alpha + 2 = 2\alpha + 2 \dots$$

An example: MaxGame

$s = (\{3, 4\}, \{1, 3\}, \{5\}, \{3\}, \{3\}, \{3\})$ and $G(s)$



$$c_1(s) = 2\alpha + 2 = 2\alpha + 2 \dots$$

$$c(s) = 7\alpha + 2$$

What to study?

What to study?

- Are there PNE?

What to study?

- Are there PNE?
- What are the social optima?

What to study?

- Are there PNE?
- What are the social optima?
- What network topologies are formed? What families of equilibrium graphs can one construct for a given α ?

What to study?

- Are there PNE?
- What are the social optima?
- What network topologies are formed? What families of equilibrium graphs can one construct for a given α ?
- How efficient are they? Price of Anarchy/Stability?

We will cover some results on SumGames

1 General model

2 Sum Game

Optimal/Equilibrium topologies

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

$$C(s) = \alpha |E| + \sum_{u, v \in V} d_G(u, v)$$

Optimal/Equilibrium topologies

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

$$C(s) = \alpha |E| + \sum_{u, v \in V} d_G(u, v)$$

- Can an edge be created by more than two players?

Optimal/Equilibrium topologies

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

$$C(s) = \alpha |E| + \sum_{u, v \in V} d_G(u, v)$$

- Can an edge be created by more than two players? **No**

Optimal/Equilibrium topologies

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

$$C(s) = \alpha |E| + \sum_{u, v \in V} d_G(u, v)$$

- Can an edge be created by more than two players? **No**
- We study them as a function of α

Optimal/Equilibrium topologies

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

$$C(s) = \alpha |E| + \sum_{u, v \in V} d_G(u, v)$$

- Can an edge be created by more than two players? **No**
- We study them as a function of α
- When is it better to add/remove an edge?

Optimal/Equilibrium topologies

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

$$C(s) = \alpha |E| + \sum_{u, v \in V} d_G(u, v)$$

- Can an edge be created by more than two players? **No**
- We study them as a function of α
- When is it better to add/remove an edge?
- Can the graph be disconnected?

Optimal/Equilibrium topologies

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

$$C(s) = \alpha |E| + \sum_{u, v \in V} d_G(u, v)$$

- Can an edge be created by more than two players? **No**
- We study them as a function of α
- When is it better to add/remove an edge?
- Can the graph be disconnected? **No**,
 $c_u(s) = \infty$ if $G(s)$ is not connected

Add an edge?

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

Add an edge?

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

- When is it better to add an edge?

Add an edge?

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

- When is it better to add an edge?
- Set $d = d_G(u, v) > 1$ and let $s'_u = s_u \cup \{v\}$

$$\begin{aligned} c_u(s_{-u}, s'_u) - c_u(s) &= \alpha + 1 - d + \sum_{w \in V, w \neq u} (d_{G'}(u, w)) - d_G(u, w) \\ &\leq \alpha + 1 - d \leq 0 \end{aligned}$$

Add an edge?

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

- When is it better to add an edge?
- Set $d = d_G(u, v) > 1$ and let $s'_u = s_u \cup \{v\}$

$$\begin{aligned} c_u(s_{-u}, s'_u) - c_u(s) &= \alpha + 1 - d + \sum_{w \in V, w \neq u} (d_{G'}(u, w)) - d_G(u, w) \\ &\leq \alpha + 1 - d \leq 0 \end{aligned}$$

- $d > \alpha$

Add an edge?

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

- When is it better to add an edge?
- Set $d = d_G(u, v) > 1$ and let $s'_u = s_u \cup \{v\}$

$$\begin{aligned} c_u(s_{-u}, s'_u) - c_u(s) &= \alpha + 1 - d + \sum_{w \in V, w \neq u} (d_{G'}(u, w)) - d_G(u, w) \\ &\leq \alpha + 1 - d \leq 0 \end{aligned}$$

- $d > \alpha$ which implies Nash topologies have **diameter** $\leq \alpha$.

Computing a Best Response

- Given a game $(1^n, \alpha)$, a strategy profile s and a player i , compute $s_i \in BR_i(s_{-i})$

Computing a Best Response

- Given a game $(1^n, \alpha)$, a strategy profile s and a player i , compute $s_i \in BR_i(s_{-i})$
- We relate the BR with a graph parameter.

Computing a Best Response

- Given a game $(1^n, \alpha)$, a strategy profile s and a player i , compute $s_i \in BR_i(s_{-i})$
- We relate the BR with a graph parameter.
- Given a graph $G = (V, E)$, with $V = \{1, \dots, n\}$, consider the following instance for the BR problem:

Computing a Best Response

- Given a game $(1^n, \alpha)$, a strategy profile s and a player i , compute $s_i \in BR_i(s_{-i})$
- We relate the BR with a graph parameter.
- Given a graph $G = (V, E)$, with $V = \{1, \dots, n\}$, consider the following instance for the BR problem:
 - The game has $n + 1$ players $\{0, 1, \dots, n\}$, choose α so that $1 < \alpha < 2$, the player will be player 0. The strategy is defined as follows:
 - Compute an orientation of E and define s_{-0} accordingly.

Computing a Best Response

- Given a game $(1^n, \alpha)$, a strategy profile s and a player i , compute $s_i \in BR_i(s_{-i})$
- We relate the BR with a graph parameter.
- Given a graph $G = (V, E)$, with $V = \{1, \dots, n\}$, consider the following instance for the BR problem:
 - The game has $n + 1$ players $\{0, 1, \dots, n\}$, choose α so that $1 < \alpha < 2$, the player will be player 0. The strategy is defined as follows:
 - Compute an orientation of E and define s_{-0} accordingly.
- As $1 < \alpha < 2$, player 0 will like to buy edges to any player at distance > 2 .
- So, in the BR graphs the radius of vertex 0 must be ≤ 2 .
- Hence, $c_0(s_{-0}, s'_0) = (\alpha + 1)|s'_0| + 2(n - |s'_0|)$

Computing a Best Response

- So, in the BR graphs the radius of vertex 0 must be ≤ 2 .
- On such graphs,

$$c_0(s_{-0}, s'_0) = (\alpha + 1)|s'_0| + 2(n - |s'_0|) = (\alpha - 1)|s'_0| + 2n$$

Computing a Best Response

- So, in the BR graphs the radius of vertex 0 must be ≤ 2 .
- On such graphs,

$$c_0(s_{-0}, s'_0) = (\alpha + 1)|s'_0| + 2(n - |s'_0|) = (\alpha - 1)|s'_0| + 2n$$
- Then, c_0 is minimized when s'_0 has minimum cardinality.

Computing a Best Response

- So, in the BR graphs the radius of vertex 0 must be ≤ 2 .
- On such graphs,

$$c_0(s_{-0}, s'_0) = (\alpha + 1)|s'_0| + 2(n - |s'_0|) = (\alpha - 1)|s'_0| + 2n$$
- Then, c_0 is minimized when s'_0 has minimum cardinality.
- To get radius ≤ 2 , $s'_0 \subseteq V$ must be a dominating set of $G = (V, E)$.

Computing a Best Response

- So, in the BR graphs the radius of vertex 0 must be ≤ 2 .
- On such graphs,

$$c_0(s_{-0}, s'_0) = (\alpha + 1)|s'_0| + 2(n - |s'_0|) = (\alpha - 1)|s'_0| + 2n$$
- Then, c_0 is minimized when s'_0 has minimum cardinality.
- To get radius ≤ 2 , $s'_0 \subseteq V$ must be a dominating set of $G = (V, E)$.
- The BR strategies for vertex 0 are the dominating sets of G having minimum size.

Computing a Best Response

- So, in the BR graphs the radius of vertex 0 must be ≤ 2 .
- On such graphs,
$$c_0(s_{-0}, s'_0) = (\alpha + 1)|s'_0| + 2(n - |s'_0|) = (\alpha - 1)|s'_0| + 2n$$
- Then, c_0 is minimized when s'_0 has minimum cardinality.
- To get radius ≤ 2 , $s'_0 \subseteq V$ must be a dominating set of $G = (V, E)$.
- The BR strategies for vertex 0 are the dominating sets of G having minimum size.
- Computing a minimum size dominating set is NP-hard, so

Computing a Best Response

- So, in the BR graphs the radius of vertex 0 must be ≤ 2 .
- On such graphs,

$$c_0(s_{-0}, s'_0) = (\alpha + 1)|s'_0| + 2(n - |s'_0|) = (\alpha - 1)|s'_0| + 2n$$
- Then, c_0 is minimized when s'_0 has minimum cardinality.
- To get radius ≤ 2 , $s'_0 \subseteq V$ must be a dominating set of $G = (V, E)$.
- The BR strategies for vertex 0 are the dominating sets of G having minimum size.
- Computing a minimum size dominating set is NP-hard, so
- **Computing a BR in the sum game** is NP-hard

Optimal topologies

$$c(s) = \alpha|E| + \sum_{u,v \in V} d_G(u, v)$$

- When two vertices u, v are not adjacent $d_G(u, v) \geq 2$.
- When two vertices u, v are adjacent $d_G(u, v) = 1$.
- Therefore for any strategy profile s ,

$$C(s) = \alpha|E| + \sum_{u,v \in V} d_G(u, v) \geq \alpha|E| + 2\left(\sum_{u,v \in V} 1 - |E|\right)$$

$$C(s) \geq \alpha|E| - 2|E| + 2n(n-1) = 2n(n-1) + (\alpha-2)|E|$$

Optimal topologies

$$c(s) = \alpha|E| + \sum_{u,v \in V} d_G(u, v)$$

- When two vertices u, v are not adjacent $d_G(u, v) \geq 2$.
- When two vertices u, v are adjacent $d_G(u, v) = 1$.
- Therefore for any strategy profile s ,

$$C(s) = \alpha|E| + \sum_{u,v \in V} d_G(u, v) \geq \alpha|E| + 2\left(\sum_{u,v \in V} 1 - |E|\right)$$

$$C(s) \geq \alpha|E| - 2|E| + 2n(n-1) = 2n(n-1) + (\alpha-2)|E|$$

- Holds with equality on graphs with diameter ≤ 2 .

Optimal topologies

- For all s , $C(s) \geq 2n(n-1) + (\alpha - 2)|E|$

Optimal topologies

- For all s , $C(s) \geq 2n(n-1) + (\alpha - 2)|E|$
- This function has different minima depending on whether $(\alpha - 2)$ is positive or negative.

Optimal topologies

- For all s , $C(s) \geq 2n(n-1) + (\alpha - 2)|E|$
- This function has different minima depending on whether $(\alpha - 2)$ is positive or negative.
- When $\alpha = 2$, the optimal cost is independent of the number of edges in the graph. So,

Optimal topologies

- For all s , $C(s) \geq 2n(n-1) + (\alpha - 2)|E|$
- This function has different minima depending on whether $(\alpha - 2)$ is positive or negative.
- When $\alpha = 2$, the optimal cost is independent of the number of edges in the graph. So,
- For $\alpha = 2$, any graph with **diameter ≤ 2 has optimal cost.**

Optimal topologies

- For all s ,

$$C(s) \geq 2n(n-1) + (\alpha - 2)|E| \geq 2n(n-1) + (\alpha - 2)(n-1)$$
- When $\alpha > 2$, to make the cost minimum we have to take the minimum number of edges in G . Of course the graph must be connected. So,

Optimal topologies

- For all s ,
$$C(s) \geq 2n(n-1) + (\alpha - 2)|E| \geq 2n(n-1) + (\alpha - 2)(n-1)$$
- When $\alpha > 2$, to make the cost minimum we have to take the minimum number of edges in G . Of course the graph must be connected. So,
- Only trees with diameter 2 have optimal cost. Then,

Optimal topologies

- For all s ,

$$C(s) \geq 2n(n-1) + (\alpha - 2)|E| \geq 2n(n-1) + (\alpha - 2)(n-1)$$
- When $\alpha > 2$, to make the cost minimum we have to take the minimum number of edges in G . Of course the graph must be connected. So,
- Only trees with diameter 2 have optimal cost. Then,
- For $\alpha > 2$, the star S_n is the unique optimal topology.

Optimal topologies

- For all s , $C(s) \geq 2n(n-1) + (\alpha - 2)|E|$

Optimal topologies

- For all s , $C(s) \geq 2n(n-1) + (\alpha - 2)|E|$
- When $\alpha < 2$, to make the cost minimum we have to take the maximum number of edges in G . Then,

Optimal topologies

- For all s , $C(s) \geq 2n(n-1) + (\alpha - 2)|E|$
- When $\alpha < 2$, to make the cost minimum we have to take the maximum number of edges in G . Then,
- For $\alpha < 2$ the complete graph K_n is the unique optimal topology.

Nash topologies

Nash topologies

- K_n (Clique) is the unique Nash topology for $\alpha < 1$

Nash topologies

- K_n (Clique) is the unique Nash topology for $\alpha < 1$
- S_n (Star) is a Nash topology for $\alpha \geq 1$
although they might be other PNE

PoA: $\alpha < 1$

- K_n is the unique Nash topology
- K_n is also an optimal topology

PoA: $\alpha < 1$

- K_n is the unique Nash topology
- K_n is also an optimal topology
- $PoA = PoS = 1$

PoA: $1 \leq \alpha < 2$

- K_n is an optimal topology
- Any Nash equilibrium must have diameter ≤ 2 , so S_n is a Nash topology with the worst social cost.

PoA: $1 \leq \alpha < 2$

- K_n is an optimal topology
- Any Nash equilibrium must have diameter ≤ 2 , so S_n is a Nash topology with the worst social cost.

$$\begin{aligned} PoA &= \frac{c(S_n)}{c(K_n)} = \frac{(n-1)(\alpha-2+2n)}{n(n-1)\frac{\alpha-2}{2}+2} \\ &= \frac{4}{2+\alpha} - \frac{4-2\alpha}{n(2+\alpha)} < \frac{4}{2+\alpha} \leq \frac{4}{3} \end{aligned}$$

PoA: $\alpha > n^2$

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

PoA: $\alpha > n^2$

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

- When $\alpha > n^2$, unless the distance is infinity, no player has incentive to buy an edge.

PoA: $\alpha > n^2$

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

- When $\alpha > n^2$, unless the distance is infinity, no player has incentive to buy an edge.
- The NE topologies are **spanning trees**

PoA: $\alpha > n^2$

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

- When $\alpha > n^2$, unless the distance is infinity, no player has incentive to buy an edge.
- The NE topologies are **spanning trees**
- The optimal topology is S_n

PoA: $\alpha > n^2$

$$c_u(s) = \alpha |s_u| + \sum_{v \in V} d_G(u, v)$$

- When $\alpha > n^2$, unless the distance is infinity, no player has incentive to buy an edge.
- The NE topologies are **spanning trees**
- The optimal topology is S_n

$$PoA = \frac{c(T_n)}{c(S_n)} \leq \frac{\alpha(n-1) + (n-1)(n-1)}{\alpha(n-1) + 1 + 2n(n-1)} = O(1)$$

General Upper bound for PoA: $\alpha < n^2$

- For a worst NE topology G ,

$$C(G) = \alpha|E| + \sum_{u,v \in V} d_G(u, v)$$

General Upper bound for PoA: $\alpha < n^2$

- For a worst NE topology G ,
$$C(G) = \alpha|E| + \sum_{u,v \in V} d_G(u, v)$$
- $d_G(u, v) < 2\sqrt{\alpha}$, otherwise u will be willing to connect to the node in the center of the shortest path from u to v to be closer by $-\sqrt{\alpha}$ to $\sqrt{\alpha}$ nodes.

General Upper bound for PoA: $\alpha < n^2$

- For a worst NE topology G ,

$$C(G) = \alpha|E| + \sum_{u,v \in V} d_G(u, v)$$
- $d_G(u, v) < 2\sqrt{\alpha}$, otherwise u will be willing to connect to the node in the center of the shortest path from u to v to be closer by $-\sqrt{\alpha}$ to $\sqrt{\alpha}$ nodes.
- Furthermore, $|E| = O(\frac{n^2}{\sqrt{\alpha}})$ (see [Fabrikant et al. 2003])

General Upper bound for PoA: $\alpha < n^2$

- For a worst NE topology G ,
$$C(G) = \alpha|E| + \sum_{u,v \in V} d_G(u, v)$$
- $d_G(u, v) < 2\sqrt{\alpha}$, otherwise u will be willing to connect to the node in the center of the shortest path from u to v to be closer by $-\sqrt{\alpha}$ to $\sqrt{\alpha}$ nodes.
- Furthermore, $|E| = O(\frac{n^2}{\sqrt{\alpha}})$ (see [Fabrikant et al. 2003])
- $C(G) \leq \alpha O(\frac{n^2}{\sqrt{\alpha}}) + n(n-1)2\sqrt{\alpha} = O(\sqrt{\alpha}n^2)$

General Upper bound for PoA: $\alpha < n^2$

- For a worst NE topology G ,
$$C(G) = \alpha|E| + \sum_{u,v \in V} d_G(u, v)$$
- $d_G(u, v) < 2\sqrt{\alpha}$, otherwise u will be willing to connect to the node in the center of the shortest path from u to v to be closer by $-\sqrt{\alpha}$ to $\sqrt{\alpha}$ nodes.
- Furthermore, $|E| = O(\frac{n^2}{\sqrt{\alpha}})$ (see [Fabrikant et al. 2003])
- $C(G) \leq \alpha O(\frac{n^2}{\sqrt{\alpha}}) + n(n-1)2\sqrt{\alpha} = O(\sqrt{\alpha}n^2)$
- $C(S_n) = \Omega(n^2)$

General Upper bound for PoA: $\alpha < n^2$

- For a worst NE topology G ,
 $C(G) = \alpha|E| + \sum_{u,v \in V} d_G(u, v)$
- $d_G(u, v) < 2\sqrt{\alpha}$, otherwise u will be willing to connect to the node in the center of the shortest path from u to v to be closer by $-\sqrt{\alpha}$ to $\sqrt{\alpha}$ nodes.
- Furthermore, $|E| = O(\frac{n^2}{\sqrt{\alpha}})$ (see [Fabrikant et al. 2003])
- $C(G) \leq \alpha O(\frac{n^2}{\sqrt{\alpha}}) + n(n-1)2\sqrt{\alpha} = O(\sqrt{\alpha}n^2)$
- $C(S_n) = \Omega(n^2)$
- Thus $PoA = O(\sqrt{\alpha})$

PoA: Conjectures

PoA on trees ≤ 5 [Fabrikant et al. 2003]

Constant PoA conjecture: For all α , $PoA = O(1)$.

Tree conjecture: for all $\alpha > n$, all NE are trees.

$O(1)$ PoA conjecture: large α

$PoA = O(1)$	
$\alpha > n^{\frac{3}{2}}$	[Lin 2003]
$\alpha > 12n \log n$	[Albers et al. 2014]
$\alpha > 273n$	[Mihalak, Schlegel, 2013]
$\alpha > 65n$	[Mamageishivii et al. 2015]
$\alpha > 17n$	[Àlvarez, Messegue 2017]
$\alpha > 4n - 13$	[Bilo, Lezner 2018]
$\alpha > (1 + \epsilon)n$	[Àlvarez, Messegue 2019]

$O(1)$ PoA conjecture: large α

$PoA = O(1)$	
$\alpha > n^{\frac{3}{2}}$	[Lin 2003]
$\alpha > 12n \log n$	[Albers et al. 2014]
$\alpha > 273n$	[Mihalak, Schlegel, 2013]
$\alpha > 65n$	[Mamangeishivii et al. 2015]
$\alpha > 17n$	[Àlvarez, Messegue 2017]
$\alpha > 4n - 13$	[Bilo, Lezner 2018]
$\alpha > (1 + \epsilon)n$	[Àlvarez, Messegue 2019]

[Àlvarez, Messegue 2019] On the price of Anarchy for High-Price links, *15th Conference on Web and Internet Economics, WINE 2019*, 316– 329

Extended version: arxiv.org/abs/1909.09799

$O(1)$ PoA conjecture: small α

$$PoA = O(1)$$

$$\alpha = O(1)$$

$$\alpha = O(\sqrt{n})$$

$$\alpha = O(n^{1-\delta}), \delta \geq 1/\log n$$

[Fabrikant et al. 2003]

[Lin 2003]

[Demaine et al. 2007]