

Manipulation

Maria Serna AGT-MIRI

Fall 2020

- 1 Strategy-proofness
- 2 Manipulation
- 3 Some manipulable rules

Strategy-proofness

- Would any of the voting rules have reporting their preferences truthfully?

Strategy-proofness

- Would any of the voting rules have reporting their preferences truthfully?
- Assume \succ is a preference profile so that \succ_i is the true preferences of voter i .

Strategy-proofness

- Would any of the voting rules have reporting their preferences truthfully?
- Assume \succ is a preference profile so that \succ_i is the true preferences of voter i .
- A voting rule F is **strategy-proof** if for every preference profile $\succ' = (\succ_{-i}, \succ'_i)$, it is not the case that $F(\succ') \succ_i F(\succ)$

Strategy-proofness: Borda count

- Borda with true preferences

Strategy-proofness: Borda count

- Borda with true preferences

N	1	2	3	Pt
	b	b	a	3
	a	a	b	2
	c	c	c	1
	d	d	d	0

Strategy-proofness: Borda count

- Borda with true preferences

N	1	2	3	Pt
	b	b	a	3
	a	a	b	2
	c	c	c	1
	d	d	d	0

Winner
b

Strategy-proofness: Borda count

- Borda with true preferences

N	1	2	3	Pt
	b	b	a	3
	a	a	b	2
	c	c	c	1
	d	d	d	0

Winner
b

- Voter 3 can make *a* win by

Strategy-proofness: Borda count

- Borda with true preferences

N	1	2	3	Pt
	b	b	a	3
	a	a	b	2
	c	c	c	1
	d	d	d	0

Winner
b

- Voter 3 can make *a* win by

N	1	2	3	Pt
	b	b	a	3
	a	a	c	2
	c	c	d	1
	d	d	b	0

Strategy-proofness: Borda count

- Borda with true preferences

N	1	2	3	Pt
	b	b	a	3
	a	a	b	2
	c	c	c	1
	d	d	d	0

Winner
b

- Voter 3 can make *a* win by

N	1	2	3	Pt
	b	b	a	3
	a	a	c	2
	c	c	d	1
	d	d	b	0

Winner
a

Strategy-proofness: Borda count

- Borda with true preferences

N	1	2	3	Pt
	b	b	a	3
	a	a	b	2
	c	c	c	1
	d	d	d	0

Winner
b

- Voter 3 can make *a* win by

N	1	2	3	Pt
	b	b	a	3
	a	a	c	2
	c	c	d	1
	d	d	b	0

Winner
a

Any of the rules we saw is strategy-proof?

Strategy-proof rules?

- Are there strategy-proof rules?

Strategy-proof rules?

- Are there strategy-proof rules?
- Dictatorial voting rule

Strategy-proof rules?

- Are there strategy-proof rules?
- Dictatorial voting rule
 - The winner is always the most preferred alternative of voter 1

Strategy-proof rules?

- Are there strategy-proof rules?
- Dictatorial voting rule
 - The winner is always the most preferred alternative of voter 1
- Constant voting rule

Strategy-proof rules?

- Are there strategy-proof rules?
- Dictatorial voting rule
 - The winner is always the most preferred alternative of voter 1
- Constant voting rule
 - The winner is always the same

Strategy-proof rules?

- Are there strategy-proof rules?
- Dictatorial voting rule
 - The winner is always the most preferred alternative of voter 1
- Constant voting rule
 - The winner is always the same
- Yes, but not very satisfactory!

Strategy-proof rules?

- Consider the following three properties:

Strategy-proof rules?

- Consider the following three properties:
- **Strategy-proof:** No voter has an incentive to misreport true preferences.

Strategy-proof rules?

- Consider the following three properties:
- **Strategy-proof:** No voter has an incentive to misreport true preferences.
- **Onto:** Every alternative can win under some preference profile.

Strategy-proof rules?

- Consider the following three properties:
- **Strategy-proof:** No voter has an incentive to misreport true preferences.
- **Onto:** Every alternative can win under some preference profile.
- **Non-dictatorial:** There is no voter i such that $F(\succ)$ is always the top alternative for voter i .

Gibbard-Satterthwaite

Theorem

For $m \geq 3$, no deterministic social choice function can be strategyproof, onto, and nondictatorial simultaneously.

Gibbard-Satterthwaite

Theorem

For $m \geq 3$, no deterministic social choice function can be strategyproof, onto, and nondictatorial simultaneously. ☹

Gibbard-Satterthwaite

Theorem

For $m \geq 3$, no deterministic social choice function can be strategyproof, onto, and nondictatorial simultaneously. ☹️

In 😊 words,

Gibbard-Satterthwaite

Theorem

For $m \geq 3$, no deterministic social choice function can be strategyproof, onto, and nondictatorial simultaneously. ☹️

In 😊 words, for $m \geq 3$, any deterministic social choice function must be at least one of the following:

Gibbard-Satterthwaite

Theorem

For $m \geq 3$, no deterministic social choice function can be strategyproof, onto, and nondictatorial simultaneously. ☹

In ☺ words, for $m \geq 3$, any deterministic social choice function must be at least one of the following:

- *dictatorial*: there exists a single fixed voter whose most-preferred alternative is chosen for every profile;
- *imposing*: there is at least one alternative that does not win under any profile;
- *manipulable* (i.e., not strategyproof).

Gibbard-Satterthwaite

Theorem

For $m \geq 3$, no deterministic social choice function can be strategyproof, onto, and nondictatorial simultaneously. ☹

In ☺ words, for $m \geq 3$, any deterministic social choice function must be at least one of the following:

- *dictatorial*: there exists a single fixed voter whose most-preferred alternative is chosen for every profile;
- *imposing*: there is at least one alternative that does not win under any profile;
- *manipulable* (i.e., not strategyproof).

The first two properties are not acceptable in most voting settings.
So, we need to assume that the voters have an incentive to misreport true preferences.

Circumventing G-S: Complexity approach

Circumventing G-S: Complexity approach

- (Bartholdi III, Tovey and Trick, Social Choice and Welfare, 1998)

Circumventing G-S: Complexity approach

- (Bartholdi III, Tovey and Trick, Social Choice and Welfare, 1998)
- As we cannot prevent a voting rule from being manipulable, this may not be a significant concern as long as determining how to manipulate it is computationally prohibitive.

Circumventing G-S: Complexity approach

- (Bartholdi III, Tovey and Trick, Social Choice and Welfare, 1998)
- As we cannot prevent a voting rule from being manipulable, this may not be a significant concern as long as determining how to manipulate it is computationally prohibitive.
- Maybe the rule is manipulable, but it is NP-hard to find a successful manipulation.

Circumventing G-S: Complexity approach

- (Bartholdi III, Tovey and Trick, Social Choice and Welfare, 1998)
- As we cannot prevent a voting rule from being manipulable, this may not be a significant concern as long as determining how to manipulate it is computationally prohibitive.
- Maybe the rule is manipulable, but it is NP-hard to find a successful manipulation.
For once NP-hardness can be good!!

- 1 Strategy-proofness
- 2 Manipulation**
- 3 Some manipulable rules

Manipulation Problem

We consider the simplest version of manipulation.

Manipulation Problem

We consider the simplest version of manipulation.

Name: F-MANIPULATION

Input: A preference profile \succ for all but one player, and a preferred candidate a .

Question: Is there a preference order P so that, in system F under the joint preference profile a wins?

Manipulation Problem

We consider the simplest version of manipulation.

Name: F-MANIPULATION

Input: A preference profile \succ for all but one player, and a preferred candidate a .

Question: Is there a preference order P so that, in system F under the joint preference profile a wins?

- The problem belongs to NP provided F is computable in polynomial time.

Manipulation Problem

We consider the simplest version of manipulation.

Name: F-MANIPULATION

Input: A preference profile \succ for all but one player, and a preferred candidate a .

Question: Is there a preference order P so that, in system F under the joint preference profile a wins?

- The problem belongs to NP provided F is computable in polynomial time.
- For **plurality**, this problem is computationally trivial:
- The only sensible manipulation is to put a as your most preferred candidate!

Manipulation Problem: BTT conditions

A voting rule satisfies the BTT conditions if

Manipulation Problem: BTT conditions

A voting rule satisfies the BTT conditions if

- Given a preference profile a winner can be computed in polynomial time.

Manipulation Problem: BTT conditions

A voting rule satisfies the BTT conditions if

- Given a preference profile a winner can be computed in polynomial time.
- Fix a preference profile for all the players but one.

Manipulation Problem: BTT conditions

A voting rule satisfies the BTT conditions if

- Given a preference profile a winner can be computed in polynomial time.
- Fix a preference profile for all the players but one.
- for every preference order P and every alternative a , a score $S(P, a)$ can be defined so that it is,

Manipulation Problem: BTT conditions

A voting rule satisfies the BTT conditions if

- Given a preference profile a winner can be computed in polynomial time.
- Fix a preference profile for all the players but one.
- for every preference order P and every alternative a , a score $S(P, a)$ can be defined so that it is,
 - **Responsive:** the candidate with the largest score wins (in the voting under the joint profile)

Manipulation Problem: BTT conditions

A voting rule satisfies the BTT conditions if

- Given a preference profile a winner can be computed in polynomial time.
- Fix a preference profile for all the players but one.
- for every preference order P and every alternative a , a score $S(P, a)$ can be defined so that it is,
 - **Responsive**: the candidate with the largest score wins (in the voting under the joint profile)
 - **Monotone**: for any two preference orders P and P' and for any candidate a , if for each voter i , $\{b \mid a P b\} \subseteq \{b \mid a P' b\}$, then $S(P, a) \leq S(P', a)$.

Greedy-Manipulation algorithm (G-Man)

Greedy-Manipulation algorithm (G-Man)

- **Input:** Preference profile for all other voters and a candidate c .

Greedy-Manipulation algorithm (G-Man)

- **Input:** Preference profile for all other voters and a candidate c .
- **Output:** A preference order, that together with the input ensures that c wins, or claim that such order does not exist.

Greedy-Manipulation algorithm (G-Man)

- **Input:** Preference profile for all other voters and a candidate c .
- **Output:** A preference order, that together with the input ensures that c wins, or claim that such order does not exist.
- **Initialization:** Place c at the top of the preference order

Greedy-Manipulation algorithm (G-Man)

- **Input:** Preference profile for all other voters and a candidate c .
- **Output:** A preference order, that together with the input ensures that c wins, or claim that such order does not exist.
- **Initialization:** Place c at the top of the preference order
- **Iterative step:** While there are unassigned candidates:

Greedy-Manipulation algorithm (G-Man)

- **Input:** Preference profile for all other voters and a candidate c .
- **Output:** A preference order, that together with the input ensures that c wins, or claim that such order does not exist.
- **Initialization:** Place c at the top of the preference order
- **Iterative step:** While there are unassigned candidates:
Determine whether a candidate b can be placed in the next lower position (independent of remaining choices) without preventing c from winning.

Greedy-Manipulation algorithm (G-Man)

- **Input:** Preference profile for all other voters and a candidate c .
- **Output:** A preference order, that together with the input ensures that c wins, or claim that such order does not exist.
- **Initialization:** Place c at the top of the preference order
- **Iterative step:** While there are unassigned candidates:
Determine whether a candidate b can be placed in the next lower position (independent of remaining choices) without preventing c from winning.
If so, place b in the next position, otherwise terminate claiming that order does not exist.

Manipulable rules by Greedy

Theorem

For any voting rule F satisfying the BTT conditions, G -Man solves the F -MANIPULATION problem.

Manipulable rules by Greedy

Theorem

For any voting rule F satisfying the BTT conditions, G -Man solves the F -MANIPULATION problem.

Proof.

Manipulable rules by Greedy

Theorem

For any voting rule F satisfying the BTT conditions, G -Man solves the F -MANIPULATION problem.

Proof.

- If Greedy-Manipulation succeeds, it constructs a preference order that guarantees that under the joint profile c wins.

Manipulable rules by Greedy

Theorem

For any voting rule F satisfying the BTT conditions, G -Man solves the F -MANIPULATION problem.

Proof.

- If Greedy-Manipulation succeeds, it constructs a preference order that guarantees that under the joint profile c wins.
- Assume that such an order exists and that Greedy-Manipulation terminates without providing an ordering. Let us reach a contradiction.

Manipulable rules by Greedy

Proof (cont).

Manipulable rules by Greedy

Proof (cont).

- Let P' be a preference order that will make c win.

Manipulable rules by Greedy

Proof (cont).

- Let P' be a preference order that will make c win.
- Let U be the set of unassigned candidates after the execution of G-Man.

Manipulable rules by Greedy

Proof (cont).

- Let P' be a preference order that will make c win.
- Let U be the set of unassigned candidates after the execution of G-Man.
- Let $u \in U$ be the candidate with highest score under P' .

Manipulable rules by Greedy

Proof (cont).

- Let P' be a preference order that will make c win.
- Let U be the set of unassigned candidates after the execution of G-Man.
- Let $u \in U$ be the candidate with highest score under P' .
- Consider any completion P of the preference order started by G-Man that places u in the first unassigned place.

Manipulable rules by Greedy

Proof (cont).

Manipulable rules by Greedy

Proof (cont).

- By responsiveness, $S(P', c) \geq S(P', u)$

Manipulable rules by Greedy

Proof (cont).

- By responsiveness, $S(P', c) \geq S(P', u)$
- By selection of u , $\{a \mid u P' a\} \subseteq \{a \mid u P a\}$.

Manipulable rules by Greedy

Proof (cont).

- By responsiveness, $S(P', c) \geq S(P', u)$
- By selection of u , $\{a \mid u P' a\} \subseteq \{a \mid u P a\}$.
So, by monotonicity

Manipulable rules by Greedy

Proof (cont).

- By responsiveness, $S(P', c) \geq S(P', u)$
- By selection of u , $\{a \mid u P' a\} \subseteq \{a \mid u P a\}$.
So, by monotonicity $S(P', u) \geq S(P, u)$

Manipulable rules by Greedy

Proof (cont).

- By responsiveness, $S(P', c) \geq S(P', u)$
- By selection of u , $\{a \mid u P' a\} \subseteq \{a \mid u P a\}$.
So, by monotonicity $S(P', u) \geq S(P, u)$
- By initialization $S(P, c) \geq S(P', c)$.

Manipulable rules by Greedy

Proof (cont).

- By responsiveness, $S(P', c) \geq S(P', u)$
- By selection of u , $\{a \mid u P' a\} \subseteq \{a \mid u P a\}$.
So, by monotonicity $S(P', u) \geq S(P, u)$
- By initialization $S(P, c) \geq S(P', c)$.
- So, $S(P, c) \geq S(P, u)$.

Manipulable rules by Greedy

Proof (cont).

- By responsiveness, $S(P', c) \geq S(P', u)$
- By selection of u , $\{a \mid u P' a\} \subseteq \{a \mid u P a\}$.
So, by monotonicity $S(P', u) \geq S(P, u)$
- By initialization $S(P, c) \geq S(P', c)$.
- So, $S(P, c) \geq S(P, u)$.
- But G-Man did not assign u , so $S(P, c) < S(P, u)$ and we get the contradiction.

Manipulable rules by Greedy

Corollary

For any voting rule F satisfying the BTT conditions, and for which the scoring rule can be computed in polynomial time G -Man solves the F -MANIPULATION problem in polynomial time.

By monotonicity, it should be possible to compute the score of the alternative ranked "first" among a set of unranked alternatives

- 1 Strategy-proofness
- 2 Manipulation
- 3 Some manipulable rules**

Plurality

Plurality

- Each voter awards one point to her top alternative
- Alternative with the most point wins

Plurality

- Each voter awards one point to her top alternative
- Alternative with the most point wins
- Let p_c be the plurality vote, for alternative c , among all voters except the manipulator.
- $S(P, c) = p_c + 1$ if $|\{a \mid c P a\}| = m - 1$, else p_c .

Plurality

- Each voter awards one point to her top alternative
- Alternative with the most point wins
- Let p_c be the plurality vote, for alternative c , among all voters except the manipulator.
- $S(P, c) = p_c + 1$ if $|\{a \mid c P a\}| = m - 1$, else p_c .
- $S(P, a)$ coincides with the plurality vote under the joint profile, so we get responsiveness.

Plurality

- Each voter awards one point to her top alternative
- Alternative with the most point wins
- Let p_c be the plurality vote, for alternative c , among all voters except the manipulator.
- $S(P, c) = p_c + 1$ if $|\{a \mid c P a\}| = m - 1$, else p_c .
- $S(P, a)$ coincides with the plurality vote under the joint profile, so we get responsiveness.
- If $\{b \mid a P b\} \subseteq \{b \mid a P' b\}$, plurality vote cannot decrease.
So we get monotonicity.

Plurality

- Each voter awards one point to her top alternative
- Alternative with the most point wins
- Let p_c be the plurality vote, for alternative c , among all voters except the manipulator.
- $S(P, c) = p_c + 1$ if $|\{a \mid c P a\}| = m - 1$, else p_c .
- $S(P, a)$ coincides with the plurality vote under the joint profile, so we get responsiveness.
- If $\{b \mid a P b\} \subseteq \{b \mid a P' b\}$, plurality vote cannot decrease. So we get monotonicity.
- Both, plurality vote and score can be computed in polynomial time.

Plurality

- Each voter awards one point to her top alternative
- Alternative with the most point wins
- Let p_c be the plurality vote, for alternative c , among all voters except the manipulator.
- $S(P, c) = p_c + 1$ if $|\{a \mid c P a\}| = m - 1$, else p_c .
- $S(P, a)$ coincides with the plurality vote under the joint profile, so we get responsiveness.
- If $\{b \mid a P b\} \subseteq \{b \mid a P' b\}$, plurality vote cannot decrease. So we get monotonicity.
- Both, plurality vote and score can be computed in polynomial time.
- **Plurality is polynomial time manipulable.**

Borda Count

Borda Count

- Each voter awards $m - k$ points to its rank k candidate.
- The candidate with the most points (**positional score**) wins.

Borda Count

- Each voter awards $m - k$ points to its rank k candidate.
- The candidate with the most points (**positional score**) wins.
- Let p_c be the positional score for candidate c among all voters except the manipulator.
- $S(P, c) = p_c + |\{a \mid c \succ_P a\}|$.

Borda Count

- Each voter awards $m - k$ points to its rank k candidate.
- The candidate with the most points (**positional score**) wins.
- Let p_c be the positional score for candidate c among all voters except the manipulator.
- $S(P, c) = p_c + |\{a \mid c \succ P a\}|$.
- $S(P, a)$ coincides with the positional score in the joint profile, so we get responsiveness.

Borda Count

- Each voter awards $m - k$ points to its rank k candidate.
- The candidate with the most points (**positional score**) wins.
- Let p_c be the positional score for candidate c among all voters except the manipulator.
- $S(P, c) = p_c + |\{a \mid c P a\}|$.
- $S(P, a)$ coincides with the positional score in the joint profile, so we get responsiveness.
- If $\{b \mid a P b\} \subseteq \{b \mid a P' b\}$, the positional score cannot decrease. So we get monotonicity.

Borda Count

- Each voter awards $m - k$ points to its rank k candidate.
- The candidate with the most points (**positional score**) wins.
- Let p_c be the positional score for candidate c among all voters except the manipulator.
- $S(P, c) = p_c + |\{a \mid c P a\}|$.
- $S(P, a)$ coincides with the positional score in the joint profile, so we get responsiveness.
- If $\{b \mid a P b\} \subseteq \{b \mid a P' b\}$, the positional score cannot decrease. So we get monotonicity.
- Both, plurality vote and the score can be computed in polynomial time.

Borda Count

- Each voter awards $m - k$ points to its rank k candidate.
- The candidate with the most points (**positional score**) wins.
- Let p_c be the positional score for candidate c among all voters except the manipulator.
- $S(P, c) = p_c + |\{a \mid c \succ_P a\}|$.
- $S(P, a)$ coincides with the positional score in the joint profile, so we get responsiveness.
- If $\{b \mid a \succ_P b\} \subseteq \{b \mid a \succ_{P'} b\}$, the positional score cannot decrease. So we get monotonicity.
- Both, plurality vote and the score can be computed in polynomial time.
- Plurality is polynomial time manipulable.

Copeland

Copeland

- x beats y in a **pairwise election** if a strict majority of voters prefer x to y .

Copeland

- x beats y in a **pairwise election** if a strict majority of voters prefer x to y .
- Copeland
 - $Score(x) = \# \text{alternatives } x \text{ beats in pairwise elections}$
 - elect x^* with the maximum score
- $S(P, c) = Score(c)$ in the joint profile

Copeland

- x beats y in a **pairwise election** if a strict majority of voters prefer x to y .
- Copeland
 - $Score(x) = \# \text{alternatives } x \text{ beats in pairwise elections}$
 - elect x^* with the maximum score
- $S(P, c) = Score(c)$ in the joint profile
- $S(P, a)$ coincides with the Score in the joint profile, so we get responsiveness.

Copeland

- x beats y in a **pairwise election** if a strict majority of voters prefer x to y .
- **Copeland**
 - $\text{Score}(x) = \#\text{alternatives } x \text{ beats in pairwise elections}$
 - elect x^* with the maximum score
- $S(P, c) = \text{Score}(c)$ in the joint profile
- $S(P, a)$ coincides with the Score in the joint profile, so we get responsiveness.
- If $\{b \mid a P b\} \subseteq \{b \mid a P' b\}$, the score cannot decrease. So we get monotonicity.

Copeland

- x beats y in a **pairwise election** if a strict majority of voters prefer x to y .
- **Copeland**
 - $Score(x) = \# \text{alternatives } x \text{ beats in pairwise elections}$
 - elect x^* with the maximum score
- $S(P, c) = Score(c)$ in the joint profile
- $S(P, a)$ coincides with the Score in the joint profile, so we get responsiveness.
- If $\{b \mid a P b\} \subseteq \{b \mid a P' b\}$, the score cannot decrease. So we get monotonicity.
- Both, Copeland vote and the score can be computed in polynomial time.

Copeland

- x beats y in a **pairwise election** if a strict majority of voters prefer x to y .
- Copeland
 - $Score(x) = \# \text{alternatives } x \text{ beats in pairwise elections}$
 - elect x^* with the maximum score
- $S(P, c) = Score(c)$ in the joint profile
- $S(P, a)$ coincides with the Score in the joint profile, so we get responsiveness.
- If $\{b \mid a P b\} \subseteq \{b \mid a P' b\}$, the score cannot decrease. So we get monotonicity.
- Both, Copeland vote and the score can be computed in polynomial time.
- Copeland is polynomial time manipulable.

Maximin

Maximin

- Maximin
 - $Score(x) = \min_y n_{x \succ y}$
 - elect x^* with the maximum score
- Working in a similar way, Maximin is polynomial time manipulable.

STV

- Single Transferable Vote (STV): Plurality with multiple rounds

STV

- Single Transferable Vote (STV): Plurality with multiple rounds
- $m - 1$ rounds.
- In each round, the alternative with the least plurality votes is eliminated.
- The selected alternative is the standing one.

STV

- Single Transferable Vote (STV): Plurality with multiple rounds
- $m - 1$ rounds.
- In each round, the alternative with the least plurality votes is eliminated.
- The selected alternative is the standing one.
- STV-Manipulation is NP-hard (Bartholdi III and Orlin, Social Choice and Welfare, 1991)

STV

STV-Manipulation is NP-hard (Bartholdi III and Orlin, Social Choice and Welfare, 1991)

- The NP-hardness follows by a reduction from the 3-cover problems which is NP-complete problem (3-Cover).
- The basic idea is to build a large election instance introducing all sorts of constraints on the ballot of the manipulator, such that finding a ballot meeting those constraints solves a given instance of 3-Cover.