NAME

lexconv − nylex documents to and from RTF, Word, OpenDocument, Markdown

SYNOPSIS

lexconv [**−n** | **−a**] [**−w** *width*] [**−j**] *from to*

DESCRIPTION

Lexconv turns a document of *nylex*(1) (and of LEX) into a file for another word processor, or such a file into a document. The formats go by the extensions of the files:

.rtf Rich Text Format (Word, LibreOffice, WordPad, TextEdit ...); written and read

.docx Word (Office Open XML); written and read

.odt OpenDocument text (LibreOffice); written and read

.md, **.markdown**
Markdown; written and read

.html, **.htm**
a web page; written only

.txt, **.text**
plain text in UTF-8; written and read

A file of any other extension is a LEX document (**.brv**, **.ltr**...). Two of the other formats may be given as well: the text goes from one to the other. In*nyle x*, X in the document menu runs *lexconv* (the record ***=CONV**, the menu switch option /H): it asks for the document from and the one to, as **BREV** and **BREV.DOCX**, or **RAPPORT.MD** and **RAPPORT**.

Out of a LEX document

A LEX document is lines laid out on rulers; out of it come the paragraphs again. Lines that were broken by word wrap (the next word did not fit before M) or justified (on a J ruler, out to M) are joined into a paragraph, which is justified when its ruler was J. A line centred or put against M stays so. A line of columns (pieces of text two or more spaces apart: a table, tab stops) gets tab stops at its columns, numbers ending at theirs (in Markdown, HTML and text it is kept as it is, in a fixed font). **.T** and **.F** become the page header and footer, with a page number field for **(SIDA:** or **(PAGE:**; **.P** a page break, **.N** a footnote (at its place); the characters of **.C** for a pound sign, a space, a hard hyphen and a footnote's mark are turned into those, and the other print time lines are left out. Attributes 1 and 4 are underlining, 2 and 5 bold, 3 italic. Markdown gets ******bold******, *****italic***** and **<u>**underlined**</u>**, a line of columns a block of code, and a centred bold line a heading.

Into a LEX document

The paragraphs are laid out on an F ruler of the width given (the M at column 69, as in the document types of *nylex*'s system files), a J ruler for justified ones, with an empty line between paragraphs (unless the file has empty paragraphs of its own); centred and right-aligned ones are put so. Headings are bold, the first level centred. Lists, with their marks, and quotations are indented; tables and text at tab stops become lines of columns; a page break is **.P**, the header and footer **.T** and **.F**. Underlining, bold and italic become attributes 1, 2 and 3. Pictures, footnotes, comments and fields other than the page number are left out; links keep their text and, after it, their address.

OPTIONS

−n the LEX document is in 7-bit Swedish ([\ ] { | } the letters A-umlaut, O-umlaut, A-ring and their lower case), as *nylex*'s Swedish system file keeps it.

−a the LEX document is ASCII and Latin-1 (the English system file). Without either, **$LEXNAT** decides (1 or 0; *nylex* sets it), else **−n**.

−w *width*
the column of M for documents made (69).

−j paragraphs justified (a J ruler) whatever the file says.

ENVIRONMENT

LEXNAT as above.

SEE ALSO

nylex(1), lexspell(1).

NOTES

Word and OpenDocument files are zip files: they are written stored (not compressed), which every program reads, and read with an inflate of *lexconv*'s own; nothing else is needed. The older Word format (**.doc**) is not read or written: Word and LibreOffice save **.docx** and **.rtf**.