NAME

lexspell − the spelling program of nylex, for Swedish and English

SYNOPSIS

lexspell [**−d** *dictionary*] [**−u** *userlist*] [**−c** *commonlist*] [**−k swe7**|**latin1**|**utf8**] *function* [*document* [*output*]]

DESCRIPTION

Lexspell checks the spelling of *nylex*(1) documents, looks words up and keeps word lists. It is called from *nylex*'s spelling menu as LEX called its own dictionary program: a record of the system file names the program (characters 1-32), the dictionary (33-64), the user's word list (65-96), the common word list (97-128) and the function (161; when it is blank, the first character of keystore 0). The menu switch options /D (a document), /H (a document and another for the output) and /N (nothing asked) run it; *nylex* passes the record in **$LEXREC**, keystore 0 in **$LEXKS0** and the terminal's character code in **$LEXCS**. In *nylex*'s own system files the records are ***=SPLDEFC**, ***=SPLDEFA** and so on, one for each function.

Functions

C Check a document. Each word not in the dictionary nor in the word lists is shown in its line with suggestions: a number takes a suggestion, R types a correction, Return or A accepts the word for the rest of the document, L adds it to the user's list, F finishes (the changes so far are kept) and Q abandons the check (the document is left as it was). With the Swedish dictionary the letters are Swedish: R, G (godta), E (egen ordlista), A (avsluta), Z. The document is saved, the old one as *name*.bak. Attribute lines (underline, bold ...) are kept in step.

A The same, with an extra word list as well: the file named in keystore 0 after the function letter, or asked for.

E Extract the unknown words of a document into another, one a line, sorted.

S Spell words: each word typed is right, or the suggestions are shown.

M Find the words that fit a pattern: ? any letter, * any letters (crosswords: d??k*).

L List the dictionary from a word on, a screen at a time (F finishes).

W Add words to the common word list.

F Add the words of a file to the common list.

X Take words out: they go into the common list as words not to accept.

Y The same for the words of a file.

A word is right if it is in the dictionary, in the user's word list or in the common one. In Swedish a word not in the dictionary is right as well when it is a compound of parts that may begin, go in the middle of and end one (*husvagnsdäck*, *krokodilsko*), with a triple consonant written as two (*tunnål*). The suggestions are words with a letter changed, left out, added or two swapped, the word in other capitals, and the word split in two.

The messages are in Swedish or English, after the dictionary.

OPTIONS

−d *dictionary*

sv (Swedish, the default), **en-GB** (British English; also **en**) or **en-US** (American English), the files *name***.dict** in the library; or a file named with a /.

−u *userlist***, −c** *commonlist*

the word lists (default **$HOME/user.def** and **$HOME/common.def**): text files, a word a line; "-word" in the common list is a word not to accept.

−k swe7|**latin1**|**utf8**

the character code of the terminal and of the word lists typed (as *nylex*'s **−c**). Documents are in 7-bit Swedish, as LEX keeps them.

ENVIRONMENT

LEXREC, LEXKS0, LEXCS as above; LEXLIB, the library (instead of the one built in).

FILES

/usr/local/share/nylex/sv.dict, en-GB.dict, en-US.dict
: the dictionaries (on the D-NIX Amiga port in /usr/modern/lib/nylex)

$HOME/user.def, $HOME/common.def
: the word lists

SEE ALSO

nylex(1).

NOTES

The dictionaries are made by **tools/mkdict.py** of the Hunspell dictionaries that LibreOffice uses: every form the affix rules give, with flags for the parts of compounds, front-coded in blocks of 64 words with an index (832,630 Swedish words in 4.3 MB, 266,531 British English, 123,689 American English). The Swedish dictionary is Göran Andersson’s (LGPL 3), the English ones are from SCOWL and the LibreOffice project (LGPL, and a permissive licence for en-US); see dict/README. LEX-68’s own dictionary programs and dictionary are not used.