NAME

lexvmf − list and change LEX system files

SYNOPSIS

lexvmf −l *file.vmf*
lexvmf −x|**−t** *file.vmf key*
lexvmf −p|**−T** *file.vmf key* [*file*]
lexvmf −d *file .vmf key*
lexvmf −r *file .vmf*

DESCRIPTION

A system file (.vmf) of *nylex*(1) or LEX holds records under keys of up to 10 characters: menus (****MENU**, ***DOCMENU**), programs and forms, the installation (****INST**), printers (****PNST**, ***$**...), messages (****TEXT**, ***-ERROR-**xx), document types (***.BRV**), data records and, under **:***NAME***EXT**, the document index. A record is stored squashed: a byte 1-31 is a run of that many squash characters (**_**), a 0 byte ends a line. *Lexvmf* works on them.

−l lists the keys and the length of each record

−x writes the record to standard output, as it is stored

−t writes it as text: the runs opened, a newline for each 0 byte

−p puts a record in, from *file* or standard input, replacing one with the same key; it makes the system file if there is none

−T puts a record in from text (newlines become 0 bytes, runs of **_** are squashed)

−d deletes a record (it is only marked deleted, as LEX does)

−r rewrites the file without the deleted records, which packs it (nylex's menu option /3 does the same with questions)

Keys are padded with blanks to 10 characters; **x***NN* in a key is the byte *NN*, in hexadecimal.

EXAMPLES

```
lexvmf -l $HOME/nylex.vmf
lexvmf -t $HOME/nylex.vmf '**MENU'
lexvmf -t $HOME/nylex.vmf '*VDTI' > vdti.txt; vi vdti.txt
lexvmf -T $HOME/nylex.vmf '*VDTI' vdti.txt
```

SEE ALSO

nylex(1). The source distribution's lexdef.txt and tools/mklexvmf.py make a whole system file from a text description.