COSC-364 FLOW PLANNING ASSIGNMENT

Will Cowper
ID: 81163265
wgc22@uclive.ac.nz
Contribution: 50%

Jesse Sheehan
ID: 53366509
jps111@uclive.ac.nz
Contribution: 50%

May 28, 2019

1 Problem Formulation

2 Results

3 Appendix

3.1 Source Code

3.1.1 src/__main__.py

```
import sys

from lp_gen import generate_lp_file
from lp_utils import get_lp_filename, run_cplex

__TITLE__ = "COSC-364 Assignment 2"
__AUTHORS__ = [("Will Cowper", "81163265"), ("Jesse Sheehan", "53366509")]


def print_version():
    print('{0} by {1}'.format(__TITLE__, ', '.join(
        ["{0} ({1})".format(name, sid) for (name, sid) in __AUTHORS__])))


def print_usage():
    print('Usage: {0} <x> <y> <z>'.format(sys.argv[0]))


def get_problem_parameters():
    """ Returns a tuple containing the x, y and z parameters. """
    try:
        x = int(sys.argv[1])
        y = int(sys.argv[2])
        z = int(sys.argv[3])
    except:
        print_usage()
        exit(-1)

    if x <= 0:
        print("Error: x must be strictly positive")
        exit(-1)

    if y < 3:
        print("Error: y must be greater than or equal to 3")
        exit(-1)

    if z <= 0:
        print("Error: z must be strictly positive")
        exit(-1)

    return x, y, z


def save_lp_file(filename, data):
    try:
        f = open(filename, 'w')
```

```
            f.write(data)
48          f.close()
        except:
50          print("Error: could not save file '{0}'".format(filename))
            exit(-1)
52

54  def main():
        print_version()
56      if len(sys.argv) != 4:
            print_usage()
58          exit(-1)
        else:
60          x, y, z = get_problem_parameters()
            data = generate_lp_file(x, y, z)
62          filename = get_lp_filename(x, y, z)
            save_lp_file(filename, data)
64          print("Success: saved as '{0}'".format(filename))
            run_cplex(filename)
66

68  if __name__ == "__main__":
        main()
```

../src/__main__.py

3.1.2 src/lp_utils.py

```
    import functools
2   import subprocess


4
    def get_lp_filename(x, y, z):
6       """ Returns the filename that the LP data should be saved to. """
        return "problem_{0}_{1}_{2}.lp".format(x, y, z)
8


10  def run_cplex(filename):
        """ Runs cplex on the LP file. """
12      subprocess.run(
            'cplex -c "read {0}" "optimize" "display solution variables -"'.
        format(filename))
14


16  def crange(first, last):
        """ Returns a list of characters between the two characters passed in (
        inclusive).
18      >>> crange('A', 'C')
        ['A', 'B', 'C']
20      >>> crange('A', 'A')
        ['A']
22      """
        if ord(first) > ord(last):
24          raise ValueError("last must come after first")

26      else:
            return [chr(i) for i in range(ord(first), ord(last) + 1)]
```

```
28
30 def repeat(obj, n):
       """ Returns a list with obj repeated n times.
32     >>> repeat(1, 1)
       [1]
34     >>> repeat(42, 0)
       []
36     >>> repeat(5, 4)
       [5, 5, 5, 5]
38     >>> repeat([1, 2], 2)
       [[1, 2], [1, 2]]
40     """
       return [obj for _ in range(n)]
42
44 def perms(lists):
       """ Returns all the permutations of the elements.
46     >>> perms([])
       []
48     >>> perms([['a', 'b', 'c']])
       [('a',), ('b',), ('c',)]
50     >>> perms([['a', 'b', 'c'], ['x', 'y', 'z']])
       [('a', 'x'), ('a', 'y'), ('a', 'z'), ('b', 'x'), ('b', 'y'), ('b', 'z')
      , ('c', 'x'), ('c', 'y'), ('c', 'z')]
52     """
       if len(lists) == 0:
54         return []

56     elif (len(lists) == 1):
           return [(x,) for x in lists[0]]
58
       else:
60         return [(x,) + y for x in lists[0] for y in perms(lists[1:])]


62
   def concat(permutations):
64     """ Returns the permutations concatenated as strings.
       >>> concat(perms([['a', 'b', 'c']]))
66     ['a', 'b', 'c']
       >>> concat(perms([['a', 'b', 'c'], ['x', 'y', 'z']]))
68     ['ax', 'ay', 'az', 'bx', 'by', 'bz', 'cx', 'cy', 'cz']
       """
70     return [functools.reduce(lambda x, y: x + str(y), p, '') for p in
      permutations]


72
   if __name__ == "__main__":
74     import doctest
       doctest.testmod()
```

../src/lp_utils.py

3.1.3 src/lp_gen.py

```
from lp_utils import perms, concat
2
```

```
template = """\
\\ COSC-364 Assignment 2, LP Output File
MINIMIZE
     r
SUBJECT TO
     \\ DEMAND CONSTRAINTS
     {}
     \\ CAPACITY CONSTRAINTS FOR LINKS BETWEEN SOURCE AND TRANSIT NODES
     {}
     \\ CAPACITY CONSTRAINTS FOR LINKS BETWEEN TRANSIT AND DESTINATION NODES
     {}
     \\ TRANSIT NODE LOAD CONSTRAINTS
     {}
     \\ BINARY VARIABLE CONSTRAINTS (ONLY 2 ACTIVE TRANSIT NODES)
     {}
BOUNDS
     \\ NON-NEGATIVITY CONSTRAINTS
     r >= 0
     {}
BIN
     \\ BINARY VARIABLES
     {}
END
"""


def get_nodes(x, y, z):
    """ Returns a tuple containing the source, transit and destination node
    ids as integers. """
    s = list(range(1, x + 1))
    t = list(range(1, y + 1))
    d = list(range(1, z + 1))
    return s, t, d


def get_demand_constraints(s, t, d):
    """ Returns a list of demand constraints. """
    return [' + '.join(["X_{0}{1}{2}".format(i, k, j) for k in t]) + ' =
   {0}'.format(2 * i + j)
            for (i, j) in perms([s, d])]


def get_source_transit_capacity_constraints(s, t, d):
    """ Returns a list of capacity constraints for the links between the
   source and transit nodes. """
    return \
        [' + '.join(["X_{0}{1}{2}".format(i, k, j) for j in d]) +
            ' - C_{0}{1} <= 0'.format(i, k) for (i, k) in perms([s, t])]  #
    + \
    # [' + '.join(["C_{0}{1}".format(i, j) for i in s]) +
    # ' - r <= 0' for j in d]
    # don't know about the above commented lines


def get_transit_destination_capacity_constraints(s, t, d):
    """ Returns a list of capacity constraints for the links between the
   transit and destination nodes. """
    return \
```

```
        [' + '.join(["X_{0}{1}{2}".format(i, k, j) for i in s]) +
            ' - D_{0}{1} <= 0'.format(k, j) for (k, j) in perms([t, d])]


def get_transit_load_constraints(s, t, d):
    """ Returns the list of transit load constraints. """
    return [' + '.join(["X_{0}{1}{2}".format(i, k, j) for (i, j) in perms([s, d])]) +
            ' - r <= 0' for k in t]  # maybe change this line for the one below?
    # ' - L_{0} <= 0'.format(k) for k in t]


def get_binary_constraints(s, t, d):
    """ Returns a list of binary variable constraints. """
    return [' + '.join(["U_{0}{1}{2}".format(i, k, j) for k in t]) + ' = 2'
            for (i, j) in perms([s, d])]


def get_binary_variables(s, t, d):
    """ Returns a list of binary variables. """
    return ["U_{0}{1}{2}".format(i, k, j) for (i, k, j) in perms([s, t, d])]


def get_non_negativity_constraints(s, t, d):
    """ Returns a list of non-negativity constraints. """
    return ["X_{0} >= 0".format(subscript) for subscript in concat(perms([s, t, d]))]


def generate_lp_file(x, y, z):
    """ Returns the LP file contents as per the project specification. """
    s, t, d = get_nodes(x, y, z)

    demand_constraints = '\n\t'.join(get_demand_constraints(s, t, d))
    source_transit_capacity_constraints = '\n\t'.join(
        get_source_transit_capacity_constraints(s, t, d))
    transit_destination_capacity_constraints = '\n\t'.join(
        get_transit_destination_capacity_constraints(s, t, d))
    non_negativity_constraints = '\n\t'.join(get_non_negativity_constraints(
        s, t, d))
    transit_load_constraints = '\n\t'.join(
        get_transit_load_constraints(s, t, d))
    binary_variable_constraints = '\n\t'.join(get_binary_constraints(s, t, d))
    binary_variables = '\n\t'.join(get_binary_variables(s, t, d))

    return template.format(
        demand_constraints,
        source_transit_capacity_constraints,
        transit_destination_capacity_constraints,
        transit_load_constraints,
        binary_variable_constraints,
        non_negativity_constraints,
        binary_variables)
```

../src/lp_gen.py

3.2 Generated LP File

3.2.1 problem_3_2_4.lp

3.3 Plagiarism Declaration