

▼ BERT with Naive Synonym Replacement Augmentation

Real News and Fake News (~90k total)

Class: Label

Real: 1

Fake: 0

```
import tensorflow as tf

# Get the GPU device name.
device_name = tf.test.gpu_device_name()

# The device name should look like the following:
if device_name == '/device:GPU:0':
    print('Found GPU at: {}'.format(device_name))
else:
    raise SystemError('GPU device not found')

☞ Found GPU at: /device:GPU:0

import torch

# If there's a GPU available...
if torch.cuda.is_available():

    # Tell PyTorch to use the GPU.
    device = torch.device("cuda")

    print('There are %d GPU(s) available.' % torch.cuda.device_count())

    print('We will use the GPU:', torch.cuda.get_device_name(0))
```

```
# If not
```

```
# if not...
```

```
else:
```

```
    print('No GPU available, using the CPU instead.')
    device = torch.device("cpu")
```

```
☞ There are 1 GPU(s) available.
   We will use the GPU: Tesla P100-PCIE-16GB
```

```
!pip install transformers
```

```
☞ Requirement already satisfied: transformers in /usr/local/lib/python3.6/dist-packages (2.8.0)
Requirement already satisfied: sacremoses in /usr/local/lib/python3.6/dist-packages (from transformers) (0.0.
Requirement already satisfied: regex!=2019.12.17 in /usr/local/lib/python3.6/dist-packages (from transformers
Requirement already satisfied: dataclasses; python_version < "3.7" in /usr/local/lib/python3.6/dist-packages
Requirement already satisfied: filelock in /usr/local/lib/python3.6/dist-packages (from transformers) (3.0.12
Requirement already satisfied: numpy in /usr/local/lib/python3.6/dist-packages (from transformers) (1.18.2)
Requirement already satisfied: boto3 in /usr/local/lib/python3.6/dist-packages (from transformers) (1.12.40)
Requirement already satisfied: tqdm>=4.27 in /usr/local/lib/python3.6/dist-packages (from transformers) (4.38
Requirement already satisfied: sentencepiece in /usr/local/lib/python3.6/dist-packages (from transformers) (0
Requirement already satisfied: requests in /usr/local/lib/python3.6/dist-packages (from transformers) (2.21.0
Requirement already satisfied: tokenizers==0.5.2 in /usr/local/lib/python3.6/dist-packages (from transformers
Requirement already satisfied: joblib in /usr/local/lib/python3.6/dist-packages (from sacremoses->transformer
Requirement already satisfied: six in /usr/local/lib/python3.6/dist-packages (from sacremoses->transformers)
Requirement already satisfied: click in /usr/local/lib/python3.6/dist-packages (from sacremoses->transformers
Requirement already satisfied: jmespath<1.0.0,>=0.7.1 in /usr/local/lib/python3.6/dist-packages (from boto3->
Requirement already satisfied: s3transfer<0.4.0,>=0.3.0 in /usr/local/lib/python3.6/dist-packages (from boto3
Requirement already satisfied: botocore<1.16.0,>=1.15.40 in /usr/local/lib/python3.6/dist-packages (from boto
Requirement already satisfied: certifi>=2017.4.17 in /usr/local/lib/python3.6/dist-packages (from requests->t
Requirement already satisfied: urllib3<1.25,>=1.21.1 in /usr/local/lib/python3.6/dist-packages (from requests
Requirement already satisfied: idna<2.9,>=2.5 in /usr/local/lib/python3.6/dist-packages (from requests->trans
Requirement already satisfied: chardet<3.1.0,>=3.0.2 in /usr/local/lib/python3.6/dist-packages (from requests
Requirement already satisfied: python-dateutil<3.0.0,>=2.1 in /usr/local/lib/python3.6/dist-packages (from bo
Requirement already satisfied: docutils<0.16,>=0.10 in /usr/local/lib/python3.6/dist-packages (from botocore<
```

▼ No Augmentation

```
# import pandas as pd
# import numpy as np
```

```
# import sklearn
```

```

# import sklearn
# from sklearn.model_selection import train_test_split

# file = "combined_{}.csv"
# dfs = []
# for i in range(3):
#     fp = file.format(i+1)
#     read = pd.read_csv(fp)
#     read = read[['label', 'clean_text']]
#     dfs.append(read)

# dfs[2] = dfs[2][:-13000]

# data = pd.concat(dfs)
# data.tail()
# data.reset_index(inplace=True, drop=True)
# print('All Data:', data.shape)

# data.dropna(inplace=True)
# train_data, test_data = train_test_split(data, test_size=0.2)

# print('\nTrain Data:', train_data.shape)
# print(train_data[train_data.label == 1].shape[0], "Real")
# print(train_data[train_data.label == 0].shape[0], "Fake")

# print('\nTest Data:', test_data.shape)
# print(test_data[test_data.label == 1].shape[0], "Real")
# print(test_data[test_data.label == 0].shape[0], "Fake")

# sentences = train_data.clean_text.values
# labels = train_data.label.values

# train_data.head(10)

```

▼ Grover Augmentation

```
# Grover Augmentation
```

```
# import pandas as pd
# import numpy as np

# import sklearn
# from sklearn.model_selection import train_test_split

# file = "combined_{}.csv"
# dfs = []
# for i in range(3):
#     fp = file.format(i+1)
#     read = pd.read_csv(fp)
#     read = read[['label', 'clean_text']]
#     dfs.append(read)

# real_news = dfs[2].copy()
# dfs[2] = real_news[:-13000]
# data = pd.concat(dfs)
# data.tail()
# data.reset_index(inplace=True, drop=True)

# data.dropna(inplace=True)
# train_data, test_data = train_test_split(data, test_size=0.3)

# print('Train Data:', train_data.shape)
# print(train_data[train_data.label == 1].shape[0], "Real")
# print(train_data[train_data.label == 0].shape[0], "Fake")

# print('\nTest Data:', test_data.shape)
# print(test_data[test_data.label == 1].shape[0], "Real")
# print(test_data[test_data.label == 0].shape[0], "Fake")

# grover_augmentation = pd.read_csv('Grover_clean.csv')[['label', 'clean_text']]
# real_news_offset = real_news[-13000:]
# train_data = pd.concat([train_data, grover_augmentation, real_news_offset])
# train_data.dropna(inplace=True)
```

```
# print('\n-----After Augmentation -----\n')
# print('Train Data:', train_data.shape)
# print(train_data[train_data.label == 1].shape[0], "Real")
# print(train_data[train_data.label == 0].shape[0], "Fake")

# print('\nTest Data:', test_data.shape)
# print(test_data[test_data.label == 1].shape[0], "Real")
# print(test_data[test_data.label == 0].shape[0], "Fake")

# sentences = train_data.clean_text.values
# labels = train_data.label.values

# train_data.head(10)
```

▼ Naive Synonym Replacement Augmentation

```
# Naive Synonym Replacement

import pandas as pd
import numpy as np

import sklearn
from sklearn.model_selection import train_test_split

file = "combined_{}.csv"
dfs = []
for i in range(3):
    fp = file.format(i+1)
    read = pd.read_csv(fp)
    read = read[['label', 'clean_text']]
    dfs.append(read)

dfs[2] = dfs[2][:-13000]
data = pd.concat(dfs)
data.tail()
```

```
data.reset_index(inplace=True, drop=True)

data.dropna(inplace=True)
train_data, test_data = train_test_split(data, test_size=0.3)

print('Train Data:', train_data.shape)
print(train_data[train_data.label == 1].shape[0], "Real")
print(train_data[train_data.label == 0].shape[0], "Fake")

print('\nTest Data:', test_data.shape)
print(test_data[test_data.label == 1].shape[0], "Real")
print(test_data[test_data.label == 0].shape[0], "Fake")


nsr1 = pd.read_csv('Kaggle2_Mixed_SR_a_clean.csv')[['label', 'clean_text']]
nsr2 = pd.read_csv('Kaggle2_Mixed_SR_b_clean.csv')[['label', 'clean_text']]
nsr3 = pd.read_csv('LIAR_SR_clean.csv')[['label', 'clean_text']]

nsr_augmentation = pd.concat([nsr1, nsr2, nsr3])
train_data = pd.concat([train_data, nsr_augmentation])
train_data.dropna(inplace=True)

print('\n-----After Augmentation -----')
print('Train Data:', train_data.shape)
print(train_data[train_data.label == 1].shape[0], "Real")
print(train_data[train_data.label == 0].shape[0], "Fake")

print('\nTest Data:', test_data.shape)
print(test_data[test_data.label == 1].shape[0], "Real")
print(test_data[test_data.label == 0].shape[0], "Fake")

sentences = train_data.clean_text.values
labels = train_data.label.values

train_data.head(10)
```



Train Data: (41621, 2)
21957 Real
19664 Fake

Test Data: (17838, 2)
9492 Real
8346 Fake

-----After Augmentation -----

Train Data: (74491, 2)
39477 Real
35014 Fake

Test Data: (17838, 2)
9492 Real
8346 Fake

	label	clean_text
14367	0	st century wire says mexicos billionaire tycoo...
54958	1	article part feature also send via email polit...
58217	1	want receive updates partners sponsors februar...
24085	0	news never thought would see day reposted some...
19403	0	change latest newly released project veritas v...
35325	0	posted october sean adltabatabai news us ...
11143	1	tuesday afternoon president barack obamas form...
47528	1	anyone know irresponsible senator buono shes o...
27116	0	consume cranberries beyond holiday season paul...
8304	0	photo day honor guard reuters honor guard stan...

```
from transformers import BertTokenizer
```

```
# Load the BERT tokenizer.
```

```

print('Loading BERT tokenizer...')
tokenizer = BertTokenizer.from_pretrained('bert-base-uncased', do_lower_case=True)

# Print the original sentence.
print(' Original: ', sentences[0])

# Print the sentence split into tokens.
print('Tokenized: ', tokenizer.tokenize(sentences[0]))

# Print the sentence mapped to token ids.
print('Token IDs: ', tokenizer.convert_tokens_to_ids(tokenizer.tokenize(sentences[0])))

```

↳ Loading BERT tokenizer...

Downloading: 100% 232k/232k [00:00<00:00, 1.61MB/s]

```

Original:  st century wire says mexicos billionaire tycoon carlos slim saw large chuck wealth evaporate lite
Tokenized: ['st', 'century', 'wire', 'says', 'mexico', '##s', 'billionaire', 'ty', '##co', '##on', 'carlos',
Token IDs: [2358, 2301, 7318, 2758, 3290, 2015, 22301, 5939, 3597, 2239, 5828, 11754, 2387, 2312, 8057, 7177

```

```

# Tokenize all of the sentences and map the tokens to thier word IDs.
input_ids = []

```

```

# For every sentence...
for sent in sentences:
    # `encode` will:
    # (1) Tokenize the sentence.
    # (2) Prepend the `[CLS]` token to the start.
    # (3) Append the `[SEP]` token to the end.
    # (4) Map tokens to their IDs.
    encoded_sent = tokenizer.encode(
        sent,                      # Sentence to encode.
        add_special_tokens = True, # Add '[CLS]' and '[SEP]'
        max_length = 512          # Truncate all sentences.
        #return_tensors = 'pt',    # Return pytorch tensors.
    )

```

```

# Add the encoded sentence to the list.

```

```

input_ids.append(encoded_sent)

```



```

input_ids.append(encoded_sent)

# Print sentence 0, now as a list of IDs.
print('Original: ', sentences[0])
print('Token IDs:', input_ids[0])

☐➤ Original:  st century wire says mexicos billionaire tycoon carlos slim saw large chuck wealth evaporate liter
Token IDs: [101, 2358, 2301, 7318, 2758, 3290, 2015, 22301, 5939, 3597, 2239, 5828, 11754, 2387, 2312, 8057,

import statistics

print('Avg sentence length: ', statistics.mean([len(sen) for sen in input_ids]))

☐➤ Avg sentence length:  249.9547596353922

print('Max sentence length: ', max([len(sen) for sen in input_ids]))

☐➤ Max sentence length:  512

import keras
# We'll borrow the `pad_sequences` utility function to do this.
from keras.preprocessing.sequence import pad_sequences

# Set the maximum sequence length.
# I've chosen 64 somewhat arbitrarily. It's slightly larger than the
# maximum training sentence length of 47...
MAX_LEN = 256

print('\nPadding/truncating all sentences to %d values...' % MAX_LEN)

print('\nPadding token: "{:}" , ID: {:}'.format(tokenizer.pad_token, tokenizer.pad_token_id))

# Pad our input tokens with value 0.
# "post" indicates that we want to pad and truncate at the end of the sequence,
# as opposed to the beginning.
input_ids = pad_sequences(input_ids, maxlen=MAX_LEN, dtype="long",
                          value=0, truncating="post", padding="post")

```

```
print('\nDone.')
```



Padding/truncating all sentences to 256 values...

Padding token: "[PAD]", ID: 0
Using TensorFlow backend.

Done.

```
# Create attention masks
attention_masks = []
```

```
# For each sentence...
for sent in input_ids:
```

```
    # Create the attention mask.
    # - If a token ID is 0, then it's padding, set the mask to 0.
    # - If a token ID is > 0, then it's a real token, set the mask to 1.
    att_mask = [int(token_id > 0) for token_id in sent]
```

```
    # Store the attention mask for this sentence.
    attention_masks.append(att_mask)
```

```
# Use 90% for training and 10% for validation.
train_inputs, validation_inputs, train_labels, validation_labels = train_test_split(input_ids, labels,
                                                                                      random_state=2018, test_size=0.1)
```

```
# Do the same for the masks.
train_masks, validation_masks, _, _ = train_test_split(attention_masks, labels,
                                                         random_state=2018, test_size=0.1)
```

```
# Convert all inputs and labels into torch tensors, the required datatype
# for our model.
train_inputs = torch.tensor(train_inputs)
validation_inputs = torch.tensor(validation_inputs)
```

```
train_labels = torch.tensor(train_labels)
validation_labels = torch.tensor(validation_labels)
```

```
train_masks = torch.tensor(train_masks)
validation_masks = torch.tensor(validation_masks)

from torch.utils.data import TensorDataset, DataLoader, RandomSampler, SequentialSampler

# The DataLoader needs to know our batch size for training, so we specify it
# here.
# For fine-tuning BERT on a specific task, the authors recommend a batch size of
# 16 or 32.

batch_size = 32

# Create the DataLoader for our training set.
train_data = TensorDataset(train_inputs, train_masks, train_labels)
train_sampler = RandomSampler(train_data)
train_dataloader = DataLoader(train_data, sampler=train_sampler, batch_size=batch_size)

# Create the DataLoader for our validation set.
validation_data = TensorDataset(validation_inputs, validation_masks, validation_labels)
validation_sampler = SequentialSampler(validation_data)
validation_dataloader = DataLoader(validation_data, sampler=validation_sampler, batch_size=batch_size)

from transformers import BertForSequenceClassification, AdamW, BertConfig

# Load BertForSequenceClassification, the pretrained BERT model with a single
# linear classification layer on top.
model = BertForSequenceClassification.from_pretrained(
    "bert-base-uncased", # Use the 12-layer BERT model, with an uncased vocab.
    num_labels = 2, # The number of output labels--2 for binary classification.
                    # You can increase this for multi-class tasks.
    output_attentions = False, # Whether the model returns attentions weights.
    output_hidden_states = False, # Whether the model returns all hidden-states.
)

# Tell pytorch to run this model on the GPU.
model.cuda()
```



Downloading: 100%

361/361 [00:00<00:00, 1.95kB/s]

Downloading: 100%

440M/440M [00:06<00:00, 70.2MB/s]

```

BertForSequenceClassification(
  (bert): BertModel(
    (embeddings): BertEmbeddings(
      (word_embeddings): Embedding(30522, 768, padding_idx=0)
      (position_embeddings): Embedding(512, 768)
      (token_type_embeddings): Embedding(2, 768)
      (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
    (encoder): BertEncoder(
      (layer): ModuleList(
        (0): BertLayer(
          (attention): BertAttention(
            (self): BertSelfAttention(
              (query): Linear(in_features=768, out_features=768, bias=True)
              (key): Linear(in_features=768, out_features=768, bias=True)
              (value): Linear(in_features=768, out_features=768, bias=True)
              (dropout): Dropout(p=0.1, inplace=False)
            )
            (output): BertSelfOutput(
              (dense): Linear(in_features=768, out_features=768, bias=True)
              (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
              (dropout): Dropout(p=0.1, inplace=False)
            )
          )
          (intermediate): BertIntermediate(
            (dense): Linear(in_features=768, out_features=3072, bias=True)
          )
          (output): BertOutput(
            (dense): Linear(in_features=3072, out_features=768, bias=True)
            (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
            (dropout): Dropout(p=0.1, inplace=False)
          )
        )
        (1): BertLayer(
          (attention): BertAttention(
            (self): BertSelfAttention(
              (query): Linear(in_features=768, out_features=768, bias=True)
              (key): Linear(in_features=768, out_features=768, bias=True)
              (value): Linear(in_features=768, out_features=768, bias=True)
              (dropout): Dropout(p=0.1, inplace=False)
            )
            (output): BertSelfOutput(
              (dense): Linear(in_features=768, out_features=768, bias=True)
              (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
              (dropout): Dropout(p=0.1, inplace=False)
            )
          )
          (intermediate): BertIntermediate(
            (dense): Linear(in_features=768, out_features=3072, bias=True)
          )
          (output): BertOutput(
            (dense): Linear(in_features=3072, out_features=768, bias=True)
            (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
            (dropout): Dropout(p=0.1, inplace=False)
          )
        )
      )
    )
  )
)

```

```

        (query): Linear(in_features=768, out_features=768, bias=True)
        (key): Linear(in_features=768, out_features=768, bias=True)
        (value): Linear(in_features=768, out_features=768, bias=True)
        (dropout): Dropout(p=0.1, inplace=False)
    )
    (output): BertSelfOutput(
        (dense): Linear(in_features=768, out_features=768, bias=True)
        (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
        (dropout): Dropout(p=0.1, inplace=False)
    )
)
(intermediate): BertIntermediate(
    (dense): Linear(in_features=768, out_features=3072, bias=True)
)
(output): BertOutput(
    (dense): Linear(in_features=3072, out_features=768, bias=True)
    (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
    (dropout): Dropout(p=0.1, inplace=False)
)
)
(2): BertLayer(
    (attention): BertAttention(
        (self): BertSelfAttention(
            (query): Linear(in_features=768, out_features=768, bias=True)
            (key): Linear(in_features=768, out_features=768, bias=True)
            (value): Linear(in_features=768, out_features=768, bias=True)
            (dropout): Dropout(p=0.1, inplace=False)
        )
        (output): BertSelfOutput(
            (dense): Linear(in_features=768, out_features=768, bias=True)
            (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
            (dropout): Dropout(p=0.1, inplace=False)
        )
    )
    (intermediate): BertIntermediate(
        (dense): Linear(in_features=768, out_features=3072, bias=True)
    )
    (output): BertOutput(
        (dense): Linear(in_features=3072, out_features=768, bias=True)
        (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
        (dropout): Dropout(p=0.1, inplace=False)
    )
)
(3): BertLayer(

```

```

(attention): BertAttention(
  (self): BertSelfAttention(
    (query): Linear(in_features=768, out_features=768, bias=True)
    (key): Linear(in_features=768, out_features=768, bias=True)
    (value): Linear(in_features=768, out_features=768, bias=True)
    (dropout): Dropout(p=0.1, inplace=False)
  )
  (output): BertSelfOutput(
    (dense): Linear(in_features=768, out_features=768, bias=True)
    (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
    (dropout): Dropout(p=0.1, inplace=False)
  )
)
(intermediate): BertIntermediate(
  (dense): Linear(in_features=768, out_features=3072, bias=True)
)
(output): BertOutput(
  (dense): Linear(in_features=3072, out_features=768, bias=True)
  (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
  (dropout): Dropout(p=0.1, inplace=False)
)
)
(4): BertLayer(
  (attention): BertAttention(
    (self): BertSelfAttention(
      (query): Linear(in_features=768, out_features=768, bias=True)
      (key): Linear(in_features=768, out_features=768, bias=True)
      (value): Linear(in_features=768, out_features=768, bias=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
    (output): BertSelfOutput(
      (dense): Linear(in_features=768, out_features=768, bias=True)
      (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
  )
  (intermediate): BertIntermediate(
    (dense): Linear(in_features=768, out_features=3072, bias=True)
  )
  (output): BertOutput(
    (dense): Linear(in_features=3072, out_features=768, bias=True)
    (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
    (dropout): Dropout(p=0.1, inplace=False)
  )
)

```

```

    ,
)
(5): BertLayer(
  (attention): BertAttention(
    (self): BertSelfAttention(
      (query): Linear(in_features=768, out_features=768, bias=True)
      (key): Linear(in_features=768, out_features=768, bias=True)
      (value): Linear(in_features=768, out_features=768, bias=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
    (output): BertSelfOutput(
      (dense): Linear(in_features=768, out_features=768, bias=True)
      (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
  )
  (intermediate): BertIntermediate(
    (dense): Linear(in_features=768, out_features=3072, bias=True)
  )
  (output): BertOutput(
    (dense): Linear(in_features=3072, out_features=768, bias=True)
    (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
    (dropout): Dropout(p=0.1, inplace=False)
  )
)
(6): BertLayer(
  (attention): BertAttention(
    (self): BertSelfAttention(
      (query): Linear(in_features=768, out_features=768, bias=True)
      (key): Linear(in_features=768, out_features=768, bias=True)
      (value): Linear(in_features=768, out_features=768, bias=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
    (output): BertSelfOutput(
      (dense): Linear(in_features=768, out_features=768, bias=True)
      (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
  )
  (intermediate): BertIntermediate(
    (dense): Linear(in_features=768, out_features=3072, bias=True)
  )
  (output): BertOutput(
    (dense): Linear(in_features=3072, out_features=768, bias=True)
    (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
    (dropout): Dropout(p=0.1, inplace=False)
  )
)

```

```

        (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
        (dropout): Dropout(p=0.1, inplace=False)
    )
)
(7): BertLayer(
  (attention): BertAttention(
    (self): BertSelfAttention(
      (query): Linear(in_features=768, out_features=768, bias=True)
      (key): Linear(in_features=768, out_features=768, bias=True)
      (value): Linear(in_features=768, out_features=768, bias=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
    (output): BertSelfOutput(
      (dense): Linear(in_features=768, out_features=768, bias=True)
      (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
  )
  (intermediate): BertIntermediate(
    (dense): Linear(in_features=768, out_features=3072, bias=True)
  )
  (output): BertOutput(
    (dense): Linear(in_features=3072, out_features=768, bias=True)
    (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
    (dropout): Dropout(p=0.1, inplace=False)
  )
)
(8): BertLayer(
  (attention): BertAttention(
    (self): BertSelfAttention(
      (query): Linear(in_features=768, out_features=768, bias=True)
      (key): Linear(in_features=768, out_features=768, bias=True)
      (value): Linear(in_features=768, out_features=768, bias=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
    (output): BertSelfOutput(
      (dense): Linear(in_features=768, out_features=768, bias=True)
      (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
  )
  (intermediate): BertIntermediate(
    (dense): Linear(in_features=768, out_features=3072, bias=True)
  )
)

```



```

(output): BertOutput(
  (dense): Linear(in_features=3072, out_features=768, bias=True)
  (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
  (dropout): Dropout(p=0.1, inplace=False)
)
)
(9): BertLayer(
  (attention): BertAttention(
    (self): BertSelfAttention(
      (query): Linear(in_features=768, out_features=768, bias=True)
      (key): Linear(in_features=768, out_features=768, bias=True)
      (value): Linear(in_features=768, out_features=768, bias=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
    (output): BertSelfOutput(
      (dense): Linear(in_features=768, out_features=768, bias=True)
      (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
  )
  (intermediate): BertIntermediate(
    (dense): Linear(in_features=768, out_features=3072, bias=True)
  )
  (output): BertOutput(
    (dense): Linear(in_features=3072, out_features=768, bias=True)
    (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
    (dropout): Dropout(p=0.1, inplace=False)
  )
)
(10): BertLayer(
  (attention): BertAttention(
    (self): BertSelfAttention(
      (query): Linear(in_features=768, out_features=768, bias=True)
      (key): Linear(in_features=768, out_features=768, bias=True)
      (value): Linear(in_features=768, out_features=768, bias=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
    (output): BertSelfOutput(
      (dense): Linear(in_features=768, out_features=768, bias=True)
      (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
      (dropout): Dropout(p=0.1, inplace=False)
    )
  )
  (intermediate): BertIntermediate(

```

```

        (dense): Linear(in_features=768, out_features=3072, bias=True)
    )
    (output): BertOutput(
        (dense): Linear(in_features=3072, out_features=768, bias=True)
        (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
        (dropout): Dropout(p=0.1, inplace=False)
    )
)
(11): BertLayer(
    (attention): BertAttention(
        (self): BertSelfAttention(
            (query): Linear(in_features=768, out_features=768, bias=True)
            (key): Linear(in_features=768, out_features=768, bias=True)
            (value): Linear(in_features=768, out_features=768, bias=True)
            (dropout): Dropout(p=0.1, inplace=False)
        )
        (output): BertSelfOutput(
            (dense): Linear(in_features=768, out_features=768, bias=True)
            (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
            (dropout): Dropout(p=0.1, inplace=False)
        )
    )
    (intermediate): BertIntermediate(
        (dense): Linear(in_features=768, out_features=3072, bias=True)
    )
    (output): BertOutput(
        (dense): Linear(in_features=3072, out_features=768, bias=True)
        (LayerNorm): LayerNorm((768,), eps=1e-12, elementwise_affine=True)
        (dropout): Dropout(p=0.1, inplace=False)
    )
)
)
)
(pooler): BertPooler(
    (dense): Linear(in_features=768, out_features=768, bias=True)
    (activation): Tanh()
)
(dropout): Dropout(p=0.1, inplace=False)
(classifier): Linear(in_features=768, out_features=2, bias=True)
)

```

```

""" Note: AdamW is a class from the huggingface library (as opposed to pytorch),
# I believe the 'W' stands for 'Weight Decay fix"
optimizer = AdamW(model.parameters(),
                    lr = 2e-5, # args.learning_rate - default is 5e-5, our notebook had 2e-5
                    eps = 1e-8 # args.adam_epsilon - default is 1e-8.
                  )

from transformers import get_linear_schedule_with_warmup

# Number of training epochs (authors recommend between 2 and 4)
epochs = 5

# Total number of training steps is number of batches * number of epochs.
total_steps = len(train_dataloader) * epochs

# Create the learning rate scheduler.
scheduler = get_linear_schedule_with_warmup(optimizer,
                                             num_warmup_steps = 0, # Default value in run_glue.py
                                             num_training_steps = total_steps)

# Function to calculate the accuracy of our predictions vs labels
def flat_accuracy(preds, labels):
    pred_flat = np.argmax(preds, axis=1).flatten()
    labels_flat = labels.flatten()
    return np.sum(pred_flat == labels_flat) / len(labels_flat)

import time
import datetime

def format_time(elapsed):
    """
    Takes a time in seconds and returns a string hh:mm:ss
    """
    # Round to the nearest second.
    elapsed_rounded = int(round((elapsed)))

    # Format as hh:mm:ss

```

```

return str(datetime.timedelta(seconds=elapsed_rounded))

torch.cuda.empty_cache()

import random

# This training code is based on the `run_glue.py` script here:
# https://github.com/huggingface/transformers/blob/5bfcd0485ece086ebcbed2d008813037968a9e58/examples/run\_glue.py#I

# Set the seed value all over the place to make this reproducible.
seed_val = 42

random.seed(seed_val)
np.random.seed(seed_val)
torch.manual_seed(seed_val)
torch.cuda.manual_seed_all(seed_val)

# Store the average loss after each epoch so we can plot them.
loss_values = []

# For each epoch...
for epoch_i in range(0, epochs):

    # =====
    #           Training
    # =====

    # Perform one full pass over the training set.

    print("")
    print('==== Epoch {:} / {:} ====='.format(epoch_i + 1, epochs))
    print('Training...')

    # Measure how long the training epoch takes.
    t0 = time.time()

    # Reset the total loss for this epoch.

```

```
total_loss = 0
```

```
# Put the model into training mode. Don't be mislead--the call to
# `train` just changes the *mode*, it doesn't *perform* the training.
# `dropout` and `batchnorm` layers behave differently during training
# vs. test (source: https://stackoverflow.com/questions/51433378/what-does-model-train-do-in-pytorch)
model.train()

# For each batch of training data...
for step, batch in enumerate(train_dataloader):

    # Progress update every 40 batches.
    if step % 40 == 0 and not step == 0:
        # Calculate elapsed time in minutes.
        elapsed = format_time(time.time() - t0)

        # Report progress.
        print('  Batch {:>5,} of {:>5,}.    Elapsed: {:.}'.format(step, len(train_dataloader), elapsed))

    # Unpack this training batch from our dataloader.
    #
    # As we unpack the batch, we'll also copy each tensor to the GPU using the
    # `to` method.
    #
    # `batch` contains three pytorch tensors:
    #   [0]: input ids
    #   [1]: attention masks
    #   [2]: labels
    b_input_ids = batch[0].to(device)
    b_input_mask = batch[1].to(device)
    b_labels = batch[2].to(device)

    # Always clear any previously calculated gradients before performing a
    # backward pass. PyTorch doesn't do this automatically because
    # accumulating the gradients is "convenient while training RNNs".
    # (source: https://stackoverflow.com/questions/48001598/why-do-we-need-to-call-zero-grad-in-pytorch)
    model.zero_grad()

    # Perform a forward pass (evaluate the model on this training batch).
    # This will return the loss (a scalar) and the model's output, which we
```

```
# This will return the loss (rather than the model output) because we
# have provided the `labels`.
# The documentation for this `model` function is here:
# https://huggingface.co/transformers/v2.2.0/model\_doc/bert.html#transformers.BertForSequenceClassification
outputs = model(b_input_ids,
                token_type_ids=None,
                attention_mask=b_input_mask,
                labels=b_labels)

# The call to `model` always returns a tuple, so we need to pull the
# loss value out of the tuple.
loss = outputs[0]

# Accumulate the training loss over all of the batches so that we can
# calculate the average loss at the end. `loss` is a Tensor containing a
# single value; the `.item()` function just returns the Python value
# from the tensor.
total_loss += loss.item()

# Perform a backward pass to calculate the gradients.
loss.backward()

# Clip the norm of the gradients to 1.0.
# This is to help prevent the "exploding gradients" problem.
torch.nn.utils.clip_grad_norm_(model.parameters(), 1.0)

# Update parameters and take a step using the computed gradient.
# The optimizer dictates the "update rule"--how the parameters are
# modified based on their gradients, the learning rate, etc.
optimizer.step()

# Update the learning rate.
scheduler.step()

# Calculate the average loss over the training data.
avg_train_loss = total_loss / len(train_dataloader)

# Store the loss value for plotting the learning curve.
loss_values.append(avg_train_loss)
```

```

print("")
print("  Average training loss: {0:.2f}".format(avg_train_loss))
print("  Training epoch took: {}".format(format_time(time.time() - t0)))

# =====
#           Validation
# =====
# After the completion of each training epoch, measure our performance on
# our validation set.

print("")
print("Running Validation...")

t0 = time.time()

# Put the model in evaluation mode--the dropout layers behave differently
# during evaluation.
model.eval()

# Tracking variables
eval_loss, eval_accuracy = 0, 0
nb_eval_steps, nb_eval_examples = 0, 0

# Evaluate data for one epoch
for batch in validation_dataloader:

    # Add batch to GPU
    batch = tuple(t.to(device) for t in batch)

    # Unpack the inputs from our dataloader
    b_input_ids, b_input_mask, b_labels = batch

    # Telling the model not to compute or store gradients, saving memory and
    # speeding up validation
    with torch.no_grad():

        # Forward pass, calculate logit predictions.
        # This will return the logits rather than the loss because we have
        # not provided labels

```

```
# not provided labels.
# token_type_ids is the same as the "segment ids", which
# differentiates sentence 1 and 2 in 2-sentence tasks.
# The documentation for this `model` function is here:
# https://huggingface.co/transformers/v2.2.0/model\_doc/bert.html#transformers.BertForSequenceClassification
outputs = model(b_input_ids,
                 token_type_ids=None,
                 attention_mask=b_input_mask)

# Get the "logits" output by the model. The "logits" are the output
# values prior to applying an activation function like the softmax.
logits = outputs[0]

# Move logits and labels to CPU
logits = logits.detach().cpu().numpy()
label_ids = b_labels.to('cpu').numpy()

# Calculate the accuracy for this batch of test sentences.
tmp_eval_accuracy = flat_accuracy(logits, label_ids)

# Accumulate the total accuracy.
eval_accuracy += tmp_eval_accuracy

# Track the number of batches
nb_eval_steps += 1

# Report the final accuracy for this validation run.
print(" Accuracy: {:.3f}".format(eval_accuracy/nb_eval_steps))
print(" Validation took: {:s}".format(format_time(time.time() - t0)))

print("")
print("Training complete!")
```



=====
Epoch 1 / 5
=====
Training...

Batch	40	of	2,096.	Elapsed:	0:00:30.
Batch	80	of	2,096.	Elapsed:	0:01:01.
Batch	120	of	2,096.	Elapsed:	0:01:31.
Batch	160	of	2,096.	Elapsed:	0:02:01.
Batch	200	of	2,096.	Elapsed:	0:02:31.
Batch	240	of	2,096.	Elapsed:	0:03:02.
Batch	280	of	2,096.	Elapsed:	0:03:32.
Batch	320	of	2,096.	Elapsed:	0:04:02.
Batch	360	of	2,096.	Elapsed:	0:04:32.
Batch	400	of	2,096.	Elapsed:	0:05:03.
Batch	440	of	2,096.	Elapsed:	0:05:33.
Batch	480	of	2,096.	Elapsed:	0:06:03.
Batch	520	of	2,096.	Elapsed:	0:06:33.
Batch	560	of	2,096.	Elapsed:	0:07:04.
Batch	600	of	2,096.	Elapsed:	0:07:34.
Batch	640	of	2,096.	Elapsed:	0:08:04.
Batch	680	of	2,096.	Elapsed:	0:08:35.
Batch	720	of	2,096.	Elapsed:	0:09:05.
Batch	760	of	2,096.	Elapsed:	0:09:35.
Batch	800	of	2,096.	Elapsed:	0:10:05.
Batch	840	of	2,096.	Elapsed:	0:10:36.
Batch	880	of	2,096.	Elapsed:	0:11:06.
Batch	920	of	2,096.	Elapsed:	0:11:36.
Batch	960	of	2,096.	Elapsed:	0:12:07.
Batch	1,000	of	2,096.	Elapsed:	0:12:37.
Batch	1,040	of	2,096.	Elapsed:	0:13:07.
Batch	1,080	of	2,096.	Elapsed:	0:13:37.
Batch	1,120	of	2,096.	Elapsed:	0:14:08.
Batch	1,160	of	2,096.	Elapsed:	0:14:38.
Batch	1,200	of	2,096.	Elapsed:	0:15:08.
Batch	1,240	of	2,096.	Elapsed:	0:15:39.
Batch	1,280	of	2,096.	Elapsed:	0:16:09.
Batch	1,320	of	2,096.	Elapsed:	0:16:39.
Batch	1,360	of	2,096.	Elapsed:	0:17:10.
Batch	1,400	of	2,096.	Elapsed:	0:17:40.
Batch	1,440	of	2,096.	Elapsed:	0:18:10.
Batch	1,480	of	2,096.	Elapsed:	0:18:41.
Batch	1,520	of	2,096.	Elapsed:	0:19:11.
Batch	1,560	of	2,096.	Elapsed:	0:19:41.
Batch	1,600	of	2,096.	Elapsed:	0:20:11.

```
Batch 1,640 of 2,096. Elapsed: 0:20:42.
Batch 1,680 of 2,096. Elapsed: 0:21:12.
Batch 1,720 of 2,096. Elapsed: 0:21:42.
Batch 1,760 of 2,096. Elapsed: 0:22:13.
Batch 1,800 of 2,096. Elapsed: 0:22:43.
Batch 1,840 of 2,096. Elapsed: 0:23:13.
Batch 1,880 of 2,096. Elapsed: 0:23:43.
Batch 1,920 of 2,096. Elapsed: 0:24:14.
Batch 1,960 of 2,096. Elapsed: 0:24:44.
Batch 2,000 of 2,096. Elapsed: 0:25:14.
Batch 2,040 of 2,096. Elapsed: 0:25:44.
Batch 2,080 of 2,096. Elapsed: 0:26:15.
```

Average training loss: 0.34
Training epoch took: 0:26:26

Running Validation...

Accuracy: 0.851
Validation took: 0:00:56

=====
Epoch 2 / 5 =====

Training...

```
Batch 40 of 2,096. Elapsed: 0:00:30.
Batch 80 of 2,096. Elapsed: 0:01:01.
Batch 120 of 2,096. Elapsed: 0:01:31.
Batch 160 of 2,096. Elapsed: 0:02:01.
Batch 200 of 2,096. Elapsed: 0:02:31.
Batch 240 of 2,096. Elapsed: 0:03:02.
Batch 280 of 2,096. Elapsed: 0:03:32.
Batch 320 of 2,096. Elapsed: 0:04:02.
Batch 360 of 2,096. Elapsed: 0:04:32.
Batch 400 of 2,096. Elapsed: 0:05:03.
Batch 440 of 2,096. Elapsed: 0:05:33.
Batch 480 of 2,096. Elapsed: 0:06:03.
Batch 520 of 2,096. Elapsed: 0:06:34.
Batch 560 of 2,096. Elapsed: 0:07:04.
Batch 600 of 2,096. Elapsed: 0:07:34.
Batch 640 of 2,096. Elapsed: 0:08:04.
Batch 680 of 2,096. Elapsed: 0:08:34.
Batch 720 of 2,096. Elapsed: 0:09:05.
Batch 760 of 2,096. Elapsed: 0:09:35.
Batch 800 of 2,096. Elapsed: 0:10:05.
Batch 840 of 2,096. Elapsed: 0:10:35.
Batch 880 of 2,096. Elapsed: 0:11:06.
```

```

Batch    920  of  2,096.    Elapsed: 0:11:36.
Batch    960  of  2,096.    Elapsed: 0:12:06.
Batch   1,000  of  2,096.    Elapsed: 0:12:37.
Batch   1,040  of  2,096.    Elapsed: 0:13:07.
Batch   1,080  of  2,096.    Elapsed: 0:13:37.
Batch   1,120  of  2,096.    Elapsed: 0:14:07.
Batch   1,160  of  2,096.    Elapsed: 0:14:38.
Batch   1,200  of  2,096.    Elapsed: 0:15:08.
Batch   1,240  of  2,096.    Elapsed: 0:15:38.
Batch   1,280  of  2,096.    Elapsed: 0:16:08.
Batch   1,320  of  2,096.    Elapsed: 0:16:39.
Batch   1,360  of  2,096.    Elapsed: 0:17:09.
Batch   1,400  of  2,096.    Elapsed: 0:17:39.
Batch   1,440  of  2,096.    Elapsed: 0:18:09.
Batch   1,480  of  2,096.    Elapsed: 0:18:40.
Batch   1,520  of  2,096.    Elapsed: 0:19:10.
Batch   1,560  of  2,096.    Elapsed: 0:19:40.
Batch   1,600  of  2,096.    Elapsed: 0:20:10.
Batch   1,640  of  2,096.    Elapsed: 0:20:41.
Batch   1,680  of  2,096.    Elapsed: 0:21:11.
Batch   1,720  of  2,096.    Elapsed: 0:21:41.
Batch   1,760  of  2,096.    Elapsed: 0:22:11.
Batch   1,800  of  2,096.    Elapsed: 0:22:42.
Batch   1,840  of  2,096.    Elapsed: 0:23:12.
Batch   1,880  of  2,096.    Elapsed: 0:23:42.
Batch   1,920  of  2,096.    Elapsed: 0:24:13.
Batch   1,960  of  2,096.    Elapsed: 0:24:43.
Batch   2,000  of  2,096.    Elapsed: 0:25:13.
Batch   2,040  of  2,096.    Elapsed: 0:25:43.
Batch   2,080  of  2,096.    Elapsed: 0:26:14.

```

Average training loss: 0.22
 Training epoch took: 0:26:25

Running Validation...

Accuracy: 0.872
 Validation took: 0:00:56

==== Epoch 3 / 5 =====

Training...

```

Batch    40  of  2,096.    Elapsed: 0:00:30.
Batch    80  of  2,096.    Elapsed: 0:01:01.
Batch   120  of  2,096.    Elapsed: 0:01:31.
Batch   160  of  2,096.    Elapsed: 0:02:01.

```

Batch	100	of	2,096.	Elapsed: 0:02:01.
Batch	200	of	2,096.	Elapsed: 0:02:31.
Batch	240	of	2,096.	Elapsed: 0:03:02.
Batch	280	of	2,096.	Elapsed: 0:03:32.
Batch	320	of	2,096.	Elapsed: 0:04:02.
Batch	360	of	2,096.	Elapsed: 0:04:33.
Batch	400	of	2,096.	Elapsed: 0:05:03.
Batch	440	of	2,096.	Elapsed: 0:05:33.
Batch	480	of	2,096.	Elapsed: 0:06:03.
Batch	520	of	2,096.	Elapsed: 0:06:34.
Batch	560	of	2,096.	Elapsed: 0:07:04.
Batch	600	of	2,096.	Elapsed: 0:07:34.
Batch	640	of	2,096.	Elapsed: 0:08:04.
Batch	680	of	2,096.	Elapsed: 0:08:35.
Batch	720	of	2,096.	Elapsed: 0:09:05.
Batch	760	of	2,096.	Elapsed: 0:09:35.
Batch	800	of	2,096.	Elapsed: 0:10:05.
Batch	840	of	2,096.	Elapsed: 0:10:36.
Batch	880	of	2,096.	Elapsed: 0:11:06.
Batch	920	of	2,096.	Elapsed: 0:11:36.
Batch	960	of	2,096.	Elapsed: 0:12:06.
Batch	1,000	of	2,096.	Elapsed: 0:12:37.
Batch	1,040	of	2,096.	Elapsed: 0:13:07.
Batch	1,080	of	2,096.	Elapsed: 0:13:37.
Batch	1,120	of	2,096.	Elapsed: 0:14:08.
Batch	1,160	of	2,096.	Elapsed: 0:14:38.
Batch	1,200	of	2,096.	Elapsed: 0:15:08.
Batch	1,240	of	2,096.	Elapsed: 0:15:39.
Batch	1,280	of	2,096.	Elapsed: 0:16:09.
Batch	1,320	of	2,096.	Elapsed: 0:16:39.
Batch	1,360	of	2,096.	Elapsed: 0:17:09.
Batch	1,400	of	2,096.	Elapsed: 0:17:40.
Batch	1,440	of	2,096.	Elapsed: 0:18:10.
Batch	1,480	of	2,096.	Elapsed: 0:18:40.
Batch	1,520	of	2,096.	Elapsed: 0:19:11.
Batch	1,560	of	2,096.	Elapsed: 0:19:41.
Batch	1,600	of	2,096.	Elapsed: 0:20:11.
Batch	1,640	of	2,096.	Elapsed: 0:20:41.
Batch	1,680	of	2,096.	Elapsed: 0:21:12.
Batch	1,720	of	2,096.	Elapsed: 0:21:42.
Batch	1,760	of	2,096.	Elapsed: 0:22:12.
Batch	1,800	of	2,096.	Elapsed: 0:22:43.
Batch	1,840	of	2,096.	Elapsed: 0:23:13.
Batch	1,880	of	2,096.	Elapsed: 0:23:43.