



Paper



Slides

Plug-and-Play Priors for Reconstruction-based Placental Image Registration (PnP-RR)

Jiarui Xing¹, Ulugbek Kamilov^{2,3},
Wenjie Wu^{4,5}, Yong Wang⁵,
and Miaomiao Zhang^{1,6}

¹ Electrical and Computer Engineering, University of Virginia, Charlottesville, USA

² Computer Science and Engineering, Washington University in St. Louis, USA

³ Electrical and Systems Engineering, Washington University in St. Louis, USA

⁴ Biomedical Engineering, Washington University in St. Louis, USA.

⁵ Obstetrics and Gynecology, Washington University in St. Louis, USA.

⁶ Computer Science, University of Virginia, Charlottesville, USA





Paper



Slides

Brief Intro

- We proposed plug-and-play reconstruction-registration method (PnP-RR), which
 - 1) is a deformable image registration framework for noise-corrupted images
 - 2) can be used on registering placental diffusion-weighted MR images that contains noise



Paper



Slides

Brief Intro

- We proposed plug-and-play reconstruction-registration method (PnP-RR), which
 - 1) is a deformable image registration framework for noise-corrupted images
 - 2) can be used on registering placental diffusion-weighted MR images that contains noise

Contents

1. Background
 - 1) What is image registration and why we need it
 - 2) Why there is noise in the images and the basic idea to deal with it.
2. Related works and their weakness
3. Proposed method: PnP-RR
4. Experiments and results
5. Discussion and conclusion

Background


- Placenta and DW-MRI
 - **Diffusion-weighted MRI (DW-MRI)** has recently been used in placental health monitor



Background

- Placenta and DW-MRI


- Diffusion-weighted MRI (DW-MRI) has recently been used in placental health monitor
- We need to collect **several placental DW-MR images** with **different parameters** (b-values) and track how the look of placenta changes with different b-value



Background

- Placenta and DW-MRI


- Diffusion-weighted MRI (DW-MRI) has recently been used in placental health monitor
- We need to collect several placental DW-MR images with different parameters (b-values) and track how the look of placenta changes with different b-value
- However, due to **maternal breathing and fetal movements**, there would be **deformation among the images**, make it hard to track the change



Background

- Placenta and DW-MRI


- Diffusion-weighted MRI (DW-MRI) has recently been used in placental health monitor
- We need to collect several placental DW-MR images with different parameters (b-values) and track how the look of placenta changes with different b-value
- However, due to breath and movement, there would be deformation among the images, make it hard to track the change
- Therefore, **image registration** is needed to **find and cancel the deformation** and align the placenta in images.



Background

- Image Registration


- Task: find the deformation ϕ between a source Image S and a target image T



Background


- Image Registration

- Task: find the deformation ϕ between a source Image S and a target image T
- Current mainstream: optimization-based methods
 - take the deformation that minimize an energy function




Background

- B-value and noise
 - Assumption of ordinary registration method: deformation is the only difference




Background

- B-value and noise
 - Assumption of ordinary registration method: deformation is the only difference
 - However, higher b-value, stronger noise




DW-MR image from same location in different b-values




Background

- B-value and noise
 - Assumption of ordinary registration method: deformation is the only difference
 - However, higher b-value, stronger noise
 - Ordinary registration methods fail



Background

- B-value and noise
 - Assumption of ordinary registration method: deformation is the only difference
 - However, higher b-value, stronger noise
 - Ordinary registration methods fail
 - A noise-robust image registration methods is needed



Related Works

- Basic idea: denoising + registration
 - find a method to combine image denoising and image registration.
 - Image denoising
 - Example: TV denoising for white Gaussian noise



Original




Noisy Image



Denoised image


Related Works

- 2-Steps Method: denoising before registration



May **NOT** converge to **OPTIMAL** solution


- Joint Optimization Method



Requires explicit objective function;
-> **LIMITED CHOICES** for denoisers


Proposed method: PnP-RR

- Basic Idea



Proposed method: PnP-RR


- Basic Idea



- Advantages

- ☐ TV ✓
- ☐ TGV ✓
- ☐ BM3D ✓
- ☐ Neural Network ✓


Flexible to
CHOOSE DENOISER



Better
PERFORMANCE



Simple to
IMPLEMENT



Easy to
TUNE

Proposed method: PnP-RR

- Derivation
 - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

Proposed method: PnP-RR

- Derivation
 - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

- **SPLIT** Formulated as proximal algorithm

$$\begin{aligned} \operatorname{argmin}_{\tilde{T}} \frac{1}{2} \|\tilde{T} - Z\|_{L2}^2 + \tau \mathcal{R}_{\text{denoising}}(\tilde{T}) &= \text{denoise}_{\sigma}(\tilde{T} | S \circ \phi^{-1}) \quad \text{where } Z = \frac{\lambda_2 T + (1/\sigma^2)(S \circ \phi^{-1})}{\lambda_2 + (1/\sigma^2)} \\ \operatorname{argmin}_{\phi} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) &= \text{register}_{\sigma}(S, \tilde{T}^k) \quad \tau = \frac{\lambda_1}{2(\lambda_2 + (1/\sigma^2))} \end{aligned}$$

Proposed method: PnP-RR

- Derivation
 - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

- **SPLIT** Formulated as proximal algorithm

$$\begin{aligned} \operatorname{argmin}_{\tilde{T}} \frac{1}{2} \|\tilde{T} - Z\|_{L2}^2 + \tau \mathcal{R}_{\text{denoising}}(\tilde{T}) &= \text{denoise}_{\sigma}(\tilde{T} | S \circ \phi^{-1}) & \text{where} \\ \operatorname{argmin}_{\phi} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) &= \text{register}_{\sigma}(S, \tilde{T}^k) & Z = \frac{\lambda_2 T + (1/\sigma^2)(S \circ \phi^{-1})}{\lambda_2 + (1/\sigma^2)} \\ & & \tau = \frac{\lambda_1}{2(\lambda_2 + (1/\sigma^2))} \end{aligned}$$

- **REPLACE** Formulated as PnP algorithm

$\text{denoise}'_{\tau}(Z)$

$\text{register}_{\sigma}(S, \tilde{T}^k)$

Proposed method: PnP-RR

- Derivation
 - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

- **SPLIT** Formulated as proximal algorithm

$$\begin{aligned} \operatorname{argmin}_{\tilde{T}} \frac{1}{2} \|\tilde{T} - Z\|_{L2}^2 + \tau \mathcal{R}_{\text{denoising}}(\tilde{T}) &= \text{denoise}_{\sigma}(\tilde{T} | S \circ \phi^{-1}) & \text{where } Z &= \frac{\lambda_2 T + (1/\sigma^2)(S \circ \phi^{-1})}{\lambda_2 + (1/\sigma^2)} \\ \operatorname{argmin}_{\phi} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) &= \text{register}_{\sigma}(S, \tilde{T}^k) & \tau &= \frac{\lambda_1}{2(\lambda_2 + (1/\sigma^2))} \end{aligned}$$

- **REPLACE** Formulated as PnP algorithm

$\text{denoise}'_{\tau}(Z)$


$\text{register}_{\sigma}(S, \tilde{T}^k)$

Specifying an image prior


Experiments

- Data

- 2D synthetic data



- Real 3D DW-MRI data



- Algorithm Setting

- Registration algorithm

- Fourier-approximated Lie Algebras for Shooting (FLASH)^[1]

- Denoising algorithm


- Total variation (TV)
 - Total generalized variation (TGV)
 - Block-matching and 3D filtering (BM3D)

[1] Zhang, M., Liao, R., Dalca, A.V., Turk, E.A., Luo, J., Grant, P.E., Golland, P.: Frequency diffeomorphisms for efficient image registration. In: International conference on information processing in medical imaging. pp. 559–570. Springer (2017)

Experiments


- Result

- 2D synthetic data – Visual effect




Experiments

- Result
 - 2D synthetic data – Quantitative performance



Experiments


- Data
 - Real 3D DW-MRI data



All DW-MRIs are of dimension $128 \times 128 \times 50$ and underwent bias field correction, co-registration with affine transformations and intensity normalization


Experiments

- Data
 - Real 3D DW-MRI data




All DW-MRIs are of dimension $128 \times 128 \times 50$ and underwent bias field correction, co-registration with affine transformations and intensity normalization


- Result




Source




Target




FLASH



Ours (TV)



Ours (TGV)



Ours (BM3D)

Discussion

- Performance
 - Data
 - Advanced methods
- Convergence
- Time

Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images

Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task
- What's more, our model benefits from its easiness to implement, robustness to parameter tuning and better performance
- Future research will involve collecting more dataset on placental images and exploring other cutting-edge denoisers, such as deep learning-based approaches.
- Questions?

Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task

Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task
- What's more, our model benefits from its easiness to implement, robustness to parameter tuning and better performance
- Future research will involve collecting more dataset on placental images and exploring other cutting-edge denoisers, such as deep learning-based approaches.

Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task
- What's more, our model benefits from its easiness to implement, robustness to parameter tuning and better performance
- Future research will involve collecting more dataset on placental images and exploring other cutting-edge denoisers, such as deep learning-based approaches.
- Questions?

Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang