



Paper



Slides

Plug-and-Play Priors for Reconstruction-based Placental Image Registration (PnP-RR)

Jiarui Xing¹, Ulugbek Kamilov^{2,3},
Wenjie Wu^{4,5}, Yong Wang⁵,
and Miaomiao Zhang^{1,6}



¹ Electrical and Computer Engineering, University of Virginia, Charlottesville, USA

² Computer Science and Engineering, Washington University in St. Louis, USA

³ Electrical and Systems Engineering, Washington University in St. Louis, USA

⁴ Biomedical Engineering, Washington University in St. Louis, USA.

⁵ Obstetrics and Gynecology, Washington University in St. Louis, USA.

⁶ Computer Science, University of Virginia, Charlottesville, USA



Paper



Slides

Brief Intro

- We proposed **plug-and-play reconstruction-registration method (PnP-RR)**:
 - 1) Is a deformable image **registration** framework for **severely noise-corrupted images**
 - 2) Is used for registering placental diffusion-weighted MR images that contains severely noise



Paper



Slides

Brief Intro


- We proposed plug-and-play reconstruction-registration method (PnP-RR):
 - 1) Is a deformable image registration framework for severely noise-corrupted images
 - 2) Is used for registering placental diffusion-weighted MR images that contains severely noise

Contents

1. Background
 - 1) DW-MRI
 - 2) Image registration
2. Related works
3. Proposed method: PnP-RR
4. Experiments and results
5. Discussion and conclusion

Background


- Placenta and DW-MRI
 - **Diffusion-weighted MRI (DW-MRI)** for placental health monitoring



Background

- Placenta and DW-MRI


- Diffusion-weighted MRI (DW-MRI) for placental health monitor
- Collect **several placental DW-MR images** with **different parameters (b-values)**, then **track** the appearance changes



Background

- Placenta and DW-MRI


- Diffusion-weighted MRI (DW-MRI) for placental health monitor
- Collect several placental DW-MR images with different parameters (b-values); then track the appearance changes
- **Deformation** among images due to maternal breathing and fetal movements **makes tracking hard**



Background


- Placenta and DW-MRI

- Diffusion-weighted MRI (DW-MRI) for placental health monitor
- Collect several placental DW-MR images with different parameters (b-values); then track the appearance changes
- Deformation among images due to maternal breathing and fetal movements makes tracking hard
- Need **Image registration** to **find and cancel the deformation**



Background


- Image Registration
 - **Task: find the deformation** ϕ between a source Image S and a target image T



Background


- Image Registration

- Task: find the deformation ϕ between a source Image S and a target image T
- Current mainstream: **optimization-based methods**




Background

- B-value and noise
 - Higher **b-value**, stronger **noise**












Background

- B-value and noise
 - Higher b-value, stronger noise
 - Ordinary registration methods: fail on severely noise-corrupted images




Background

- B-value and noise
 - DW-MRI images with different b-values



Background

- B-value and noise
 - Higher b-value, stronger noise
 - Ordinary registration methods: fail on severely noise-corrupted images
 - A noise-robust image registration methods is needed



Related Works

- Basic idea: denoising + registration
 - **Integrate** image registration with **denoising**

Related Works

- Basic idea: denoising + registration
 - **Integrate** image registration with **denoising**
 - Denoising **example**: total variation denoising for white Gaussian noise



Original




Noisy Image



Denoised image

Related Works


- 2-Steps Method: denoising before registration



May **NOT** converge to **OPTIMAL** solution


Related Works

- 2-Steps Method: denoising before registration



May **NOT** converge to **OPTIMAL** solution


- Joint Optimization Method



Requires explicit objective function;
-> **LIMITED CHOICES** for denoisers


Proposed method: PnP-RR

- Basic Idea



Proposed method: PnP-RR


- Basic Idea



- Advantages

- ☐ TV ✓
- ☐ TGV ✓
- ☐ BM3D ✓
- ☐ Neural Network ✓

Flexible to
CHOOSE DENOISER



Better
PERFORMANCE



Simple to
IMPLEMENT



Easy to
TUNE

Proposed method: PnP-RR

- Derivation
 - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

Proposed method: PnP-RR

- Derivation
 - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

- **SPLIT** Formulated as proximal algorithm

$$\operatorname{argmin}_{\phi} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) = \text{register}_{\sigma}(S, \tilde{T}^k)$$

$$\operatorname{argmin}_{\tilde{T}} \frac{1}{2} \|\tilde{T} - Z\|_{L2}^2 + \tau \mathcal{R}_{\text{denoising}}(\tilde{T}) = \text{denoise}_{\tau}(\tilde{T} | S \circ \phi^{-1}) \quad \text{where}$$

$$Z = \frac{\lambda_2 T + (1/\sigma^2)(S \circ \phi^{-1})}{\lambda_2 + (1/\sigma^2)}$$
$$\tau = \frac{\lambda_1}{2(\lambda_2 + (1/\sigma^2))}$$

Proposed method: PnP-RR

- Derivation
 - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

- **SPLIT** Formulated as proximal algorithm

$$\operatorname{argmin}_{\phi} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) = \text{register}_{\sigma}(S, \tilde{T}^k)$$

$$\operatorname{argmin}_{\tilde{T}} \frac{1}{2} \|\tilde{T} - Z\|_{L2}^2 + \tau \mathcal{R}_{\text{denoising}}(\tilde{T}) = \text{denoise}_{\tau}(\tilde{T} | S \circ \phi^{-1}) \quad \text{where}$$

$$Z = \frac{\lambda_2 T + (1/\sigma^2)(S \circ \phi^{-1})}{\lambda_2 + (1/\sigma^2)}$$

$$\tau = \frac{\lambda_1}{2(\lambda_2 + (1/\sigma^2))}$$

- **REPLACE** Formulated as PnP algorithm

Replace with
arbitrary denoiser

$$\text{register}_{\sigma}(S, \tilde{T}^k)$$

$$\text{denoise}'_{\tau}(Z)$$

Proposed method: PnP-RR

- Derivation
 - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

- **SPLIT** Formulated as proximal algorithm

$$\operatorname{argmin}_{\phi} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) = \text{register}_{\sigma}(S, \tilde{T}^k)$$

$$\operatorname{argmin}_{\tilde{T}} \frac{1}{2} \|\tilde{T} - Z\|_{L2}^2 + \tau \mathcal{R}_{\text{denoising}}(\tilde{T}) = \text{denoise}_{\tau}(\tilde{T} | S \circ \phi^{-1})$$

where

$$Z = \frac{\lambda_2 T + (1/\sigma^2)(S \circ \phi^{-1})}{\lambda_2 + (1/\sigma^2)}$$

$$\tau = \frac{\lambda_1}{2(\lambda_2 + (1/\sigma^2))}$$

- **REPLACE** Formulated as PnP algorithm

Replace with
arbitrary denoiser

$$\text{register}_{\sigma}(S, \tilde{T}^k)$$


$$\text{denoise}'_{\tau}(Z)$$

Specifying an image prior


Experiments

- Data

- 2D synthetic data





Source S




Target T

- Real 3D DW-MRI data

Source S



Target T



- Algorithm Setting

- Registration algorithm
 - Fourier-approximated Lie Algebras for Shooting (FLASH)^[1]
- Denoising algorithm
 - Total variation (TV)
 - Total generalized variation (TGV)
 - Block-matching and 3D filtering (BM3D)


[1] Zhang, M., Liao, R., Dalca, A.V., Turk, E.A., Luo, J., Grant, P.E., Golland, P.: Frequency diffeomorphisms for efficient image registration. In: International conference on information processing in medical imaging. pp. 559–570. Springer (2017)

Experiments


- Result

- 2D synthetic data – Visual effect

Source
and
Target




Result
(deformed
source)




Experiments

- Result
 - 2D synthetic data – Quantitative performance



Experiments


- Data
 - Real 3D DW-MRI data



All DW-MRIs are of dimension $128 \times 128 \times 50$ and underwent bias field correction, co-registration with affine transformations and intensity normalization


Experiments

- Data
 - Real 3D DW-MRI data




All DW-MRIs are of dimension $128 \times 128 \times 50$ and underwent bias field correction, co-registration with affine transformations and intensity normalization


- Result




Source




Target




FLASH



Ours (TV)



Ours (TGV)



Ours (BM3D)

Discussion

- Performance
 - Data
 - Advanced methods
- Convergence
- Time

Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images

Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task

Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task
- What's more, our model benefits from its easiness to implement, robustness to parameter tuning and better performance

Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task
- What's more, our model benefits from its easiness to implement, robustness to parameter tuning and better performance
- Future research will involve collecting more dataset on placental images and exploring other cutting-edge denoisers, such as deep learning-based approaches.

Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task
- What's more, our model benefits from its easiness to implement, robustness to parameter tuning and better performance
- Future research will involve collecting more dataset on placental images and exploring other cutting-edge denoisers, such as deep learning-based approaches.
- Questions?

Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang