



Paper



Slides

# Plug-and-Play Priors for Reconstruction-based Placental Image Registration (PnP-RR)

Jiarui Xing<sup>1</sup>, Ulugbek Kamilov<sup>2,3</sup>,  
Wenjie Wu<sup>4,5</sup>, Yong Wang<sup>5</sup>,  
and Miaomiao Zhang<sup>1,6</sup>



<sup>1</sup> Electrical and Computer Engineering, University of Virginia, Charlottesville, USA

<sup>2</sup> Computer Science and Engineering, Washington University in St. Louis, USA

<sup>3</sup> Electrical and Systems Engineering, Washington University in St. Louis, USA

<sup>4</sup> Biomedical Engineering, Washington University in St. Louis, USA.

<sup>5</sup> Obstetrics and Gynecology, Washington University in St. Louis, USA.

<sup>6</sup> Computer Science, University of Virginia, Charlottesville, USA



Paper



Slides

# Brief Intro

- We proposed **plug-and-play reconstruction-registration method (PnP-RR)**, which
  - 1) is a deformable image registration framework for noise-corrupted images
  - 2) can be used on registering placental diffusion-weighted MR images that contains noise



Paper



Slides

# Brief Intro


- We proposed plug-and-play reconstruction-registration method (PnP-RR), which
  - 1) is a deformable image registration framework for noise-corrupted images
  - 2) can be used on registering placental diffusion-weighted MR images that contains noise

# Contents

1. Background
  - 1) What is image registration and why we need it
  - 2) Why there is noise in the images and the basic idea to deal with it.
2. Related works and their weakness
3. Proposed method: PnP-RR
4. Experiments and results
5. Discussion and conclusion

# Background


- Placenta and DW-MRI
  - **Diffusion-weighted MRI (DW-MRI)** for placental health monitoring



# Background

- Placenta and DW-MRI


- Diffusion-weighted MRI (DW-MRI) for placental health monitor
- Collect **several placental DW-MR images** with **different parameters (b-values)**, then **track** the appearance changes



# Background

- Placenta and DW-MRI


- Diffusion-weighted MRI (DW-MRI) for placental health monitor
- Collect several placental DW-MR images with different parameters (b-values); then track the appearance changes
- **Deformation** among images due to maternal breathing and fetal movements **makes tracking hard**



# Background


- Placenta and DW-MRI

- Diffusion-weighted MRI (DW-MRI) for placental health monitor
- Collect several placental DW-MR images with different parameters (b-values); then track the appearance changes
- Deformation among images due to maternal breathing and fetal movements makes tracking hard
- Need **Image registration** to **find and cancel the deformation**



# Background

- Image Registration
  - **Task: find the deformation  $\phi$**  between a source Image  $S$  and a target image  $T$






# Background


- Image Registration

- Task: find the deformation  $\phi$  between a source Image  $S$  and a target image  $T$
- Current mainstream: **optimization-based methods**
  - take the deformation that minimize an energy function












# Background

- B-value and noise
  - Higher **b-value**, stronger **noise**




# Background

- B-value and noise
  - DW-MRI images with different b-values




# Background

- B-value and noise
  - Higher b-value, stronger noise
  - Ordinary registration methods: fail on severely noise-corrupted images



# Background

- B-value and noise
  - Higher b-value, stronger noise
  - Ordinary registration methods: fail on severely noise-corrupted images
  - A noise-robust image registration methods is needed



## Related Works

- Basic idea: denoising + registration
  - Find a method to **integrate** image registration with **denoising**

# Related Works

- Basic idea: denoising + registration
  - Find a method to integrate image registration with denoising
  - Denoising **example**: TV denoising for white Gaussian noise



Original




Noisy Image



Denoised image


## Related Works

- 2-Steps Method: denoising before registration



May **NOT** converge to **OPTIMAL** solution

- Joint Optimization Method




Requires explicit objective function;  
-> **LIMITED CHOICES** for denoisers

$$\operatorname{argmin}_{\phi, T} \frac{1}{\sigma^2} \operatorname{dist}(S \circ \phi^{-1}, T) + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 R_{\text{denoising}}(\tilde{T}) + \lambda_2 \operatorname{dist}(T, \tilde{T})$$




# Proposed method: PnP-RR

- Basic Idea



# Proposed method: PnP-RR


- Basic Idea



- Advantages

- ☐ TV ✓
- ☐ TGV ✓
- ☐ BM3D ✓
- ☐ Neural Network ✓

Flexible to  
CHOOSE DENOISER



Better  
PERFORMANCE



Simple to  
IMPLEMENT



Easy to  
TUNE

# Proposed method: PnP-RR

- Derivation
  - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

# Proposed method: PnP-RR

- Derivation
  - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

- **SPLIT** Formulated as proximal algorithm

$$\begin{aligned} \operatorname{argmin}_{\tilde{T}} \frac{1}{2} \|\tilde{T} - Z\|_{L2}^2 + \tau \mathcal{R}_{\text{denoising}}(\tilde{T}) &= \text{denoise}_{\sigma}(\tilde{T} | S \circ \phi^{-1}) \quad \text{where} \quad Z = \frac{\lambda_2 T + (1/\sigma^2)(S \circ \phi^{-1})}{\lambda_2 + (1/\sigma^2)} \\ \operatorname{argmin}_{\phi} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) &= \text{register}_{\sigma}(S, \tilde{T}^k) \quad \tau = \frac{\lambda_1}{2(\lambda_2 + (1/\sigma^2))} \end{aligned}$$

# Proposed method: PnP-RR

- Derivation
  - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

- **SPLIT** Formulated as proximal algorithm

$$\begin{aligned} \operatorname{argmin}_{\tilde{T}} \frac{1}{2} \|\tilde{T} - Z\|_{L2}^2 + \tau \mathcal{R}_{\text{denoising}}(\tilde{T}) &= \text{denoise}_{\sigma}(\tilde{T} | S \circ \phi^{-1}) & \text{where} \\ \operatorname{argmin}_{\phi} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) &= \text{register}_{\sigma}(S, \tilde{T}^k) & Z = \frac{\lambda_2 T + (1/\sigma^2)(S \circ \phi^{-1})}{\lambda_2 + (1/\sigma^2)} \\ & & \tau = \frac{\lambda_1}{2(\lambda_2 + (1/\sigma^2))} \end{aligned}$$

- **REPLACE** Formulated as PnP algorithm

$\text{denoise}'_{\tau}(Z)$

$\text{register}_{\sigma}(S, \tilde{T}^k)$

# Proposed method: PnP-RR

- Derivation
  - **JOINT** denoising-registration objective function

$$\operatorname{argmin}_{\phi, \tilde{T}} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) + \lambda_1 \mathcal{R}_{\text{denoising}}(\tilde{T}) + \lambda_2 \|T - \tilde{T}\|_{L2}^2$$

- **SPLIT** Formulated as proximal algorithm

$$\begin{aligned} \operatorname{argmin}_{\tilde{T}} \frac{1}{2} \|\tilde{T} - Z\|_{L2}^2 + \tau \mathcal{R}_{\text{denoising}}(\tilde{T}) &= \text{denoise}_{\sigma}(\tilde{T} | S \circ \phi^{-1}) & \text{where} \\ \operatorname{argmin}_{\phi} \frac{1}{\sigma^2} \|S \circ \phi^{-1} - \tilde{T}\|_{L2}^2 + \mathcal{R}_{\text{reg}}(\phi) &= \text{register}_{\sigma}(S, \tilde{T}^k) & Z = \frac{\lambda_2 T + (1/\sigma^2)(S \circ \phi^{-1})}{\lambda_2 + (1/\sigma^2)} \\ & & \tau = \frac{\lambda_1}{2(\lambda_2 + (1/\sigma^2))} \end{aligned}$$

- **REPLACE** Formulated as PnP algorithm

$\text{denoise}'_{\tau}(Z)$


$\text{register}_{\sigma}(S, \tilde{T}^k)$

Specifying an image prior


# Experiments

- Data

- 2D synthetic data



- Real 3D DW-MRI data



- Algorithm Setting

- Registration algorithm

- Fourier-approximated Lie Algebras for Shooting (FLASH)<sup>[1]</sup>

- Denoising algorithm


- Total variation (TV)
    - Total generalized variation (TGV)
    - Block-matching and 3D filtering (BM3D)

[1] Zhang, M., Liao, R., Dalca, A.V., Turk, E.A., Luo, J., Grant, P.E., Golland, P.: Frequency diffeomorphisms for efficient image registration. In: International conference on information processing in medical imaging. pp. 559–570. Springer (2017)

# Experiments

- Result


- 2D synthetic data – Visual effect






# Experiments

- Result
  - 2D synthetic data – Quantitative performance



# Experiments


- Data
  - Real 3D DW-MRI data



All DW-MRIs are of dimension  $128 \times 128 \times 50$  and underwent bias field correction, co-registration with affine transformations and intensity normalization


# Experiments

- Data
  - Real 3D DW-MRI data




All DW-MRIs are of dimension  $128 \times 128 \times 50$  and underwent bias field correction, co-registration with affine transformations and intensity normalization


- Result




Source




Target




FLASH



Ours (TV)



Ours (TGV)



Ours (BM3D)

# Discussion

- Performance
  - Data
  - Advanced methods
- Convergence
- Time

## Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images

## Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

## Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task

## Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

## Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task
- What's more, our model benefits from its easiness to implement, robustness to parameter tuning and better performance

## Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang

## Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task
- What's more, our model benefits from its easiness to implement, robustness to parameter tuning and better performance
- Future research will involve collecting more dataset on placental images and exploring other cutting-edge denoisers, such as deep learning-based approaches.

## Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang



# Conclusion

- We presented a novel reconstruction-based registration algorithm, named PnP-RR, for severely noise-corrupted images
- In contrast to previous approaches, our model has the flexibility to allow arbitrary denoising algorithm integrated with the registration task
- What's more, our model benefits from its easiness to implement, robustness to parameter tuning and better performance
- Future research will involve collecting more dataset on placental images and exploring other cutting-edge denoisers, such as deep learning-based approaches.
- Questions?

# Our Team



Jiarui Xing



Ulugbek Kamilov



Wenjie Wu



Yong Wang



Miaomiao Zhang