Claude Certified Architect, Professional. Practice test (original items)

Key fact Decision rule Exam tip Trap

126 items, 42 units. Read each stem and pick the answer that meets every stated constraint. Each item states how many answers to select. The items are original. They do not copy any exam item.

F1 Architecture and business foundations

1. A team plans a new workload on Claude Haiku 5.5. Each request has input tokens and output tokens, and each token class has its own rate. The team needs a monthly figure before launch and must build no new service. Which approach meets the constraint?

Select one answer.

A. Multiply the input tokens by the input rate and ignore the output tokens.

B. Build a usage service that writes each request and its usage to a database.

C. Multiply each token class by its own rate, add the classes, then scale by request volume and days.

D. Enable a workspace spend limit and report the limit as the monthly figure.

2. A finance owner wants a hard monthly stop on the spend of one team. The team's API keys currently sit in the Default Workspace. Which change meets the constraint?

Select one answer.

A. Set a spend limit on the Default Workspace that holds the team's keys.

B. Raise the rate limits for the team's model, which also caps its monthly spend.

C. Turn on usage reports, which stop requests when spend passes the budget.

D. Create a workspace for the team, create new keys there, and set its spend limit.

3. A team runs two Claude Haiku 5.5 workloads. Nightly reports can wait up to 24 hours, and a live chat feature needs answers at once. The team must forecast each workload at its correct rate. Which two statements meet the constraint?

Select two answers.

A. Price both workloads at the batch rate, which keeps one simple forecast.

B. Price the nightly reports at the batch rate, which is 50 percent below the base price.

C. Price the live chat at the cache hit rate, because chat prompts repeat.

D. Price the live chat at the base input and output rates per million tokens.

F2 LLM foundations

4. A team must answer questions about one 600,000-token report in a single request. The team uses Claude Opus 5.5 and expects an answer of about 8,000 tokens. Which design meets the constraint?

Select one answer.

A. Split the report into chunks and send one request for each chunk.

B. Send the full report in one request and set max_tokens to 8,000.

C. Send the full report in one request with server-side compaction enabled on every turn.

D. Set max_tokens to 1,000,000 so the window holds the full report.

5. A team deploys Claude Haiku 5.5 on Claude Platform on AWS. The application must send the model ID that this platform uses. Which choice meets the constraint?

Select one answer.

A. The ID claude-haiku-5-5, the same ID that the Claude API uses.

B. A custom alias that a config service resolves to a model ID on each request.

C. The Foundry deployment name, which this platform uses in place of a model ID.

D. The Bedrock-style ID anthropic.claude-haiku-5-5 in the model field.

6. A support app lets Claude look up order status through a tool. The app must run each lookup in its own code behind its permission checks. Which two options meet the constraint?

Select two answers.

A. Return each result as a tool_result block with the next request.

B. Let the model call the order API directly with its own network access.

C. Set stop_reason to tool_result so the loop continues.

D. Repeat the request while stop_reason is tool_use, and exit on end_turn.

F3 Software and distributed systems

7. A batch job receives HTTP 429 with a retry-after header of 30 seconds. The request is valid. The job must honor the server wait time and send the same request. Which action meets the constraint?

Select one answer.

A. Resend the same request at once in a loop with no delay.

B. Ask the model in the prompt to wait 30 seconds and send the request again.

C. Move the job to a new queue service with priority lanes before each retry.

D. Wait 30 seconds, then resend the same request.

8. A report tool sends a Messages request without streaming. Each report can run for 15 minutes, and the user reads the text as it arrives. Which change meets the constraint?

Select one answer.

A. Stream the Messages response and read each event as it arrives.

B. Create a Message Batch for each report and poll until processing ends.

C. Keep the request without streaming, and write the full response to a database table when it ends.

D. Set the client timeout to 24 hours, because idle connections never drop.

9. A chat app streams Claude Opus 5.5 responses to users. Some streams end with an error event after partial text. The app must not show partial text as a final answer. Which two actions meet the constraint?

Select two answers.

A. Treat the stream as complete once the HTTP status is 200.

B. Handle error events in the same loop that handles content events.

C. Show streamed text as a draft until the final message arrives.

D. Set a resume flag on the Messages request to continue a cut stream.

F4 Security and identity

10. A CI pipeline calls the Claude API for nightly evals. The CI platform issues a signed identity token for each job. The constraint: no static API key may be stored in CI. Which design meets the constraint?

Select one answer.

A. Store a workspace API key in the CI secrets manager with a 30-day expiry.

B. Build a token broker that holds the key in a vault and issues short tokens to each job.

C. Register the CI identity provider as a federation issuer and create a federation rule for the pipeline.

D. Use a Bedrock short-term bearer token, which lasts up to 12 hours, for the Claude API calls.

11. A nightly job reads usage by workspace and also sends Messages requests for the product. The constraint: each call must use the key type that the API accepts for it. Which key plan meets the constraint?

Select one answer.

A. Use one workspace API key for both the usage reads and the Messages requests.

B. Use an Admin API key for the usage reads and a workspace API key for the Messages requests.

C. Create a separate organization with its own Admin API key, and a second key for requests.

D. Use the Default Workspace key for the usage reads, because it is an Admin API key.

12. A health tech team sends regulated prompts through the Messages API. The contract forbids saving prompts and responses at rest. Which two actions meet the constraint?

Select two answers.

A. Ask the account team to enable ZDR for the organization.

B. Keep the regulated prompts in the Console playground, since ZDR covers the Console.

C. Turn on platform activity logs, which keep prompts out of storage at rest.

D. Check that each feature in use is eligible for zero data retention before launch.

D1.1 Business problem to Claude solution

13. A claims team extracts fixed fields from forms that share one layout. The team must cut model cost and return the same output for the same input. Which design meets the constraint?

Select one answer.

A. Read the fixed fields with code rules and skip the model call.

B. Send each form to Claude Haiku 5.5 at temperature 0, which returns the same output for the same input.

C. Send each form to Claude Opus 5.5 for field extraction, since the largest tier is the most accurate.

D. Send each form to Claude Haiku 5.5, where cache hits make repeated field reads free.

14. A product owner wants summaries that read well. The team must decide whether a model change can ship, and the decision needs a result that passes or fails. Which success criterion meets the constraint?

Select one answer.

A. Summaries read well to the support team.

B. A rating from the model itself looks like a metric, so the team ships when the rating is high.

C. Summaries score at least 4 out of 5 on a rubric for a fixed test set, signed by the support lead.

D. Summaries score well on a rubric, reviewed live on a dashboard after release.

15. A team scores 50,000 nightly support tickets for a report due next morning. Live chat answers must arrive within seconds. The team must keep token cost low for the nightly work. Which two options meet the constraint?

Select two answers.

A. Send the live chat through the Message Batches API to lower its token cost.

B. Send the nightly tickets through the Message Batches API at the batch rate.

C. Read each nightly result as the model writes it, before the batch ends.

D. Keep live chat on the synchronous Messages API for answers at once.

D1.2 End-to-end architecture

16. A support chatbot answers each message on its own, so follow-up answers ignore earlier turns. The model must stay the same. Which change meets the constraint?

Select one answer.

A. Assume the Messages API keeps earlier turns and reuses them on each call.

B. Switch to a larger model tier, which keeps earlier turns in memory.

C. Store turns in a graph database with embeddings, and send only the newest message with each call.

D. Store the conversation history in the app and send the full history with each request.

17. A benefits app sends a claim draft to a claims system that needs a fixed object shape. Each claim value must match the source record. The check must run in code and add no model call. Which design meets the constraint?

Select one answer.

A. Ask the model in the prompt to check its own draft before it returns.

B. Request structured outputs, then compare each claim with the source record in code.

C. Enable strict tool use so the claim values match the source records.

D. Request structured outputs, then send each draft back to the model to compare with the source record.

18. A pipeline returns wrong totals for some reports. No log shows which stage produces the wrong value. The team must find the stage that breaks before it changes the model. Which two actions meet the constraint?

Select two answers.

A. Log the stage name and the token counts for each model call.

B. Switch to a larger model tier and compare the totals on the next run.

C. Log each stop reason with a count for each request.

D. Enable prompt caching, which records the stage that produced each wrong total.

D1.3 Architectural pattern selection

19. A finance app reads one invoice, classifies it, and posts one record. The steps are fixed, and one model judgment is needed for the class. The app must keep control of the write. Which pattern meets the constraint?

Select one answer.

A. Run an agent loop with a session budget, and let the agent post each record through the MCP connector.

B. Send the invoice to Claude with network access, and let the model post the record.

C. Run the fixed steps in app code, with one model call for the classification, then post in app code.

D. Use a server-executed tool to post the record, so the app runs no code.

20. A research job searches the web, and each result decides the next search. The steps are unknown until the run starts. The team must stop spend at a fixed cap for each session. Which pattern meets the constraint?

Select one answer.

A. Hard-code the search steps in code, with one model call for each step.

B. Run an agent with six subagents and a merge step, with no session budget.

C. Set effort to low, which stops new model requests at the cap.

D. Run an agent loop with a session budget that pauses the session at the cap.

21. A checker reads one file, runs one fixed test command, and writes a report. The steps are known, and the app must keep the order of the steps. Which two options meet the constraint?

Select two answers.

A. Call each step from application code in a fixed order, with a model call only for the report text.

B. Let the model choose the next step from a tool list after each result.

C. Run each step from application code, and check each result before the next step starts.

D. Enable a server-executed web search tool to run the test command on your machine.

D1.4 Multi-agent orchestration

22. A lead agent reviews three separate code areas. Each area needs its own system prompt and tools. The team needs one merged report that one agent owns. Which design meets the constraint?

Select one answer.

A. The lead agent delegates each area to a subagent with its own prompt and tools, then merges the subagent reports.

B. Three peer agents write separate reports to a shared folder, and the user merges them by hand.

C. The subagents share one conversation history, so the lead reads every turn of each subagent.

D. One agent reviews all three areas with one system prompt and one tool set.

23. A team must review 900 repositories in parallel and show progress while the work runs. The lead must not send follow-up messages to each worker during the run. Which design meets the constraint?

Select one answer.

A. Chat with each subagent in turn, and send follow-up messages until each one finishes.

B. Start one workflow run that reads the repositories in parallel, with one session budget for the whole session.

C. Start a workflow run for each repository, each with a session budget of its own.

D. Start one workflow run, and have the lead send each worker a follow-up message about its progress.

24. Three steps edit one shared report. Each step needs the result of the step before it. The team wants one coherent report. Which two options meet the constraint?

Select two answers.

A. Run the three steps as parallel subagents, each with the full report in its prompt.

B. Keep the three steps in one agent, so each step sees the earlier result.

C. Enable the shared sandbox so each subagent sees the earlier conversation history.

D. Run the steps in order in one thread, and check each step result before the next one starts.

D1.5 Task decomposition

25. A team must score 150,000 document requests overnight with batch pricing. No request needs an answer at once, and each request is under 1 KB. Each batch must stay within the documented limits. Which plan meets the constraint?

Select one answer.

A. Send all 150,000 requests in one batch, since a batch can hold them all.

B. Send the 150,000 requests one at a time through the synchronous Messages API overnight.

C. Split the job into two batches, each under 100,000 requests, and collect both result sets.

D. Set the batch expiry to 29 days so all 150,000 requests finish in time.

26. A contract pipeline extracts party names first, then computes the fee from those names. A wrong name in step one would change the fee in step two. The team must stop a wrong name before step two runs. Which design meets the constraint?

Select one answer.

A. Run the name step and the fee step in parallel, so both finish sooner.

B. Check the party names in code after the fee step, and route each fee to a reviewer.

C. Turn on compaction, which removes wrong party names from earlier turns.

D. Check the party names in code before the fee step, and stop the chain at a failed check.

27. A team has 80,000 review texts for overnight scoring. A live widget scores one text while a user types. The team must keep each path on the right API. Which two options meet the constraint?

Select two answers.

A. Send the live widget requests through a batch, so each score costs less.

B. Split the overnight texts into batches of 256 requests, since a batch holds 256 requests.

C. Send the overnight texts as one Message Batch, since the batch holds up to 100,000 requests.

D. Send the live widget requests through the synchronous Messages API, one call per text.

D1.6 Business-value alignment

28. A summary request on Claude Haiku 5.5 uses 3,000 input tokens and 800 output tokens. The prompt is under 100,000 tokens. The team needs the cost per request from published prices. Which method meets the constraint?

Select one answer.

A. Multiply all 3,800 tokens by the input price per million tokens.

B. Multiply each token count by its own rate, divide by one million, and add the two results.

C. Multiply each token count by its own rate, then write each result to a cost ledger with a dashboard.

D. Price all input tokens at the cache hit rate, because the prompt is reused.

29. A team wants to book savings from a cheaper model tier. The cheaper tier passes 91 percent of the eval set, and the agreed threshold is 95 percent. The constraint: keep a value claim only while the quality threshold holds. Which action meets the constraint?

Select one answer.

A. Book the savings now, and tune the threshold after the next quarter.

B. Set a session budget on the cheaper tier, which proves the savings hold.

C. Hold the savings claim until the cheaper tier passes the threshold on the same eval set.

D. Book the savings now, and rebuild the eval set with 10,000 cases before any re-test.

30. A long agent run follows fixed steps, and no user waits for it. Finance caps the spend for the run. The team needs a budget that stops new requests at the cap and shows spend during the run. Which two options meet the constraint?

Select two answers.

A. Set a session budget when the session is created, so new requests stop at the cap.

B. Set the budget after the bill arrives, so the total can be corrected.

C. Set a workspace spend limit of the same amount on the Default Workspace.

D. Read usage.list_cost on the session object, which holds the running list cost.

D2.1 Model selection and tier trade-offs

31. A ticket router classifies five million tickets each month. Claude Haiku 5.5 clears the measured quality floor on the team's test set. The constraint: use the lowest-cost tier that clears the floor. Which choice meets the constraint?

Select one answer.

A. Route every ticket to claude-haiku-5-5, the lowest tier that clears the floor.

B. Route every ticket to Claude Haiku 4.5, which costs less per million tokens than Haiku 5.5.

C. Route every ticket to Claude Fable 5.1, the top tier, for the highest safety margin.

D. Set effort to max on Claude Haiku 5.5, which moves its price to the Sonnet tier.

32. A code assistant runs on Claude Haiku 5.5. It misses the quality floor on about 8 percent of requests at the default effort. The team must keep the same model and raise quality with the least change. Which change meets the constraint?

Select one answer.

A. Move all traffic to Claude Fable 5.1, which clears the floor on every request.

B. Raise effort to high only for the requests that miss the floor, and keep the medium default for the rest.

C. Set a thinking budget_tokens value of 20,000 on Haiku 5.5 to raise thinking depth.

D. Set effort to xhigh on every request and rebuild the eval set with extra checks.

33. A team runs one extraction task on Claude Haiku 5.5. Most requests clear the quality floor at the default effort. The constraint: keep cost and latency low while the quality floor holds. Which two options meet the constraint?

Select two answers.

A. Send all traffic to Claude Opus 5.5, so every request clears the floor.

B. Keep Haiku 5.5 for all traffic, and set low effort for simple requests.

C. Set a thinking budget_tokens value on Haiku 5.5 to cut output tokens.

D. Escalate only the requests that miss the floor to Claude Sonnet 5.5.

D2.2 System prompts, templates, and guardrails

34. A support assistant must never show one customer's order data to another customer. The rule must hold for every user input. Which change meets the constraint?

Select one answer.

A. Add a stricter rule to the system prompt that forbids cross-customer data.

B. Filter order records in code by the signed-in customer ID before each call.

C. Send all order records, and ask the model to show only the signed-in customer's records.

D. Set an output schema that lists only the customer ID field.

35. A billing service parses each model reply into database fields. The team needs one fixed JSON shape, with no retry loop for shape errors. Which change meets the constraint?

Select one answer.

A. Ask in the prompt for JSON only, then parse the text with a pattern match.

B. Let the model write prose, then split each paragraph into fields in code.

C. Send a JSON schema in output_config format, then check the stop reason before parsing.

D. Send a JSON schema in the prompt text, then retry the call when the shape fails to parse.

36. A shared assistant sends one system prompt with every request, and the cache must keep its stable text. The team must also tie each saved answer to one prompt version. Which two changes meet both constraints?

Select two answers.

A. Insert the tenant name into the system prompt on each request.

B. Keep the stable instructions in one system block, stored in version control.

C. Turn on automatic prompt version history in the Claude Console.

D. Log the prompt version with each saved answer.

D2.3 Prompt techniques

37. A ticket classifier misses its accuracy bar on new labels. The team has no budget for model training, and it wants the smallest prompt change first. Which change should the team try first?

Select one answer.

A. Train a custom classifier on the full ticket history before any prompt change.

B. Enable citations, so each label links to its source text.

C. Add three to five varied labeled examples in example tags, then run the evals.

D. Add the examples, and also turn on adaptive thinking for every call.

38. A migration moves an extraction service to a Claude 4.6 model. Each request ends with a prefilled assistant turn, and the API returns a 400 error. The fix must keep the output format and run on Claude 4.6.

Select one answer.

A. Turn thinking off, so the prefilled assistant turn is accepted.

B. Remove the prefill, and state the output format in the system prompt.

C. Keep the prefill, and add structured outputs to the same request.

D. Keep the prefill, and route these calls to an earlier model.

39. A routing service needs one label from a fixed enum for each ticket. The call targets Claude Opus 5.5, which rejects forced tool use. Which two changes meet the constraints?

Select two answers.

A. Use tool_choice auto with a strict tool that has an enum field.

B. Set tool_choice to one named tool, so the model must call it.

C. Use structured outputs with an enum in the schema.

D. Add a prompt caching breakpoint to the label instructions.

D2.4 Context and token management

40. A chat service sends long histories. Each turn must fit an input budget that the app sets before the call, and the model must stay the same. Which change meets both constraints?

Select one answer.

A. Set effort to low, so the input token count falls.

B. Skip counting, and rely on the usage fields after each response.

C. Count tokens before each send, and switch to a larger-window model when the count is high.

D. Count tokens with the target model ID, and trim history that exceeds the budget.

41. An agent task fills its context with old tool results. The team wants no extra summarization call, and recent work must stay in context. Which change meets both constraints?

Select one answer.

A. Add the clear_tool_uses strategy with the context-management beta header.

B. Start a separate summary request on every turn, then send that summary.

C. Clear all tool results on every turn, including the most recent ones.

D. Use the token counting endpoint to delete old turns from the history.

42. A long agent task loses an early constraint after a default summary. Recent turns must stay word for word after the summary. Which two changes meet both constraints?

Select two answers.

A. Let the default summary run, and trust it to keep every constraint.

B. Write a custom summarization prompt that keeps the early constraint.

C. Set a keep_recent_turns parameter to five in the compaction request.

D. Pick a cut point, and send the later turns after the summary block.

D2.5 Reuse and prompt caching

43. A research app sends the same 30,000-token reference set with every question. Answers must not change, and the input cost per call must drop. Which change meets both constraints?

Select one answer.

A. Replace the reference set with a short summary, which shrinks each call.

B. Place the reference set first, and mark its last stable block with cache_control.

C. Place each new question first, then the reference set, and mark the last block with cache_control.

D. Send the reference set through the token counting endpoint before each call.

44. A multi-turn assistant adds two blocks on each turn. The team wants one cache setting and no breakpoint edits. Which change meets both constraints?

Select one answer.

A. Add explicit cache_control to four blocks, and omit the top-level field.

B. Add a top-level cache_control field, and move an explicit breakpoint to the newest block on each turn.

C. Add a cache_mode parameter set to auto in the request body.

D. Add one top-level cache_control field to the request.

45. A batch job sends a tool list that never changes, then a weekly document. Calls arrive about every 30 minutes. The tool list must stay cached between calls, and the weekly document must not break that cache. Which two changes meet both constraints?

Select two answers.

A. Set ttl to 1h on the breakpoint after the tool list, before the document.

B. Place the weekly document first, then cache from its last block.

C. Keep the weekly document after the breakpoint, so its edits do not break the cache.

D. Set a cache TTL of 2h on the request, so the whole prompt stays cached.

D3.1 Tool capability scope

46. An invoice agent has 60 tools from several MCP servers. Most requests use three tools. The team must cut the tool schema tokens sent per call, and every tool must stay available.

Select one answer.

A. Remove 40 tools from the agent, so the list fits the prompt.

B. Set cache_control on every deferred tool, so their schemas stay cached.

C. Add tool search, defer the rarely used tools, and keep the three common tools non-deferred.

D. Add tool search, and set defer_loading to true on every tool, including the tool search tool.

47. Two lookup tools do the same job, and their descriptions are almost identical. The agent often picks the wrong one. The fix must remove the ambiguity from the tool list itself.

Select one answer.

A. Add a longer system prompt rule that names which lookup to use.

B. Merge the two lookups into one tool with an action parameter and a clear description.

C. Keep both lookups, and add a classifier model that routes each request first.

D. Set defer_loading to true on both lookup tools.

48. A finance agent runs a nightly report task in Claude Code. The task never calls a refund write tool, but a wrong refund fired last week. The team must block that tool and keep the report read tool.

Select two answers.

A. Add a deny rule for the refund write tool in the task's settings.

B. Keep the refund tool, and add audit logging of each call.

C. Turn on tool search, so the refund tool loads only when searched.

D. Remove the refund write tool from the task's tool list.

D3.2 Authentication and authorization in integrations

49. An internal assistant calls a remote MCP server. The server must record which employee asked for each action. Which change meets the constraint?

Select one answer.

A. Use one shared service key, and add the employee name to the prompt.

B. Send each user's OAuth token in authorization_token for that server.

C. Send one shared OAuth token for all users, and route all calls through a logging proxy.

D. Set the anthropic-workspace-id header to the employee's team workspace.

50. A workload runs on Claude Platform on AWS. The security team needs IAM to control each caller, and the workload has no user consent flow. Which change meets both constraints?

Select one answer.

A. Store a long-lived API key in the code, and skip IAM policies.

B. Add an OAuth consent screen for each user before each call.

C. Sign with SigV4 from one shared role for all callers, and log each request ID in a second store.

D. Enable outbound web identity federation, sign with SigV4, and scope IAM to the workspace ARN.

51. On the Claude API, two tenants must not share prompt caches or API keys. The team also wants a separate monthly spend limit for each tenant. Which two changes meet both constraints?

Select two answers.

A. Use one workspace for both tenants, and name each tenant in a header.

B. Rename the Default Workspace to the first tenant, then archive it later.

C. Create one workspace per tenant, and scope each tenant key to its workspace.

D. Set a monthly spend limit on each tenant workspace.

D3.3 Accuracy and latency trade-offs

52. Users must see the first words of a reply before the full answer is ready. The model and the answer quality must stay the same. Which change meets both constraints?

Select one answer.

A. Stream the response, so text appears as the tokens arrive.

B. Enable fast mode, which cuts the time to first token.

C. Send each request as a Message Batch, and read the results the next day.

D. Cache each full answer in a custom store, and show it only after the answer is complete.

53. An evaluation run has 50,000 prompts. Results can arrive within one day, and the run must cost less than standard calls. No user waits for these results.

Select one answer.

A. Send each prompt one at a time on the standard path, with high effort.

B. Buy a Priority Tier commitment, which gives half-price calls.

C. Submit one Message Batch, and also run the full set on the standard path.

D. Submit the prompts as one Message Batch, and read results after processing ends.

54. A classifier meets its accuracy floor at medium effort, but its latency target is tight. Many requests are simple, and a short answer is enough for them. Which two changes meet both constraints?

Select two answers.

A. Move all requests to a larger model at high effort.

B. Set effort lower for simple requests, and keep medium effort for the rest.

C. Enable fast mode on Claude Haiku 5.5, which cuts the first-token wait.

D. Ask for a shorter answer in the prompt when output length adds time.

D3.4 Observability at scale

55. An incident review must find which tool call sent a bad record. Prompt logs show the text but no tool hop. Prompt text must stay out of the trace data.

Select one answer.

A. Store full prompt content in the spans, so each hop shows its text.

B. Read the usage report by hour, which lists each tool call.

C. Emit one trace per run, with a span for each model and tool hop, in metadata only mode.

D. Emit one span per run with no child spans, in metadata only mode, and export it to two collectors.

56. Finance needs a monthly split of API spend by workspace, reconciled with billing. The figures must come from platform reports, not from app logs.

Select one answer.

A. Call the cost report with an Admin API key, grouped by workspace.

B. Call the cost report and the usage report hourly, both grouped by workspace.

C. Add up input tokens from each app response, then multiply by list prices.

D. Call the cost report with hourly buckets for a monthly split.

57. A security team audits developer tool use in Claude Code. The OTLP destination must stay fixed for every developer, and MCP tool arguments must appear in the audit trail. Which two changes meet both constraints?

Select two answers.

A. Pin the OTLP endpoint and credentials in managed settings.

B. Enable telemetry in each repository's project settings file.

C. Set OTEL_LOG_USER_PROMPTS to 1 to capture tool arguments.

D. Set OTEL_LOG_TOOL_DETAILS to 1 to capture MCP call arguments.

D3.5 The RAG pipeline

58. A support answer must name the source of each claim. The response must stay free text, with no JSON schema. Which change meets both constraints?

Select one answer.

A. Ask the model in the prompt to list sources after each claim.

B. Pass each chunk as a search result block with source and title, and enable citations.

C. Pass each chunk as search results with citations disabled, and add a reranker before the call.

D. Enable structured outputs with a source field for each claim.

59. A policy document has tables split across chunks, and answers cite the wrong row. Each citation must point to one table row.

Select one answer.

A. Keep sentence chunking, and switch to a larger generation model.

B. Send each table as a plain text document, and switch to the largest embedding model.

C. Build one custom content block per table row, sent as a custom content document.

D. Turn on contextual retrieval, so the table rows group automatically.

60. The right passage appears in the candidate list, but it ranks low. The answer model needs that passage among the top passages. Which two changes meet the ranking constraint?

Select two answers.

A. Switch to a larger generation model, with the same candidate list.

B. Add a reranker that reorders the candidate list for the query.

C. Set input_type to None on the query embedding, so ranking uses raw similarity.

D. Send only the top reranked passages to the answer model.

D3.6 Retrieval strategies

61. An app answers stock-count questions from an index that refreshes hourly. Users need the current count, and policy questions must stay on the index. Which change meets both constraints?

Select one answer.

A. Refresh the index every five minutes, and keep the snapshot as the only source.

B. Enable the SSE transport on the connector, so stock values stream in.

C. Route stock questions to a read tool on the inventory server, and keep policy questions on the index.

D. Route stock questions and policy questions to a read tool on the inventory server.

62. A query contains an error code, and users also ask about the same docs in plain words. A semantic index alone misses the exact code. The fix must find both the code and the paraphrased passages.

Select one answer.

A. Use a semantic index only, and raise the number of candidates it returns.

B. Store the codes as binary embeddings, which keeps exact matches.

C. Run two semantic matchers with different models, and merge both lists.

D. Run keyword and semantic matchers, then merge both candidate lists.

63. A chat app must answer with live order status from a remote server. The app must not run an MCP client in its code, and answers must not come from a stored snapshot. Which two changes meet both constraints?

Select two answers.

A. Define the server in mcp_servers, and reference it from one MCP toolset.

B. Copy the order status into the index every hour, and search that copy.

C. Send the request with the MCP connector beta header.

D. Read order status through MCP resources, which the connector loads.

D3.7 Integration mechanisms

64. One backend service calls an internal billing API from a single host. No other host needs these tools, and the team wants no extra protocol layer.

Select one answer.

A. Register the billing API as a stdio server in Claude Code for the backend.

B. Call the billing API directly from the backend code with its own client.

C. Wrap the billing API in an MCP server, and let the backend connect as its client.

D. Put a CLI wrapper around the API, and parse its text output in the backend.

65. Four hosts written in different languages need the same ticket lookup tools. The team wants one tool schema, and each host connects as a client.

Select one answer.

A. Write a separate client library for each host that calls the service.

B. Use the MCP connector with a stdio server on each host.

C. Build one MCP server that exposes the ticket tools, and let each host connect.

D. Build one MCP server with tools, resources, and prompts, and let each host connect.

66. A Claude Code team must block one claude.ai connector tool before Claude sees it. The same team must also add an internal service that runs over HTTP. Which two changes meet both constraints?

Select two answers.

A. Add the risky connector tool with an allow rule, so it runs without a prompt.

B. Add the internal service with claude mcp add and the http transport.

C. Set the idle timeout to zero, so the risky tool stays hidden.

D. Set the organization control for that connector tool to blocked.

D3.8 Progressive discovery and monolithic context

67. An agent loads 60 tools on every request, and most definitions go unused. The three most common tools must answer each turn without an extra search step. Which setup meets both constraints?

Select one answer.

A. Build a custom embedding index that ranks all 60 tools and injects the top five into each system prompt.

B. Add cache_control to each deferred tool, so the API keeps its schema warm between searches.

C. Set defer_loading to true on the 57 rare tools, keep the three common tools non-deferred, and add the tool search tool.

D. Set defer_loading to true on all 60 tools, so every request starts with a search step.

68. An SDK agent uses 12 MCP tools in a small context window. The team wants tool search to start only when definitions reach a set share of the window. Which setting meets the constraint?

Select one answer.

A. Set alwaysLoad to 10 percent, so each server activates tool search once its tools reach that share.

B. Set ENABLE_TOOL_SEARCH to auto, so tools load upfront until definitions reach 10 percent of the window.

C. Set ENABLE_TOOL_SEARCH to false, so every tool definition loads on every turn.

D. Write a ranking service that selects tool definitions before each SDK call, on top of the default settings.

69. A team writes a domain agent with 1,500 lines of guidance. Each request must carry only short metadata until a task needs the details. Which two designs meet this constraint?

Select two answers.

A. Keep the skill name and description in the system prompt, and read the reference files only when a task needs them.

B. Enable network access in the skill sandbox, so the model fetches reference pages from a URL on demand.

C. Paste all 1,500 lines into the system prompt, so the model never needs a second read.

D. Keep SKILL.md under 500 lines, and move detailed sections into separate files that each task reads when relevant.

D4.1 Evaluation metrics

70. A support bot team sees fluency rise 12 percent after a prompt change. Resolution rate stays flat. The release decision needs one primary metric with a threshold set before tuning starts.

Select one answer.

A. Set the threshold in the Console evaluation tool, which computes the primary metric for you.

B. Resolution rate on the held-out set, with a threshold and an owner set before the next run.

C. Fluency score as the primary metric, with no threshold, because the grader scores it automatically.

D. Fifteen dashboard metrics, each with its own threshold, reviewed before the primary metric is chosen.

71. A team moved to a cheaper model, and monthly spend fell. Completed tasks fell more. The team needs a daily report of value per task for each model version.

Select one answer.

A. Compare total monthly spend only, because finance reads the bill and the bill fell.

B. Read the Cost API in one-minute buckets for each task, since minute buckets show spend per task.

C. Build a warehouse pipeline that joins every token count with task outcomes in real time.

D. Daily spend divided by completed tasks gives value per task, so compare that value for each model and prompt version.

72. A dashboard must show cost and latency for a streaming chat feature. It must also show the quality threshold for the same release. Which two items meet these constraints?

Select two answers.

A. Read time to first token from the Usage API, which reports latency for each bucket.

B. Measure time to first token for streaming calls, and baseline latency for other calls.

C. Track 20 latency percentiles for every route, each with its own alert owner.

D. Show cost per completed task beside the quality threshold, with daily totals from the Usage and Cost API.

D4.2 Evaluation datasets and frameworks

73. An eval set of 500 clean prompts scores 96 percent. Production users paste long documents and send empty messages, and failures rise. The set must predict production at a low daily cost.

Select one answer.

A. Add production samples with long, empty, and irrelevant inputs, and grade the checkable cases with code.

B. Have three reviewers grade every case by hand before each daily run, to catch subtle errors.

C. Enable the Console evaluation tool to build the production sample, then score the sample with code.

D. Add a versioned set with a dashboard per case type, plus production samples that include edge cases.

74. A nightly run grades 30,000 outputs. Most outputs need an exact match on one field, and a few need a judgment about tone. The team must avoid human graders, and each grader must be reliable.

Select one answer.

A. Send all 30,000 outputs to an LLM grader without a reliability test, to keep the setup simple.

B. Add a second LLM grader that cross-checks each tone verdict before the run ends.

C. Grade exact-match outputs with code, and grade tone with an LLM grader after a reliability test.

D. Use a grader setting that caches each verdict, so repeated nightly runs skip the scoring step.

75. A team builds an eval set for a chat assistant. The set must match real traffic and cover unusual input. The team must not hand-grade every case. Which two steps meet these constraints?

Select two answers.

A. Use a built-in Console sampler that labels ambiguous cases automatically.

B. Sample recent production traffic, so the cases match the real task mix.

C. Rebuild the set every hour from the live traffic log, so it never ages.

D. Add empty, long, and irrelevant inputs as edge cases, with expected answers that code can check.

D4.3 A/B tests and iteration

76. A team ships a new prompt after one week of higher scores. The score moved 2 points, and the traffic mix changed that week. The team needs to measure the prompt effect on the same traffic and period.

Select one answer.

A. Check this week against last week on the primary metric, since the prompt went live on Monday.

B. Split traffic into a control arm and a candidate arm with a fixed assignment rule, then compare the primary metric.

C. Run a shadow copy for every user, plus a 90-day holdout, before any arm is compared.

D. Turn on the Usage API arm tag, so each arm reports its own spend automatically.

77. A candidate model clears the quality floor by 3 points. Its cost per completed task is 25 percent higher than the control. The change ships only when it clears the floor and holds or lowers cost per completed task. Which choice meets this rule?

Select one answer.

A. Ship the candidate, because a higher quality score means the team meets its target.

B. Apply the effort discount to the candidate, which lowers its per-token price for every task.

C. Add three more arms with new prompts, and decide only after all of them report, to find a cheaper candidate.

D. Keep the control, because the candidate raises cost per completed task.

78. A team runs checkable tasks on a model whose default effort is high. The team needs lower cost per completed task, and the pass rate must stay the same. Which two changes meet both constraints?

Select two answers.

A. Run the first pass at low effort, and re-run only the failed tasks at high effort.

B. Set a higher effort on every task, so each pass rate improves before the cost check.

C. Measure the low-effort pass on the eval set, and confirm the pass rate before the change ships.

D. Turn on a discount for failed tasks, so each re-run costs nothing.

D4.4 Diagnosis at the correct layer

79. Cache read tokens dropped to zero after a team edited the tool list in a shared template. The model stayed the same. The team must name the changed layer first, with the smallest fix.

Select one answer.

A. Raise the cache duration to one hour, so the prefix stays cached while the tool list changes.

B. Read cache_miss_reason in the response, and fix the earliest changed block first.

C. Rewrite the whole prompt template, then measure hit rates over a month of traffic.

D. Turn on the streaming cache trace in the Console, which lists each changed block after every response.

80. An assistant gives different figures for the same question across three runs. The model and the prompt did not change. The team needs a check that flags unsupported answers, with no new model.

Select one answer.

A. Move the assistant to a larger model tier, since a stronger model returns the same figure on each run.

B. Enable a consistency flag in the Messages API that blocks answers with a figure that varies.

C. Run the same prompt several times, and flag answers that disagree on a key figure.

D. Route each question through three model tiers, and vote on the answer from all three.

81. Cache reads fell after a prompt edit. Two later blocks also changed, so the first reason may hide the others. The team must find the fix and confirm it with cache evidence. Which two steps meet these constraints?

Select two answers.

A. Change the cache duration and the prompt wording in one release, to save a diagnosis round.

B. Fix the earliest divergence first, because later reasons can hide behind it.

C. Read cache_miss_reason from the usage export, which names each changed block.

D. Confirm the fix with the cache read token count on the next request.

D4.5 Optimization under quality floors

82. A nightly job scores 40,000 eval cases. No user waits for the result. The team wants the lowest token price, and every call that a user sees must stay synchronous.

Select one answer.

A. Stream the nightly job, so its first results arrive sooner at the same token price.

B. Move the nightly job to batch processing, and keep user-facing calls synchronous.

C. Raise the rate limit for the nightly job, so each call returns in one pass.

D. Build a custom queue service with retries, dashboards, and a priority lane for the nightly job.

83. A chat feature must meet a response time target. Easy and hard requests arrive on the same route. The quality floor is known for each request type. The team must cut cost only where the floor still holds.

Select one answer.

A. Route all traffic to the fastest tier at low effort, since it has the lowest latency for every request.

B. Train a learned router that scores each request, retrains weekly, and logs every routing decision.

C. Turn on the faster-mode flag for the stronger tier, which cuts latency and leaves the output as is.

D. Route easy request types to the faster tier at low effort, after each type clears the floor on the eval set.

84. An unattended grader run has 150,000 requests. No user waits for the results. The run must fit the batch limits, and the team must read every result within the result availability period. Which two actions meet these constraints?

Select two answers.

A. Split the 150,000 requests into at least two batches, each within 100,000 requests and 256 MB.

B. Set a priority option that returns the batch within five minutes, which the Batch API offers.

C. Read each batch result within 29 days of batch creation, while the results are still available.

D. Move the run to a dedicated workspace with its own rate limits, and add a second model for every row.

D4.6 Production monitoring

85. Monthly spend rose 30 percent while completed tasks stayed flat. The team needs an alert before the budget breaks. The alert must reflect the value of each task, and it needs a named owner.

Select one answer.

A. Alert on total token count per day, since token counts rise with spend.

B. Alert on 40 metrics, with latency, token counts, and per-user spend among them, each with its own owner.

C. Alert on cost per completed task, and name the owner who acts when the line breaks.

D. Set the Cost API to alert on one-minute buckets, so spend breaks show within a minute.

86. The data rules allow only metadata in the observability destination. A request failed across three services. The team uses the Claude API and needs the order and timing of each hop for that one request.

Select one answer.

A. Export full content for every request, then search the prompts for the failed call.

B. Read the per-hop trace for the failed request, with metadata-only export.

C. Build a custom span format and tracing service before the next incident.

D. Turn on the claude_code.session.count metric, which records the timing of each hop.

87. A team pinned a model ID. Live quality dropped after an infrastructure update, and no code changed. The team must find the cause with evidence before it changes the model. Which two actions meet this constraint?

Select two answers.

A. Freeze the infrastructure that serves the model ID, so no update can change observable behavior.

B. Compare live metrics with the baseline from before the update, and record the model ID with each metric.

C. Rewrite the prompt with a new template and retrain the grader before any metric comparison.

D. Check prompt and data changes from the same period before the team changes the model ID.

D5.1 Guardrails and safety controls

88. Users type free text into a support app that reaches the main model. The team needs a check before the main call. The check must return a parseable verdict that code can count.

Select one answer.

A. Add a stricter system prompt that tells the main model to refuse harmful messages, then send every message.

B. Screen each message with a lightweight model that returns a boolean verdict, and block a harmful verdict.

C. Screen each message with the main model at high effort, and store the full reasoning for each message.

D. Turn on the computer use classifiers for each message, since they scan text before the model reads it.

89. A Claude Code agent must never run the deploy script. The system prompt forbids it, but the agent still proposes the command. The team needs a rule that Claude Code enforces before the command runs.

Select one answer.

A. Add three more sentences to the system prompt that repeat the deploy ban, and ask the agent to confirm.

B. Move the deploy script into a separate container with its own network policy, outside the reach of the agent.

C. Set the sandbox allowed domains to exclude the deploy host, so the script cannot reach it.

D. Add a deny rule for the deploy command in the permission settings, which Claude Code checks before it runs.

90. An agent runs shell commands on a developer machine. Untrusted issue text can steer those commands. The shell must not reach unknown hosts. The Read tool must not open credential files. Which two settings meet both constraints?

Select two answers.

A. Run /sandbox to turn on the sandbox, and keep the allowed domain list empty until a task needs a host.

B. Add a sandbox denyRead entry for the credential files, so the Read tool cannot open them.

C. Run the agent in a separate virtual machine for each issue, with its own network and disk.

D. Add permission deny rules for the credential paths, so the Read tool cannot open those files.

D5.2 Risks and failure modes

91. A new agent loops overnight and drives API spend up. The team shares one organization across three projects. The team needs a monthly ceiling for each project and a stop for a single runaway loop.

Select one answer.

A. Set a monthly spend limit on each project workspace with alerts, and cap tool calls per run in code.

B. Raise the workspace rate limit, so the loop finishes its work within the same hour.

C. Set a spend limit on the Default Workspace that holds the project key.

D. Create a separate organization for each project, each with its own billing and dashboard.

92. An audited workflow calls an alias for an earlier model. The output must stay fixed through a validation period. The team must also find any deprecated use before the retirement date.

Select one answer.

A. Keep the alias, since aliases for earlier models point to a fixed snapshot that never moves.

B. Move the workflow to the newest model now, and skip the replacement test to save time.

C. Pin a dated snapshot ID, and export usage by key and model to find deprecated use.

D. Build a shadow environment that replays every request to two model IDs, with a dashboard per token.

93. An assistant summarizes a long contract, and a wrong claim has a real cost. The model must stay the same. Each claim must point to source text. Which two controls meet these constraints?

Select two answers.

A. Use a larger model tier for summaries, because larger tiers invent fewer contract terms.

B. Ask for word-for-word quotes before the summary, because the contract is a long document.

C. Turn on contract mode, which blocks any summary that lacks a citation.

D. Remove each summary claim that has no source quote, after the quote check runs.

D5.3 Human-in-the-loop validation

94. A managed agent can delete customer records through an MCP tool. A deletion cannot be undone. Each deletion must wait for a person to approve it before the tool runs.

Select one answer.

A. Subscribe to the session.status_idled webhook, which pauses the session before each deletion.

B. Run an offline reviewer job that samples sessions after each deletion, and reports the results weekly.

C. Add an approval service with a hook, a review queue, and a separate audit database for each tool.

D. Set the permission policy to always_ask for the delete tool, so the session pauses until a reply arrives.

95. A Claude Code team wants a check on shell commands that no permission rule can express. The check must block a command that touches a production host before the command runs.

Select one answer.

A. Print a warning from the hook and exit with code 0, so the developer sees the reason.

B. Set permissionDecision to allow in the hook JSON, which lets the command run with a warning.

C. Add a PreToolUse hook on the shell matcher that exits with code 2 when the host check fails.

D. Route every shell command to an approval service with a review queue and a manual reply.

96. An agent edits files in a reversible way across 5,000 sessions each day. Review can happen after each action, and a tested undo path must exist. Which two steps meet these constraints?

Select two answers.

A. Set evaluated_permission to review, which pauses each file edit until a reviewer answers.

B. Sample sessions at a random rate for offline review, and send flagged actions to a human reviewer.

C. Test a rollback procedure before the run, so a flagged file edit can be reversed.

D. Require approval for every file edit before it runs, with a decision record for each edit.

D5.4 Regulatory compliance and data controls

97. A clinic sends patient notes to the Messages API. The contract requires that prompts and responses not persist after each response. The clinic also tests prompts in the Console playground.

Select one answer.

A. Keep default retention, and encrypt each prompt in the clinic network before it leaves.

B. Enable ZDR for the organization, send API calls only with its keys, and keep patient data out of the playground.

C. Enable HIPAA readiness, which stops storage of prompts after each response.

D. Enable ZDR, and attach a customer-managed key to a new workspace for all stored data.

98. A company must keep inference in the United States for a model at version 4.6 or later. The rule must hold even when application code omits the residency setting.

Select one answer.

A. Set the application server region to US, which keeps inference in the United States.

B. Set inference_geo to us on each request, and leave the workspace allowed list open.

C. Set default_inference_geo and allowed_inference_geos to us on the workspace.

D. Create a new workspace with US workspace geo, and set its default and allowed inference geos to us.

99. A bank must hold its own keys for new stored data, and it must show who read which records. The audit record must remain after a key is revoked. Which two actions meet these constraints?

Select two answers.

A. Attach a customer-managed key to a new workspace before its first request.

B. Re-encrypt old workspaces under the customer key, with the key added after the first request.

C. Export Activity Feed events to an internal audit store on a schedule.

D. Create a separate workspace and customer key for every team, each with its own Compliance Access Key.

D5.5 Responsible AI

100. A marketplace moderates listings in six languages. The rules change every month. The team must update the rules without new labeled training data. Which design meets the constraint?

Select one answer.

A. Retrain a custom classifier for each language after every rule change.

B. Use the built-in safety classifiers as the marketplace rules.

C. Put the written rules and edge-case examples in the prompt, and constrain the verdict with a JSON schema.

D. Put the written rules in the prompt, and have a person approve every verdict before a listing goes live.

101. A compliance dashboard must count declined requests by policy area. The team cannot change the model. Which method meets the constraint?

Select one answer.

A. HTTP error responses look like the standard count, since each declined request returns an error status code.

B. Read stop_reason on each response, and count the stop_details category when stop_reason is refusal.

C. Read the category value from the usage field, which lists the policy area of each call.

D. Log every full prompt, response, and header for each call, then sort the logs by policy area.

102. A release review asks for evidence that the product works for each user group. The review also asks which model the product uses. Select two actions that meet both requests.

Select two answers.

A. Build an evaluation set with a group label for each user group, and set a floor for each group.

B. Cite the model system card as the fairness result for product users.

C. Request subgroup fairness metrics that Anthropic publishes for each Claude model.

D. Record the model system card link and the exact model ID in the release record.

D6.1 Structured discovery

103. A product owner asks for a fast and accurate answer bot. The team has no number for either word. The team must set a pass or fail check before any design work. Which step meets the constraint?

Select one answer.

A. Pick the largest model, and tune the wording until the demo looks accurate.

B. Enable a workspace spend limit so that the bot stays fast and accurate.

C. Set a metric, a threshold, and an owner, and add a weekly human panel to score every answer.

D. Convert fast and accurate into a latency threshold and a task fidelity score, with an owner who signs each threshold.

104. A project team needs a monthly spend cap for its own traffic only. The cap must not include traffic from other teams. Which setup meets the constraint?

Select one answer.

A. Create a project workspace and a staging workspace, scope each API key, and set a spend limit on each.

B. Use the Default Workspace with a shared key, and set a spend limit there.

C. Create a workspace for the project, scope its API key to that workspace, and set a spend limit on it.

D. Set a per-minute rate limit on the project key, which caps the monthly spend.

105. A support bot team builds an evaluation set. The team wants a fast check loop and coverage of rare cases from real traffic. Select two actions that meet both requests.

Select two answers.

A. Score every answer with a human panel before each test run.

B. Add edge cases from real traffic to the test set.

C. Use code-based checks wherever the output format allows them.

D. Use the workspace spend limit as the pass threshold for each answer.

D6.2 Trade-off communication

106. A budget owner compares two models. Model X has a lower price per token. Model Y finishes each task with fewer requests. The owner must choose on the cost of one completed task. Which measure meets the constraint?

Select one answer.

A. Sum the token prices across all requests for one completed task, then compare the totals.

B. Compare the per-token list prices, since they are published and stable.

C. Build a per-developer cost dashboard with attribution before any comparison.

D. Read the price field in each Messages API response to compare the two models.

107. A proposal moves a quality-sensitive task to a cheaper model tier. The team has no test on its own tasks. The decision must rest on measured quality and cost for real traffic. Which step meets the constraint?

Select one answer.

A. Switch the task to the cheaper tier, since its per-token price is lower.

B. Read the Usage and Cost API totals and treat them as a quality score for each answer.

C. Sample production tasks weighted like real traffic, and plot each tier score against its spend.

D. Rebuild the product on three providers, then run a six-month comparison on real traffic.

108. A finance audience and a security audience review a model option. The vendor claims zero risk and perfect accuracy. The record must give each audience the facts it decides on. Select two entries that meet this constraint.

Select two answers.

A. Attach the Usage and Cost API export as proof of zero risk.

B. State the cost per completed task with the date of the price list.

C. Show the per-token list price alone as the cost field for each option.

D. Name the measured accuracy with its evaluation set, and give an uncertainty beside it.

D6.3 Feedback and expectation alignment

109. A finance lead wants daily cost totals in USD for each team workspace. The script must use credentials that the usage and cost endpoints accept. Which setup meets the constraint?

Select one answer.

A. Call the usage and cost endpoints with the workspace API key that the script already holds.

B. Set the Cost API bucket to one minute to get finer daily totals.

C. Stream each response usage field into a warehouse, and rebuild the totals every hour.

D. Call the usage and cost endpoints with an Admin API key, and read the daily cost report by workspace.

110. An on-call engineer must see a traffic spike within seconds. The team has a usage report and a cost report. The team cannot wait for a daily total. Which action meets the constraint?

Select one answer.

A. Poll the Usage and Cost API once per minute and alert on each new total.

B. Set a monthly spend alert on the workspace to catch a spike within seconds.

C. Read the usage fields in each live response, and log them as responses return.

D. Add a live response log, and also run a weekly cost review with finance.

111. A company runs one workspace for each team. The owner wants a monthly budget for each team and rate limits for each model. Select two settings that meet both requests.

Select two answers.

A. Set a monthly spend limit and alerts on each team workspace.

B. Set a per-minute spend limit on each workspace to cap traffic bursts.

C. Set rate limits per model on requests, input tokens, and output tokens per minute.

D. Put every team on the Default Workspace, and set one spend limit there.

D6.4 Architecture documentation

112. A decision record names a model by family only. A successor cannot tell which model the evaluation measured. The record must name the measured model exactly. Which entry meets the constraint?

Select one answer.

A. Attach the full evaluation notebook and every raw response to the record.

B. Write the exact model ID and the platform in the record.

C. Record the model family name only, since the family name identifies the model.

D. Record the API version header as the model ID for the evaluation.

113. A decision record names a model ID. The platform posts a retirement notice with a date for that ID. The notice names a replacement model. The team must keep the record accurate and avoid an outage on that date. Which action meets the constraint?

Select one answer.

A. Record the retirement date beside the ID, then test the named replacement before that date.

B. Keep the ID in the record, since a dateless ID is a fixed snapshot that never retires.

C. Freeze all model work for the year, and rebuild every decision record from scratch.

D. Add the Usage page CSV to the record as the model version number.

114. A team writes a decision record for a Claude model in production. A successor must run the system later and must check the decision. Select two entries that meet both needs.

Select two answers.

A. Record the model family and let the successor choose the newest model.

B. Record the workspace spend limit as the model version for the decision.

C. Record the exact model ID with its platform and deprecation date.

D. Write the review criteria that reopen the decision as measurable thresholds.

D6.5 Lifecycle phases

115. A release moves the client to API version 2026-10-21. Every request now fails with a 400 error, because the client sends a temperature value. The fix must remove the cause and pass a test gate before release. Which action meets the constraint?

Select one answer.

A. Keep the temperature value, and add a retry with backoff, since the error may clear.

B. Raise the workspace rate limit, so that the 400 errors clear.

C. Remove the temperature value, and also rewrite the prompts and logs before the test gate.

D. Remove the temperature value from each request, then run the test gate before release.

116. A deprecation notice names a retirement date for a model that the production service calls. The notice names a replacement. The team must avoid an outage on the retirement date. Which action meets the constraint?

Select one answer.

A. Wait for the retirement date, then switch the model in one release.

B. Export usage by API key and model, test the named replacement, and move traffic before the date.

C. Move the whole product to a new cloud platform, and rewrite its prompts before the date.

D. Keep the retired model on a backup route, which still returns answers after the date.

117. A team runs development and production traffic in one shared workspace. The team needs separate rate limits and separate cost reports for each environment. Select two changes that meet both requests.

Select two answers.

A. Create a production workspace, and scope the production API key to it.

B. Rename the Default Workspace to production, since the Default Workspace can be renamed.

C. Create a development workspace, and set lower rate limits on it than on production.

D. Keep one workspace, and add an environment label to each API key name.

D7.1 Team configuration for Claude Code

118. A team wants the agent to never read files in a secrets folder, in every clone. A note in CLAUDE.md asks the agent to avoid that folder. The block must hold even when the model ignores the note. Which change meets the constraint?

Select one answer.

A. Deploy the deny rule in managed settings, and add a sandbox on every developer machine.

B. Add the deny rule to the personal local settings of the team lead only.

C. Add a Read deny rule for the secrets folder in the committed settings file.

D. Add a PostToolUse hook that blocks reads of the secrets folder.

119. A team wants a research subagent that only reads files. The subagent must not receive any write tool. Which setup meets the constraint?

Select one answer.

A. Set the tools field to Read and Grep, and add a second reviewer subagent for each folder.

B. Create the subagent without a tools field, and add a CLAUDE.md line that forbids edits.

C. Set the model field to read-only, which blocks write tools for the subagent.

D. Set the subagent tools field to Read and Grep only.

120. A team needs one enforced rule on every clone. One developer also needs a personal exception that does not weaken the team rule. Select two actions that meet both needs.

Select two answers.

A. Commit the team deny rule in the shared settings file.

B. Put the team deny rule in the user settings file of each developer.

C. Put a personal allow rule for one extra command in the local settings file, which stays out of git.

D. Put the team deny rule in CLAUDE.md, which Claude Code enforces as a permission.

D7.2 AI-assisted workflows with Claude Code

121. A CI job runs Claude Code to check a pull request. The job must restrict the run to the Read and Grep tools. A failed run must fail the job. Which command setup meets both constraints?

Select one answer.

A. Run claude -p with --allowedTools set to Read and Grep, then check the exit status.

B. Run claude -p with --json-schema, which limits the tools that the run can use.

C. Run claude -p with --tools set to Read and Grep, then check the exit status in the next CI step.

D. Run claude -p with --tools set to Read and Grep, check the exit status, and store every transcript in a database.

122. A script runs Claude Code and reads one typed field from the reply. The script must also record the total cost of each run. Which setup meets both constraints?

Select one answer.

A. Run with --output-format json and --json-schema, then read structured_output and total_cost_usd.

B. Parse the free-text reply with a pattern match, and skip the cost field.

C. Run with --output-format json and --json-schema, and store every full transcript in a database.

D. Run with --tools set to a fixed list, and read the per-model breakdown from the --tools output.

123. A team wants one credential for six repositories that run comment-triggered workflows. The credential must not depend on the subscription of one person. Select two actions that meet the constraint.

Select two answers.

A. Run the setup-token command, and store the OAuth token as one organization-level secret.

B. Create an API key in the Claude Console for the shared secret.

C. Set the use_bedrock input to true, which shares one credential across repositories.

D. Store one organization-level Actions secret that all six repositories share.

D7.3 Diagnosis and operational resolution

124. A hook in the shared settings file does not run after edits. The team must find out whether the hook is loaded. The check must not change any file. Which action meets the constraint?

Select one answer.

A. Run /hooks, then start with claude --debug, and export the metrics to a collector.

B. Run /hooks in the current session to see the hook configuration.

C. Add a CLAUDE.md line that asks Claude to run the hook after each edit.

D. Run /context to list each hook match and its exit code.

125. Cost rose after a prompt change in the sessions of one team. The team must find the cause before it changes the model. The first step must use per-session data. Which action meets the constraint?

Select one answer.

A. Switch to a smaller model at once, since a smaller model lowers the cost of each session.

B. Check claude_code.session.count to see the cost of each prompt.

C. Run /usage in each affected session to read its cost.

D. Export OpenTelemetry metrics to a team collector, and build a cost dashboard before any session is checked.

126. An agent edit must be undone. Some changes came from a Bash command that changed files Claude never edited. The undo must cover both kinds of change. Select two actions that meet the constraint.

Select two answers.

A. Use /rewind to undo the tracked Claude edits from the recent checkpoints.

B. Press Esc twice to rewind the Bash-only file change, since rewind covers every change.

C. Set cleanupPeriodDays to 90 to restore snapshots that were already deleted.

D. Use version control to revert the files that only the Bash command changed.

Answer key

F1 Architecture and business foundations

1. A team plans a new workload on Claude Haiku 5.5. Each request has input tokens and output tokens, and each token class has its own rate. The team needs a monthly figure before launch and must build no new service. Which approach meets the constraint?

Select one answer.

A. Multiply the input tokens by the input rate and ignore the output tokens.

B. Build a usage service that writes each request and its usage to a database.

C. Multiply each token class by its own rate, add the classes, then scale by request volume and days.

D. Enable a workspace spend limit and report the limit as the monthly figure.

Answer: C. Each token class has its own rate per million tokens, so the cost of one request is the sum of its classes. Scaling that cost by request volume and days gives the monthly figure without a new service.

Trap. The input-only estimate looks simple, but output tokens bill at their own rate, so it understates the bill.

Source. https://platform.claude.com/docs/en/about-claude/pricing

2. A finance owner wants a hard monthly stop on the spend of one team. The team's API keys currently sit in the Default Workspace. Which change meets the constraint?

Select one answer.

A. Set a spend limit on the Default Workspace that holds the team's keys.

B. Raise the rate limits for the team's model, which also caps its monthly spend.

C. Turn on usage reports, which stop requests when spend passes the budget.

D. Create a workspace for the team, create new keys there, and set its spend limit.

Answer: D. The Default Workspace cannot have a spend limit. A separate workspace with its own spend limit stops that team's requests at the limit. Rate limits control requests per minute, not monthly spend.

Trap. Usage reports look like budget control, but a report alone does not stop usage.

Source. https://platform.claude.com/docs/en/manage-claude/workspaces

3. A team runs two Claude Haiku 5.5 workloads. Nightly reports can wait up to 24 hours, and a live chat feature needs answers at once. The team must forecast each workload at its correct rate. Which two statements meet the constraint?

Select two answers.

A. Price both workloads at the batch rate, which keeps one simple forecast.

B. Price the nightly reports at the batch rate, which is 50 percent below the base price.

C. Price the live chat at the cache hit rate, because chat prompts repeat.

D. Price the live chat at the base input and output rates per million tokens.

Answer: B, D. Batch pricing is 50 percent off and applies to work that can wait. Live chat needs answers at once, so it stays on the standard base rates.

Trap. Cache hit pricing looks like a discount for repeated chat prompts, but it applies only to the cached tokens, not the whole workload.

Source. https://platform.claude.com/docs/en/about-claude/pricing

F2 LLM foundations

4. A team must answer questions about one 600,000-token report in a single request. The team uses Claude Opus 5.5 and expects an answer of about 8,000 tokens. Which design meets the constraint?

Select one answer.

A. Split the report into chunks and send one request for each chunk.

B. Send the full report in one request and set max_tokens to 8,000.

C. Send the full report in one request with server-side compaction enabled on every turn.

D. Set max_tokens to 1,000,000 so the window holds the full report.

Answer: B. The context window holds the input and the new output of a turn. Opus 5.5 has a 1M-token window, so the report fits, and max_tokens caps only the output at 8,000.

Trap. Setting max_tokens to 1,000,000 looks like a window fix, but max_tokens caps only the output of a response.

Source. https://platform.claude.com/docs/en/build-with-claude/context-windows

5. A team deploys Claude Haiku 5.5 on Claude Platform on AWS. The application must send the model ID that this platform uses. Which choice meets the constraint?

Select one answer.

A. The ID claude-haiku-5-5, the same ID that the Claude API uses.

B. A custom alias that a config service resolves to a model ID on each request.

C. The Foundry deployment name, which this platform uses in place of a model ID.

D. The Bedrock-style ID anthropic.claude-haiku-5-5 in the model field.

Answer: A. This platform reuses the first-party model IDs, with no Bedrock-style prefix. Claude Haiku 5.5 therefore uses claude-haiku-5-5 here.

Trap. The Bedrock-style ID looks right for Haiku 5.5, but this platform omits the anthropic prefix.

Source. https://platform.claude.com/docs/en/build-with-claude/claude-platform-on-aws

6. A support app lets Claude look up order status through a tool. The app must run each lookup in its own code behind its permission checks. Which two options meet the constraint?

Select two answers.

A. Return each result as a tool_result block with the next request.

B. Let the model call the order API directly with its own network access.

C. Set stop_reason to tool_result so the loop continues.

D. Repeat the request while stop_reason is tool_use, and exit on end_turn.

Answer: A, D. The app runs each tool and returns its output as a tool_result block. The loop repeats while stop_reason is tool_use and exits on the other documented stop reasons.

Trap. Setting stop_reason to tool_result looks like a loop control, but tool_result is a block type that the app sends, not a stop reason.

Source. https://platform.claude.com/docs/en/agents-and-tools/tool-use/how-tool-use-works

F3 Software and distributed systems

7. A batch job receives HTTP 429 with a retry-after header of 30 seconds. The request is valid. The job must honor the server wait time and send the same request. Which action meets the constraint?

Select one answer.

A. Resend the same request at once in a loop with no delay.

B. Ask the model in the prompt to wait 30 seconds and send the request again.

C. Move the job to a new queue service with priority lanes before each retry.

D. Wait 30 seconds, then resend the same request.

Answer: D. A 429 response with a retry-after header tells the caller how long to wait. Wait that long, then resend the same valid request, which meets the constraint.

Trap. A prompt that says retry looks like a retry policy, but your app must resend the request, not the model.

Source. https://platform.claude.com/docs/en/api/rate-limits

8. A report tool sends a Messages request without streaming. Each report can run for 15 minutes, and the user reads the text as it arrives. Which change meets the constraint?

Select one answer.

A. Stream the Messages response and read each event as it arrives.

B. Create a Message Batch for each report and poll until processing ends.

C. Keep the request without streaming, and write the full response to a database table when it ends.

D. Set the client timeout to 24 hours, because idle connections never drop.

Answer: A. Streaming sends server-sent events as the model writes, so the user reads text before the response ends. A batch returns results only after processing, so it fails the constraint.

Trap. Setting the client timeout to 24 hours looks like the fix for long calls, but some networks drop idle connections whatever the timeout.

Source. https://platform.claude.com/docs/en/build-with-claude/streaming

9. A chat app streams Claude Opus 5.5 responses to users. Some streams end with an error event after partial text. The app must not show partial text as a final answer. Which two actions meet the constraint?

Select two answers.

A. Treat the stream as complete once the HTTP status is 200.

B. Handle error events in the same loop that handles content events.

C. Show streamed text as a draft until the final message arrives.

D. Set a resume flag on the Messages request to continue a cut stream.

Answer: B, C. An error can arrive after the 200 status, so the loop must handle error events as well as content events. Streamed text stays provisional until the final message arrives.

Trap. Resume looks like the fix for a cut stream, but the docs describe a continuation message on newer models, not a request flag.

Source. https://platform.claude.com/docs/en/build-with-claude/streaming

F4 Security and identity

10. A CI pipeline calls the Claude API for nightly evals. The CI platform issues a signed identity token for each job. The constraint: no static API key may be stored in CI. Which design meets the constraint?

Select one answer.

A. Store a workspace API key in the CI secrets manager with a 30-day expiry.

B. Build a token broker that holds the key in a vault and issues short tokens to each job.

C. Register the CI identity provider as a federation issuer and create a federation rule for the pipeline.

D. Use a Bedrock short-term bearer token, which lasts up to 12 hours, for the Claude API calls.

Answer: C. Federation lets the workload exchange its signed identity token for a short-lived Anthropic token. No static key sits in CI, and the federation rule sets the scope and lifetime.

Trap. A key with a 30-day expiry looks short-lived, but it is still a static API key stored in CI.

Source. https://platform.claude.com/docs/en/manage-claude/workload-identity-federation

11. A nightly job reads usage by workspace and also sends Messages requests for the product. The constraint: each call must use the key type that the API accepts for it. Which key plan meets the constraint?

Select one answer.

A. Use one workspace API key for both the usage reads and the Messages requests.

B. Use an Admin API key for the usage reads and a workspace API key for the Messages requests.

C. Create a separate organization with its own Admin API key, and a second key for requests.

D. Use the Default Workspace key for the usage reads, because it is an Admin API key.

Answer: B. An Admin API key authenticates the Usage and Cost API. A workspace API key covers the Messages requests, so each key does one job.

Trap. One workspace key for both calls looks simpler, but a workspace key cannot authenticate the Usage and Cost API.

Source. https://platform.claude.com/docs/en/manage-claude/admin-api-keys

12. A health tech team sends regulated prompts through the Messages API. The contract forbids saving prompts and responses at rest. Which two actions meet the constraint?

Select two answers.

A. Ask the account team to enable ZDR for the organization.

B. Keep the regulated prompts in the Console playground, since ZDR covers the Console.

C. Turn on platform activity logs, which keep prompts out of storage at rest.

D. Check that each feature in use is eligible for zero data retention before launch.

Answer: A, D. ZDR is enabled for each organization by the account team, and Anthropic does not store prompts or responses at rest under ZDR. Eligibility depends on the feature, so the team checks each feature before launch.

Trap. Platform activity logs look like a data control, but logs do not enable zero data retention.

Source. https://platform.claude.com/docs/en/manage-claude/api-and-data-retention

D1.1 Business problem to Claude solution

13. A claims team extracts fixed fields from forms that share one layout. The team must cut model cost and return the same output for the same input. Which design meets the constraint?

Select one answer.

A. Read the fixed fields with code rules and skip the model call.

B. Send each form to Claude Haiku 5.5 at temperature 0, which returns the same output for the same input.

C. Send each form to Claude Opus 5.5 for field extraction, since the largest tier is the most accurate.

D. Send each form to Claude Haiku 5.5, where cache hits make repeated field reads free.

Answer: A. Fixed layouts map to fixed outputs, so code rules return the same result with no per-token cost. Only open input needs a model call (Inference).

Trap. Cache hits look like free reads, but cache hits still cost a small amount per million tokens.

Source. https://platform.claude.com/docs/en/about-claude/pricing

14. A product owner wants summaries that read well. The team must decide whether a model change can ship, and the decision needs a result that passes or fails. Which success criterion meets the constraint?

Select one answer.

A. Summaries read well to the support team.

B. A rating from the model itself looks like a metric, so the team ships when the rating is high.

C. Summaries score at least 4 out of 5 on a rubric for a fixed test set, signed by the support lead.

D. Summaries score well on a rubric, reviewed live on a dashboard after release.

Answer: C. A success criterion needs a metric, a threshold, and a named owner (Inference). A rubric score on a fixed test set gives a pass or fail result that the owner can sign.

Trap. A rating from the model itself looks like a metric, but the same model then grades its own output.

Source. https://platform.claude.com/docs/en/test-and-evaluate/develop-tests

15. A team scores 50,000 nightly support tickets for a report due next morning. Live chat answers must arrive within seconds. The team must keep token cost low for the nightly work. Which two options meet the constraint?

Select two answers.

A. Send the live chat through the Message Batches API to lower its token cost.

B. Send the nightly tickets through the Message Batches API at the batch rate.

C. Read each nightly result as the model writes it, before the batch ends.

D. Keep live chat on the synchronous Messages API for answers at once.

Answer: B, D. Batches cost 50 percent less, and most batches finish within 1 hour, so overnight work fits. Live chat needs answers at once, so it stays on the synchronous API.

Trap. The batch rate looks like a saving for live chat too. But batch results arrive only when the batch ends, so chat answers would not arrive within seconds.

Source. https://platform.claude.com/docs/en/build-with-claude/batch-processing

D1.2 End-to-end architecture

16. A support chatbot answers each message on its own, so follow-up answers ignore earlier turns. The model must stay the same. Which change meets the constraint?

Select one answer.

A. Assume the Messages API keeps earlier turns and reuses them on each call.

B. Switch to a larger model tier, which keeps earlier turns in memory.

C. Store turns in a graph database with embeddings, and send only the newest message with each call.

D. Store the conversation history in the app and send the full history with each request.

Answer: D. The Messages API is stateless, so the app sends the full conversation history with each request. The model stays the same, and each answer can use the earlier turns.

Trap. Server-side memory looks like the simplest fix, but the Messages API keeps no turns between calls.

Source. https://platform.claude.com/docs/en/build-with-claude/working-with-messages

17. A benefits app sends a claim draft to a claims system that needs a fixed object shape. Each claim value must match the source record. The check must run in code and add no model call. Which design meets the constraint?

Select one answer.

A. Ask the model in the prompt to check its own draft before it returns.

B. Request structured outputs, then compare each claim with the source record in code.

C. Enable strict tool use so the claim values match the source records.

D. Request structured outputs, then send each draft back to the model to compare with the source record.

Answer: B. Structured outputs constrain the response to the schema. A code check then compares each value with its source record, and no model call runs in the check.

Trap. Strict tool use looks like a value check, but it validates only tool names and inputs against the schema.

Source. https://platform.claude.com/docs/en/build-with-claude/structured-outputs

18. A pipeline returns wrong totals for some reports. No log shows which stage produces the wrong value. The team must find the stage that breaks before it changes the model. Which two actions meet the constraint?

Select two answers.

A. Log the stage name and the token counts for each model call.

B. Switch to a larger model tier and compare the totals on the next run.

C. Log each stop reason with a count for each request.

D. Enable prompt caching, which records the stage that produced each wrong total.

Answer: A, C. A log line with the stage name ties each model call to its stage (Inference). Stop reasons show how each call ended, such as a stop at max_tokens. Together they locate the stage that breaks before any model change.

Trap. A larger model tier looks like a quick fix, but it hides the stage that breaks and raises cost.

Source. https://platform.claude.com/docs/en/agents-and-tools/tool-use/how-tool-use-works

D1.3 Architectural pattern selection

19. A finance app reads one invoice, classifies it, and posts one record. The steps are fixed, and one model judgment is needed for the class. The app must keep control of the write. Which pattern meets the constraint?

Select one answer.

A. Run an agent loop with a session budget, and let the agent post each record through the MCP connector.

B. Send the invoice to Claude with network access, and let the model post the record.

C. Run the fixed steps in app code, with one model call for the classification, then post in app code.

D. Use a server-executed tool to post the record, so the app runs no code.

Answer: C. The steps are fixed, so app code runs them in order. The model makes only the classification judgment, and the app keeps control of the write.

Trap. An agent loop looks thorough for an invoice, but its planned steps add cost and variation that fixed code does not need.

Source. https://platform.claude.com/docs/en/agents-and-tools/tool-use/how-tool-use-works

20. A research job searches the web, and each result decides the next search. The steps are unknown until the run starts. The team must stop spend at a fixed cap for each session. Which pattern meets the constraint?

Select one answer.

A. Hard-code the search steps in code, with one model call for each step.

B. Run an agent with six subagents and a merge step, with no session budget.

C. Set effort to low, which stops new model requests at the cap.

D. Run an agent loop with a session budget that pauses the session at the cap.

Answer: D. An agent loop chooses each step from the results so far, which fits steps that are unknown. A session budget stops new model requests when list cost reaches the cap.

Trap. Setting effort to low looks like a spend control, but only a session budget stops new requests at the cap.

Source. https://platform.claude.com/docs/en/managed-agents/budgets

21. A checker reads one file, runs one fixed test command, and writes a report. The steps are known, and the app must keep the order of the steps. Which two options meet the constraint?

Select two answers.

A. Call each step from application code in a fixed order, with a model call only for the report text.

B. Let the model choose the next step from a tool list after each result.

C. Run each step from application code, and check each result before the next step starts.

D. Enable a server-executed web search tool to run the test command on your machine.

Answer: A, C. Application code keeps the step order, and the model writes only the report text. Each result is checked before the next step runs, so a failure stops the chain early.

Trap. A model that picks the next tool looks flexible, but the order then depends on the model rather than on your code.

Source. https://platform.claude.com/docs/en/agents-and-tools/tool-use/how-tool-use-works

D1.4 Multi-agent orchestration

22. A lead agent reviews three separate code areas. Each area needs its own system prompt and tools. The team needs one merged report that one agent owns. Which design meets the constraint?

Select one answer.

A. The lead agent delegates each area to a subagent with its own prompt and tools, then merges the subagent reports.

B. Three peer agents write separate reports to a shared folder, and the user merges them by hand.

C. The subagents share one conversation history, so the lead reads every turn of each subagent.

D. One agent reviews all three areas with one system prompt and one tool set.

Answer: A. Each subagent works with its own prompt, tools, and conversation history. The lead agent receives the subagent's final report and owns the merge.

Trap. Shared history looks like a way to give the lead full context, but each subagent keeps its own conversation history.

Source. https://code.claude.com/docs/en/agent-sdk/subagents

23. A team must review 900 repositories in parallel and show progress while the work runs. The lead must not send follow-up messages to each worker during the run. Which design meets the constraint?

Select one answer.

A. Chat with each subagent in turn, and send follow-up messages until each one finishes.

B. Start one workflow run that reads the repositories in parallel, with one session budget for the whole session.

C. Start a workflow run for each repository, each with a session budget of its own.

D. Start one workflow run, and have the lead send each worker a follow-up message about its progress.

Answer: B. A workflow run reads the items in parallel and combines the findings. Runs count toward the session budget, so one session budget covers all runs.

Trap. Separate budgets for each run look like tighter control, but runs count toward one session budget.

Source. https://platform.claude.com/docs/en/managed-agents/multiagent-orchestration

24. Three steps edit one shared report. Each step needs the result of the step before it. The team wants one coherent report. Which two options meet the constraint?

Select two answers.

A. Run the three steps as parallel subagents, each with the full report in its prompt.

B. Keep the three steps in one agent, so each step sees the earlier result.

C. Enable the shared sandbox so each subagent sees the earlier conversation history.

D. Run the steps in order in one thread, and check each step result before the next one starts.

Answer: B, D. One thread keeps each earlier result in its history, so later steps see it. The fixed order and the check after each step keep one coherent report.

Trap. A shared sandbox looks like shared context, but each subagent still keeps its own conversation history.

Source. https://platform.claude.com/docs/en/managed-agents/multiagent-orchestration

D1.5 Task decomposition

25. A team must score 150,000 document requests overnight with batch pricing. No request needs an answer at once, and each request is under 1 KB. Each batch must stay within the documented limits. Which plan meets the constraint?

Select one answer.

A. Send all 150,000 requests in one batch, since a batch can hold them all.

B. Send the 150,000 requests one at a time through the synchronous Messages API overnight.

C. Split the job into two batches, each under 100,000 requests, and collect both result sets.

D. Set the batch expiry to 29 days so all 150,000 requests finish in time.

Answer: C. A batch holds up to 100,000 requests or 256 MB, whichever limit comes first. Two batches of 75,000 requests of 1 KB each stay under both limits and keep batch pricing.

Trap. One batch for everything looks simplest, but a batch holds at most 100,000 requests or 256 MB.

Source. https://platform.claude.com/docs/en/build-with-claude/batch-processing

26. A contract pipeline extracts party names first, then computes the fee from those names. A wrong name in step one would change the fee in step two. The team must stop a wrong name before step two runs. Which design meets the constraint?

Select one answer.

A. Run the name step and the fee step in parallel, so both finish sooner.

B. Check the party names in code after the fee step, and route each fee to a reviewer.

C. Turn on compaction, which removes wrong party names from earlier turns.

D. Check the party names in code before the fee step, and stop the chain at a failed check.

Answer: D. The fee step depends on the name step, so a code check between the steps catches a wrong name at its source. A stop at the failed check keeps the wrong name out of step two.

Trap. Compaction looks like a cleanup step, but it writes a summary of older turns and does not validate values.

Source. https://platform.claude.com/docs/en/build-with-claude/compaction

27. A team has 80,000 review texts for overnight scoring. A live widget scores one text while a user types. The team must keep each path on the right API. Which two options meet the constraint?

Select two answers.

A. Send the live widget requests through a batch, so each score costs less.

B. Split the overnight texts into batches of 256 requests, since a batch holds 256 requests.

C. Send the overnight texts as one Message Batch, since the batch holds up to 100,000 requests.

D. Send the live widget requests through the synchronous Messages API, one call per text.

Answer: C, D. A batch holds up to 100,000 requests or 256 MB, and its results come after processing. A live widget needs each answer while the user types, so it uses the synchronous API.

Trap. The number 256 looks like a request count, but it is the 256 MB size limit of a batch.

Source. https://platform.claude.com/docs/en/build-with-claude/batch-processing

D1.6 Business-value alignment

28. A summary request on Claude Haiku 5.5 uses 3,000 input tokens and 800 output tokens. The prompt is under 100,000 tokens. The team needs the cost per request from published prices. Which method meets the constraint?

Select one answer.

A. Multiply all 3,800 tokens by the input price per million tokens.

B. Multiply each token count by its own rate, divide by one million, and add the two results.

C. Multiply each token count by its own rate, then write each result to a cost ledger with a dashboard.

D. Price all input tokens at the cache hit rate, because the prompt is reused.

Answer: B. Haiku 5.5 has separate base rates for input and output, both per million tokens. Here the input costs 0.0003 dollars and the output costs 0.0004 dollars, for 0.0007 dollars in total.

Trap. A cache hit rate looks like a cheap input price, but it applies only to tokens that the cache actually returns.

Source. https://platform.claude.com/docs/en/about-claude/pricing

29. A team wants to book savings from a cheaper model tier. The cheaper tier passes 91 percent of the eval set, and the agreed threshold is 95 percent. The constraint: keep a value claim only while the quality threshold holds. Which action meets the constraint?

Select one answer.

A. Book the savings now, and tune the threshold after the next quarter.

B. Set a session budget on the cheaper tier, which proves the savings hold.

C. Hold the savings claim until the cheaper tier passes the threshold on the same eval set.

D. Book the savings now, and rebuild the eval set with 10,000 cases before any re-test.

Answer: C. The claim needs the cheaper tier to pass the agreed threshold on the same eval set. A session budget caps spend, but it does not measure quality.

Trap. The early savings claim looks like progress, but the cheaper tier fails the agreed threshold today.

Source. https://platform.claude.com/docs/en/managed-agents/budgets

30. A long agent run follows fixed steps, and no user waits for it. Finance caps the spend for the run. The team needs a budget that stops new requests at the cap and shows spend during the run. Which two options meet the constraint?

Select two answers.

A. Set a session budget when the session is created, so new requests stop at the cap.

B. Set the budget after the bill arrives, so the total can be corrected.

C. Set a workspace spend limit of the same amount on the Default Workspace.

D. Read usage.list_cost on the session object, which holds the running list cost.

Answer: A, D. A session budget is set when the session is created, and it stops new model requests at the cap. The platform prices the session continuously, and usage.list_cost on the session object holds that running total.

Trap. A workspace spend limit looks like the same control, but the Default Workspace cannot have a spend limit.

Source. https://platform.claude.com/docs/en/managed-agents/budgets

D2.1 Model selection and tier trade-offs

31. A ticket router classifies five million tickets each month. Claude Haiku 5.5 clears the measured quality floor on the team's test set. The constraint: use the lowest-cost tier that clears the floor. Which choice meets the constraint?

Select one answer.

A. Route every ticket to claude-haiku-5-5, the lowest tier that clears the floor.

B. Route every ticket to Claude Haiku 4.5, which costs less per million tokens than Haiku 5.5.

C. Route every ticket to Claude Fable 5.1, the top tier, for the highest safety margin.

D. Set effort to max on Claude Haiku 5.5, which moves its price to the Sonnet tier.

Answer: A. The lowest tier that clears the measured floor has the lowest price for the work. Haiku 5.5 costs 0.10 dollars per million input tokens for prompts up to 100,000 tokens.

Trap. Fable 5.1 for every ticket looks safest, but it adds cost that the measured floor does not require.

Source. https://platform.claude.com/docs/en/about-claude/pricing

32. A code assistant runs on Claude Haiku 5.5. It misses the quality floor on about 8 percent of requests at the default effort. The team must keep the same model and raise quality with the least change. Which change meets the constraint?

Select one answer.

A. Move all traffic to Claude Fable 5.1, which clears the floor on every request.

B. Raise effort to high only for the requests that miss the floor, and keep the medium default for the rest.

C. Set a thinking budget_tokens value of 20,000 on Haiku 5.5 to raise thinking depth.

D. Set effort to xhigh on every request and rebuild the eval set with extra checks.

Answer: B. Effort is set per request on the same model, so only the requests that miss the floor get more effort. Haiku 5.5 supports high effort, and its default is medium.

Trap. A thinking budget looks like a direct depth control, but budget_tokens returns a 400 error on Haiku 5.5.

Source. https://platform.claude.com/docs/en/build-with-claude/effort

33. A team runs one extraction task on Claude Haiku 5.5. Most requests clear the quality floor at the default effort. The constraint: keep cost and latency low while the quality floor holds. Which two options meet the constraint?

Select two answers.

A. Send all traffic to Claude Opus 5.5, so every request clears the floor.

B. Keep Haiku 5.5 for all traffic, and set low effort for simple requests.

C. Set a thinking budget_tokens value on Haiku 5.5 to cut output tokens.

D. Escalate only the requests that miss the floor to Claude Sonnet 5.5.

Answer: B, D. Haiku 5.5 is the lowest-priced current model in this set and handles most requests. Low effort reduces thinking on simple requests, and escalation sends only the misses to a higher tier.

Trap. Opus 5.5 for all traffic looks like a safe floor, but it raises cost for requests that Haiku 5.5 already clears.

Source. https://platform.claude.com/docs/en/build-with-claude/effort

D2.2 System prompts, templates, and guardrails

34. A support assistant must never show one customer's order data to another customer. The rule must hold for every user input. Which change meets the constraint?

Select one answer.

A. Add a stricter rule to the system prompt that forbids cross-customer data.

B. Filter order records in code by the signed-in customer ID before each call.

C. Send all order records, and ask the model to show only the signed-in customer's records.

D. Set an output schema that lists only the customer ID field.

Answer: B. Code checks ownership for every input before the model receives any record. A system prompt is guidance, so it cannot enforce access alone (Inference).

Trap. A stricter system prompt rule looks like access control, but it is guidance that code must enforce (Inference).

Source. https://platform.claude.com/docs/en/test-and-evaluate/strengthen-guardrails/mitigate-jailbreaks

35. A billing service parses each model reply into database fields. The team needs one fixed JSON shape, with no retry loop for shape errors. Which change meets the constraint?

Select one answer.

A. Ask in the prompt for JSON only, then parse the text with a pattern match.

B. Let the model write prose, then split each paragraph into fields in code.

C. Send a JSON schema in output_config format, then check the stop reason before parsing.

D. Send a JSON schema in the prompt text, then retry the call when the shape fails to parse.

Answer: C. The schema in output_config format constrains the reply shape, so a retry loop is not needed in most cases. Code still checks the stop reason before it parses the text.

Trap. A prompt that asks for JSON only looks equal to a schema, but nothing constrains the text.

Source. https://platform.claude.com/docs/en/build-with-claude/structured-outputs

36. A shared assistant sends one system prompt with every request, and the cache must keep its stable text. The team must also tie each saved answer to one prompt version. Which two changes meet both constraints?

Select two answers.

A. Insert the tenant name into the system prompt on each request.

B. Keep the stable instructions in one system block, stored in version control.

C. Turn on automatic prompt version history in the Claude Console.

D. Log the prompt version with each saved answer.

Answer: B, D. One stable system block keeps the cached prefix identical across requests. A version label on each saved answer ties it to one prompt (Inference).

Trap. A tenant name in the system prompt looks like personalization, but a change to the system content invalidates the system and messages caches.

Source. https://platform.claude.com/docs/en/build-with-claude/prompt-caching

D2.3 Prompt techniques

37. A ticket classifier misses its accuracy bar on new labels. The team has no budget for model training, and it wants the smallest prompt change first. Which change should the team try first?

Select one answer.

A. Train a custom classifier on the full ticket history before any prompt change.

B. Enable citations, so each label links to its source text.

C. Add three to five varied labeled examples in example tags, then run the evals.

D. Add the examples, and also turn on adaptive thinking for every call.

Answer: C. Three to five examples in example tags steer the output pattern without training. Measure the result first, and add more examples only if the evals need them.

Trap. Custom training on the full history looks like the strongest fix, but the team has no training budget.

Source. https://platform.claude.com/docs/en/build-with-claude/prompt-engineering/claude-prompting-best-practices

38. A migration moves an extraction service to a Claude 4.6 model. Each request ends with a prefilled assistant turn, and the API returns a 400 error. The fix must keep the output format and run on Claude 4.6.

Select one answer.

A. Turn thinking off, so the prefilled assistant turn is accepted.

B. Remove the prefill, and state the output format in the system prompt.

C. Keep the prefill, and add structured outputs to the same request.

D. Keep the prefill, and route these calls to an earlier model.

Answer: B. Claude 4.6 and later models reject a prefilled final assistant turn. A system prompt instruction keeps the output format without the prefill.

Trap. Thinking turned off looks like a valid fix, but the prefilled final turn still returns a 400 error on Claude 4.6.

Source. https://platform.claude.com/docs/en/build-with-claude/prompt-engineering/claude-prompting-best-practices

39. A routing service needs one label from a fixed enum for each ticket. The call targets Claude Opus 5.5, which rejects forced tool use. Which two changes meet the constraints?

Select two answers.

A. Use tool_choice auto with a strict tool that has an enum field.

B. Set tool_choice to one named tool, so the model must call it.

C. Use structured outputs with an enum in the schema.

D. Add a prompt caching breakpoint to the label instructions.

Answer: A, C. Tool choice auto works with strict tool use on Opus 5.5. Structured outputs with an enum also return one label from the fixed list.

Trap. A named tool choice looks like the simplest way to lock the label, but Opus 5.5 rejects forced tool use with a 400 error.

Source. https://platform.claude.com/docs/en/build-with-claude/thinking

D2.4 Context and token management

40. A chat service sends long histories. Each turn must fit an input budget that the app sets before the call, and the model must stay the same. Which change meets both constraints?

Select one answer.

A. Set effort to low, so the input token count falls.

B. Skip counting, and rely on the usage fields after each response.

C. Count tokens before each send, and switch to a larger-window model when the count is high.

D. Count tokens with the target model ID, and trim history that exceeds the budget.

Answer: D. The token counting endpoint reports the input size before the call. The app trims the history, so each turn fits the budget on the same model.

Trap. Usage fields in a response look like a budget check, but those counts arrive only after the call is sent.

Source. https://platform.claude.com/docs/en/build-with-claude/token-counting

41. An agent task fills its context with old tool results. The team wants no extra summarization call, and recent work must stay in context. Which change meets both constraints?

Select one answer.

A. Add the clear_tool_uses strategy with the context-management beta header.

B. Start a separate summary request on every turn, then send that summary.

C. Clear all tool results on every turn, including the most recent ones.

D. Use the token counting endpoint to delete old turns from the history.

Answer: A. The clear_tool_uses strategy removes old tool results by rule, so no summary call is needed. The beta header enables context editing.

Trap. A separate summary on every turn looks thorough, but it adds the model call that the constraint rules out.

Source. https://platform.claude.com/docs/en/build-with-claude/context-editing

42. A long agent task loses an early constraint after a default summary. Recent turns must stay word for word after the summary. Which two changes meet both constraints?

Select two answers.

A. Let the default summary run, and trust it to keep every constraint.

B. Write a custom summarization prompt that keeps the early constraint.

C. Set a keep_recent_turns parameter to five in the compaction request.

D. Pick a cut point, and send the later turns after the summary block.

Answer: B, D. A custom summarization prompt can require the early constraint in the summary. No parameter selects kept turns, so the cut point sets which turns stay word for word.

Trap. A keep_recent_turns parameter looks like the direct control, but no parameter sets which turns are kept.

Source. https://platform.claude.com/docs/en/build-with-claude/compaction-keep-recent-turns

D2.5 Reuse and prompt caching

43. A research app sends the same 30,000-token reference set with every question. Answers must not change, and the input cost per call must drop. Which change meets both constraints?

Select one answer.

A. Replace the reference set with a short summary, which shrinks each call.

B. Place the reference set first, and mark its last stable block with cache_control.

C. Place each new question first, then the reference set, and mark the last block with cache_control.

D. Send the reference set through the token counting endpoint before each call.

Answer: B. A cache hit needs an identical prefix up to the breakpoint. Cache reads cost a fraction of the base input price, and the answers stay the same.

Trap. A short summary looks like a cost fix, but it changes the answers that must stay the same.

Source. https://platform.claude.com/docs/en/build-with-claude/prompt-caching

44. A multi-turn assistant adds two blocks on each turn. The team wants one cache setting and no breakpoint edits. Which change meets both constraints?

Select one answer.

A. Add explicit cache_control to four blocks, and omit the top-level field.

B. Add a top-level cache_control field, and move an explicit breakpoint to the newest block on each turn.

C. Add a cache_mode parameter set to auto in the request body.

D. Add one top-level cache_control field to the request.

Answer: D. Automatic caching moves the breakpoint to the last cacheable block as the conversation grows. One top-level field enables it, so the team needs no breakpoint edits.

Trap. Explicit breakpoints on four blocks look more controlled, but they need edits each time the stable content moves.

Source. https://platform.claude.com/docs/en/build-with-claude/prompt-caching

45. A batch job sends a tool list that never changes, then a weekly document. Calls arrive about every 30 minutes. The tool list must stay cached between calls, and the weekly document must not break that cache. Which two changes meet both constraints?

Select two answers.

A. Set ttl to 1h on the breakpoint after the tool list, before the document.

B. Place the weekly document first, then cache from its last block.

C. Keep the weekly document after the breakpoint, so its edits do not break the cache.

D. Set a cache TTL of 2h on the request, so the whole prompt stays cached.

Answer: A, C. A 1-hour TTL keeps the tool list cached across 30-minute gaps. Content after the breakpoint can change without a miss on the cached prefix.

Trap. A document placed first looks harmless, but any change at or before the breakpoint causes a cache miss.

Source. https://platform.claude.com/docs/en/build-with-claude/prompt-caching

D3.1 Tool capability scope

46. An invoice agent has 60 tools from several MCP servers. Most requests use three tools. The team must cut the tool schema tokens sent per call, and every tool must stay available.

Select one answer.

A. Remove 40 tools from the agent, so the list fits the prompt.

B. Set cache_control on every deferred tool, so their schemas stay cached.

C. Add tool search, defer the rarely used tools, and keep the three common tools non-deferred.

D. Add tool search, and set defer_loading to true on every tool, including the tool search tool.

Answer: C. Tool search keeps deferred definitions out of the first prompt, so frequent tools stay in context. All 60 tools remain available to the agent.

Trap. Setting cache_control on deferred tools looks like a cost fix, but a deferred tool with cache_control returns a 400 error.

Source. https://platform.claude.com/docs/en/agents-and-tools/tool-use/tool-search-tool

47. Two lookup tools do the same job, and their descriptions are almost identical. The agent often picks the wrong one. The fix must remove the ambiguity from the tool list itself.

Select one answer.

A. Add a longer system prompt rule that names which lookup to use.

B. Merge the two lookups into one tool with an action parameter and a clear description.

C. Keep both lookups, and add a classifier model that routes each request first.

D. Set defer_loading to true on both lookup tools.

Answer: B. One tool with one name leaves the model no near match to pick. The docs name tool description detail as the most important factor in tool performance.

Trap. A system prompt rule that names the right lookup looks like a fix, but two tools with the same job still split the choice.

Source. https://platform.claude.com/docs/en/agents-and-tools/tool-use/define-tools

48. A finance agent runs a nightly report task in Claude Code. The task never calls a refund write tool, but a wrong refund fired last week. The team must block that tool and keep the report read tool.

Select two answers.

A. Add a deny rule for the refund write tool in the task's settings.

B. Keep the refund tool, and add audit logging of each call.

C. Turn on tool search, so the refund tool loads only when searched.

D. Remove the refund write tool from the task's tool list.

Answer: A, D. A deny rule or a removed tool ends the permission, and a log entry does not. A deferred tool still loads when the model searches for it, so tool search does not block the call.

Trap. Tool search looks like a safety fix, but a deferred tool still loads when the model finds it.

Source. https://code.claude.com/docs/en/permissions

D3.2 Authentication and authorization in integrations

49. An internal assistant calls a remote MCP server. The server must record which employee asked for each action. Which change meets the constraint?

Select one answer.

A. Use one shared service key, and add the employee name to the prompt.

B. Send each user's OAuth token in authorization_token for that server.

C. Send one shared OAuth token for all users, and route all calls through a logging proxy.

D. Set the anthropic-workspace-id header to the employee's team workspace.

Answer: B. The server checks a bearer token that names the signed-in user. A name typed into a prompt cannot prove who asked (Inference).

Trap. A shared key with a name in the prompt looks like attribution, but the system cannot verify a name that the user typed (Inference).

Source. https://platform.claude.com/docs/en/agents-and-tools/mcp-connector

50. A workload runs on Claude Platform on AWS. The security team needs IAM to control each caller, and the workload has no user consent flow. Which change meets both constraints?

Select one answer.

A. Store a long-lived API key in the code, and skip IAM policies.

B. Add an OAuth consent screen for each user before each call.

C. Sign with SigV4 from one shared role for all callers, and log each request ID in a second store.

D. Enable outbound web identity federation, sign with SigV4, and scope IAM to the workspace ARN.

Answer: D. Outbound web identity federation is disabled by default, so requests fail until it is enabled. An IAM policy on the workspace ARN then limits each caller.

Trap. An OAuth consent screen looks like user control, but Claude Platform on AWS does not support OAuth.

Source. https://platform.claude.com/docs/en/build-with-claude/claude-platform-on-aws

51. On the Claude API, two tenants must not share prompt caches or API keys. The team also wants a separate monthly spend limit for each tenant. Which two changes meet both constraints?

Select two answers.

A. Use one workspace for both tenants, and name each tenant in a header.

B. Rename the Default Workspace to the first tenant, then archive it later.

C. Create one workspace per tenant, and scope each tenant key to its workspace.

D. Set a monthly spend limit on each tenant workspace.

Answer: C, D. Prompt caches stay isolated by workspace on the Claude API. Each new workspace can also have its own spend limit.

Trap. A tenant header in one workspace looks like isolation, but both tenants then share one prompt cache and one spend limit.

Source. https://platform.claude.com/docs/en/manage-claude/workspaces

D3.3 Accuracy and latency trade-offs

52. Users must see the first words of a reply before the full answer is ready. The model and the answer quality must stay the same. Which change meets both constraints?

Select one answer.

A. Stream the response, so text appears as the tokens arrive.

B. Enable fast mode, which cuts the time to first token.

C. Send each request as a Message Batch, and read the results the next day.

D. Cache each full answer in a custom store, and show it only after the answer is complete.

Answer: A. Streaming sends output as the model generates it, so the first words appear before the answer ends. Streaming does not reduce the total generation work (Inference).

Trap. Fast mode looks like a first-token fix, but its speed gain applies to output tokens per second, not to time to first token.

Source. https://platform.claude.com/docs/en/build-with-claude/streaming

53. An evaluation run has 50,000 prompts. Results can arrive within one day, and the run must cost less than standard calls. No user waits for these results.

Select one answer.

A. Send each prompt one at a time on the standard path, with high effort.

B. Buy a Priority Tier commitment, which gives half-price calls.

C. Submit one Message Batch, and also run the full set on the standard path.

D. Submit the prompts as one Message Batch, and read results after processing ends.

Answer: D. Batch usage is charged at half the standard API price. Results can take up to 24 hours, which fits an evaluation run that no user waits on.

Trap. Standard calls look simple, but they keep standard pricing for a job that can wait a day.

Source. https://platform.claude.com/docs/en/build-with-claude/batch-processing

54. A classifier meets its accuracy floor at medium effort, but its latency target is tight. Many requests are simple, and a short answer is enough for them. Which two changes meet both constraints?

Select two answers.

A. Move all requests to a larger model at high effort.

B. Set effort lower for simple requests, and keep medium effort for the rest.

C. Enable fast mode on Claude Haiku 5.5, which cuts the first-token wait.

D. Ask for a shorter answer in the prompt when output length adds time.

Answer: B, D. Lower effort cuts output and thinking work on simple requests. A shorter answer cuts output time, and medium effort keeps the accuracy floor on harder requests.

Trap. A larger model looks like the safer choice for accuracy, but each call takes longer and can miss the latency target (Inference).

Source. https://platform.claude.com/docs/en/build-with-claude/effort

D3.4 Observability at scale

55. An incident review must find which tool call sent a bad record. Prompt logs show the text but no tool hop. Prompt text must stay out of the trace data.

Select one answer.

A. Store full prompt content in the spans, so each hop shows its text.

B. Read the usage report by hour, which lists each tool call.

C. Emit one trace per run, with a span for each model and tool hop, in metadata only mode.

D. Emit one span per run with no child spans, in metadata only mode, and export it to two collectors.

Answer: C. One trace ID links each model and tool hop, so the review can find the hop that acted. Metadata only mode keeps prompt text out of the spans.

Trap. A usage report by hour looks like tool-level detail, but it groups token totals by model, workspace, or key.

Source. https://platform.claude.com/docs/en/manage-claude/opentelemetry

56. Finance needs a monthly split of API spend by workspace, reconciled with billing. The figures must come from platform reports, not from app logs.

Select one answer.

A. Call the cost report with an Admin API key, grouped by workspace.

B. Call the cost report and the usage report hourly, both grouped by workspace.

C. Add up input tokens from each app response, then multiply by list prices.

D. Call the cost report with hourly buckets for a monthly split.

Answer: A. The cost report returns USD totals, and it groups results by workspace. Its daily buckets suit a monthly split that finance reconciles with billing.

Trap. Input token totals from app responses look exact, but finance needs the platform cost totals for billing reconciliation.

Source. https://platform.claude.com/docs/en/manage-claude/usage-cost-api

57. A security team audits developer tool use in Claude Code. The OTLP destination must stay fixed for every developer, and MCP tool arguments must appear in the audit trail. Which two changes meet both constraints?

Select two answers.

A. Pin the OTLP endpoint and credentials in managed settings.

B. Enable telemetry in each repository's project settings file.

C. Set OTEL_LOG_USER_PROMPTS to 1 to capture tool arguments.

D. Set OTEL_LOG_TOOL_DETAILS to 1 to capture MCP call arguments.

Answer: A, D. Managed settings keep the destination fixed for every developer. Tool details log MCP server names, tool names, and input arguments.

Trap. A project setting that enables telemetry looks simple, but Claude Code ignores OTel exporter variables in project settings.

Source. https://code.claude.com/docs/en/monitoring-usage

D3.5 The RAG pipeline

58. A support answer must name the source of each claim. The response must stay free text, with no JSON schema. Which change meets both constraints?

Select one answer.

A. Ask the model in the prompt to list sources after each claim.

B. Pass each chunk as a search result block with source and title, and enable citations.

C. Pass each chunk as search results with citations disabled, and add a reranker before the call.

D. Enable structured outputs with a source field for each claim.

Answer: B. Each citation links a claim to a search result block that carries your source and title. Citations are disabled by default, so the request must enable them.

Trap. A prompt that asks for sources looks equivalent, but the names are not tied to retrieved blocks, so you cannot check them (Inference).

Source. https://platform.claude.com/docs/en/build-with-claude/search-results

59. A policy document has tables split across chunks, and answers cite the wrong row. Each citation must point to one table row.

Select one answer.

A. Keep sentence chunking, and switch to a larger generation model.

B. Send each table as a plain text document, and switch to the largest embedding model.

C. Build one custom content block per table row, sent as a custom content document.

D. Turn on contextual retrieval, so the table rows group automatically.

Answer: C. Custom content documents keep your blocks as they are, with no further chunking. Each row block can then be cited on its own.

Trap. Contextual retrieval looks like a table fix, but the docs do not describe it.

Source. https://platform.claude.com/docs/en/build-with-claude/citations

60. The right passage appears in the candidate list, but it ranks low. The answer model needs that passage among the top passages. Which two changes meet the ranking constraint?

Select two answers.

A. Switch to a larger generation model, with the same candidate list.

B. Add a reranker that reorders the candidate list for the query.

C. Set input_type to None on the query embedding, so ranking uses raw similarity.

D. Send only the top reranked passages to the answer model.

Answer: B, D. A reranker returns candidates in relevance order for the query. The top reranked passages then reach the answer model.

Trap. A larger generation model looks like the fix, but it does not change the candidate order (Inference).

Source. https://platform.claude.com/docs/en/build-with-claude/embeddings

D3.6 Retrieval strategies

61. An app answers stock-count questions from an index that refreshes hourly. Users need the current count, and policy questions must stay on the index. Which change meets both constraints?

Select one answer.

A. Refresh the index every five minutes, and keep the snapshot as the only source.

B. Enable the SSE transport on the connector, so stock values stream in.

C. Route stock questions to a read tool on the inventory server, and keep policy questions on the index.

D. Route stock questions and policy questions to a read tool on the inventory server.

Answer: C. A read tool returns the value as it stands at call time. Policy text changes less often, so it can stay in the index (Inference).

Trap. A faster index refresh looks like the fix for stale counts, but the index still holds a snapshot (Inference).

Source. https://platform.claude.com/docs/en/agents-and-tools/mcp-connector

62. A query contains an error code, and users also ask about the same docs in plain words. A semantic index alone misses the exact code. The fix must find both the code and the paraphrased passages.

Select one answer.

A. Use a semantic index only, and raise the number of candidates it returns.

B. Store the codes as binary embeddings, which keeps exact matches.

C. Run two semantic matchers with different models, and merge both lists.

D. Run keyword and semantic matchers, then merge both candidate lists.

Answer: D. A keyword matcher finds exact codes, and a semantic matcher finds paraphrases. The merged candidate list covers both query shapes (Inference).

Trap. A larger candidate count from the semantic index looks like coverage, but a vector match can still miss the exact code (Inference).

Source. https://platform.claude.com/docs/en/build-with-claude/embeddings

63. A chat app must answer with live order status from a remote server. The app must not run an MCP client in its code, and answers must not come from a stored snapshot. Which two changes meet both constraints?

Select two answers.

A. Define the server in mcp_servers, and reference it from one MCP toolset.

B. Copy the order status into the index every hour, and search that copy.

C. Send the request with the MCP connector beta header.

D. Read order status through MCP resources, which the connector loads.

Answer: A, C. The connector calls the remote server's tools from the Messages API, so the app needs no MCP client. The beta header enables the connector.

Trap. MCP resources look like a live feed, but the connector supports only tool calls from the MCP specification.

Source. https://platform.claude.com/docs/en/agents-and-tools/mcp-connector

D3.7 Integration mechanisms

64. One backend service calls an internal billing API from a single host. No other host needs these tools, and the team wants no extra protocol layer.

Select one answer.

A. Register the billing API as a stdio server in Claude Code for the backend.

B. Call the billing API directly from the backend code with its own client.

C. Wrap the billing API in an MCP server, and let the backend connect as its client.

D. Put a CLI wrapper around the API, and parse its text output in the backend.

Answer: B. One consumer on one host needs no shared protocol, so direct calls meet the need with the least machinery (Inference).

Trap. An MCP server looks like the standard integration, but it adds a protocol layer that a single host does not need (Inference).

Source. https://platform.claude.com/docs/en/agents-and-tools/mcp-connector

65. Four hosts written in different languages need the same ticket lookup tools. The team wants one tool schema, and each host connects as a client.

Select one answer.

A. Write a separate client library for each host that calls the service.

B. Use the MCP connector with a stdio server on each host.

C. Build one MCP server that exposes the ticket tools, and let each host connect.

D. Build one MCP server with tools, resources, and prompts, and let each host connect.

Answer: C. One server holds one tool schema, and each host connects to it as a client. The team maintains one definition for all hosts (Inference).

Trap. A client library for each host looks flexible, but each copy becomes a second schema to maintain (Inference).

Source. https://platform.claude.com/docs/en/agents-and-tools/mcp-connector

66. A Claude Code team must block one claude.ai connector tool before Claude sees it. The same team must also add an internal service that runs over HTTP. Which two changes meet both constraints?

Select two answers.

A. Add the risky connector tool with an allow rule, so it runs without a prompt.

B. Add the internal service with claude mcp add and the http transport.

C. Set the idle timeout to zero, so the risky tool stays hidden.

D. Set the organization control for that connector tool to blocked.

Answer: B, D. The http transport adds a remote server by URL. A blocked control removes the connector tool from the list before Claude sees it.

Trap. An allow rule looks like a control, but it lets the tool run without a prompt.

Source. https://code.claude.com/docs/en/mcp

D3.8 Progressive discovery and monolithic context

67. An agent loads 60 tools on every request, and most definitions go unused. The three most common tools must answer each turn without an extra search step. Which setup meets both constraints?

Select one answer.

A. Build a custom embedding index that ranks all 60 tools and injects the top five into each system prompt.

B. Add cache_control to each deferred tool, so the API keeps its schema warm between searches.

C. Set defer_loading to true on the 57 rare tools, keep the three common tools non-deferred, and add the tool search tool.

D. Set defer_loading to true on all 60 tools, so every request starts with a search step.

Answer: C. Tool search loads a tool only when a search finds it, so rare definitions cost no tokens until then. The common tools stay non-deferred, so they need no search step.

Trap. Setting defer_loading on all 60 tools looks like the cheapest setup, but every common call then needs a search round trip.

Source. https://platform.claude.com/docs/en/agents-and-tools/tool-use/tool-search-tool

68. An SDK agent uses 12 MCP tools in a small context window. The team wants tool search to start only when definitions reach a set share of the window. Which setting meets the constraint?

Select one answer.

A. Set alwaysLoad to 10 percent, so each server activates tool search once its tools reach that share.

B. Set ENABLE_TOOL_SEARCH to auto, so tools load upfront until definitions reach 10 percent of the window.

C. Set ENABLE_TOOL_SEARCH to false, so every tool definition loads on every turn.

D. Write a ranking service that selects tool definitions before each SDK call, on top of the default settings.

Answer: B. The auto value loads tools upfront until definitions reach 10 percent of the context window. Tool search then starts, so the threshold rule meets the constraint without extra code.

Trap. The alwaysLoad setting sounds like a threshold, but it only loads the tools of one server upfront.

Source. https://code.claude.com/docs/en/agent-sdk/tool-search

69. A team writes a domain agent with 1,500 lines of guidance. Each request must carry only short metadata until a task needs the details. Which two designs meet this constraint?

Select two answers.

A. Keep the skill name and description in the system prompt, and read the reference files only when a task needs them.

B. Enable network access in the skill sandbox, so the model fetches reference pages from a URL on demand.

C. Paste all 1,500 lines into the system prompt, so the model never needs a second read.

D. Keep SKILL.md under 500 lines, and move detailed sections into separate files that each task reads when relevant.

Answer: A, D. Only the skill name and description load at startup, and reference files load only when a task reads them. A SKILL.md body under 500 lines keeps the loaded part small.

Trap. Network access in the skill sandbox looks like a way to fetch files on demand, but skills on the API run with no network access.

Source. https://platform.claude.com/docs/en/agents-and-tools/agent-skills/best-practices

D4.1 Evaluation metrics

70. A support bot team sees fluency rise 12 percent after a prompt change. Resolution rate stays flat. The release decision needs one primary metric with a threshold set before tuning starts.

Select one answer.

A. Set the threshold in the Console evaluation tool, which computes the primary metric for you.

B. Resolution rate on the held-out set, with a threshold and an owner set before the next run.

C. Fluency score as the primary metric, with no threshold, because the grader scores it automatically.

D. Fifteen dashboard metrics, each with its own threshold, reviewed before the primary metric is chosen.

Answer: B. Resolution rate measures the goal directly, so it can decide the release. A threshold and an owner set before tuning give the number a fixed bar. (Inference)

Trap. A fluency score that rose 12 percent looks like a win, but it does not measure the goal and has no threshold.

Source. https://platform.claude.com/docs/en/test-and-evaluate/develop-tests

71. A team moved to a cheaper model, and monthly spend fell. Completed tasks fell more. The team needs a daily report of value per task for each model version.

Select one answer.

A. Compare total monthly spend only, because finance reads the bill and the bill fell.

B. Read the Cost API in one-minute buckets for each task, since minute buckets show spend per task.

C. Build a warehouse pipeline that joins every token count with task outcomes in real time.

D. Daily spend divided by completed tasks gives value per task, so compare that value for each model and prompt version.

Answer: D. The Cost API reports spend in USD by daily bucket, which fits a daily report. The per-task value then compares versions on the same unit of value.

Trap. One-minute Cost API buckets look right for per-task spend, but the Cost API supports only daily buckets.

Source. https://platform.claude.com/docs/en/manage-claude/usage-cost-api

72. A dashboard must show cost and latency for a streaming chat feature. It must also show the quality threshold for the same release. Which two items meet these constraints?

Select two answers.

A. Read time to first token from the Usage API, which reports latency for each bucket.

B. Measure time to first token for streaming calls, and baseline latency for other calls.

C. Track 20 latency percentiles for every route, each with its own alert owner.

D. Show cost per completed task beside the quality threshold, with daily totals from the Usage and Cost API.

Answer: B, D. Time to first token matters most for streaming, and baseline latency covers the full response of other calls. Cost per completed task sits beside the threshold, so both show in one view.

Trap. A latency read from the Usage API looks right, but the Usage API reports token counts and not response times.

Source. https://platform.claude.com/docs/en/test-and-evaluate/strengthen-guardrails/reduce-latency

D4.2 Evaluation datasets and frameworks

73. An eval set of 500 clean prompts scores 96 percent. Production users paste long documents and send empty messages, and failures rise. The set must predict production at a low daily cost.

Select one answer.

A. Add production samples with long, empty, and irrelevant inputs, and grade the checkable cases with code.

B. Have three reviewers grade every case by hand before each daily run, to catch subtle errors.

C. Enable the Console evaluation tool to build the production sample, then score the sample with code.

D. Add a versioned set with a dashboard per case type, plus production samples that include edge cases.

Answer: A. Production samples expose failures that clean prompts hide. Code graders score checkable cases at low cost, so the daily run stays cheap.

Trap. A Console tool that builds the production sample sounds like a shortcut, but the docs describe no tool that samples production traffic.

Source. https://platform.claude.com/docs/en/test-and-evaluate/develop-tests

74. A nightly run grades 30,000 outputs. Most outputs need an exact match on one field, and a few need a judgment about tone. The team must avoid human graders, and each grader must be reliable.

Select one answer.

A. Send all 30,000 outputs to an LLM grader without a reliability test, to keep the setup simple.

B. Add a second LLM grader that cross-checks each tone verdict before the run ends.

C. Grade exact-match outputs with code, and grade tone with an LLM grader after a reliability test.

D. Use a grader setting that caches each verdict, so repeated nightly runs skip the scoring step.

Answer: C. Code graders are the fastest and most reliable method for exact matches. An LLM grader handles tone only after a test confirms its reliability.

Trap. A grader setting that caches verdicts sounds like a cost fix, but the docs do not describe such a setting.

Source. https://platform.claude.com/docs/en/test-and-evaluate/develop-tests

75. A team builds an eval set for a chat assistant. The set must match real traffic and cover unusual input. The team must not hand-grade every case. Which two steps meet these constraints?

Select two answers.

A. Use a built-in Console sampler that labels ambiguous cases automatically.

B. Sample recent production traffic, so the cases match the real task mix.

C. Rebuild the set every hour from the live traffic log, so it never ages.

D. Add empty, long, and irrelevant inputs as edge cases, with expected answers that code can check.

Answer: B, D. Sampled production cases reflect the real task mix. Edge cases expose failures that clean samples hide, and code checks the expected answers.

Trap. An hourly rebuild of the set looks thorough, but the constraints do not need that upkeep.

Source. https://platform.claude.com/docs/en/test-and-evaluate/develop-tests

D4.3 A/B tests and iteration

76. A team ships a new prompt after one week of higher scores. The score moved 2 points, and the traffic mix changed that week. The team needs to measure the prompt effect on the same traffic and period.

Select one answer.

A. Check this week against last week on the primary metric, since the prompt went live on Monday.

B. Split traffic into a control arm and a candidate arm with a fixed assignment rule, then compare the primary metric.

C. Run a shadow copy for every user, plus a 90-day holdout, before any arm is compared.

D. Turn on the Usage API arm tag, so each arm reports its own spend automatically.

Answer: B. A control arm and a candidate arm see the same period and traffic mix. The difference then reflects the change, not the traffic mix.

Trap. A check of this week against last week looks like a before and after test, but the traffic mix changed in between.

Source. https://platform.claude.com/docs/en/test-and-evaluate/develop-tests

77. A candidate model clears the quality floor by 3 points. Its cost per completed task is 25 percent higher than the control. The change ships only when it clears the floor and holds or lowers cost per completed task. Which choice meets this rule?

Select one answer.

A. Ship the candidate, because a higher quality score means the team meets its target.

B. Apply the effort discount to the candidate, which lowers its per-token price for every task.

C. Add three more arms with new prompts, and decide only after all of them report, to find a cheaper candidate.

D. Keep the control, because the candidate raises cost per completed task.

Answer: D. The candidate fails the cost rule because its cost per completed task rises. The control is the only choice that meets the rule.

Trap. A switch on the higher quality score looks right, but the change also has to hold or lower cost per completed task.

Source. https://platform.claude.com/docs/en/about-claude/models/optimizing-for-cost-and-intelligence

78. A team runs checkable tasks on a model whose default effort is high. The team needs lower cost per completed task, and the pass rate must stay the same. Which two changes meet both constraints?

Select two answers.

A. Run the first pass at low effort, and re-run only the failed tasks at high effort.

B. Set a higher effort on every task, so each pass rate improves before the cost check.

C. Measure the low-effort pass on the eval set, and confirm the pass rate before the change ships.

D. Turn on a discount for failed tasks, so each re-run costs nothing.

Answer: A, C. In Anthropic tests, low effort with failed tasks re-run at high effort cost about 40 percent less at the same pass rate. The eval set confirms the pass rate before the change ships.

Trap. A discount for failed tasks sounds like a cost fix, but the docs do not describe such a discount.

Source. https://platform.claude.com/docs/en/about-claude/models/optimizing-for-cost-and-intelligence

D4.4 Diagnosis at the correct layer

79. Cache read tokens dropped to zero after a team edited the tool list in a shared template. The model stayed the same. The team must name the changed layer first, with the smallest fix.

Select one answer.

A. Raise the cache duration to one hour, so the prefix stays cached while the tool list changes.

B. Read cache_miss_reason in the response, and fix the earliest changed block first.

C. Rewrite the whole prompt template, then measure hit rates over a month of traffic.

D. Turn on the streaming cache trace in the Console, which lists each changed block after every response.

Answer: B. The response reports the earliest point of divergence and its reason type. The first fix goes to that block, which confirms the layer before any other change.

Trap. A longer cache duration looks like a quick fix, but a changed prefix misses the cache at any duration.

Source. https://platform.claude.com/docs/en/build-with-claude/cache-diagnostics

80. An assistant gives different figures for the same question across three runs. The model and the prompt did not change. The team needs a check that flags unsupported answers, with no new model.

Select one answer.

A. Move the assistant to a larger model tier, since a stronger model returns the same figure on each run.

B. Enable a consistency flag in the Messages API that blocks answers with a figure that varies.

C. Run the same prompt several times, and flag answers that disagree on a key figure.

D. Route each question through three model tiers, and vote on the answer from all three.

Answer: C. Several runs of one prompt expose answers that disagree. Disagreement on a key figure signals a possible hallucination, and the check needs no new model.

Trap. A consistency flag in the Messages API sounds like a direct fix, but the docs do not describe such a flag.

Source. https://platform.claude.com/docs/en/test-and-evaluate/strengthen-guardrails/reduce-hallucinations

81. Cache reads fell after a prompt edit. Two later blocks also changed, so the first reason may hide the others. The team must find the fix and confirm it with cache evidence. Which two steps meet these constraints?

Select two answers.

A. Change the cache duration and the prompt wording in one release, to save a diagnosis round.

B. Fix the earliest divergence first, because later reasons can hide behind it.

C. Read cache_miss_reason from the usage export, which names each changed block.

D. Confirm the fix with the cache read token count on the next request.

Answer: B, D. The response reports only the earliest divergence, so later changes can stay hidden until that block is fixed. The cache read count on the next request confirms the fix.

Trap. The usage export sounds like the place for the miss reason, but the docs attach cache_miss_reason to the response itself.

Source. https://platform.claude.com/docs/en/build-with-claude/cache-diagnostics

D4.5 Optimization under quality floors

82. A nightly job scores 40,000 eval cases. No user waits for the result. The team wants the lowest token price, and every call that a user sees must stay synchronous.

Select one answer.

A. Stream the nightly job, so its first results arrive sooner at the same token price.

B. Move the nightly job to batch processing, and keep user-facing calls synchronous.

C. Raise the rate limit for the nightly job, so each call returns in one pass.

D. Build a custom queue service with retries, dashboards, and a priority lane for the nightly job.

Answer: B. The Message Batches API gives 50 percent off each token for work that can wait. Synchronous calls stay on the Messages API, so users keep fast answers.

Trap. Streaming the nightly job looks like a speed fix, but the job still pays the synchronous token price.

Source. https://platform.claude.com/docs/en/build-with-claude/batch-processing

83. A chat feature must meet a response time target. Easy and hard requests arrive on the same route. The quality floor is known for each request type. The team must cut cost only where the floor still holds.

Select one answer.

A. Route all traffic to the fastest tier at low effort, since it has the lowest latency for every request.

B. Train a learned router that scores each request, retrains weekly, and logs every routing decision.

C. Turn on the faster-mode flag for the stronger tier, which cuts latency and leaves the output as is.

D. Route easy request types to the faster tier at low effort, after each type clears the floor on the eval set.

Answer: D. A cheaper route saves cost only where it clears the quality floor. The faster tier at low effort then serves the easy types and keeps the floor.

Trap. Routing all traffic to the fastest tier looks like the simplest latency fix, but hard requests then miss the quality floor.

Source. https://platform.claude.com/docs/en/test-and-evaluate/strengthen-guardrails/reduce-latency

84. An unattended grader run has 150,000 requests. No user waits for the results. The run must fit the batch limits, and the team must read every result within the result availability period. Which two actions meet these constraints?

Select two answers.

A. Split the 150,000 requests into at least two batches, each within 100,000 requests and 256 MB.

B. Set a priority option that returns the batch within five minutes, which the Batch API offers.

C. Read each batch result within 29 days of batch creation, while the results are still available.

D. Move the run to a dedicated workspace with its own rate limits, and add a second model for every row.

Answer: A, C. A batch holds up to 100,000 requests or 256 MB, whichever limit comes first. Results stay downloadable for 29 days after creation.

Trap. A priority option for five-minute results sounds useful, but the docs do not describe one for batches.

Source. https://platform.claude.com/docs/en/build-with-claude/batch-processing

D4.6 Production monitoring

85. Monthly spend rose 30 percent while completed tasks stayed flat. The team needs an alert before the budget breaks. The alert must reflect the value of each task, and it needs a named owner.

Select one answer.

A. Alert on total token count per day, since token counts rise with spend.

B. Alert on 40 metrics, with latency, token counts, and per-user spend among them, each with its own owner.

C. Alert on cost per completed task, and name the owner who acts when the line breaks.

D. Set the Cost API to alert on one-minute buckets, so spend breaks show within a minute.

Answer: C. Cost per completed task shows whether spend buys finished work. A named owner turns the alert into a control that someone acts on. (Inference)

Trap. One-minute Cost API buckets look like faster alerts, but the Cost API supports only daily buckets.

Source. https://platform.claude.com/docs/en/manage-claude/usage-cost-api

86. The data rules allow only metadata in the observability destination. A request failed across three services. The team uses the Claude API and needs the order and timing of each hop for that one request.

Select one answer.

A. Export full content for every request, then search the prompts for the failed call.

B. Read the per-hop trace for the failed request, with metadata-only export.

C. Build a custom span format and tracing service before the next incident.

D. Turn on the claude_code.session.count metric, which records the timing of each hop.

Answer: B. A trace shows the order and timing of each hop in one request. Metadata-only spans still carry identifiers and timing, so the data rules hold.

Trap. The session count metric sounds like timing data, but it counts sessions as each one starts.

Source. https://platform.claude.com/docs/en/manage-claude/opentelemetry

87. A team pinned a model ID. Live quality dropped after an infrastructure update, and no code changed. The team must find the cause with evidence before it changes the model. Which two actions meet this constraint?

Select two answers.

A. Freeze the infrastructure that serves the model ID, so no update can change observable behavior.

B. Compare live metrics with the baseline from before the update, and record the model ID with each metric.

C. Rewrite the prompt with a new template and retrain the grader before any metric comparison.

D. Check prompt and data changes from the same period before the team changes the model ID.

Answer: B, D. A pinned ID fixes the weights, so the infrastructure that serves it remains a likely cause of the shift. A baseline and the change history point to the actual cause.

Trap. A setting that freezes the infrastructure sounds like a fix, but the docs describe no such setting.

Source. https://platform.claude.com/docs/en/about-claude/models/model-ids-and-versions

D5.1 Guardrails and safety controls

88. Users type free text into a support app that reaches the main model. The team needs a check before the main call. The check must return a parseable verdict that code can count.

Select one answer.

A. Add a stricter system prompt that tells the main model to refuse harmful messages, then send every message.

B. Screen each message with a lightweight model that returns a boolean verdict, and block a harmful verdict.

C. Screen each message with the main model at high effort, and store the full reasoning for each message.

D. Turn on the computer use classifiers for each message, since they scan text before the model reads it.

Answer: B. A lightweight model such as Haiku 5.5 screens the input before the main call. Structured output limits the screen to a boolean that code can parse and count.

Trap. A stricter system prompt looks like a control, but the model can still follow an injected instruction, and no code stops the call.

Source. https://platform.claude.com/docs/en/test-and-evaluate/strengthen-guardrails/mitigate-jailbreaks

89. A Claude Code agent must never run the deploy script. The system prompt forbids it, but the agent still proposes the command. The team needs a rule that Claude Code enforces before the command runs.

Select one answer.

A. Add three more sentences to the system prompt that repeat the deploy ban, and ask the agent to confirm.

B. Move the deploy script into a separate container with its own network policy, outside the reach of the agent.

C. Set the sandbox allowed domains to exclude the deploy host, so the script cannot reach it.

D. Add a deny rule for the deploy command in the permission settings, which Claude Code checks before it runs.

Answer: D. Claude Code evaluates deny rules first, and the model cannot override that result. A deny rule for the command blocks each attempt before the command runs.

Trap. A sandbox domain list sounds like it blocks the deploy, but that list controls only the hosts that sandboxed commands reach.

Source. https://code.claude.com/docs/en/permissions

90. An agent runs shell commands on a developer machine. Untrusted issue text can steer those commands. The shell must not reach unknown hosts. The Read tool must not open credential files. Which two settings meet both constraints?

Select two answers.

A. Run /sandbox to turn on the sandbox, and keep the allowed domain list empty until a task needs a host.

B. Add a sandbox denyRead entry for the credential files, so the Read tool cannot open them.

C. Run the agent in a separate virtual machine for each issue, with its own network and disk.

D. Add permission deny rules for the credential paths, so the Read tool cannot open those files.

Answer: A, D. The sandbox routes shell network traffic through a proxy, and its allowed domain list starts empty. Permission rules govern the built-in Read tool, which the sandbox does not cover.

Trap. A denyRead entry in the sandbox looks like it blocks the Read tool, but the sandbox does not stop that tool.

Source. https://code.claude.com/docs/en/sandboxing

D5.2 Risks and failure modes

91. A new agent loops overnight and drives API spend up. The team shares one organization across three projects. The team needs a monthly ceiling for each project and a stop for a single runaway loop.

Select one answer.

A. Set a monthly spend limit on each project workspace with alerts, and cap tool calls per run in code.

B. Raise the workspace rate limit, so the loop finishes its work within the same hour.

C. Set a spend limit on the Default Workspace that holds the project key.

D. Create a separate organization for each project, each with its own billing and dashboard.

Answer: A. A workspace spend limit caps monthly spend for each project, and alerts fire at thresholds that you choose. A call cap in code stops one runaway run within minutes. (Inference)

Trap. A higher rate limit looks like a fix for a stalled loop, but it allows more calls and raises spend.

Source. https://platform.claude.com/docs/en/manage-claude/workspaces

92. An audited workflow calls an alias for an earlier model. The output must stay fixed through a validation period. The team must also find any deprecated use before the retirement date.

Select one answer.

A. Keep the alias, since aliases for earlier models point to a fixed snapshot that never moves.

B. Move the workflow to the newest model now, and skip the replacement test to save time.

C. Pin a dated snapshot ID, and export usage by key and model to find deprecated use.

D. Build a shadow environment that replays every request to two model IDs, with a dashboard per token.

Answer: C. A dated snapshot ID stays fixed for the validation period. A usage export by key and model shows which calls still use deprecated models.

Trap. An alias for an earlier model sounds fixed, but it points to the most recent snapshot for that minor version.

Source. https://platform.claude.com/docs/en/about-claude/models/model-ids-and-versions

93. An assistant summarizes a long contract, and a wrong claim has a real cost. The model must stay the same. Each claim must point to source text. Which two controls meet these constraints?

Select two answers.

A. Use a larger model tier for summaries, because larger tiers invent fewer contract terms.

B. Ask for word-for-word quotes before the summary, because the contract is a long document.

C. Turn on contract mode, which blocks any summary that lacks a citation.

D. Remove each summary claim that has no source quote, after the quote check runs.

Answer: B, D. Quotes before the summary ground each claim in the text of the document. Claims with no quote are removed, so each claim that stays in the summary is checkable.

Trap. A larger model tier looks like the fix for invented terms, but the constraints keep the same model.

Source. https://platform.claude.com/docs/en/test-and-evaluate/strengthen-guardrails/reduce-hallucinations

D5.3 Human-in-the-loop validation

94. A managed agent can delete customer records through an MCP tool. A deletion cannot be undone. Each deletion must wait for a person to approve it before the tool runs.

Select one answer.

A. Subscribe to the session.status_idled webhook, which pauses the session before each deletion.

B. Run an offline reviewer job that samples sessions after each deletion, and reports the results weekly.

C. Add an approval service with a hook, a review queue, and a separate audit database for each tool.

D. Set the permission policy to always_ask for the delete tool, so the session pauses until a reply arrives.

Answer: D. The always_ask policy pauses the session until a reviewer answers the approval request. The pause happens before the tool runs, so the deletion waits for the answer.

Trap. The status idled webhook sounds like a pause control, but it only reports that a session went idle.

Source. https://platform.claude.com/docs/en/managed-agents/permission-policies

95. A Claude Code team wants a check on shell commands that no permission rule can express. The check must block a command that touches a production host before the command runs.

Select one answer.

A. Print a warning from the hook and exit with code 0, so the developer sees the reason.

B. Set permissionDecision to allow in the hook JSON, which lets the command run with a warning.

C. Add a PreToolUse hook on the shell matcher that exits with code 2 when the host check fails.

D. Route every shell command to an approval service with a review queue and a manual reply.

Answer: C. A PreToolUse hook that exits with code 2 prevents the tool call. The matcher limits the hook to shell commands, so other tools stay unaffected.

Trap. A warning printed from a hook with exit code 0 looks like a block, but the call continues.

Source. https://code.claude.com/docs/en/hooks

96. An agent edits files in a reversible way across 5,000 sessions each day. Review can happen after each action, and a tested undo path must exist. Which two steps meet these constraints?

Select two answers.

A. Set evaluated_permission to review, which pauses each file edit until a reviewer answers.

B. Sample sessions at a random rate for offline review, and send flagged actions to a human reviewer.

C. Test a rollback procedure before the run, so a flagged file edit can be reversed.

D. Require approval for every file edit before it runs, with a decision record for each edit.

Answer: B, C. Random sampling covers high volume at low review cost. (Inference) Flagged actions reach a person, and a tested rollback path makes each flagged edit reversible.

Trap. Setting evaluated_permission to review sounds like a pause control, but that field only reports the decision on each tool call event.

Source. https://platform.claude.com/docs/en/managed-agents/secure-deployment-monitoring

D5.4 Regulatory compliance and data controls

97. A clinic sends patient notes to the Messages API. The contract requires that prompts and responses not persist after each response. The clinic also tests prompts in the Console playground.

Select one answer.

A. Keep default retention, and encrypt each prompt in the clinic network before it leaves.

B. Enable ZDR for the organization, send API calls only with its keys, and keep patient data out of the playground.

C. Enable HIPAA readiness, which stops storage of prompts after each response.

D. Enable ZDR, and attach a customer-managed key to a new workspace for all stored data.

Answer: B. Zero data retention means Anthropic does not store prompts or responses at rest after the response returns. ZDR does not cover Console usage, so patient data stays out of the playground.

Trap. HIPAA readiness sounds like the no-storage setting, but it adds safeguards and does not require deletion after each response.

Source. https://platform.claude.com/docs/en/manage-claude/api-and-data-retention

98. A company must keep inference in the United States for a model at version 4.6 or later. The rule must hold even when application code omits the residency setting.

Select one answer.

A. Set the application server region to US, which keeps inference in the United States.

B. Set inference_geo to us on each request, and leave the workspace allowed list open.

C. Set default_inference_geo and allowed_inference_geos to us on the workspace.

D. Create a new workspace with US workspace geo, and set its default and allowed inference geos to us.

Answer: C. The default geo applies when a request omits inference_geo. The allowed list rejects any request that names another geo, so application code cannot skip the rule.

Trap. A region on the application server sounds like it sets inference location, but inference_geo controls where inference runs.

Source. https://platform.claude.com/docs/en/manage-claude/data-residency

99. A bank must hold its own keys for new stored data, and it must show who read which records. The audit record must remain after a key is revoked. Which two actions meet these constraints?

Select two answers.

A. Attach a customer-managed key to a new workspace before its first request.

B. Re-encrypt old workspaces under the customer key, with the key added after the first request.

C. Export Activity Feed events to an internal audit store on a schedule.

D. Create a separate workspace and customer key for every team, each with its own Compliance Access Key.

Answer: A, C. CMEK protects data written after the key takes effect, so a key set up before the first request covers all new data. The Activity Feed sits under the Anthropic key, so audit records survive a key revocation.

Trap. A key added after the first request sounds like it protects old data, but earlier data is not re-encrypted.

Source. https://platform.claude.com/docs/en/manage-claude/cmek

D5.5 Responsible AI

100. A marketplace moderates listings in six languages. The rules change every month. The team must update the rules without new labeled training data. Which design meets the constraint?

Select one answer.

A. Retrain a custom classifier for each language after every rule change.

B. Use the built-in safety classifiers as the marketplace rules.

C. Put the written rules and edge-case examples in the prompt, and constrain the verdict with a JSON schema.

D. Put the written rules in the prompt, and have a person approve every verdict before a listing goes live.

Answer: C. The written rules and examples in the prompt are the control, so a rule change needs an edit to text, not new training data. A JSON schema keeps each verdict parseable.

Trap. A custom classifier for each language looks rigorous, but each rule change then needs new labels and a new training cycle.

Source. https://platform.claude.com/docs/en/about-claude/use-case-guides/content-moderation

101. A compliance dashboard must count declined requests by policy area. The team cannot change the model. Which method meets the constraint?

Select one answer.

A. HTTP error responses look like the standard count, since each declined request returns an error status code.

B. Read stop_reason on each response, and count the stop_details category when stop_reason is refusal.

C. Read the category value from the usage field, which lists the policy area of each call.

D. Log every full prompt, response, and header for each call, then sort the logs by policy area.

Answer: B. A decline arrives as a regular response with the stop reason refusal, not as an error. The stop_details category names the policy area, so the count needs no error parsing.

Trap. HTTP error responses look like the standard count, but a decline returns a normal response with a stop reason.

Source. https://platform.claude.com/docs/en/build-with-claude/refusals-and-fallback

102. A release review asks for evidence that the product works for each user group. The review also asks which model the product uses. Select two actions that meet both requests.

Select two answers.

A. Build an evaluation set with a group label for each user group, and set a floor for each group.

B. Cite the model system card as the fairness result for product users.

C. Request subgroup fairness metrics that Anthropic publishes for each Claude model.

D. Record the model system card link and the exact model ID in the release record.

Answer: A, D. The per-group evaluation tests the product on its own users, and a floor blocks a release that fails one group. (Inference) The system card and the exact model ID document the model that the product uses.

Trap. A system card cited as fairness evidence looks sufficient, but the card describes model tests, not the product users.

Source. https://platform.claude.com/docs/en/resources/overview

D6.1 Structured discovery

103. A product owner asks for a fast and accurate answer bot. The team has no number for either word. The team must set a pass or fail check before any design work. Which step meets the constraint?

Select one answer.

A. Pick the largest model, and tune the wording until the demo looks accurate.

B. Enable a workspace spend limit so that the bot stays fast and accurate.

C. Set a metric, a threshold, and an owner, and add a weekly human panel to score every answer.

D. Convert fast and accurate into a latency threshold and a task fidelity score, with an owner who signs each threshold.

Answer: D. Task fidelity and latency are common success criteria, and each needs a threshold before design starts. The owner who signs each threshold is general practice. (Inference)

Trap. The largest model with tuned wording looks productive, but the team then builds toward a bar that nobody measured.

Source. https://platform.claude.com/docs/en/test-and-evaluate/develop-tests

104. A project team needs a monthly spend cap for its own traffic only. The cap must not include traffic from other teams. Which setup meets the constraint?

Select one answer.

A. Create a project workspace and a staging workspace, scope each API key, and set a spend limit on each.

B. Use the Default Workspace with a shared key, and set a spend limit there.

C. Create a workspace for the project, scope its API key to that workspace, and set a spend limit on it.

D. Set a per-minute rate limit on the project key, which caps the monthly spend.

Answer: C. A workspace has its own spend limit, and a key scoped to that workspace counts only toward it. The Default Workspace offers no spend limit, so the project needs its own workspace.

Trap. A spend limit on the Default Workspace looks like the simplest cap, but that workspace accepts no spend limit.

Source. https://platform.claude.com/docs/en/manage-claude/workspaces

105. A support bot team builds an evaluation set. The team wants a fast check loop and coverage of rare cases from real traffic. Select two actions that meet both requests.

Select two answers.

A. Score every answer with a human panel before each test run.

B. Add edge cases from real traffic to the test set.

C. Use code-based checks wherever the output format allows them.

D. Use the workspace spend limit as the pass threshold for each answer.

Answer: B, C. Code-based checks rank first in speed and reliability in the docs. Test sets should follow the real task mix and include edge cases.

Trap. A human panel on every answer looks thorough, but the docs call human grades slow and expensive.

Source. https://platform.claude.com/docs/en/test-and-evaluate/develop-tests

D6.2 Trade-off communication

106. A budget owner compares two models. Model X has a lower price per token. Model Y finishes each task with fewer requests. The owner must choose on the cost of one completed task. Which measure meets the constraint?

Select one answer.

A. Sum the token prices across all requests for one completed task, then compare the totals.

B. Compare the per-token list prices, since they are published and stable.

C. Build a per-developer cost dashboard with attribution before any comparison.

D. Read the price field in each Messages API response to compare the two models.

Answer: A. A lower token price does not show what a finished task costs. Compare models on cost per completed task, because you pay for completed tasks.

Trap. The lower per-token price looks cheaper, but the model that needs more requests can cost more per completed task.

Source. https://platform.claude.com/docs/en/about-claude/models/optimizing-for-cost-and-intelligence

107. A proposal moves a quality-sensitive task to a cheaper model tier. The team has no test on its own tasks. The decision must rest on measured quality and cost for real traffic. Which step meets the constraint?

Select one answer.

A. Switch the task to the cheaper tier, since its per-token price is lower.

B. Read the Usage and Cost API totals and treat them as a quality score for each answer.

C. Sample production tasks weighted like real traffic, and plot each tier score against its spend.

D. Rebuild the product on three providers, then run a six-month comparison on real traffic.

Answer: C. Production tasks show how each tier performs on real traffic. A score beside the spend shows whether the cheaper tier meets the bar at a lower cost per task.

Trap. A switch on the lowest per-token price looks like a saving, but the team then has no evidence that the cheaper tier meets the bar.

Source. https://platform.claude.com/docs/en/about-claude/models/optimizing-for-cost-and-intelligence

108. A finance audience and a security audience review a model option. The vendor claims zero risk and perfect accuracy. The record must give each audience the facts it decides on. Select two entries that meet this constraint.

Select two answers.

A. Attach the Usage and Cost API export as proof of zero risk.

B. State the cost per completed task with the date of the price list.

C. Show the per-token list price alone as the cost field for each option.

D. Name the measured accuracy with its evaluation set, and give an uncertainty beside it.

Answer: B, D. Finance decides on cost per completed task, and list prices drift over time. Security needs a measured figure with its evaluation set and uncertainty, not an absolute claim. (Inference)

Trap. An attached usage export looks like evidence, but that report measures spend, not risk.

Source. https://platform.claude.com/docs/en/about-claude/models/optimizing-for-cost-and-intelligence

D6.3 Feedback and expectation alignment

109. A finance lead wants daily cost totals in USD for each team workspace. The script must use credentials that the usage and cost endpoints accept. Which setup meets the constraint?

Select one answer.

A. Call the usage and cost endpoints with the workspace API key that the script already holds.

B. Set the Cost API bucket to one minute to get finer daily totals.

C. Stream each response usage field into a warehouse, and rebuild the totals every hour.

D. Call the usage and cost endpoints with an Admin API key, and read the daily cost report by workspace.

Answer: D. The usage and cost endpoints accept Admin API credentials only, so a workspace key fails. The Cost report gives daily totals in USD, and it can group them by workspace.

Trap. A workspace API key looks sufficient for a script, but the usage and cost endpoints do not accept workspace keys.

Source. https://platform.claude.com/docs/en/manage-claude/usage-cost-api

110. An on-call engineer must see a traffic spike within seconds. The team has a usage report and a cost report. The team cannot wait for a daily total. Which action meets the constraint?

Select one answer.

A. Poll the Usage and Cost API once per minute and alert on each new total.

B. Set a monthly spend alert on the workspace to catch a spike within seconds.

C. Read the usage fields in each live response, and log them as responses return.

D. Add a live response log, and also run a weekly cost review with finance.

Answer: C. The aggregate reports typically lag each request by up to 5 minutes, so they are too slow for this check. Per-response usage fields report each call as it completes.

Trap. Polling the usage endpoints every minute looks fast, but the aggregate data can trail each request by up to 5 minutes.

Source. https://platform.claude.com/docs/en/manage-claude/usage-cost-api

111. A company runs one workspace for each team. The owner wants a monthly budget for each team and rate limits for each model. Select two settings that meet both requests.

Select two answers.

A. Set a monthly spend limit and alerts on each team workspace.

B. Set a per-minute spend limit on each workspace to cap traffic bursts.

C. Set rate limits per model on requests, input tokens, and output tokens per minute.

D. Put every team on the Default Workspace, and set one spend limit there.

Answer: A, C. A spend limit and its alerts apply to one workspace, so each team gets its own budget. Rate limits cap requests and tokens per minute for each model.

Trap. One spend limit on the Default Workspace looks like a shared budget, but that workspace accepts no spend limit.

Source. https://platform.claude.com/docs/en/manage-claude/workspaces

D6.4 Architecture documentation

112. A decision record names a model by family only. A successor cannot tell which model the evaluation measured. The record must name the measured model exactly. Which entry meets the constraint?

Select one answer.

A. Attach the full evaluation notebook and every raw response to the record.

B. Write the exact model ID and the platform in the record.

C. Record the model family name only, since the family name identifies the model.

D. Record the API version header as the model ID for the evaluation.

Answer: B. From the 4.6 generation on, a dateless ID names one fixed snapshot. The exact ID and the platform let a successor identify the measured model.

Trap. A model family name looks like enough, but it does not name the snapshot that the evaluation measured.

Source. https://platform.claude.com/docs/en/about-claude/models/model-ids-and-versions

113. A decision record names a model ID. The platform posts a retirement notice with a date for that ID. The notice names a replacement model. The team must keep the record accurate and avoid an outage on that date. Which action meets the constraint?

Select one answer.

A. Record the retirement date beside the ID, then test the named replacement before that date.

B. Keep the ID in the record, since a dateless ID is a fixed snapshot that never retires.

C. Freeze all model work for the year, and rebuild every decision record from scratch.

D. Add the Usage page CSV to the record as the model version number.

Answer: A. Every model ID has its own retirement schedule, and a notice sets the date. A tested replacement lets the team move traffic before that date.

Trap. A dateless ID looks permanent, but it is a fixed snapshot that still follows its own retirement schedule.

Source. https://platform.claude.com/docs/en/about-claude/model-deprecations

114. A team writes a decision record for a Claude model in production. A successor must run the system later and must check the decision. Select two entries that meet both needs.

Select two answers.

A. Record the model family and let the successor choose the newest model.

B. Record the workspace spend limit as the model version for the decision.

C. Record the exact model ID with its platform and deprecation date.

D. Write the review criteria that reopen the decision as measurable thresholds.

Answer: C, D. The exact ID, the platform, and the deprecation date tell a successor what runs and when it retires. Measurable review criteria tell the successor when to reopen the decision. (Inference)

Trap. A model family name looks like a stable reference, but it does not identify the snapshot that was measured.

Source. https://platform.claude.com/docs/en/about-claude/models/model-ids-and-versions

D6.5 Lifecycle phases

115. A release moves the client to API version 2026-10-21. Every request now fails with a 400 error, because the client sends a temperature value. The fix must remove the cause and pass a test gate before release. Which action meets the constraint?

Select one answer.

A. Keep the temperature value, and add a retry with backoff, since the error may clear.

B. Raise the workspace rate limit, so that the 400 errors clear.

C. Remove the temperature value, and also rewrite the prompts and logs before the test gate.

D. Remove the temperature value from each request, then run the test gate before release.

Answer: D. The 400 error comes from a parameter that the new API version removes. The parameter removal fixes the cause, and the test gate confirms the release before traffic moves. (Inference)

Trap. A retry with backoff looks like a standard fix, but the parameter itself causes the 400 error on each request.

Source. https://platform.claude.com/docs/en/api/versioning

116. A deprecation notice names a retirement date for a model that the production service calls. The notice names a replacement. The team must avoid an outage on the retirement date. Which action meets the constraint?

Select one answer.

A. Wait for the retirement date, then switch the model in one release.

B. Export usage by API key and model, test the named replacement, and move traffic before the date.

C. Move the whole product to a new cloud platform, and rewrite its prompts before the date.

D. Keep the retired model on a backup route, which still returns answers after the date.

Answer: B. The usage export lists each API key and model, so the team finds every caller of the old model. The test and the move come before the date, because requests to a retired model fail.

Trap. A switch at the retirement date looks simple, but requests to a retired model fail after that date.

Source. https://platform.claude.com/docs/en/about-claude/model-deprecations

117. A team runs development and production traffic in one shared workspace. The team needs separate rate limits and separate cost reports for each environment. Select two changes that meet both requests.

Select two answers.

A. Create a production workspace, and scope the production API key to it.

B. Rename the Default Workspace to production, since the Default Workspace can be renamed.

C. Create a development workspace, and set lower rate limits on it than on production.

D. Keep one workspace, and add an environment label to each API key name.

Answer: A, C. Each request runs in exactly one workspace, so each environment needs its own workspace for keys, limits, and reports. The Default Workspace cannot be renamed, so the team creates new workspaces instead.

Trap. A rename of the Default Workspace looks like the quickest split, but that workspace cannot be renamed.

Source. https://platform.claude.com/docs/en/manage-claude/workspaces

D7.1 Team configuration for Claude Code

118. A team wants the agent to never read files in a secrets folder, in every clone. A note in CLAUDE.md asks the agent to avoid that folder. The block must hold even when the model ignores the note. Which change meets the constraint?

Select one answer.

A. Deploy the deny rule in managed settings, and add a sandbox on every developer machine.

B. Add the deny rule to the personal local settings of the team lead only.

C. Add a Read deny rule for the secrets folder in the committed settings file.

D. Add a PostToolUse hook that blocks reads of the secrets folder.

Answer: C. A deny rule in the committed settings file reaches every clone after a pull. The rule blocks the read before the tool runs, so the result does not depend on the model.

Trap. A PostToolUse hook that blocks reads looks like enforcement, but that hook runs only after the tool call succeeds.

Source. https://code.claude.com/docs/en/permissions

119. A team wants a research subagent that only reads files. The subagent must not receive any write tool. Which setup meets the constraint?

Select one answer.

A. Set the tools field to Read and Grep, and add a second reviewer subagent for each folder.

B. Create the subagent without a tools field, and add a CLAUDE.md line that forbids edits.

C. Set the model field to read-only, which blocks write tools for the subagent.

D. Set the subagent tools field to Read and Grep only.

Answer: D. The tools field limits the tools that a subagent can use. Read and Grep cannot write files, so the role stays read-only.

Trap. A CLAUDE.md line that forbids edits looks like a restriction, but a subagent without a tools field inherits every tool.

Source. https://code.claude.com/docs/en/sub-agents

120. A team needs one enforced rule on every clone. One developer also needs a personal exception that does not weaken the team rule. Select two actions that meet both needs.

Select two answers.

A. Commit the team deny rule in the shared settings file.

B. Put the team deny rule in the user settings file of each developer.

C. Put a personal allow rule for one extra command in the local settings file, which stays out of git.

D. Put the team deny rule in CLAUDE.md, which Claude Code enforces as a permission.

Answer: A, C. The shared settings file applies to every clone after a pull. The local file stays out of git, and a deny rule from any scope still applies.

Trap. A personal settings file looks flexible, but it cannot enforce the rule across the team.

Source. https://code.claude.com/docs/en/settings

D7.2 AI-assisted workflows with Claude Code

121. A CI job runs Claude Code to check a pull request. The job must restrict the run to the Read and Grep tools. A failed run must fail the job. Which command setup meets both constraints?

Select one answer.

A. Run claude -p with --allowedTools set to Read and Grep, then check the exit status.

B. Run claude -p with --json-schema, which limits the tools that the run can use.

C. Run claude -p with --tools set to Read and Grep, then check the exit status in the next CI step.

D. Run claude -p with --tools set to Read and Grep, check the exit status, and store every transcript in a database.

Answer: C. The --tools flag restricts which built-in tools exist for the run. The exit status tells the CI step whether the run succeeded.

Trap. An --allowedTools list looks like a restriction, but the flag only lets the listed tools run without a prompt.

Source. https://code.claude.com/docs/en/cli-reference

122. A script runs Claude Code and reads one typed field from the reply. The script must also record the total cost of each run. Which setup meets both constraints?

Select one answer.

A. Run with --output-format json and --json-schema, then read structured_output and total_cost_usd.

B. Parse the free-text reply with a pattern match, and skip the cost field.

C. Run with --output-format json and --json-schema, and store every full transcript in a database.

D. Run with --tools set to a fixed list, and read the per-model breakdown from the --tools output.

Answer: A. The json output format with a schema returns typed fields in structured_output. The JSON output also includes total_cost_usd for each run.

Trap. A pattern match on free text looks simple, but it gives the script no typed field and no cost value.

Source. https://code.claude.com/docs/en/headless

123. A team wants one credential for six repositories that run comment-triggered workflows. The credential must not depend on the subscription of one person. Select two actions that meet the constraint.

Select two answers.

A. Run the setup-token command, and store the OAuth token as one organization-level secret.

B. Create an API key in the Claude Console for the shared secret.

C. Set the use_bedrock input to true, which shares one credential across repositories.

D. Store one organization-level Actions secret that all six repositories share.

Answer: B, D. The OAuth token is tied to one subscription, but an API key from the Claude Console can serve a shared secret. An organization-level Actions secret lets the repositories share one stored copy.

Trap. An OAuth token from the setup command looks easy to share, but it is tied to the subscription of one person.

Source. https://code.claude.com/docs/en/github-actions

D7.3 Diagnosis and operational resolution

124. A hook in the shared settings file does not run after edits. The team must find out whether the hook is loaded. The check must not change any file. Which action meets the constraint?

Select one answer.

A. Run /hooks, then start with claude --debug, and export the metrics to a collector.

B. Run /hooks in the current session to see the hook configuration.

C. Add a CLAUDE.md line that asks Claude to run the hook after each edit.

D. Run /context to list each hook match and its exit code.

Answer: B. The /hooks command shows the hook configurations in the current session. The command only reads configuration, so no file changes.

Trap. A CLAUDE.md line that asks for the hook looks like a fix, but a guidance note never starts a hook.

Source. https://code.claude.com/docs/en/commands

125. Cost rose after a prompt change in the sessions of one team. The team must find the cause before it changes the model. The first step must use per-session data. Which action meets the constraint?

Select one answer.

A. Switch to a smaller model at once, since a smaller model lowers the cost of each session.

B. Check claude_code.session.count to see the cost of each prompt.

C. Run /usage in each affected session to read its cost.

D. Export OpenTelemetry metrics to a team collector, and build a cost dashboard before any session is checked.

Answer: C. The /usage command shows the cost of the current session. Per-session cost identifies the affected sessions before any model change.

Trap. A smaller model looks like the fastest cost fix, but it may miss the cause and can lower answer quality.

Source. https://code.claude.com/docs/en/costs

126. An agent edit must be undone. Some changes came from a Bash command that changed files Claude never edited. The undo must cover both kinds of change. Select two actions that meet the constraint.

Select two answers.

A. Use /rewind to undo the tracked Claude edits from the recent checkpoints.

B. Press Esc twice to rewind the Bash-only file change, since rewind covers every change.

C. Set cleanupPeriodDays to 90 to restore snapshots that were already deleted.

D. Use version control to revert the files that only the Bash command changed.

Answer: A, D. Rewind restores file edits that Claude tracked, within the checkpoints that the session keeps. Files that only a Bash command changed are not tracked, so version control reverts them.

Trap. A double Esc press looks like a full undo, but rewind does not track Bash changes to files that Claude never edited.

Source. https://code.claude.com/docs/en/checkpointing