



Visibility

CS 355: Interactive Graphics and Image Processing

Two Parts of 3D Rendering


- Two key parts of 3D rendering:
 - What is visible where? (*Visibility*)
 - What light is coming from there? (*Lighting*)

Visibility

- Parts of visibility:
 - ✓ Where is everything relative to the camera?
(world-to-camera transformation)
 - ✓ What is within the field of view?
(clip matrix)
- What is in front of what else?


Back-Face Culling

- Simple idea:
 - Faces that point *towards* camera may be seen
 - Faces that point *away* from camera cannot be seen




Occlusion Testing

- See what is in front of what else
- Test for things that fall on the same camera position
- If opaque, one object *occludes* the other



Occlusion Testing

- Three common ways:
 - Ordered rendering (painter's algorithm)
 - Image space testing (z-buffering)
 - Ray casting



Painter's Algorithm

- Simple idea:
 - Render from back to front (decreasing z)
 - Draw things over top of others on screen
 - Last one drawn wins!
- Big problem:
 - Polygon depth isn't strictly ordered
 - Intersecting
 - Mutually overlapping

This technique isn't used much anymore,
but the idea shows up in lots of places

Z-Buffering


canonical screen coordinates

$$\begin{bmatrix} x/w \\ y/w \\ z/w \\ 1 \end{bmatrix} \sim \begin{bmatrix} x \\ y \\ z \\ w \end{bmatrix} = \begin{bmatrix} \text{zoom}_x & 0 & 0 & 0 \\ 0 & \text{zoom}_y & 0 & 0 \\ 0 & 0 & \frac{f+n}{f-n} & 0 \\ 0 & 0 & \frac{-2nf}{f-n} & 1 \end{bmatrix} \begin{bmatrix} X_c \\ Y_c \\ Z_c \\ 1 \end{bmatrix}$$

normalized depth


Z-Buffering

- Keep an image buffer that stores the depth of what is currently rendered at each pixel
- Render in any order
- Drawn new stuff *only if closer*




Z-Buffering

- Issue:
Quantization of the
finite-precision z buffer
- Round-off error may
be an issue (most use
floating point)
- Nonlinear by depth
(coarser farther away)



Z-Buffering


- Issue:
Discretization of the
image z buffer
- Hard to do antialiasing
(partial painting of
pixels on boundaries)



Ray Casting


- Idea: shoot a ray out from the camera's focal point through the pixel location
- What does it hit first?
- Lots of ray-primitive intersection tests

(Arthur Appel, 1968)



Objects & Bounding Boxes

- Almost all of these ideas can be accelerated by grouping primitives and using bounding boxes
- Typically AABBs in original object space
- Transform to a general BB in camera space
- Throw out if all corners are out of view, not visible, etc.



Coming up...

- Lighting