


Web Mining : Accomplishments & Future Directions

Jaideep Srivastava
University of Minnesota
USA

svivasta@cs.umn.edu
<http://www.cs.umn.edu/faculty/srivasta.html>

Mr. Prasanna Desikan's help in preparing these slides is acknowledged



Web Mining



- *Web* is a collection of inter-related files on one or more *Web servers*.
- Web mining is
 - the application of data mining techniques to extract knowledge from Web data
- Web data is
 - Web content – text, image, records, etc.
 - Web structure – hyperlinks, tags, etc.
 - Web usage – http logs, app server logs, etc.



Pre-processing Web Data

❑ Web Content

- Extract “snippets” from a Web document that represents the Web Document


❑ Web Structure

- Identifying interesting graph patterns or pre-processing the whole web graph to come up with metrics such as PageRank

❑ Web Usage

- User identification, session creation, robot detection and filtering, and extracting usage path patterns

Web Usage Mining



What is Web Usage Mining?



- A *Web* is a collection of inter-related files on one or more *Web servers*
- *Web Usage Mining*
 - ➔ Discovery of meaningful patterns from data generated by client-server transactions on one or more Web localities
- Typical Sources of Data
 - ➔ automatically generated data stored in server *access logs*, *referrer logs*, *agent logs*, and client-side *cookies*
 - ➔ user profiles
 - ➔ meta data: page attributes, content attributes, usage data

ECLF Log File Format



IP Address	rfc931	authuser	Date and time of request	request	status	bytes	referer	user agent
128.101.35.92	-	-	[09/Mar/2002:00:03:18 -0600]	"GET /~harum/ HTTP/1.0"	200	3014	http://www.cs.umn.edu/	Mozilla/4.7 [en] (X11; I; SunOS 5.8 sun4u)

IP address: IP address of the remote host

Rfc931: the remote login name of the user

Authuser: the username as which the user has authenticated himself

Date: date and time of the request

Request: the request line exactly as it came from the client

Status: the HTTP response code returned to the client

Bytes: The number of bytes transferred

Referer: The url the client was on before requesting your url

User_agent: The software the client claims to be using



Issues in Usage Data

- ❖ Session Identification
- ❖ CGI Data
- ❖ Caching
- ❖ Dynamic Pages
- ❖ Robot Detection and Filtering
- ❖ Transaction Identification
 - ✓ Identify Unique Users
 - ✓ Identify Unique User transaction

Session Identification Problems



- “AOL Effect”: Single IP Address/ Multiple Users
 - ISP Proxy Servers
 - Public Access Machines
- “WebTV Effect”: Multiple IP Addresses/ Single Session
 - Rotating IP for load balancing
 - Privacy tools

Session Identification Solutions




- Cookies - small piece of code that is saved on the client machine
- User Login – Require user to use login ID with password
- Embedded SessionID.
- IP+Agent.
- Client-side tracking

Caching Problems





- Clients and Proxy Servers save local copies of pages that have been accessed
- Uses of the “back” and “forward” buttons on a browser may access local copy instead of requesting a new one from the server

Server Log Incompleteness due to Caching



Access pattern: index, page1, index, page2
Record in server log:: index, page1, page2


Wrong Access Timings Recorded at Server




Missed Page Views at Server



- Viewing time for cached pages



Caching Solutions



- Dynamic content greatly reduces the number of cached page accesses
 - Advantages: Fewer “missed” page views
 - Disadvantages: Increased Server traffic
- “Negative” expiration dates for pages force browsers to request a new version

Associations in Web Transactions



- Association Rules:

- ➔ discovers affinities among sets of items across transactions

$$X \xrightarrow{\alpha, \sigma} Y$$

where X, Y are sets of items, $\alpha = \text{confidence}$, $\sigma = \text{support}$

- Examples:

- ➔ 60% of clients who accessed `/products/`, also accessed `/products/software/webminer.htm`.

- ➔ 30% of clients who accessed `/special-offer.html`, placed an online order in `/products/software/`.

- ➔ (Actual Example from IBM official Olympics Site)

- $\{\text{Badminton, Diving}\} \Rightarrow \{\text{Table Tennis}\} (\alpha = 69.7\%, \sigma = 0.35\%)$

Other Patterns from Web Transactions



- Sequential Patterns:
 - 30% of clients who visited `/products/software/`, had done a search in **Yahoo** using the keyword “software” before their visit
 - 60% of clients who placed an online order for WEBMINER, placed another online order for software within 15 days
- Clustering and Classification
 - clients who often access `/products/software/webminer.html` tend to be from educational institutions.
 - clients who placed an online order for software tend to be students in the 20-25 age group and live in the United States.
 - 75% of clients who download software from `/products/software/demos/` visit between 7:00 and 11:00 pm on weekends.

Path and Usage Pattern Discovery



- Types of Path/Usage Information
 - Most Frequent paths traversed by users
 - Entry and Exit Points
 - Distribution of user session durations / User Attrition
- Examples:
 - 60% of clients who accessed `/home/products/file1.html`, followed the path `/home ==> /home/whatsnew ==> /home/products ==> /home/products/file1.html`
 - (Olympics Web site) 30% of clients who accessed sport specific pages started from the *Sneakpeek* page.
 - 65% of clients left the site after 4 or less references.

Implications of Web Usage Mining for E-commerce




- Electronic Commerce
 - determine lifetime value of clients
 - design cross marketing strategies across products
 - evaluate promotional campaigns
 - target electronic ads and coupons at user groups based on their access patterns
 - predict user behavior based on previously learned rules and users' profile
 - present dynamic information to users based on their interests and profiles

Implications for Other Applications



- Effective and Efficient Web Presence
 - determine the best way to structure the Web site
 - identify “weak links” for elimination or enhancement
 - A “site-specific” web design agent
 - Pre-fetch files that are most likely to be accessed
- Intra-Organizational Applications
 - enhance workgroup management & communication
 - evaluate Intranet effectiveness and identify structural needs & requirements

Web Content Mining




Definition



- ❖ Web Content Mining is the process of extracting useful information from the contents of Web documents.
 - Content data corresponds to the collection of facts a Web page was designed to convey to the users. It may consist of text, images, audio, video, or structured records such as lists and tables.
- ❖ Research activities in this field also involve using techniques from other disciplines such as Information Retrieval (IR) and natural language processing (NLP).

Pre-processing Content



Content Preparation

- Extract text from HTML.
- Perform Stemming.
- Remove Stop Words.
- Calculate Collection Wide Word Frequencies (DF).
- Calculate per Document Term Frequencies (TF).

Vector Creation

- Common Information Retrieval Technique.
- Each document (HTML page) is represented by a sparse vector of term weights.
- TFIDF weighting is most common.
- Typically, additional weight is given to terms appearing as keywords or in titles.



Common Mining Techniques

The more basic and popular data mining techniques include:

- ❖ Classification
- ❖ Clustering
- ❖ Associations

The other significant ideas:

- ❖ Topic Identification, tracking and drift analysis
- ❖ Concept hierarchy creation
- ❖ Relevance of content.



Document Classification

- “Supervised” technique
- Categories are defined and documents are assigned to one or more existing categories
- The “definition” of a category is usually in the form of a term vector that is produced during a “training” phase
- Training is performed through the use of documents that have already been classified (often by hand) as belonging to a category

Document Clustering




- “Unsupervised” technique
- Documents are divided into groups based on a similarity metric
- No pre-defined notion of what the groups should be
- Most common similarity metric is the dot product between two document vectors

Topic Identification and Tracking



- Combination of Clustering and Classification
- As new documents are added to a collection
 - An attempt is made to assign each document to an existing topic (category)
 - The collection is also checked for the emergence of new topics
 - The drift in the topic(s) are also identified



Concept Hierarchy Creation

- Creation of concept hierarchies is important to understand the category and sub categories a document belongs to
- Key Factors
 - Organization of categories; e.g. Flat, Tree, or Network
 - Maximum number of categories per document.
 - Category Dimensions; e.g. Subject, Location, Time, Alphabetical, Numerical



Web Content Mining Applications

- ❖ Identify the topics represented by a Web Documents
- ❖ Categorize Web Documents
- ❖ Find Web Pages across different servers that are similar
- ❖ Applications related to relevance
 - ✓ Queries – Enhance standard Query Relevance with User, Role, and/or Task Based Relevance
 - ✓ Recommendations – List of top “n” relevant documents in a collection or portion of a collection.
 - ✓ Filters – Show/Hide documents based on relevance score