

# King Basics for Ada Software Engineers

*Jeffrey R. Carter*  
*2023 March*

## Introduction

King is a high-level, strongly typed, general-purpose language for engineering software inspired by my many decades of software engineering and the many languages I have been exposed to. It has modules for encapsulation and information hiding, high-level concurrency, user-defined numeric types, fixed-point types, non-numeric enumeration types, maps, sequences, sets, and run-time checks. It does not have arrays, pointers, go-to statements, or programming by extension.

Contrary to popular belief, "King" is not an acronym, and does not stand for Knowledgeable, Intelligent, Nice, and Great. Nor is it intended to mean that King is the king of languages. Instead, it is named for Ada King (née Byron), the Countess of Lovelace, who should be familiar to all Ada software engineers.

This document is intended for people with good Ada and software engineering knowledge. Many features will be explained by reference to similar features in Ada or to software engineering concepts. As with Ada, understanding visibility is key to understanding King, and a good grasp of Ada's visibility concepts is essential.

## Hello World

It is customary to begin such a document with the traditional "Hello, World" program. Here it is in King:

```
-- The traditional Hello-World program

use King.IO.Text;

Hello_World : procedure body is
    Message = "Hello, World!"; -- This is a named string
Hello_World : begin
    King.IO.Text.Put_Line (Line => Message); -- Implicitly converted to String
Hello_World : when E =>
    E.Raise;
Hello_World : end procedure;
```

This should be pretty clear. The main difference from Ada is the `Name : syntax` for most constructs and the exception handling. `Hello_World` is a library-level, parameterless, main-program procedure body, which is the only kind of subprogram unit allowed at library-level. It is also the only kind of subprogram body that does not complete a separate specification.

The first line is a comment. King comments are identical to Ada comments.

The next line is a `use` statement, which is equivalent to Ada's `with` statement. It makes the named module visible to the compilation unit. Unlike Ada's `with`, a `use` statement also makes the primitive operators of types declared in the module directly visible. The primitive operators of enumeration types include the enumeration literals. A `use` statement may only name a single module. King has no equivalent to Ada's `use` statement. As in Ada, all statements are terminated by a semicolon.

The next non-null line introduces a procedure body named `Hello_World`. Unlike Ada, the name comes first, followed by a colon, as with object declarations. Procedures with parameter lists have them between procedure and the terminating semicolon for a procedure specification, and between procedure and body for a procedure body. Functions are similar, but use the reserved word `function` and have `return subtype` after the parameter list.

The next line declares a *named string*. Ada has named numbers; King has *named values*, which include Ada's named numbers, but also include named strings and *named characters*. There can only be one name in a named-value declaration. Character literals and named characters have type `universal_character` (any Unicode character), and string literals and named strings have type `universal_string` (sequences of `universal_character`). These are implicitly converted to any character or string type, much as universal numeric types are implicitly converted to any corresponding numeric type. King also implicitly converts values of `universal_integer` to `universal_real` when needed.

This declaration is nested directly in `Hello_World`, and so is indented one indentation level of 3 spaces (tabs are not allowed in King source text). Indentation in King directly reflects the nesting level of statements. This results in slightly different indentation in some cases than Ada, in which standard formatting sometimes indents things more than their nesting level.

The next line is a `begin`, which terminates the declarative region and separates it from the executable statements. The procedure name must precede `begin` as shown. While the repetitions of the procedure name are overkill for a short example like this, in real software it can significantly improve readability. Having separate declarative regions makes it easier to find declarations when reading code.

The **when** line terminates the executable statements and introduces the exception handler. Every subprogram must have an exception handler, to document that all possible exceptions have been considered. The procedure name must begin this line.

The reserved word **when** is followed by a name for the `Exception_Occurrence` being handled and an arrow. `Exception_Occurrence` is a predefined module type described more fully later; all exceptions are of this type. Procedure `Raise` is defined for the type, and raises the exception. The exception handler here is the form when no exception handling is needed. There is a special

form of the case statement for dealing with different exceptions when exception handling is needed. It will be described later.

Finally, the end line terminates the procedure just as in Ada, except for the position of the name, which is mandatory, and repeating that this is a procedure.

Except for the spaces around the comment symbol and in comments, all of the spaces in this example are required.

## Modules

No language is worth using if it lacks explicit support for modularity. King modules are similar to packages in Ada. Unlike packages, they do not have any equivalent to private parts and cannot contain declarations of variables of assignable types in the specification. Like most things in King, they come in two parts: the specification and the body. Modules implement the software-engineering concepts of encapsulation and information hiding.

### Example

As a trivial example consider a very poor random-number generator:

```
-- A very poor random-number generator

Bad_Random : module is
  type State is hidden;
  -- Initial value is the result of calling Set_Seed with a
  -- Seed of Result'Last

  type Result is range 0 .. 2 ^ 16 - 1 with
    Signed_Representation => False,
    Overflow_Checking => False;

  Set_Seed : procedure (State : out State; Seed : in Result <- Result'Last);
  -- Sets State to produce the sequence of values defined by
  -- Seed

  Random : function (State : in out State) return Result;
  -- Returns the next value in the sequence defined by State
  -- and updates State accordingly
Bad_Random : end module;
```

This is a module specification. Here **State** is a *hidden type*. Its full declaration will be a record type in the module body. No operations are implicitly defined for a hidden type except assignment and the membership tests `in` and `not in`. Given an object `O` of a composite type, one can call a primitive operation `Op` with a first parameter of the type using `Object.Operation` notation: `O.Op`;

**Result** is an unsigned integer type with  $2^{16}$  values and no overflow checking, similar to an equivalent modular type in Ada (King uses `^` for exponentiation). Note the aspect clauses for the declaration, which are similar to Ada's. By default, integer types have `Signed_Representation => True` and

Overflow\_Checking => True. Both of these aspects apply to the base type, **Result'Base**, which in this case should be the same as **Result**.

The combinations of these two aspects yields four kinds of integer types, compared to Ada's two.

Numeric literals can be given as here for base 10, or with Ada's based-literal notation for any base from 2 to 36, including 10. Letters used for digits greater than 9 must be capitals, as must the E that introduces an exponent.

The module contains two subprogram specifications.

Procedure **Set\_Seed** has a parameter named **State** that has subtype **State**. This demonstrates that subtype names come from a different namespace than other identifiers; when the same identifier is used as a subtype name and another identifier, as here, the namespace that an identifier belongs to is clear from context. **Seed** has a default value of **Result'Last** as indicated by the assignment symbol **<-** followed by the default value, so one can call the procedure without supplying a value for that parameter.

Function **Random** uses and changes its parameter and returns the next random value.

Parameter modes (**in**, **in out**, and **out**) are required for all subprogram parameters. Each parameter in a parameter list must have its own mode and subtype.

A module specification that declares something that must be completed must be completed by a module body:

```
Bad_Random : module body is
  type State is record -- Full type must be a record
    Seed : Result is Result'Last;
  end record State;

  Set_Seed : procedure (State : out State; Seed : in Result <- Result'Last) is
    (State.Seed <- Seed);

  Random : function (State : in out State) return Result body is
    null; -- Declarative region must have a declarative item
  Random : begin
    State.Seed <- State.Seed + 1;

    return State.Seed; -- I told you this is a bad RNG
  Random : when E =>
    E.Raise;
  Random : end function;
Bad_Random : begin
  null;
Bad_Random : when E =>
  E.Raise;
Bad_Random : end module;
```

The component **Seed** of type **State** has an explicit default initial value of **Result'Last**. Initial values are introduced by **is** rather than the assignment symbol as in Ada. As we've seen, named values are introduced by **=**, and

defaults that are not initial values by <-. In the absence of explicit initial values, objects and components of most scalar types are initialized to the 'First of their subtypes unless they have the `Default_Value` aspect specified.

Components of record types are nested directly within the type, so they must be indented one indentation level. This imposes formatting of record types as shown, unlike the formatting used by the Ada Reference Manual (ARM).

`Set_Seed` is an example of a statement procedure, which is defined fully later.

As noted in the comment, a declarative region must have at least one declarative item. The null declaration, used here, must appear if there are no others.

Assignment statements are much as in Ada, except for the assignment symbol.

Incrementing `Seed` should overflow and wrap around to zero when its value is `Result'Last`.

Module bodies have a sequence of statements for elaboration and an exception handler for those statements, and these must be given for all modules.

## ***Compiling Hidden Types***

King has separate compilation similar to Ada's, and it is possible to compile code that uses a module specification before the module body is available. Some may wonder how a compiler can deal with a unit that declares an object of type `State` if the module body is not available. How much space should be allocated for the object? How should it be initialized? One option is to introduce a level of indirection. However, the expected way it should be handled is for the compiler to do incremental compilation, and the final increment and code generation to happen when all the bodies in the system are available, but retaining the information from previous increments to minimize the effort. Incremental compilers existed in 1984, so we should be able to do this now.

In this way the need for indirection can be avoided, because the increment when the full type becomes known allows for enough space to be allocated and initialization to be arranged. The compiler would also be expected to expand calls to `Set_Seed` in line, if that would be an optimization, after its body becomes available.

## ***Macro Modules***

Modules can be parameterized to act on different types or with different operations, similar to generic packages in Ada. Such modules are called *macro modules*. ("Generic" might be a better term, but "macro" alliterates.)

```
-- A simple bounded-list module that can create lists of any definite type
-- with assignment and equality
```

```
Bounded_Lists : macro
  type Element is hidden with <-;
```

```

"=" : function (Left : in Element; Right : in Element) return Boolean is <>;
Bounded_Lists : module is
  type List (Max_Length : Position_Value) is hidden with
    Default_Initial_Condition => List.Is_Empty;

  type Position is hidden with
    Default_Initial_Condition => Position = Invalid;

  Invalid : constant Position;

  Length : function (List : in List) return Count_Value;
  -- Returns the number of Elements in List

  Is_Empty : function (List : in List) return Boolean is
    (List.Length = 0);

  Is_Full : function (List : in List) return Boolean is
    (List.Length = List.Max_Length);

  Clear : procedure (List : in out List) with
    Postcondition => List.Is_Empty;

  First : function (List : in List) return Position;
  -- Returns the Position of the first Element in List
  -- Returns Invalid if List.Is_Empty

  Last : function (List : in List) return Position;
  -- Returns the Position of the last Element in List
  -- Returns Invalid if List.Is_Empty

  Valid : function (List : in List; Position : in Position) return Boolean;
  -- Returns True if Position is a valid Position for List; False otherwise
  -- Returns False if List.Is_Empty

  Next : function (List : in List; Position : in Position)
  return Position with
    Precondition => List.Valid (Position);
  -- Returns the Position in List after Position
  -- Returns Invalid if Position = List.Last

  Previous : function (List : in List; Position : in Position)
  return Position with
    Precondition => List.Valid (Position);
  -- Returns the Position in List before Position
  -- Returns Invalid if Position = List.First

  Value : function (List : in List; Position : in Position)
  return Element with
    Precondition => List.Valid (Position);
  -- Returns the Element stored in List at Position

  Append : procedure (Onto : in out List; Item : in Element) with
    Precondition  => not Onto.Is_Full,
    Postcondition => not Onto.Is_Empty and Onto.Value (Onto.Last) = Item;

  Insert : procedure
    (Into : in out List; Before : in Position; Item : in Element)
  with
    Precondition  => not Into.Is_Full and Into.Valid (Before),

```

```

    Postcondition =>
        not Into.Is_Empty and Into.Value (Into.Previous (Before) ) = Item;

Delete : procedure (From : in out List; Position : in out Position) with
    Precondition  => From.Valid (Position),
    Postcondition => not From.Is_Full and Position = Invalid;
-- Deletes the Element stored in From at Position and makes Position invalid

type Location_Result (Found : Boolean <- False) is record
    case Found is
        when False =>
            null;
        when True =>
            Position : Position;
    end case;
end record Location_Result;

Location : function (Within : in List; Item : in Element)
return Location_Result with
    Postcondition => (if Location'Result.Found then
                        Within.Value (Location'Result.Position) = Item
                      else
                        True);
-- If Within contains an Element that is "=" to Item, returns a value with
-- Found of True and Position of the Position where Item is stored
-- Otherwise, returns Location_Result'(Found => False)
Bounded_Lists : end module;

```

The body of a macro module is the same as for a module, so we won't look at it here. Also, lists are part of King's standard library, so it's unlikely anyone would ever implement a general-purpose one.

The name of a macro module is introduced on the **macro** line, in keeping with the general approach used so far. This also makes the name known if the **module** line is not visible because of positioning of the text or because the macro parameters are large.

The formal parameter **Element** will match any definite type with assignment. If **with** <- had been omitted, it would match any definite type. The macro function parameter "=" means such a function must also exist for the type.

**Position\_Value** is a subtype defined in module **King\_Predefined\_Environment**, which is equivalent to Ada's package **Standard**. **Count\_Value** is similar. The declarations are

```

type Unbounded_Integer is range <> with Default_Value => 0;
subtype Count_Value is Unbounded_Integer with Predicate => Count_Value >= 0;
subtype Position_Value is Unbounded_Integer with
    Predicate => Position_Value > 0,
    Default_Value => 1;

```

**Unbounded\_Integer** is an unbounded integer type. This is the kind of integer used by the compiler to calculate static integer values exactly, sometimes referred to as a big integer. Unbounded integers do not have the 'First and 'Last attributes defined, so the aspect **Default\_Value** must be specified.



Unbounded integer types always have signed representations and cannot overflow.

Subtypes of unbounded integer types can have range constraints, but as we want all non-negative and all positive values for the constraints here, we can't use a range constraint and have to use a predicate instead.

There are also unbounded real types. Unbounded numeric types are usually implemented in software. Universal and static expressions are usually evaluated using unbounded numbers.

`Is_Empty` and `Is_Full` are expression functions, which are similar to Ada's. Since the bodies of the functions and their postconditions are identical, it avoids repetition to use them for these. Speaking of postconditions, here we see King's pre- and postconditions, which are similar to Ada's.

`Location_Result` is a variant record type, similar to Ada's. Note the indentation of the case part.

### ***Child Units and Hidden Modules***

For name-space control, library-level modules and hidden modules may have child units, which may be any of the possible library-level compilation units:

- Modules
- Macro modules
- Hidden modules
- Hidden macro modules
- Main-program procedure bodies

Thus, a module or hidden-module name can be the head of a hierarchy of unit names. Child units do not extend their parents and do not automatically have visibility into them. Any module may use any other, regardless of position in a hierarchy, so long as the dependencies are not circular. Using a child unit does not use its ancestors.

A hidden [macro] module must be a library-level child unit and is identified by having the reserved word **hidden** before **module** in its specification. Hidden modules allow for further partitioning of a logical piece of a system without making that partitioning externally visible. To this end, a hidden module can only be used by

- The body of its parent
- The body of a descendant module of its parent
- The specification of a hidden descendant module of its parent

[Hidden] macro modules and main-program procedure bodies cannot have children. Hidden modules can only have hidden children.



## ***Macro Parameters***

### **Macro Type Parameters**

King's macro type parameters, from most general to most specific, are

**type T is hidden (<>);**

The actual parameter may be any type, definite or indefinite, with or without assignment. Within the module it is an indefinite type without assignment.

**type T is hidden (<>) with <-;**

The actual parameter may be any type with assignment, including a hidden type before the full type declaration. Within the module it is an indefinite type with assignment.

**type T is hidden;**

The actual parameter may be any definite type, with or without assignment. Within the module it is a definite type without assignment.

**type T is hidden with <-;**

The actual parameter may be any definite type with assignment. Within the module it is a definite type with assignment.

Macro hidden-type parameters have no operations defined for them by default. Operations may be defined through macro subprograms, such as "=" in the example above.

**type T is map key\_subtype => value\_subtype;**

The actual parameter may be any map type with the given key and value subtypes. Often either or both of the mapped subtypes will be other formal type parameters.

**type T is sequence\_set of element\_subtype;**

where **sequence\_set** is one of **sequence** | **set**. The actual parameter may be any corresponding type with a matching element subtype; the element subtype will often be another formal type parameter.

**type T is delta digits range <>;**

The actual parameter may be any numeric type. Within the module, only integer literals and `universal_integer` values may be used with the type.

**type T is delta digits <>;**

The actual parameter may be any real type.

```
type T is range (<>);
```

The actual parameter may be any discrete type (enumeration or integer type).

```
type T is (<>);
```

The actual parameter may be any enumeration type.

```
type T is delta <>;
```

The actual parameter may be any fixed-point type.

```
type T is digits <>;
```

The actual parameter may be any floating-point type.

```
type T is range <>;
```

The actual parameter may be any integer type.

### Macro Constant Parameters

Constant parameters allow passing values to the module. The value may be a literal, expression, variable, or constant. Within the module, the value is constant (may not be assigned to) and has the value of the actual at the point of the macro expansion (the formal is a copy of the actual).

```
Name : constant subtype_indication;
```

### Macro Subprogram Parameters

Subprogram parameters are often used to provide operations for type parameters.

```
Name : subprogram_definition [is default];
```

### *Subprogram Defaults*

```
<>  
Actual_Name
```

These are the same as in Ada: if no actual is supplied, a visible matching subprogram with the same name as the formal (<>) or named Actual\_Name is used.

For a function, an expression-function definition may be used; the given expression function is used if no actual is supplied:

```
Less_Than : function (Left : in T; Right : in T) return Boolean is  
    (Left < Right);
```

For a procedure, a [declare-]statement-procedure definition may be used; the given [declare-]statement procedure is used if no actual is supplied:

```
Do_Something : procedure (Value : in out T) is (null);
```

## Tasks

Few programs these days do not need to deal with concurrency. GUIs are inherently parallel, and the prevalence of multi-core processors means that understanding concurrency is essential for software engineers, and high-level concurrency features are essential for languages.

Tasks are King's main feature for concurrency and come in two flavors: active tasks and passive tasks. Active tasks are like Ada's tasks in that they are self-scheduling, but there are no entries or rendezvous in King. Active tasks communicate through passive tasks. Passive tasks are similar to Ada's protected objects. Assignment is not defined for task types.

Unlike Ada's shared-memory tasking model, the only variables declared outside a task that the task can access are passive tasks. This is more restrictive than the shared-memory model, but makes it easy for King compilers to target any kind of platform, not just shared-memory symmetric multiprocessors.

A consequence of this restriction on what global variables a task may access is that a task cannot call a subprogram that might access such a variable. Subprograms by default may not do so. Subprograms may be marked with the aspect `Task_Safe => False` to indicate that they do access task-prohibited global variables. The compiler must ensure that subprograms adhere to the task-safety restrictions unless they are marked as task unsafe. An entire module may be marked as task unsafe to indicate that all of its subprograms are task unsafe.

A task may call task-unsafe subprograms provided they are declared within the task. As everything is declared within the environment task, it may call such subprograms.

### Active Tasks

An active task provides an independent thread of control. Conceptually, each active task is considered to run on its own processor, though in reality there may be more active tasks than actual processors.

The dining-philosophers problem should have an active task for each philosopher:

```
type Philosopher_ID is (Archimedes, Descartes, Hegel, Kant, Socrates);
```

```
type Philosopher (ID : Philosopher_ID <- Archimedes) is task;
```

The syntax for an active task lacks task subprograms, which are present for a passive task.

This task-type specification must be completed by a body, but as tasks usually need to access passive tasks, we'll put off looking at one until later.

## Ending Task Execution

Normally, active tasks run until they determine that they should stop. Sometimes it is necessary for a task to end the execution of another task. This is done with an **end** statement

```
end Task_Name;
```

If the task is performing a call to a passive-task operation that is not queued or waiting for access to the task structure, the task continues until it returns from that call before ending. This ensures that the internal state of the passive task remains consistent.

## Dynamic Creation of Active Tasks

Sometimes it's necessary to create an arbitrary number of tasks of the same type, or with different values of the task's discriminants. These are done with a task aggregate or a **new** statement.

```
Philosopher'(ID => Socrates)      -- aggregate for a type with discriminants
Name'(others => <>)                -- aggregate for a type without discriminants
new Philosopher (ID => Socrates); -- new statement
```

The task resulting from the aggregate may be used to initialize a component (see below) or passed as an **in** mode parameter. The task resulting from the **new** statement exists but has no name, so it cannot be ended. It must either stop itself, or run forever.

## Passive Tasks

Passive tasks have no associated thread of control, but do provide for mutual exclusion. Only one of a passive task's operations may be executed at a time. Unlike Ada's protected objects, which are special-purpose constructs for protecting access to shared data and so limit the actions they may perform, passive tasks are a general-purpose building block for anything that needs mutual exclusion without a thread of control.

In the dining-philosophers problem, the philosophers need to obtain two chopsticks to dine. As there are as many chopsticks as there are philosophers, this can lead to contention. Mutual exclusion is needed to prevent two philosophers from using the same chopstick at the same time:

```
type Chopstick_Control is task
  Has_Sticks : function (ID : in Philosopher_ID) return Boolean;
  -- Returns True if Picked has been called with ID and returned True;
  -- False otherwise
```

```

Picked : function (ID : in Philosopher_ID) return Boolean with
    Precondition => not Has_Sticks (ID),
    Postcondition => Picked'Result = Has_Sticks (ID);
-- Tries to get the chopsticks for philosopher ID
-- Returns True if both chopsticks could be obtained and False otherwise

Put : procedure (ID : in Philosopher_ID) with
    Precondition => Has_Sticks (ID),
    Postcondition => not Has_Sticks (ID);
-- Puts down the chopsticks for philosopher ID
end task Chopstick_Control;

```

The body of a passive task has whatever declarations are needed, followed by a subprogram body with barrier for each of its subprograms:

```

use King.Algorithms.Wrapping;
...
Wrap : module is new King.Algorithms.Wrapping (Element => Philosopher_ID);
...
Chopstick_Control : task body is
    type State_Map is map Philosopher_ID => Boolean;

    Stick : State_Map is State_Map'(others => False);
    -- True indicates that the chopstick is in use; False, not in use
    Owner : State_Map is State_Map'(others => False);
    -- True indicates that the philosopher has picked up his chopsticks;
    -- False, he has not

    Has_Sticks : function (ID : in Philosopher_ID) return Boolean when True is
        (Owner (ID) );

    Picked : function (ID : in Philosopher_ID) return Boolean when True body is
        Success : constant Boolean is
            not Stick (ID) and not Stick (Wrap.Next (ID) );
    Picked : begin
        if Success then -- Both chopsticks are available
            Stick (ID) <- True; -- Make them unavailable
            Stick (Wrap.Next (ID) ) <- True;
            Owner (ID) <- True;
        end if;
        -- else Stick and Owner are unchanged

        return Success;
    Picked : when E =>
        E.Raise;
    Picked : end function;

    Put : procedure (ID : in Philosopher_ID) when True body is
        null;
    Put : begin
        Stick (ID) <- False; -- Make the chopsticks available
        Stick (Wrap.Next (ID) ) <- False;
        Owner (ID) <- False;
    Put : when E =>
        E.Raise;
    Put : end procedure;
Chopstick_Control : end task;

```

Wrap is an expansion of the macro module `King.Algorithms.Wrapping`, similar to a generic instantiation in Ada. It provides function `Wrap.Next`, which gives the next value after its argument, wrapping around from the last value to the first.

**State\_Map** is a map type, used in a manner similar to an Ada array type, but the key of a map type need not be discrete.

After declaring the state variables, initialized so all the chopsticks are available (all aggregates must be qualified), we have the bodies for the subprograms. These are the same as regular subprograms, except for the barrier introduced by **when**. Procedures act much the same as entry bodies in Ada. Functions only differ in that they also return a value. In this case all the subprograms may always proceed, so the barriers are `True`. This is because barriers cannot reference the subprogram parameters.

Internal calls, calls to other subprograms of a passive task from within one of the task's subprograms, do not queue and raise the exception `Program_Error` if the called subprogram's barrier is `False`. Preconditions are evaluated after the caller has obtained access to the task. Postconditions are evaluated before the caller relinquishes access to the task. Any calls to the task's functions in pre- and postconditions are internal calls.

Small functions like `Has_Sticks` that query the task's state, have `True` barriers, and are only used in pre- and postconditions are common.

## Calls to Passive Task Operations

A call to a passive task operation, including to a function, proceeds much like a call to a protected entry in Ada. Since there is no restriction on what a passive task operation may do, implementations in which a task executes an operation on behalf of another task are not suitable for King's passive tasks.

## Priorities

All tasks, active and passive, have an associated *priority*. When there are fewer actual processors than active tasks, the priority helps determine which task gets to run when an actual processor becomes available. An active task executing an operation of a passive task takes on the passive task's priority for the duration of the operation.

There exist the following declarations in module `King_Predefined_Environment`:

```
type Any_Priority is range 1 .. 64;
```

```
Max_Interrupt_Priority = 16;
```

```
subtype Interrupt_Priority is Any_Priority range 1 .. Max_Interrupt_Priority;
```

```
subtype Priority is Any_Priority range  
  Max_Interrupt_Priority + 1 .. Any_Priority'Last;
```

```
Default_Priority = (Priority'First + Priority'Last) / 2;
```

Following normal usage, the smaller the priority's numeric value, the higher the priority. Priority 1 is the highest priority and 64, the lowest.

A task's priority may be specified by the Priority aspect. For an active task, the aspect takes a value of subtype **Priority**; for a passive task, **Any\_Priority**. The default priority of an active task is **Default\_Priority**; of a passive task, **Priority**'First.

## ***Protected Queues***

Queues with mutually exclusive access are a common mechanism for communication between tasks, so King provides them in its standard library. They can be either bounded or unbounded. King also includes normal, non-mutually exclusive queues of both kinds, which will be discussed later. Assignment is not defined for protected queues, but is for normal queues. The specification of the unbounded protected queue module will be shown in the discussion of the standard library below.

Continuing the dining-philosophers problem, the philosopher tasks need to report their state changes somehow, and should spend as little time as possible doing so. A queue of messages from the tasks, processed by a reporting task, does just that, so we would declare:

```
Message_Queue : module is new King.Data_Structures.Queues.Unbounded.Protected
  (Element => String);
```

```
subtype Message_Queue is Message_Queue.Handle;
```

with the predefined type **String** defined as

```
type String is sequence of Unicode;
```

**Unicode** is the Unicode character set. Queue component types have to be definite types with assignment.

## ***Active Task Bodies***

We can now look at active task bodies. These are similar to parameterless procedure bodies, except for the reserved word **task** instead of **procedure**. Returning to the **Philosopher** task type, its body might be

```
Chopsticks      : Chopstick_Control;  
Message_Queue : Message_Queue;
```

```
Philosopher : task body is  
  Thinking = 10.0; -- Times in seconds  
  Talking  = Thinking;  
  Eating   = Thinking;  
Philosopher : begin  
  All_Rounds : for Round in Integer range 1 .. 10 loop  
    Message_Queue.Put  
      (Item => ID'Image & " thinking for " &  
        Thinking'Image (Before => 0, After => 1, Exponent => 0) );
```



```

wait of Thinking;

Message_Queue.Put (Item => ID'Image & " waiting for podium");
Podium.Talk (ID => ID, Talking => Talking);
Message_Queue.Put (Item => ID'Image & " waiting for chopsticks");

Get_Sticks : loop
    exit Get_Sticks when Chopsticks.Picked (ID);

    wait of 1.0;
Get_Sticks : end loop;

Message_Queue.Put
    (Item => ID'Image & " eating for " &
     Eating'Image (Before => 0, After => 1, Exponent => 0) );

wait of Eating;
All_Rounds : end loop;
Philosopher : when Error =>
    Message_Queue.Put (Item => ID'Image & " ended by " & Error.Information);
Philosopher : end task;

```

Not much here should need explanation. We assume the existence of a passive task `Podium` that controls access to the floor, putting a message on the queue when a philosopher is talking and blocking the caller for `Talking` seconds. We also assume an active task that takes messages off the queue and outputs them.

String literals, which have type *universal\_string*, are a form of aggregate for string types such as *String*. A string literal is `' '` followed by zero or more graphic characters except `' '` followed by `' '`. Values of *universal\_string* containing `' '` or non-graphic characters may be created by concatenating string literals and the appropriate character literals or non-character literals of a character type.

```
NUL_Terminated = "abcdef" & NUL;
```

Because this is a *universal\_string*, `NUL` is the corresponding character from *Unicode*.

The attribute `'Image` for enumeration literals returns a *String* of the defining occurrence of the literal. For real values, including *universal\_real*, the function also has the arguments `Before`, `After`, `Exponent`, and `Base`, with appropriate defaults for the type. `Before => 0` uses as many digits as necessary before the point to represent the value. `After => 0` has no digits after the point and no point, and `Exponent => 0` has no exponent part. The base defaults to 10.

King has two kinds of **wait** statements that block a task for a period of time. The **wait of** statement, used here, is for a relative amount of time, and blocks the task for the number of seconds given. It can be read as, "Perform a wait of this many seconds." The **wait for** statement, not yet seen, takes a *Duration* value and blocks the task until that time arrives, unless it is in the past. It can be read as, "Wait for this time to arrive." The duration is the number of

seconds since the epoch, which is not defined, but meaningful values can be constructed using the standard library.

All loops must be named, and the name must appear on **exit** statements.

All that remains now is to declare the philosophers and give them all their IDs:

```
type Philosophers is map Philosopher_ID => Philosopher;  
  
Philosopher : constant Philosophers is  
  Philosophers'(for ID in Philosopher_ID => Philosopher'(ID => ID) );
```

This declares a map from **Philosopher\_ID** to **Philosopher** tasks and initializes it with a map aggregate. Since the map values are tasks, the component expression is a task aggregate. The resulting map object has the task with discriminant ID keyed by ID.

The reader may want to implement Podium and the reporter task, and put everything together in a main-program procedure as an exercise.

## Identifiers

The intention is that King identifiers should be

English\_Words\_With\_Initial\_Capitals\_Separated\_By\_Underlines

King uses English reserved words with the intention that King source text should be similar to English text, so non-English words should not be part of identifiers.

The characters allowed in identifiers are

- Capital letters    'A' .. 'Z'
- Small letters     'a' .. 'z'
- Digits            '0' .. '9'
- The underline    '\_'

An identifier is made up of words separated by underlines. There is an initial word and zero or more subsequent words. The initial word must begin with a capital letter. Subsequent words can begin with a capital letter or a digit. Within a word, a capital letter cannot come after a small letter. If an identifier has subsequent words, the initial word cannot be A, An, or The. Names may not contain any information about the thing named that is provided by the language. Type names may not contain Type; records, Record; macro modules, Macro; and so on; and this applies to abbreviations such as T[y[p]], Rec, and M.

King is case insensitive: this, This, and THIS are the same identifier. (The first is illegal because the first letter is not capitalized.) King is case aware, however: there is a defining occurrence of an identifier, and all other uses of that identifier must have the same casing as the defining occurrence. For

things that have separate specifications and bodies, the defining occurrence is the first appearance in the specification. For things that are declared, the defining occurrence is the declaration. For names of loop and declare statements, the defining occurrence is the first line of the statement. For exception objects in exception handlers, the defining occurrence appears after **when**.

Reserved words must be all small letters, even when used as an attribute.

## **Types**

### ***Numeric Types***

#### **Integer Types**

Integer types come in two kinds, bounded and unbounded. We have seen examples of both.

#### ***Unbounded Integer Types***

The range of values that can be stored in unbounded integers is limited only by the available memory. They are usually implemented in software and may not be suitable for some algorithms.

#### ***Bounded Integer Types***

Bounded integers have specified lower and upper bounds. The compiler must accept all bounded integer type declarations, regardless of the range of values covered. By default, bounded integers have a signed representation and overflow checking, but either or both can be changed as we have seen. To have an unsigned representation, the lower bound of the type must be non-negative.

Typically the target processor will have a number of hardware integer types, of 1, 2, 4, and 8 bytes. If the range of a bounded integer type will fit in a single hardware integer type, then the smallest hardware integer type that will hold the range is the base type for the type. With a signed representation, the base type will be roughly symmetrical around zero, regardless of the given bounds. If overflow checking is not done for such a type, it applies to the base type; if an overflow occurs, it may result in a value that is not in the given range.

If the range is too big for the largest hardware integer, but will fit in two of them, then the base type will be two such hardware integers chained together. For larger ranges, more and more hardware integers may be chained together.

The compiler may set a limit  $N > 1$  of the number of hardware integers it can chain together. If an integer type requires more than  $N$  hardware integers, the compiler may use an unbounded integer as the base type. In that case, the desired representation is ignored. If overflow checking is not done for the type, then subtracting one from the lower bound will give the upper bound, and adding one to the upper bound will give the lower bound.

There exist the predefined types

```
type Integer is range -(2 ^ 15) + 1 .. 2 ^ 15 - 1;  
subtype Natural is Integer range 0 .. Integer'Last;  
subtype Positive is Integer range 1 .. Integer'Last;  
  
type Byte_Value is range 0 .. 255 with Signed_Representation => False;
```

### ***Integer Operations***

King has the same unary and binary integer operators as Ada (King uses "^" for exponentiation, as seen above).

The module King.Platform\_Information has the named integers

```
Max_Signed_Hardware_Integer = implementation_defined_positive_integer;  
Max_Unsigned_Hardware_Integer = implementation_defined_positive_integer;
```

A signed integer type with

```
range -Max_Signed_Hardware_Integer .. Max_Signed_Hardware_Integer
```

will fit in a single hardware integer, as will an unsigned integer type with

```
range 0 .. Max_Unsigned_Hardware_Integer
```

Integer types that fit in a single hardware integer have bit-wise logical operators defined for them, and attribute functions for rotation and shifting. The attribute 'Bit\_Wise\_Operators is True for integer types with bit-wise logical operators and False for all other integer types.

### **Real Types**

Real types come in two kinds, floating-point and fixed-point, both of which come in bounded and unbounded forms.

#### ***Floating-Point Types***

Floating-point types are defined using the reserved word `digits`. Bounded versions have an explicit number of digits; the compiler must accept all bounded floating-point declarations. If a declaration does not fit in a hardware floating-point type, or if the platform does not have hardware floating-point types, then the declaration's base type may be an unbounded floating-point type.

Unbounded versions use the `box` for the number of digits. Either kind may include an optional range constraint for the first-named subtype. Bounded types have a default range that increases with the number of digits; for types that fit in a hardware type, according to the requirements of the hardware type; for types that don't fit in a hardware type (or if there are no such types), as specified for floating-point model numbers in ARM G.

There exist the predefined types

```

type Float is digits 7;
subtype Natural_Float is Float range 0 .. Float'Last;
subtype Positive_Float is Float range Float'Next (0) .. Float'Last;

type Rational is digits <> with
  Default_Value => 0;
subtype Natural_Rational is Rational with
  Predicate => Natural_Rational >= 0;
subtype Positive_Rational is Rational with
  Predicate => Positive_Rational > 0,
  Default_Value => 1;

```

**Rational** is the same as the type used by the compiler to evaluate static real expressions.

### ***Fixed-Point Types***

Fixed-point types use the reserved word **delta**. Bounded versions have an explicit range, and unbounded versions use the box for the range. Conceptually, a fixed-point type is stored as an integer, with the value represented being the integer multiplied by the delta for the type. Unlike Ada, there is no *small* for a type that may differ from the delta. This eliminates surprises and the need for a separate form for currency values. The base type of a fixed-point type is a signed type roughly symmetrical around zero. Rounding for fixed-point types follows the rules for Ada's decimal fixed-point types.

The range of values represented by a fixed-point type with an explicit range must include both ends of the range, rounded to the nearest representable value if they are not multiples of the delta.

The compiler must accept all bounded fixed-point declarations. If there is no bounded representation for a bounded fixed-point type declaration, the base type may use an unbounded representation.

There exists the predefined type

```

type Duration is delta 10.0 ^ -9 range <> with
  Default_Value => 0;
subtype Natural_Duration is Duration with
  Predicate => Natural_Duration >= 0;
subtype Positive_Duration is Duration with
  Predicate => Positive_Duration > 0,
  Default_Value => Duration'delta;

```

Duration represents seconds with an accuracy of a nanosecond. It is used by **wait** statements and by time handling.

Unlike Ada, King allows a binary operator to be followed by a unary operator and its operand without requiring parentheses, as shown in the **delta** expression above.

## Enumeration Types

King's enumeration types are declared and used much the same as Ada's, except for the use visibility of enumeration literals. Position numbers returned by 'Position start with one, while the attributes 'Representation and 'From\_Representation return and take the internal representation of the values, which by default start with zero.

There exist the predefined types

```
type Boolean is (False, True);
```

```

type Unicode is (NUL, SOH, STX, ETX, EOT, ENQ, ACK, BEL,
BS, HT, LF, VT, FF, CR, SO, SI,
DLE, DC1, DC2, DC3, DC4, NAK, SYN, ETB,
CAN, EM, SUB, ESC, FS, GS, RS, US,
' ', '!', '"', '#', '$', '%', '&', '\'',
'(', ')', '*', '+', ',', '-', '.', '/',
'0', '1', '2', '3', '4', '5', '6', '7',
'8', '9', ':', ';', '<', '=', '>', '?',
'@', 'A', 'B', 'C', 'D', 'E', 'F', 'G',
'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O',
'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W',
'X', 'Y', 'Z', '[', '\', ']', '^', '_',
`', 'a', 'b', 'c', 'd', 'e', 'f', 'g',
'h', 'i', 'j', 'k', 'l', 'm', 'n', 'o',
'p', 'q', 'r', 's', 't', 'u', 'v', 'w',
'x', 'y', 'z', '{', '|', '}', '~', DEL,
R01, R02, BPH, NBH, R03, NEL, SSA, ESA,
HTS, HTJ, VTS, PLD, PLU, RI, SS2, SS3,
DCS, PU1, PU2, STS, CCH, MW, SPA, EPA,
SOS, R04, SCI, CSI, ST, OSC, PM, APC,
'...', '¡', '¢', '£', '¤', '¥', '¦', '§', -- NBSP ' ' (A0)
'°', '©', 'ª', «, ¬, SFH, ®, ¯, -- soft- SFH (AD)
'±', '²', '³', '¼', '½', '¾', '¿',
'À', 'Á', 'Â', 'Ã', 'Ä', 'Å', 'Æ', 'Ç',
'È', 'É', 'Ê', 'Ë', 'Ì', 'Í', 'Î', 'Ï',
'Ð', 'Ñ', 'Ò', 'Ó', 'Ô', 'Õ', 'Ö', '×',
'Ø', 'Ù', 'Ú', 'Û', 'Ü', 'Ý', 'Þ', 'ß',
'à', 'á', 'â', 'ã', 'ä', 'å', 'æ', 'ç',
'è', 'é', 'ê', 'ë', 'ì', 'í', 'î', 'ï',
'ð', 'ñ', 'ò', 'ó', 'ô', 'õ', 'ö', '÷',
'ø', 'ù', 'ú', 'û', 'ü', 'ý', 'þ', 'ÿ',
...) with

```

**Unicode** has literals for all 1,112,064 Unicode code points. Character literals are used for graphic code points like 'A'. Meaningful identifiers are used for non-graphic code points with a meaningful name like NUL. Remaining positions have identifiers of the form U\_hhhhhh, where hhhhhh is the hexadecimal representation of the code point (with capital letters for digits greater than 9).

The Bit\_Size aspect specifies that values of **Unicode** may be packed into 21 bits. There is also the aspect Byte\_Size which specifies the minimum size in bytes; only one of these aspects may be specified. There are also attributes with the same names for querying these values.

If `Bit_Size` is specified for a subtype, then `Byte_Size` is defined as

$$\text{Byte\_Size} = (\text{Bit\_Size} + 7) / 8$$

If `Byte_Size` is specified, then `Bit_Size` is defined as

$$\text{Bit\_Size} = 8 * \text{Byte\_Size}$$

There are three predefined subtypes of **Unicode**:

```
subtype Basic_Multilingual_Plane is Unicode range
  NUL .. Unicode'From_Representation (16#FFFF#)
with
  Byte_Size => 2;
subtype Latin_1 is Unicode range NUL .. 'ÿ' with
  Byte_Size => 1;
subtype ASCII is Unicode range NUL .. DEL with
  Bit_Size => 7;
```

Unlike Ada's type **Character**, King's does not have any "magic" positions that can only be referenced by position number or representation. This eliminates the need for something like Ada's package `Latin_1`. Literals of a character type are implicitly converted to the equivalent **universal\_character** value when used in places where that is needed.

## Composite Types

### Map Types

Maps map from keys to associated values. In Ada, when all of the keys for a map have discrete subtypes, a constrained array type is often used to implement a map. King uses a notation similar to Ada's one-dimensional constrained array types for maps, but the key subtype may be any assignable type.

```
type Name is map key_subtype => value_subtype;
```

Map types have assignment if the value subtype has assignment; similarly for individual mappings. If the value subtype lacks assignment, the map must be initialized when declared and may only be used to access those initial values, as in the map of **Philosopher** tasks above.

For an assignable map `M` with a key `K`, you can set the mapped value with an assignment statement:

```
M (K) <- Value;
```

You retrieve the value for a key with the same notation:

```
Value <- M (K);
```



If no value has been specified for a key, retrieving its value raises `Constraint_Violation`. Maps have the predefined function

```
M.Defined (K)
```

which returns `True` if `M (K)` returns a value and `False` if it raises `Constraint_Violation`.

A map aggregate is similar to an Ada qualified array aggregate using named notation.

## Sequence Types

Sequence types define sequences, with items in a sequence defined by their position number.

```
type Name is sequence of Element;
```

The component subtype must have assignment. Individual positions in a sequence may be accessed by giving the position number in brackets:

```
S [I] := Value;  
Value := S [I];
```

Position numbers have subtype `Position_Value` and must be in `1 .. S.Length`.

Slicing is also defined for sequences:

```
S [Low .. High] := S [Low - 1 .. High - 1];
```

(A named subtype of `Position_Value` may be used in place of an explicit range.) If the range is non-null, both values must be in `1 .. S.Length`.

Sequence aggregates are similar to Ada's qualified array aggregates using positional notation, except sequence aggregates use brackets rather than parentheses.

```
type Demo is sequence of Boolean;
```

```
Demo : Demo is Demo'[True, True, True, False];
```

Named notation may be used following positional notation, provided that each use of named notation identifies multiple positions with the same value, or follows named notation that does so. So the above could also be represented as

```
Demo'[1 .. 3 => True, 4 => False];
```

Sequences can be combined using `"&"` much like Ada's one-dimensional arrays.

Sequences can be extended

```
Demo <- Demo & False;
```

and items can be deleted

```
Delete : procedure (S : in out ST; Position : in Position_Value) with  
    Precondition => Position in 1 .. S.Length;
```

## Set Types

Mathematical sets are implemented in King with set types:

```
type Name is set of universe_subtype;
```

The universe subtype must have assignment. The following binary operators are defined for sets:

- "+" Union
- "\*" Intersection
- "-" Difference
- "/" Symmetric difference
- "<=" Subset
- "<" Proper subset
- ">=" Superset
- ">" Proper superset
- "=" Equality

A set may appear as the right operand of [**not**] **in**.

Set aggregates are the same as Ada's qualified array aggregates using positional notation, but with braces rather than parentheses:

```
if Color in Colors'{Green, Yellow, Red} then
```

## Record Types

Except for the syntax differences, record types are declared and used much as in Ada.

Record aggregates are the same as Ada's qualified record aggregates using named notation.

Record types have assignment if all of their component subtypes have assignment. Record types that complete hidden types must always have assignment.

## Derived Types

King has derived types very similar to those of Ada 83. However, King restricts the parent type to those declared in the current declarative part, including enclosing declarative parts up to and including King\_Predefined\_Environment.

## Module Types

A module can implement an Abstract Data Type (ADT), with state held in an object and passed to the module's operations, as for Bad\_Random above, or it can implement an Abstract State Machine (ASM), with state in the module body. ASM modules are inherently task unsafe. An ASM version of Bad\_Random would look like

```
-- A very poor random-number generator
```

```
Bad_Random : module with Task_Safe => False is
  type Result is range 0 .. 2 ** 16 - 1 with
    Signed_Representation => False,
    Overflow_Checking => False;

  Set_Seed : procedure (Seed : in Result <- Result'Last);
  -- Sets the state of the generator to produce the sequence of values
  -- defined by Seed

  Random : function return Result;
  -- Returns the next value
Bad_Random : end module;
```

Its body would be

```
Bad_Random : module body is
  State : Result is Result'Last;

  Set_Seed : procedure (Seed : in Result <- 0) is (State <- Seed);

  Random : function return Result is
    null;
  Random : begin
    State <- State + 1;

    return State;
  Random : when E =>
    E.Raise;
  Random : end function;
Bad_Random : begin
  null;
Bad_Random : when E =>
  E.Raise;
Bad_Random : end module;
```

Set\_Seed is a statement procedure, as with the ADT version given earlier.

Module types are a way of defining ASM types. A module-type version of Bad\_Random would be

```

type Result is range 0 .. 2 ** 16 - 1 with
    Signed_Representation => False,
    Overflow_Checking => False;

-- A very poor random-number generator

type Bad_Random is module
    Set_Seed : procedure (Seed : in Result <- Result'Last);
    -- Sets the state of the generator to produce the sequence of values
    -- defined by Seed

    Random : function return Result;
    -- Returns the next value
end module Bad_Random;

```

The specification of a module type can only contain subprogram specifications, so the declaration of **Result** must be pulled out.

The body of this type is identical to the body of the ASM module version.

An object of a module type is effectively a module, and its operations are called the same way. Unlike modules, module types can be the parameters of subprograms. Assignment is not defined for module types, so they serve as the equivalent of Ada's limited types.

There exists the predefined type

```

type Exception_Occurrence is module
    Name : function return String;
    -- Returns the full name of the occurrence

    Message : function return String;
    -- Returns the message associated with the occurrence

    Information : function return String;
    -- Returns Name & ' ' & Message & implementation_defined_String

    Set : procedure (Message : in String) with
        Postcondition => Message = Exception_Occurrence.Message;

    Raise : procedure (Message : in String <- "");
    -- Raises the occurrence.
    -- If Message is not null, uses it instead of the currently associated
    -- message
end module Exception_Occurrence;

```

This is the type of exception objects.

## Boolean Types

A boolean type is the predefined type **Boolean** or any type derived from it. A value of any boolean type may be used where a *boolean\_expression* is required (**if**, **else\_if**, or after **when** in barriers and **exit** and **return** statements).

## Character Types

A character type is any enumeration type with a character literal as an enumeration literal, such as type **Unicode**. A *universal\_character* value is implicitly converted to any character type if it is valid.

## String Types

A string type is any sequence type with a character type as the component type, such as type **String**. A *universal\_string* value is implicitly converted to any string type if it is valid.

There are several restricted subtypes of **String**:

```
subtype BMP_String is String with
  Predicate => (for all C of BMP_String => C in Basic_Multilingual_Plane);
subtype Latin_1_String is String with
  Predicate => (for all C of Latin_1_String => C in Latin_1);
subtype ASCII_String is String with
  Predicate => (for all C of ASCII_String => C in ASCII);
```

## Stack and Heap Allocation

How a compiler implements subprogram calls (stack frames) is an implementation issue that should not concern the developer. In Ada, a large object that does not fit on the stack often results in **Storage\_Error**, and the developer then explicitly puts the object on the heap (via an access type) to avoid this.

King requires that an object declaration succeed if there is room in memory for the object; no distinction is made between stack and heap memory. King therefore requires that an object declaration that does not fit on the stack must be tried on the heap before raising **Memory\_Exhausted**.

Most large objects in King are dynamically sized, and so are probably allocated on the heap anyway, and this is not an issue. But large constant objects may be declared that need not be dynamic; consider the **Philosopher** map in the dining-philosophers example if there were a large number of philosophers.

## Exceptions

Exceptions are somewhat different from Ada. Rather than exceptions and corresponding exception occurrences in handlers, all exceptions are exception occurrences. Rather than multiple handlers, King has a single handler and a special form of the case statement for handling multiple exceptions. The predefined exceptions are

```
Constraint_Violation : Exception_Occurrence;
Memory_Exhausted     : Exception_Occurrence;
Program_Error         : Exception_Occurrence;
```

## Expressions

Expressions are much as they are in Ada. There is also the **declare** expression, which is

```
(declare DE_declaration {DE_Declaration} begin expression)
```

where *DE\_Declaration* is a constant or subtype declaration.

## ***Static Expressions and Subexpressions***

Static expressions only involve values known by the compiler during compilation. Static expressions are evaluated exactly by the compiler. Static numeric expressions are evaluated using universal operations, which always have their usual mathematical meaning. Static string expressions use the universal "&" operator, which always performs simple concatenation.

A static subexpression is a part of a non-static expression that only uses static values and may be evaluated during compilation without changing the entire expression's value. Static subexpressions are evaluated the same way as static expressions, by the compiler, exactly, and using universal operations.

```
Pi = 3.14159;  
X : Angle;  
...  
X <- X + Pi / 2;
```

The compiler must calculate  $Pi / 2$  exactly (1.570795) and use that value at run time, even if "/" has been redefined for subtype **Angle**. The redefined operator will be used if one of the operands is qualified as being of the subtype: **Angle**'(Pi) / 2. We don't expect the compiler to evaluate the redefined "/" during compilation, so the subexpression will be evaluated at run time.

## **Subprograms**

King has function and procedure subprograms similar to those in Ada 83. There are also special forms known as expression functions and statement procedures, which do not allow for separate specifications and bodies. Normal subprograms, except for main-program procedures, which may not have a specification, have two separate parts, the specification and the body, as we have seen.

We have encountered expression functions and statement procedures already. Statement procedures come in two flavors, simple statement procedures and declare-statement procedures. A simple statement procedure has the form

```
Name : procedure [(parameters)] is (simple_statement);
```

where *Simple\_Statement* is an assignment, null, or procedure-call statement. The simple statement is terminated by the right parenthesis, not by a semicolon. Since we can write

```
Nothing : procedure is (null);
```

King has no need of a special case for null procedures.

Declare-statement procedures are similar but have a declarative part much like declare expressions:

```
Name : procedure [(parameters)] is  
      (declare DE_declaration {DE_Declaration} begin simple_statement);
```

Expression functions and statement procedures are useful for simple subprograms where the postcondition and implementation are very similar. A main-program procedure cannot be a statement procedure.

## Compound Statements

### *Conditional Statements*

#### Case Statements

Ordinary case statements are, except for formatting, the same as in Ada. There is a special form of the case statement for exception handling:

```
Name : when Occurrence_Name =>  
      case Occurrence_Name is  
        when exception_occurrence {| exception_occurrence}=>  
          <statements>  
      {when exception_occurrence {| exception_occurrence}=>  
        <statements>}  
      when others =>  
        <statements>  
      end case;
```

This form can only appear in an exception handler and only the exception handler's occurrence name may appear after **case**. The exception occurrences appearing in the case branches are declared exceptions, such as Constraint\_Violation or King.IO.Invalid\_Name. There must be an **others** case, as it is possible to handle exceptions that are not visible.

#### If Statements

The **if** statement has two forms in King. The first has an **if** part and an optional **else** part.

```
      if boolean_expression then  
        <statements>  
    [else  
      <statements>]  
    end if;
```

The other has **else\_if** parts and a mandatory **else** part.

```
      if boolean_expression then  
        <statements>  
      else_if boolean_expression then  
        <statements>
```



```

{else_if boolean_expression then
  <statements>}
else
  <statements>
end if;

```

## Loop Statements

There are two kinds of loops in King, **for** loops and general loops. All loops must be named, and the loop name must appear on **exit** statements. The syntax is

```

Name : [for prefix] loop
      <statements>
Name : end loop;

```

"**for** prefix" can be one of

```
for Loop_Variable in [reverse] discrete_subtype_name
```

or

```
for Loop_Variable in [reverse] discrete_subtype_definition
```

where *discrete\_subtype\_definition* is

```
[discrete_subtype_name] range Low .. High
```

(the subtype name is needed if Low and High are both universal),

or

```
for Loop_Variable in [reverse] map_or_sequence'range
```

where *map\_or\_sequence* is a map or sequence object name. For a map, *Loop\_Variable* takes on all the values of the key for which values are defined, in an implementation-defined order; **reverse** is not allowed for maps. For a sequence, *Loop\_Variable* takes on all of the position numbers for the object. Finally,

```
for Element of map_sequence_or_set
```

where *map\_sequence\_or\_set* is a map, sequence, or set object name. *Element* refers to each value stored in the object (for a set, each value that is a member of the set). For a set, *Element* is a constant; for the others, a variable.

The **exit** statement is

```
exit Loop_Name [when boolean_expression];
```

## Declare Statements

The declare statement, similar to Ada's block statement, provides a local declarative region, sequence of statements, and exception handler.

```
Name : declare
      <declarations>
Name : begin
      <statements>
Name : when Occurrence_Name =>
      <exception handling>
Name : end declare;
```

## Select Statements

Select statements allow *blocking calls* to be abandoned if they don't start soon enough.

```
Name : select
      <blocking call>

      [<statements>]
{Name : or
      <blocking call>

      [<statements>]}
Name : or
      <wait statement>

      [<statements>]
Name : end select;
```

A blocking call is a call to a subprogram of a passive task. Where the blocking call is a function call, it must be part of an expression that is part of a valid statement. There can only be one blocking call controlling a branch of a select statement.

If the **wait** statement expires before any of the blocking calls start execution, the blocking calls are abandoned and any statements after the **wait** are executed.

If one of the blocking calls starts first, the other blocking calls and the **wait** are abandoned; after the blocking call finishes, any statements after the blocking call are executed.

If the **wait** is a relative wait with a value of zero or less, or an absolute wait with a time that is not in the future, and none of the blocking calls can start immediately, then the blocking calls are all abandoned and any statements after the **wait** are executed. This is similar to Ada's conditional entry call.

## Parallel Statements

Parallel statements provide the opportunity for light-weight threading for parallel execution of code. Whether the opportunity is taken, and how many threads are used if it is, is up to the compiler and run-time system.

## ***Task Declare Statements***

Task declare statements provide for parallel execution of arbitrary blocks of code.

```
Name : task declare
      <declarations>
Name : begin
      <statements>
Name : and
      <statements>
{Name : and
  <statements>}
Name : end task declare;
```

If there are fewer threads than statement blocks, the statement blocks are executed by threads in textual order. None of the statement blocks can contain a transfer-of-control statement out of the block. If an exception is raised within a statement-block thread, all of the threads end their execution and control transfers to the appropriate exception handler. Execution continues after the task declare statement when all of the statement blocks have completed.

## ***Task Loop Statements***

A task loop is a **for** loop with the reserved word **task** before **loop**. A task loop cannot contain the reserved word **reverse**. A task loop indicates that all of the iterations of the loop may proceed in parallel. If there are fewer threads than iterations, each thread will execute the loop body for a single subset of the iterations. A task loop cannot contain a transfer-of-control statement out of the loop. If an exception is raised within a task-loop thread, all of the threads end their execution and control transfers to the appropriate exception handler. Execution continues after the task loop statement when all of the threads have completed.

## ***Restrictions***

Anything that can be done by a task declare or task loop statement can be done by ordinary sequential code. They may, therefore, access any variables that sequential code may access, with some restrictions. In the following, *object* refers to a simple variable, a component of a map, sequence, or set variable (except when the variable is packed with parts of multiple components in the same byte), or to an object of a module type. Different branches of a task declare statement and different iterations of a task loop statement may not:

- Modify the same object
- Read an object that is modified by a different branch or iteration

The compiler must detect and reject violations of these. Operations of an object of a module type are assumed to modify the variable.

## Transfer-of-Control Statements

King's transfer-of-control statements are the **exit** and **return** statements. The **exit** statement was described above. The **return** statement is

```
return [expression] [when boolean_expression];
```

A **return** statement without an expression may appear in an active task body to end the execution of the task.

## Assignment and Assignable Types

Assignment is defined for some types, and not for others. Types for which assignment is defined are said to *have assignment* or *be assignable*; types for which assignment is not defined are said to *lack assignment* or *be non-assignable*.

- Elementary (enumeration and numeric types) are assignable
- Hidden types are assignable
- Record types with the Assign aspect defined (see below) are assignable
- Task types are non-assignable
- Module types are non-assignable
- Set and sequence types are assignable
- Map types are assignable if their value types are assignable and non-assignable otherwise

In addition, assignment is not defined for

- Constants of any type
- Parameters of mode **in** of any type

## User-Defined Assignment, Initialization, and Finalization

Conceptually, each record type **R** has three attribute procedures

```
R'Assign : procedure (To : in out R; From : in R);  
R'Initialize : procedure (Item : in out R);  
R'Finalize : procedure (Item : in out R);
```

which are called to perform assignment, initialization, and finalization of objects of the type (no such calls need actually be made for the default cases). These can be defined by supplying matching procedures via the Assign, Initialize, and Finalize aspects for the type. Since the full type for a hidden type must be a record type, these are defined for the full types of hidden types as well.

```
type R is record  
  F : Integer;
```

```

end record R with
  Assign => Aardvark, Initialize => Impala, Finalize => Frog;

Aardvark : procedure (To : in out R; From : in R);
Impala   : procedure (Item : in out R);
Frog     : procedure (Item : in out R);

```

The procedure `R'Default_Assign` represents how `R` is assigned if it is assignable and no procedure is supplied for `Assign`. It may be called within an `Assign` procedure to obtain that assignment (using an assignment statement would result in recursion).

The compiler may not optimize away objects of a type with the `Finalize` aspect specified.

## The Standard Library

### *The Predefined Environment*

We have encountered many of the types and exceptions declared in the module `King_Predefined_Environment` already. There is also

```

type Byte_List is sequence of Byte_Value;

```

### *Platform Information*

We have encountered the maximum hardware integer values declared in the module `King.Platform_Information` already. There is also the named integer

```

Max_Hardware_Digits = implementation_defined_natural_integer;

```

This will be zero if the platform does not have hardware floating-point.

There are also types for all of the hardware integer types provided by the platform, both signed and unsigned. These have names of the form `Signed_n` and `Unsigned_n`, where  $n$  is the number of bytes used by the type. Typically these will be 1, 2, 4, and 8.

If the platform provides hardware floating-point, there will also be types for all of the hardware floating-point types provided. These have names of the form `Float_n`, where  $n$  is the number of digits provided by the type.

There is also

```

type Address_Value is hidden;

"=" : function (Left : in Address_Value; Right : in Address_Value)
return Boolean;

"<" : function (Left : in Address_Value; Right : in Address_Value)
return Boolean;

"<=" : function (Left : in Address_Value; Right : in Address_Value)
return Boolean;

```

```

">" : function (Left : in Address_Value; Right : in Address_Value)
return Boolean;

">=" : function (Left : in Address_Value; Right : in Address_Value)
return Boolean;

"\ " : function (Right : in Count_Value) return Address_Value;
-- Raises Constraint_Violation if Right does not correspond to a valid
-- Address_Value

"\ " : function (Right : in Address_Value) return Count_Value;

```

This is the first time we have encountered the unary conversion operator "\".

## ***Input-Output***

### **Binary I/O**

For binary I/O, there exists the module

```

King.IO : module is
  type File_Mode is (In_File, In_Out_File, Out_File, Append_File);
  subtype Input_Mode is File_Mode range In_File .. In_Out_File;
  subtype Output_Mode is File_Mode range In_Out_File .. Append_File;

  Invalid_Name : Exception_Occurrence;
  -- Name supplied to Open or Create is invalid
  Invalid_File : Exception_Occurrence; -- File not suitable for I/O
  EOF_Encountered : Exception_Occurrence;
  -- Attempt to read past the end of file

  type File_Handle is task
    Is_Open : function return Boolean; -- Initially returns False

    Mode : function return File_Mode with
      Precondition => Is_Open;

    Name : function return String with
      Precondition => Is_Open;
      -- Returns the Name used to open or create the file

    Size : function return Count_Value with
      Precondition => Is_Open;
      -- Returns the size of the file in bytes

    Open : procedure (Name : in String; Mode : in File_Mode) with
      Precondition => not Is_Open,
      Postcondition => Is_Open;
      -- If a valid file named Name exists, opens it in Mode
      -- Raises Invalid_Name if no file named Name exists
      -- Raises Invalid_File if Name exists but is not valid for I/O

    Create : procedure (Name : in String; Mode : in Output_Mode) with
      Precondition => not Is_Open,
      Postcondition => Is_Open;
      -- Raises Invalid_Name if Name is not a valid name for a file
      -- Raises Invalid_File if Name is valid but cannot be created
      -- If Name does not exist, creates an empty file with that name

```

```

-- and opens it in Mode. Mode = Append_File is the same as Out_File
-- If Name exists and Mode /= Append_File, deletes the existing file
-- and then proceeds as if the file had not existed
-- If Name exists and Mode = Append_File, opens the file in Mode

Close : procedure with
    Precondition => Is_Open,
    Postcondition => not Is_Open;

End_Of_File : function return Boolean with
    Precondition => Is_Open and then Mode in Input_Mode;

Seek : procedure (Position : in Position_Value) with
    Precondition => Is_Open and then Position in 1 .. Size + 1;
-- Sets the current position of the file to Position
-- Size + 1 is the end of the file; attempting to read will raise
-- EOF_Encountered
-- Writing will append to the file

Value : function (Position : in Count_Value <- 0) return Byte_Value with
    Precondition => Is_Open and then
        (Mode in Input_Mode and Position in 0 .. Size);
-- If Position > 0, effectively calls Seek with Position
-- Returns the byte at the current position in the file
-- Advances the current position of the file to the next position

Put : procedure (Item : in Byte_Value; Position : in Count_Value <- 0)
with
    Precondition => Is_Open and then
        (Mode in Output_Mode and Position in 0 .. Size + 1);
-- If Position > 0, effectively calls Seek with Position
-- Writes Item at the current position in the file
-- Advances the current position of the file to the next position

Get : procedure (Item : out Byte_List; Position : in Count_Value <- 0)
with
    Precondition => Is_Open and then
        (Mode in Input_Mode and Position in 0 .. Size);
-- If Position > 0, effectively calls Seek with Position
-- Does the equivalent of
--   Read : for I in Item'range loop
--       Item [I] <- Value;
--   Read : end loop;

Put : procedure (Item : in Byte_List; Position : in Count_Value <- 0)
with
    Precondition => Is_Open and then
        (Mode in Output_Mode and Position in 0 .. Size + 1);
-- If Position > 0, effectively calls Seek with Position
-- Calls Put for each byte in Item with Position => 0
end task File_Handle;

Standard_Input  : constant File_Handle;
Standard_Output : constant File_Handle;
Standard_Error  : constant File_Handle;
King.IO : end module;

```



Seek is not appropriate for all files. If it is applied to an inappropriate file, `Invalid_File` is raised. Specifically, Seek may not be applied to `Standard_Input`, `Standard_Output`, or `Standard_Error`.

For all types except module and task types, there is the attribute pseudo-function

```
T'As_Byte_List : function (Item : in T) return Byte_List;
```

As with all type-based attribute subprograms with a first parameter of the type, it can be applied to a value of the type with

```
V'As_Byte_List
```

The length of the result is `T'Byte_Size`. Usually this does not require any execution; it simply allows the compiler to treat the bytes of `V` as a `Byte_List`. This is called a pseudo-function because it's really a view conversion; as such, the result is not a constant as for real functions.

For every fixed-sized subtype and every value of such a subtype, there is the attribute `'Byte_Size` that is the minimum number of bytes needed to hold a value of the subtype, or to hold the value.

A type is fixed-sized if it is an enumeration type, a bounded numeric type represented by a fixed number of bytes, or a record type with all components of fixed-sized types.

For all types except module and task types there is the attribute pseudo-function

```
T'From_Byte_List : function (List : in Byte_List) return T with  
  Precondition => List.Length >= T'Byte_Size;
```

The bytes in `List [1 .. T'Byte_Size]` are interpreted as a value of the subtype. As with `'As_Byte_List`, this usually does not require any execution, and is really a view conversion. If it is possible for `List` to contain a sequence of bytes that is not the representation of a valid value of `T`, then a check is performed that `List` is valid. `Constraint_Violation` is raised if it is not.

Given

```
X : A;
```

the calls

```
B'From_Byte_List (X'As_Byte_List)
```

are equivalent to Ada's `Unchecked_Conversion`.

With these attributes and this module, one can perform arbitrary, heterogeneous binary I/O.

## Text I/O

For Latin-1 text I/O, there exists the module

```
use King.IO;
```

```
King.IO.Text : module is
  subtype File_Handle is King.IO.File_Handle;

  subtype Input_Mode is King.IO.Input_Mode;
  subtype Output_Mode is King.IO.Output_Mode;

  Standard_Input : constant File_Handle renames King.IO.Standard_Input;
  Standard_Output : constant File_Handle renames King.IO.Standard_Output;

  type EOL_ID is (DOS_Windows_EOL, Mac_EOL, Unix_EOL, Native_EOL);
  -- Indicates the kind of system that output EOLs should be written for
  -- DOS_Windows_EOL: CR-LF
  -- Mac_EOL:          CR
  -- Unix_EOL:         LF
  -- Native_EOL:       The native EOL for the system the program is running on

  -- For input operations, the Boolean parameter Any_EOL, defaulted to True,
  -- indicates if the operation should recognize EOLs from any system (True)
  -- or only those native to the system the program is running on

  End_Of_Line : function
    (File : in File_Handle <- Standard_Input; Any_EOL : in Boolean <- True)
  return Boolean with
    Precondition => File.Is_Open and then File.Mode in Input_Mode;
  -- Returns True if the next thing in File is a line terminator;
  -- False otherwise

  Skip_Line : procedure (Number : in Position_Value <- 1;
                        File : in File_Handle <- Standard_Input;
                        Any_EOL : in Boolean <- True)
  with
    Precondition => File.Is_Open and then File.Mode in Input_Mode;
  -- Skips Number line terminators in File

  New_Line : procedure (Number : in Position_Value <- 1;
                        File : in File_Handle <- Standard_Output;
                        EOL : in EOL_ID <- Native_EOL)
  with
    Precondition => File.Is_Open and then File.Mode in Output_Mode;
  -- Writes Number line terminators to File

  Next : function
    (File : in File_Handle <- Standard_Input; Any_EOL : in Boolean <- True)
  return Latin_1 with
    Precondition => File.Is_Open and then File.Mode in Input_Mode;
  -- Skips any line terminators in File, then returns the next character

  Put : procedure
    (Item : in Latin_1; File : in File_Handle <- Standard_Output)
  with
    Precondition => File.Is_Open and then File.Mode in Output_Mode;
  -- Writes Item to File

  Next_Line : function
```

```

    (File : in File_Handle <- Standard_Input; Any_EOL : in Boolean <- True)
return Latin_1_String with
    Precondition => File.Is_Open and then File.Mode in Input_Mode;
-- Returns all the characters in File until the next line terminator
-- Skips the line terminator

Put : procedure
    (Item : in Latin_1_String; File : in File_Handle <- Standard_Output)
with
    Precondition => File.Is_Open and then File.Mode in Output_Mode;
-- Calls Put to File for each character in Item

Put_Line : procedure (Item : in Latin_1_String;
                      File : in File_Handle <- Standard_Output
                      EOL : in EOL_ID <- Native_EOL)
with
    Precondition => File.Is_Open and then File.Mode in Output_Mode;
-- Has the effect of doing
-- Put (Item => Item, File => File);
-- New_Line (Number => 1, File => File, EOL => EOL);
King.IO.Text : end module;

```

Text I/O is very similar to Ada's. There are no pages, and no line or column counting. You can read and write files with line terminators for any of the major operating systems.

You can, of course, mix binary I/O operations with text operations for the same file. `End_Of_File`, being a binary operation, works correctly, unlike Ada's equivalent for text files.

There are equivalent modules `King.IO.BMP_Text` and `King.IO.Unicode_Text` for little-endian I/O of 2- and 3-byte values.

[TBD: module(s) for I/O of encoded (UTF-8, -16, -32) text]

User-defined character and string types may be written and read using the `'As_Universal` attribute function, which converts any character value to the equivalent universal\_character value. Consider the case of Roman numbers:

```

type Roman_Numeral is ('I', 'V', 'X', 'L', 'C', 'D', 'M') with Bit_Size => 3;
type Roman_Number is sequence of Roman_Numeral;

Value : Roman_Number;
...
Put : for C of Value loop
    King.IO.Text.Put (Item => C'As_Universal);
Put : end loop;

Value.Clear;

Get_Line : loop
    exit Get_Line when King.IO.Text.End_Of_Line;

    Value <- Value & King.IO.Text.Next'As_Universal;
Get_Line : end loop;

King.IO.Text.Skip_Line;

```

## Directory Operations

King.IO.Directories : **module is** ...

## Command Line

For querying the command line, there is the module

```
King.Command_Line : module is
  Command : function return Latin_1_String;
  -- Returns the command name used to run the program

  Count : function return Count_Value;
  -- Returns the number of command-line arguments provided

  Value : function (Position : in Position_Value) return Latin_1_String with
    Precondition => Position in Position_Value range 1 .. Count;
  -- Returns the argument at Position
King.Command_Line : end module;
```

## Time and Date

For obtaining and manipulating times and dates, King has the modules

```
King.Calendar : module is
  Update_Interval = implementation_defined_real_number;
  -- The value returned by Clock changes at this interval (in seconds)

  Clock : function return Natural_Duration;
  -- A monotonic clock returning the number of seconds since the epoch
  -- (which is implementation defined)
King.Calendar : end module;
```

Calendar is King's equivalent to Ada's Real\_Time. Update\_Interval must be one millisecond or less, ideally one microsecond or less. The **wait for** statement takes a **Duration** that is interpreted the same as a value obtained from Clock, and blocks the task until Clock would return a value >= that given.

```
King.Calendar.UTC : module is
  To_UTC : function (Monotonic : in Duration) return Duration;
  -- Converts Monotonic, a monotonic time (an offset from the monotonic epoch),
  -- to a UTC time [an offset from the CE epoch (0001-01-01 00:00:00.00)]

  From_UTC : function (UTC : in Duration) return Duration;
  -- Converts UTC, a UTC time, to a monotonic time

  Local_Offset : function return Duration;
  -- Returns the offset added to UTC to obtain the local system time

  subtype Year_Number is Unbounded_Integer with
    Predicate => Year_Number /= 0, Default_Value => 1;
  -- Negative values represent years BCE
```

```

-- Zero is excluded because the calendar has no year zero

subtype CE_Year is Year_Number with
  Predicate => CE_Year > 0;

subtype Month_Number is Integer range 1 .. 12;
subtype Day_Number is Integer range 1 .. 31;
subtype Day_Seconds is Duration range 0 .. 86_400 - Duration'delta;
subtype Hour_Number is Integer range 0 .. 23;
subtype Minute_Number is Integer range 0 .. 59;
subtype Minute_Seconds is Duration range 0 .. 60 - Duration'delta;

type Time_YMDS is record
  Year : Year_Number;
  Month : Month_Number;
  Day : Day_Number;
  Seconds : Day_Seconds;
end record Time_YMDS;

Days_In_Month : function (Time : in Natural_Duration) return Day_Number;
Days_In_Month : function (Year : in CE_Year; Month : in Month_Number)
return Day_Number;

"\ " : function (Time : in Natural_Duration) return Time_YMDS;
"\ " : function (Time : in Time_YMDS) return Duration with
  Precondition => Time.Year > 0 and then
    Time.Day in Day_Number range
      1 .. Days_In_Month (Time.Year, Time.Month);
-- Conversions between CE time values and Time_YMDS

type Time_YMDHMS is record
  Year : Year_Number;
  Month : Month_Number;
  Day : Day_Number;
  Hour : Hour_Number;
  Minute : Minute_Number;
  Seconds : Minute_Seconds;
end record Time_YMDHMS;

Image : function (Time : in Time_YMDHMS) return String is
  (Time.Year'Image (Width => 4, Zero_Filled => True) & '-' &
   Time.Month'Image (Width => 2, Zero_Filled => True) & '-' &
   Time.Day'Image (Width => 2, Zero_Filled => True) & ' ' &
   Time.Hour'Image (Width => 2, Zero_Filled => True) & ':' &
   Time.Minute'Image (Width => 2, Zero_Filled => True) & ':' &
   Time.Seconds'Image
    (Before => 2, After => 2, Exponent => 0, Zero_Filled => True) ) with
  Precondition => Time.Year < 0 or else Time.Day in Day_Number range
    1 .. Days_In_Month (Time.Year, Time.Month);

"\ " : function (Time : in Natural_Duration) return Time_YMDHMS;
"\ " : function (Time : in Time_YMDHMS) return Natural_Duration with
  Precondition => Time.Year > 0 and then
    Time.Day in Day_Number range
      1 .. Days_In_Month (Time.Year, Time.Month);
-- Conversions between CE time values and Time_YMDHMS

type Time_HMS is record
  Hour : Hour_Number;
  Minute : Minute_Number;

```

```

    Seconds : Minute_Seconds;
end record Time_HMS;

"\ " : function (Time : in Day_Seconds) return Time_HMS;
"\ " : function (HMS : in Time_HMS) return Day_Seconds;
-- Conversions between Day_Seconds and Time_HMS

type Day_Name is
    (Sunday, Monday, Tuesday, Wednesday, Thursday, Friday, Saturday);

Day_Of_Week : function (Time : in Natural_Duration) return Day_Name;
Day_Of_Week : function
    (Year : in CE_Year; Month : in Month_Number; Day : in Day_Number)
return Day_Name with
    Precondition => Day in Day_Number range 1 .. Days_In_Month (Year, Month);
-- Only defined for years CE

Leap_Year : function (Time : in Natural_Duration) return Boolean;
Leap_Year : function (Year : in CE_Year) return Boolean;
King.Calendar.UTC : end module;

```

## ***Data Structures***

```
King.Data_Structures : module is ...
```

### **Lists (Linked Sequences)**

```

King.Data_Structures.Lists : module is ...
King.Data_Structures.Lists.Unbounded : module is ...
King.Data_Structures.Lists.Unbounded.Protected : module is ...
King.Data_Structures.Lists.Unbounded.Unprotected : module is ...
King.Data_Structures.Lists.Bounded : module is ...
King.Data_Structures.Lists.Bounded.Protected : module is ...
King.Data_Structures.Lists.Bounded.Unprotected : module is ...

```

### **Queues**

```

King.Data_Structures.Queues : module is ...
King.Data_Structures.Queues.Bounded : module is ...
King.Data_Structures.Queues.Unbounded : module is ...
King.Data_Structures.Queues.Unbounded.Protected : macro
    type Element is hidden with <-;
King.Data_Structures.Queues.Unbounded.Protected : module is
    type Handle is task
        Put : procedure (Item : in Element);

```

```

-- Adds Item to the tail of the queue

Head : function return Element;
-- Removes the Element at the head of the queue and returns it
-- Blocks the caller if the queue is empty until the queue becomes
-- non-empty

Length : function return Count_Value;
-- Returns the number of Elements in the queue

Value : function (Position : in Position_Value) return Element with
    Precondition => Position in 1 .. Length;
-- Returns the value of the Element in the queue at Position
-- Position 1 is head of the queue
end task Handle;
King.Data_Structures.Queues.Unbounded.Protected : end module;

```

## Stacks

```

King.Data_Structures.Stacks : module is ...

King.Data_Structures.Stacks.Unbounded : module is ...

King.Data_Structures.Stacks.Unbounded.Protected : module is ...

King.Data_Structures.Stacks.Unbounded.Unprotected : module is ...

King.Data_Structures.Stacks.Bounded : module is ...

King.Data_Structures.Stacks.Bounded.Protected : module is ...

King.Data_Structures.Stacks.Bounded.Unprotected : module is ...

```

## Bags

```

King.Data_Structures.Bags : module is ...

King.Data_Structures.Bags.Unbounded : module is ...

King.Data_Structures.Bags.Unbounded.Protected : module is ...

King.Data_Structures.Bags.Unbounded.Unprotected : module is ...

King.Data_Structures.Bags.Bounded : module is ...

King.Data_Structures.Bags.Bounded.Protected : module is ...

King.Data_Structures.Bags.Bounded.Unprotected : module is ...

```

## Holders

```

King.Data_Structures.Holders : macro
    type Element (<>) is hidden with <-;
King.Data_Structures.Holders : module is
    type Holder is module
        Is_Empty : function return Boolean;

```

```

-- Returns True until Put has been called; False thereafter

Put : procedure (Item : in Element) with
  Postcondition => not Is_Empty and Value = Item;

Value : function return Element with
  Precondition => not Is_Empty;
end module Holder;
King.Data_Structures.Holders : end module;

```

## Searchable Structures

```
King.Data_Structures.Searchable : module is ...
```

### $O(1)$

Hash tables

### $O(\log N)$

Balanced trees or skip lists

```

King.Data_Structures.Searchable.O_Log_N : macro
  type Element is hidden with <-;

  "=" : function (Left : in Element; Right : in Element) return Boolean is <>;
  "<" : function (Left : in Element; Right : in Element) return Boolean is <>;
King.Data_Structures.Searchable.O_Log_N : module is
  type Structure is hidden;

  Length : function (Structure : in Structure) return Count_Value;
  -- Returns the number of Elements stored in Structure

  Is_Empty : function (Structure : in Structure) return Boolean is
    (Structure.Length = 0);

  Clear : procedure (Structure : in out Structure) with
    Postcondition => Structure.Is_Empty;

  type Result (Found : Boolean <- False) is record
    case Found is
      when False =>
        null;
      when True =>
        Item : Element;
    end case;
  end record Result;

  Contains : function (Structure : in Structure; Item : in Element)
  return Result;
  -- If Structure contains a value = Item, returns a Result with Found
  -- of True and Item = the stored value
  -- Returns Result'(Found => False) otherwise

  Insert : procedure (Structure : in out Structure; Item : in Element) with
    Postcondition => Structure.Contains (Item).Found;
  -- If Structure contains a value = Item, replaces it with Item

```



```

-- Otherwise, adds Item to Structure

Delete : procedure (Structure : in out Structure; Item : in Element) with
    Postcondition => not Structure.Contains (Item).Found;
-- If Structure contains a value = Item, deletes it from Structure
-- Otherwise, has no effect

First : function (Structure : in Structure) return Element with
    Precondition => not Structure.Is_Empty;
-- Returns the first value (in "<" order) in Structure

Last : function (Structure : in Structure) return Element with
    Precondition => not Structure.Is_Empty;
-- Returns the last value (in "<" order) in Structure

Iteration : macro
    Action : procedure (Item : in Element; Stop : in out Boolean);
Iteration : module is
    Iterate : procedure (Over : in Structure);
        -- Passes each value in Over, in "<" order, to Action with
        -- Stop set to False
        -- Stops iteration if Action sets Stop to True
    Iteration : end module;
King.Data_Structures.Searchable.O_Log_N : end module;

```

Type **Structure** will usually need to have user-defined assignment and finalization.

## ***Algorithms***

```
King.Algorithms : module is ...
```

### **Binary Search**

### **Hashing**

### **Numerics**

```
King.Algorithms.Numerics : module is ...
```

## ***Functions***

### ***Random-Number Generation***

```
King.Algorithms.Numerics.Random : module is
    subtype Uniform is Float range 0 .. Float'Previous (1);
King.Algorithms.Numerics.Random : end module;
```

```
use King.Platform_Information;
```

```
King.Algorithms.Numerics.Random.Unsigned_4 : module is
```

```

subtype U4 is King.Platform_Information.Unsigned_4;

type Generator is module -- Initially seeded with zero
  Set_Seed : procedure (Seed : in U4);
  -- Seeds the generator with Seed

  Randomize : procedure;
  -- Seeds the generator with a value derived from the clock

  Random : function return U4;
  -- Returns a random value
end module Generator;
King.Algorithms.Numerics.Random.Unsigned_4 : end module;

use King.Platform_Information;

King.Algorithms.Numerics.Random.Unsigned_4_Ranges : module is
  subtype U4 is King.Platform_Information.Unsigned_4;

  Random : function (Value : in U4; Min : in U4; Max : in U4) return U4 with
    Precondition => Min <= Max;
  -- Given a random Value (from
  -- King.Algorithms.Numerics.Random.Unsigned_4.Random), returns a uniformly
  -- distributed value in Min .. Max
King.Algorithms.Numerics.Random.Unsigned_4_Ranges : end module;

use King.Algorithms.Numerics.Random;
use King.Platform_Information;

King.Algorithms.Numerics.Random.Floating : module is
  subtype Uniform is King.Algorithms.Numerics.Random.Uniform;
  subtype S4 is King.Platform_Information.Signed_4;

  type Generator is module -- Initially seeded with zero
    Set_Seed : procedure (Seed : in S4);
    -- Seeds the generator with Seed

    Randomize : procedure;
    -- Seeds the generator with a value derived from the clock

    Random : function return Uniform;
    -- Returns a random value
  end module Generator;
King.Algorithms.Numerics.Random.Floating : end module;

```

***Linear Regression***

***Complex Numbers***

***Matrices and Vectors***

**Pattern Matching**

***Regular Expressions***

***Quick String Matching***

**Min/Max**

```
King.Algorithms.Min_Max : macro
  type Element (<>) is hidden;

  "<" : function (Left : in Element; Right : in Element) return Boolean is <>;
King.Algorithms.Min_Max : module is
  Min : function (Left : in Element; Right : in Element) return Element is
    (if Left < Right then Left else Right);
  Max : function (Left : in Element; Right : in Element) return Element is
    (if Left < Right then Right else Left);
King.Algorithms.Min_Max : end module;
```

**Strings**

**Sorting**

***Heap***

***Insertion***

***Quick***

***Radix***

**Wrapping**

```
King.Algorithms.Wrapping : macro
  type Element is (<>);
King.Algorithms.Wrapping : module
  Previous : function (Item : in Element) return Element is
    (if Item = Element'First then Element'Last else Item'Previous);

  Next : function (Item : in Element) return Element is
    (if Item = Element'Last then Element'First else Item'Next);
King.Algorithms.Wrapping : end module;
```

## GUI

King comes with a GUI library for portable GUI applications. Since King is a concurrent language, its GUI does not use the callback model often used by GUI libraries for sequential languages to work around the inherent parallelism of GUIs..

```
King.GUI : module is
  type Widget_Kind_ID is (Audio_Player,   Background_Text, Button,
                          Check_Box,      Graphic_Area,   Radio_Buttons,
                          Selection_List, Text_Area,       Text_Box,
                          Video_Player);

  type Widget_ID is hidden with
    Default_Initial_Condition => Widget_ID = Invalid_Widget;

  Invalid_Widget : constant Widget_ID;

  "=" : function (Left : in Widget_ID; Right : in Widget_ID) return Boolean;

  -- GUI/window preparation and destruction

  type Window_ID is hidden with
    Default_Initial_Condition => Window_ID = Invalid_Window;
  -- A GUI has at least one "window", identified by a Window_ID
  -- The exact meaning of a window is implementation defined

  Invalid_Window : constant Window_ID;
  Main_Window    : constant Window_ID;

  Set_Up : function (ID : in Window_ID <- Main_Window) return Boolean with
    Precondition => ID /= Invalid_Window;
  -- Returns True after function Set_Up has returned ID and ID has not been
  -- torn down; False otherwise

  Kind : function (Widget : in Widget_ID) return Widget_Kind_ID with
    Precondition => Set_Up and Widget /= Invalid_Widget;
  -- Returns the kind of widget identified by Widget

  type Alignment_ID is (Left, Center, Right);

  type Row_Alignment is map Position_Value => Alignment_ID;

  type Grid_Set is map Position_Value => Row_Alignment;

  Set_Up : function (Grid : in Grid_Set <- Grid_Set'(1 => (1 => Center) ));
    Main : in Boolean <- True)
  return Window_ID with
    Precondition  => Main = not Main_Window.Set_Up and
                      (for all R of Grid => R.Size = Grid (1).Size),
    Postcondition => Set_Up'Result.Set_Up;
  -- Sets up a window with a grid of Grid.Size rows by Grid (1).Size
  -- columns of display areas
  -- Each display area has the alignment given by Grid for its row and column
  -- Returns the ID of the new window; returns Main_Window if Main

  Tear_Down : procedure (ID : in Window_ID <- Main_Window) with
    Precondition => ID.Set_Up, Postcondition => not ID.Set_Up;
  -- Reverses the effect of Set_Up and destroys any widgets that have been
```

```

-- created for ID
-- Tearing down Main_Window tears down any other windows first

Num_Rows : function (ID : in Window_ID <- Main_Window) return Positive with
    Precondition => ID.Set_Up;
Num_Columns : function (ID : in Window_ID <- Main_Window) return Positive
with
    Precondition => ID.Set_Up;
-- Returns the number of rows or columns in the Grid passed to Set_Up

-- For the New_[Widget] functions in child modules, if Below, the widget
-- appears below any existing widgets in its display area;
-- otherwise, it appears to the right of the most recent widget in its
-- display area
-- All New_[Widget] functions return the ID of the new widget
-- All New_[Widget] functions take the ID of a window and the Row and Column
-- of the display area in that window in which the widget will be created

-- Event handling

type Event_Kind_ID is (Primary_Click, Middle_Click, Secondary_Click);
-- Primary button is usually the left button, and secondary the right,
-- but for left handers they may be switched

type Event_Info (Widget_Kind : Widget_Kind_ID <- Text_Box) is record
    ID : Widget_ID;

    case Widget_Kind is
    when Button | Selection_List =>
        Event_Kind : Event_Kind_ID;
    when others =>
        null;
    end case;
end record Event_Info;

Event_Info_Queue : module is new
    King.Data_Structures.Queues.Unbounded.Protected (Element => Event_Info);
subtype Event_Info_Queue is Event_Info_Queue.Handle;

Event_Queue : constant Event_Info_Queue;

-- General operations

Set_Title : procedure (Title : in String; ID : in Window_ID <- Main_Window)
with
    Precondition => ID.Set_Up;
-- Sets the window title to Title

Show_Message_Box : procedure
    (Text : in String; ID : in Window_ID <- Main_Window)
with
    Precondition => ID.Set_Up;
-- Shows a dialog box with Text and an OK button

type File_Info (Picked : Boolean <- False) is record
    case Picked is
    when False =>
        null;
    when True =>
        Name : String;

```

```

    end case;
end record File_Info;

Selected_File : function (Initial_Directory : in String <- ".")
return File_Info;
-- Opens a file-selection dialog with the files for Initial_Directory
-- If the user cancels the dialog, returns (Picked => False)
-- Otherwise, the return value has Picked => True and the Name component
-- contains the full path of the selected file
King.GUI : end module;

use King.GUI;

King.GUI.Widgets : module is
  subtype Window_ID is King.GUI.Window_ID;
  subtype Widget_ID is King.GUI.Widget_ID;

  Main_Window : constant Window_ID renames King.GUI.Main_Window;

  Valid_Position : function
    (ID : in Window_ID; Row : in Positive; Column : in Positive)
  return Boolean is
    ID.Set_Up and then
    (Row in 1 .. ID.Num_Rows and
     Column in 1 .. ID.Num_Columns);

  New_Audio_Player : function (Row      : in Positive;
                               Column    : in Positive;
                               Below     : in Boolean   <- False;
                               Source     : in String    <- "";
                               Controls   : in Boolean   <- True;
                               ID        : in Window_ID <- Main_Window)
  return Widget_ID with
    Precondition => Valid_Position (ID, Row, Column);
  -- Creates an Audio_Player
  -- Source is the audio file name to load; if "", then no audio file is loaded
  -- If Controls, then controls are displayed for the player and the user can
  -- use them to control the player
  -- Otherwise, no controls are displayed and control of the player must be
  -- done by the program

  New_Background_Text : function (Row      : in Positive;
                                  Column    : in Positive;
                                  Text      : in String;
                                  Below     : in Boolean   <- False;
                                  ID        : in Window_ID <- Main_Window)
  return Widget_ID with
    Precondition => Valid_Position (ID, Row, Column);
  -- Creates a new Background_Text with contents Text
  -- Like a label, background text is not in any visible widget;
  -- unlike a label, background text is not associated with a widget

  New_Button : function (Row      : in Positive;
                          Column    : in Positive;
                          Text      : in String;
                          Below     : in Boolean   <- False;
                          ID        : in Window_ID <- Main_Window)
  return Widget_ID with
    Precondition => Valid_Position (ID, Row, Column);
  -- Creates a Button with button label Text.

```

```

-- Clicks on buttons generate events
(ID)
New_Check_Box : function (Row      : in Positive;
                          Column   : in Positive;
                          Label    : in String;
                          Below    : in Boolean  <- False;
                          Active   : in Boolean  <- False;
                          ID       : in Window_ID <- Main_Window)

return Widget_ID with
  Precondition => Valid_Position (ID, Row, Column);
-- Creates a new Check_Box with label Label
-- If Active, the box will be checked; otherwise, it will be unchecked

New_Graphic_Area : function (Row      : in Positive;
                             Column   : in Positive;
                             Width    : in Positive;
                             Height   : in Positive;
                             Below    : in Boolean  <- False;
                             ID       : in Window_ID <- Main_Window)

return Widget_ID with
  Precondition => Valid_Position (ID, Row, Column);
-- Creates a new Graphic_Area of Width by Height pixels
-- (0, 0) is the upper-left corner; (Width - 1, Height - 1) is the
-- lower-right corner

type Text_List is sequence of String;

Empty_List : constant Text_List is Text_List'[1 .. 0 => <>];

type Orientation_ID is (Horizontal, Vertical);

New_Radio_Buttons : function (Row      : in Positive;
                              Column   : in Positive;
                              Label     : in Text_List;
                              Below     : in Boolean  <- False;
                              Orientation : in Orientation_ID <- Vertical;
                              ID        : in Window_ID <- Main_Window)

return Widget_ID with
  Precondition => Valid_Position (ID, Row, Column);
-- Creates Label.Length radio buttons
-- Label contains the labels for the buttons
-- Orientation = Horizontal results in a row of buttons
--               = Vertical   has each button after the 1st below the preceding
--                           buttons
-- The first button will be active
-- The operations Set_Active and Active for radio buttons take an Index;
-- Index refers to the button for Label [Index]

New_Selection_List : function (Row      : in Positive;
                              Column   : in Positive;
                              Text      : in Text_List <- Empty_List;
                              Below     : in Boolean  <- False;
                              Height    : in Positive <- 1;
                              Multiple_Select : in Boolean  <- False;
                              ID        : in Window_ID <- Main_Window)

return Widget_ID with
  Precondition => Valid_Position (ID, Row, Column);
-- Text contains the initial set of options; it may be empty
-- Height is in lines; 1 results in a drop-down list;
-- otherwise it scrolls if it has more than Height options

```

```

-- If Multiple_Select, the user can select more than one option at a time;
-- otherwise, only one option may be selected at a time
-- The set of options may be modified later using Insert and Delete
-- Clicks on selection lists generate events

New_Text_Area : function (Row      : in Positive;
                          Column  : in Positive;
                          Text    : in String   <- "";
                          Below   : in Boolean  <- False;
                          Width   : in Positive <- 20;
                          Height  : in Positive <- 2;
                          ID      : in Window_ID <- Main_Window)

return Widget_ID with
    Precondition => Valid_Position (ID, Row, Column);
-- Creates a new Text Area with initial content of Text
-- Width is width of area in characters
-- Height is height of area in lines

New_Text_Box : function (Row      : in Positive;
                        Column    : in Positive;
                        Text      : in String   <- "";
                        Label     : in String   <- "";
                        Placeholder : in String  <- "";
                        Below     : in Boolean  <- False;
                        Width     : in Positive <- 20;
                        ID        : in Window_ID <- Main_Window)

return Widget_ID with
    Precondition => Valid_Position (ID, Row, Column);
-- Creates a new Text Box with initial content of Text
-- LFs in Text will cause line breaks
-- Label will appear to the left of the text box
-- If Placeholder /= "", Placeholder will appear in the text box when it is
-- empty and awaiting input
-- Width is width of box in characters

New_Video_Player : function (Row      : in Positive;
                          Column    : in Positive;
                          Below     : in Boolean  <- False;
                          Source    : in String   <- "";
                          Controls  : in Boolean  <- True;
                          ID        : in Window_ID <- Main_Window)

return Widget_ID with
    Precondition => Valid_Position (ID, Row, Column);
-- Creates a Video_Player
-- Source is the video file name to load; if "", then no video file is loaded
-- If Controls, then controls are displayed for the player and the user can
-- use them to control the player
-- Otherwise, no controls are displayed and control of the player must be
-- done by the program
King.GUI.Widgets : end module;

use King.GUI;

King.GUI.Media_Control : module is -- Media-player control
    subtype Widget_ID is King.GUI.Widget_ID;

    Set_Source : procedure (ID : in Widget_ID; Source : in String) with
        Precondition =>
            King.GUI.Set_Up and then ID.Kind in Audio_Player | Video_Player;
-- Makes Source the media source file name for ID and loads Source

```



```

Source : function (ID : in Widget_ID) return String with
    Precondition =>
        King.GUI.Set_Up and then ID.Kind in Audio_Player | Video_Player;
-- Returns the media source file name for ID

Ready : function (ID : in Widget_ID) return Boolean with
    Precondition =>
        King.GUI.Set_Up and then ID.Kind in Audio_Player | Video_Player;
-- Returns True if ID is ready to play its source; False otherwise
-- There is a perceptible (to a computer) delay between a call to Set_Source
-- and Ready returning True

Play : procedure (ID : in Widget_ID) with
    Precondition =>
        King.GUI.Set_Up and then ID.Kind in Audio_Player | Video_Player;
-- Plays the current source from the current position for ID

Pause : procedure (ID : in Widget_ID) with
    Precondition =>
        King.GUI.Set_Up and then ID.Kind in Audio_Player | Video_Player;
-- Pauses playback for ID

Paused : function (ID : in Widget_ID) return Boolean with
    Precondition =>
        King.GUI.Set_Up and then ID.Kind in Audio_Player | Video_Player;
-- Returns True if playback is paused for ID; False otherwise

Playback_Ended : function (ID : in Widget_ID) return Boolean with
    Precondition =>
        King.GUI.Set_Up and then ID.Kind in Audio_Player | Video_Player;
-- Returns True if playback has ended for ID; False otherwise

Length : function (ID : in Widget_ID) return Natural_Duration with
    Precondition =>
        King.GUI.Set_Up and then ID.Kind in Audio_Player | Video_Player;
-- Returns the length of the current source for ID in seconds

Set_Position : procedure (ID : in Widget_ID; Position : in Natural_Duration)
with
    Precondition => Set_Up and then ID.Kind in Audio_Player | Video_Player;
-- Sets the current position for ID to Position in seconds
-- 0.0 is the beginning and Length (ID) is the end

Position : function (ID : in Widget_ID) return Natural_Duration with
    Precondition =>
        King.GUI.Set_Up and then ID.Kind in Audio_Player | Video_Player;
-- Returns the current position of ID in seconds
King.Gui.Media_Control : end module;

use King.GUI;

King.GUI.Check_Boxes : module is -- Check box operations
    subtype Widget_ID is King.GUI.Widget_ID;

    Set_Active : procedure (ID : in Widget_ID; Active : in Boolean) with
        Precondition => King.GUI.Set_Up and then ID.Kind = Check_Box;
    -- If Active, makes ID checked, else makes ID unchecked

    Active : function (ID : in Widget_ID) return Boolean with

```



```

    Peru,           Pink,           Plum,
    Powder_Blue,    Purple,
    Red,            Rosy_Brown,      Royal_Blue,
    Saddle_Brown,   Salmon,          Sandy_Brown,
    Sea_Green,      Sea_Shell,       Sienna,
    Silver,         Sky_Blue,        Slate_Blue,
    Slate_Gray,     Slate_Grey,       Snow,
    Spring_Green,   Steel_Blue,
    Tan,           Teal,
    Tomato,        Turquoise,
    Violet,
    Wheat,         White,
    Yellow,        Yellow_Green);

To_Color : function (Color : in Color_ID) return Color_Info;
To_ID     : function (Color : in Color_Info) return Color_ID with
    Precondition => (for some ID in Color_ID => To_Color (ID) = Color);
-- Conversions between Color_Info and Color_ID

-- Graphic area operations that work in whole or in part on coordinates
-- outside the drawing area succeed, but the parts that involve coordinates
-- outside the drawing area have no effect

Width : function (ID : in Widget_ID) return Positive with
    Precondition => King.GUI.Set_Up and then ID.Kind = Graphic_Area;
Height : function (ID : in Widget_ID) return Positive with
    Precondition => King.GUI.Set_Up and then ID.Kind = Graphic_Area;
-- Return the Width and Height parameters used when ID was created

Set_Pixel : procedure (ID      : in Widget_ID;
                      X       : in Integer;
                      Y       : in Integer;
                      Color   : in Color_Info <- To_Color (Black) )
with
    Precondition => King.GUI.Set_Up and then ID.Kind = Graphic_Area;
-- If (X, Y) is in the drawing area, sets it to Color

Pixel : function (ID : in Widget_ID; X : in Natural; Y : in Natural)
return Color_Info with
    Precondition => King.GUI.Set_Up and then ID.Kind = Graphic_Area and then
        (X in Integer range 0 .. Width (ID)- 1 and
         Y in Integer range 0 .. Height (ID)- 1;
-- Returns the color at (X, Y)

Draw_Line : procedure (ID      : in Widget_ID;
                      From_X  : in Integer;
                      From_Y  : in Integer;
                      To_X    : in Integer;
                      To_Y    : in Integer;
                      Color   : in Color_Info <- To_Color (Black) )
with
    Precondition => King.GUI.Set_Up and then ID.Kind = Graphic_Area;
-- Draws a line from (From_X, From_Y) to (To_X, To_Y) in Color

type Optional_Color (None : Boolean) is record
    case None is
        when False =>
            Color : Color_Info;
        when True =>
            null;

```

```

    end case;
end record Optional_Color;

Draw_Rectangle : procedure (ID           : in Widget_ID;
                           From_X       : in Integer;
                           From_Y       : in Integer;
                           To_X         : in Integer;
                           To_Y         : in Integer;
                           Line_Color   : in Optional_Color <-
                                Optional_Color'(None => False,
                                                Color => To_Color (Black) );
                           Fill_Color   : in Optional_Color <-
                                Optional_Color'(None => True) )

with
    Precondition => King.GUI.Set_Up and then ID.Kind = Graphic_Area;
-- Draws a rectangle with one corner at (From_x, From_Y) and
-- the opposite corner at (To_X, To_Y)
-- If not Line_Color.None, the rectangle will have a line around it in
-- Line_Color.Color
-- If not Fill_Color.None, the rectangle will be filled with Fill_Color.Color
-- If Line_Color.None and Fill_Color.None, does nothing

Draw_Arc : procedure (ID           : in Widget_ID;
                     X             : in Integer;
                     Y             : in Integer;
                     Radius        : in Positive;
                     Start         : in Float;
                     Stop          : in Float;
                     Counter_Clockwise : in Boolean <- False;
                     Line_Color    : in Optional_Color <-
                                Optional_Color'(None => False,
                                                Color => To_Color (Black) );
                     Fill_Color    : in Optional_Color <-
                                Optional_Color'(None => True) )

with
    Precondition => King.GUI.Set_Up and then ID.Kind = Graphic_Area;
-- Draws an arc with center at (X, Y) and radius Radius (in pixels) from
-- angle Start to angle Stop
-- Angles are in radians and increase clockwise
-- If Counter_Clockwise, draws an arc counter-clockwise from Start to Stop;
-- otherwise, draws clockwise
-- If not Line_Color.None, the arc will have a line along it in
-- Line_Color.Color; if not Fill_Color.None as well, there will also
-- be lines between the ends of the arc and the center point
-- If not Fill_Color.None, the arc will be filled with Fill_Color.Color
-- If Line_Color.None and Fill_Color.None, does nothing
King.GUI.Graphic_Operqations : end module;

use King.GUI;

King.GUI.Radio_Buttons : module is -- Radio Button operations
    subtype Widget_ID is King.GUI.Widget_ID;

    Num_Buttons : function (ID : in Widget_ID) return Count_Value with
        Precondition => King.GUI.Set_Up and then ID.Kind = Radio_Buttons;
    -- Returns the number of buttons in ID

    Set_Active : procedure (ID : in Widget_ID; Index : in Position_Value) with
        Precondition => King.GUI.Set_Up and then
            ID.Kind = Radio_Buttons and then

```

```

        Index in Unbounded_Integer range 1 .. Num_Buttons (ID),
        Postcondition => Active (ID) = Index;
-- Makes Index the active button of ID

Active : function (ID : in Widget_ID) return Position_Value with
    Precondition => King.GUI.Set_Up and then ID.Kind = Radio_Buttons;
-- Returns the index of the active button of ID
King.GUI.Radio_Buttons : end module;

use King.GUI;

King.GUI.Selection_Lists : module is -- Selection List operations
    subtype Widget_ID is King.GUI.Widget_ID;

    Multiple_Select : function (ID : Widget_ID) return Boolean with
        Precondition => King.GUI.Set_Up and then ID.Kind = Selection_List;
-- Returns the value of Multiple_Select used to create ID

    Num_Options : function (ID : in Widget_ID) return Count_Value with
        Precondition => King.GUI.Set_Up and then ID.Kind = Selection_List;
-- Returns the number of options in ID

    Clear : procedure (ID : in Widget_ID) with
        Precondition  => King.GUI.Set_Up and then ID.Kind = Selection_List,
        Postcondition => Num_Options (ID) = 0;

    Set_Selected : procedure
        (ID : in Widget_ID; Index : in Position_Value; Selected : in Boolean)
    with
        Precondition => King.GUI.Set_Up and then
            ID.Kind = Selection_List and then
                Index in Position_Value range 1 .. Num_Options (ID);
-- Makes Selected (ID, Index) return Selected

    Selected : function (ID : in Widget_ID) return Count_Value with
        Precondition => King.GUI.Set_Up and then
            ID.Kind = Selection_List and then
                not Multiple_Select (ID);
-- Returns the index of the currently selected option in ID or
-- zero if there is no selection

    Selected : function (ID : in Widget_ID; Index : in Position_Value)
    return Boolean with
        Precondition => King.GUI.Set_Up and then
            ID.Kind = Selection_List and then
                Index in Position_Value range 1 .. Num_Options (ID);
-- Returns True if option Index in ID is selected; False otherwise

    Text : function (ID : in Widget_ID; Index : in Position_Value)
    return String with
        Precondition => King.GUI.Set_Up and then
            ID.Kind = Selection_List and then
                Index in Position_Value range 1 .. Num_Options (ID);
-- Returns the text of option Index

    Insert : procedure
        (ID : in Widget_ID; Text : in String; Before : in Position_Value)
    with
        Precondition => King.GUI.Set_Up and then ID.Kind = Selection_List;
-- if Before > Num_Options (ID), appends Text to the options of ID

```

```

-- Otherwise, inserts Text as the option with index Before,
-- moving up the options previously at Before .. Num_Options (ID)

Delete : procedure (ID : in Widget_ID; Index : in Position_Value) with
    Precondition => King.GUI.Set_Up and then
        ID.Kind = Selection_List and then
            Index in Unbounded_Integer range 1 .. Num_Options (ID);
-- Deletes the option at Index, moving down the options previously at
-- Index + 1 .. Num_Options (ID)
King.GUI.Selection_Lists : end module;

use King.GUI;

King.GUI.Text_Operations : module is -- General text operations
    subtype Widget_ID is King.GUI.Widget_ID;

    Set_Text : procedure (ID : in Widget_ID; Text : in String) with
        Precondition => King.GUI.Set_Up and then
            ID.Kind in Background_Text .. Button |
                Selection_List .. Text_Box and then
                (if ID.Kind = Selection_List then
                    not Multiple_Select (ID)
                else
                    True);
-- Sets the text for ID to Text
-- For a Selection_List, sets the text for the current selection; if no
-- selection, has no effect
-- For a Text_Area, embedded LFs cause line breaks

    Text : function (ID : in Widget_ID) return String with
        Precondition => King.GUI.Set_Up and then
            ID.Kind in Background_Text .. Button |
                Selection_List .. Text_Box and then
                (if ID.Kind = Selection_List then
                    not Multiple_Select (ID)
                else
                    True);
-- Returns the text for ID
-- For a Selection_List, returns the text of the current selection; if no
-- selection, returns ""
-- For a Text_Area, line breaks are encoded as Lfs
King.GUI.Text_Operations : end module;

```

[There needs to be much more to the GUI.]

## Reserved Words

King has the following reserved words:

<b>all</b>	<b>and</b>		
<b>begin</b>	<b>body</b>		
<b>case</b>	<b>constant</b>		
<b>declare</b>	<b>delta</b>	<b>digits</b>	
<b>else</b>	<b>else_if</b>	<b>end</b>	<b>exit</b>
<b>for</b>	<b>function</b>		
<b>hidden</b>			
<b>if</b>	<b>in</b>	<b>is</b>	
<b>loop</b>			

macro	map	module			
new	not	null			
of	or	others	out		
procedure					
range	record	renames	return	reverse	
select	separate	sequence	set	some	subtype
task	then	type			
use					
wait	when	with			
xor					

## Run-Time Checks

Of course King has run-time checks similar to Ada's, including pre- and postcondition checks. Unlike Ada, King has no way to suppress them.

### *Unchecked Pre- and Postconditions*

Normal pre- and postconditions document the software and also provide checks for correctness. However, in some cases, actually checking such conditions may lead to software not meeting its timing requirements. Consider

```
subtype Potential_Prime is Unbounded_Integer with
  Predicate => Potential_Prime > 1,
  Default_Value => 2;

P : procedure (Prime : in Potential_Prime) with
  Precondition =>
    (for all I in Potential_Prime range 2 .. Prime / 2 => Prime rem I /= 0);
```

This documents and checks that Prime is a prime number. Prime may be arbitrarily large, and performing the exhaustive check that it is prime could take an arbitrarily long time. If you can't wait 100 years for a subprogram call to proceed, you might be inclined to leave off the precondition, or state it as a comment.

For such cases, King provides the aspects `Unchecked_Precondition` and `Unchecked_Postcondition`. These provide documentation but do not generate checks. Unless your case is as egregious as this example, you should always start with normal conditions, only making them unchecked if measurement shows it is necessary.

## Parameter Association

We have seen many examples of parameter associations, but certain requirements of them may not be clear. Procedure calls, macro expansions, and discriminant associations must use named notation. Function calls must use positional notation for the first parameter. Subsequent function parameters may use either positional or named notation, whichever is clearer. When a function call uses `Object.Operation` notation, the `Object` is the first parameter, so all other parameters may use either positional or named notation.

## One at a Time

A general rule in King is "one at a time". A use clause may only name a single module. A declaration may only declare a single thing. Each parameter in a subprogram parameter list has its own colon, mode, and subtype. Each macro parameter has its own terminator semicolon. Each discriminant in a discriminant list has its own colon and subtype. A parameter or discriminant association only associates a single parameter or discriminant. Only one statement may appear on a line.

An exception to this rule is in aggregates using named notation, where multiple names or index values separated by `..` and `|` may appear.

## Required Whitespace

In the remarks about the Hello-World program, it was noted that most of the spaces in the program are required. Here we'll define when whitespace is required in more detail. Some definitions

- Spaces: One or more space characters
- Line end: A line terminator and any immediately preceding comment
- Whitespace: Spaces or one or more line ends

An indentation level is three space characters.

Binary operators, the assignment symbol, stand alone colons, and arrow symbols must be preceded by spaces and followed by whitespace.

Unary operators that are symbols must be preceded by whitespace and there must be no whitespace between them and their operands.

Unary operators that are reserved words must be preceded by whitespace and separated from their operands by a single space.

Terminator semicolons must be followed by whitespace including at least one line end.

There must be no whitespace between a semicolon and what precedes it.

Sequences of parentheses/brackets/braces of the same type must be separated by spaces.

Left parentheses/brackets/braces not preceded by a left same thing must be preceded by whitespace. Left parentheses/brackets/braces not followed by a left same thing must be not be followed by whitespace.

Right parentheses/brackets/braces not followed by a right same thing must be followed by punctuation or whitespace. Right parentheses/brackets/braces not preceded by a right same thing must not be preceded by whitespace.

There must be one blank line between use clauses and the rest of the compilation unit.



There must be one blank line between compound statements and surrounding statements at the same indentation level.

There must be one blank line between transfer of control statements (return, exit, raise) and surrounding statements at the same indentation level.

There must be one blank line between wait statements and surrounding statements at the same indentation level.

There must be no blank lines between statements at different indentation levels.

## Elaboration

The use clauses and elaboration-time subprogram calls in a program establish a directed, acyclic graph of elaboration order. Modules must be elaborated in this order. When the graph allows a set of modules to be elaborated at the same time, the modules in the set must be elaborated in **String** "<" order of their full names.

## Distribution

A program may be divided into partitions, and partitions may run on physically separate machines (a distributed system). A named active task is designated the master task of a partition, and the partition name is the task name. By default, there is a single partition with the environment task as its master task. Passive tasks and other active tasks may be associated with a partition, indicating that their data is stored on and their execution is performed by the same machine as the master task of the partition. Active tasks may make calls to passive tasks in other partitions; partitioning does not change the visibility or scope of objects in the program.

A master task is indicated by the `Master_Task` aspect; things are associated with a master task by the `Partition` aspect naming the master task.

[Mechanism for multiple, dynamic instances of a partition?]

## Source Code, Text Files, and File Names

A King compilation unit is a sequence of lines, each of which is a sequence of Unicode characters. King does not define how this source code is stored or how it is provided to the compiler. However, the kinds of systems that King is expected to be used on have file systems and native text-file formats, and most compilers read their source code from such text files. It is likely that King compilers on such systems will do the same.

A King compiler that reads its source code from text files may put no restrictions on the number of compilation units in a file, or on the names of the files it reads. The operation of the compiler must be the same regardless of how compilation units are stored in files and what the file names are. The compiler must accept and process module specifications, even if the compilation does not produce any IR or object code, and regardless of whether the module body is present. It must accept and process library-level

bodies, provided their specifications are known to the compiler, even if separate subunits are not present.

## ***Suggested Organization and Naming***

That said, it is usually a good idea to develop software with one compilation unit per file, with a consistent naming scheme that results in the system's tools presenting the files in a meaningful order. It is suggested that a King compilation unit be in a file named by the identifying occurrence of the full unit name, followed by an appropriate extension. Recommended extensions are .kg1 for specifications, .kg2 for library-level bodies, and .kg3 for separate subunits. So the specification of module

King.Data\_Structures.Queues.Unbounded.Protected would be in a file named King.Data\_Structures.Queues.Unbounded.Protected.kg1 with its body in King.Data\_Structures.Queues.Unbounded.Protected.kg2. If it has a separate subunit named Insert, that would be in King.Data\_Structures.Queues.Unbounded.Protected.Insert.kg3.

## **KILLAR**

The standard library has a number of modules that are difficult or impossible to implement in King. For implementing them, there is a King-like language, called the King Implementation Language for Libraries with Arrays and References (KILLAR), that can be used to implement such modules.

KILLAR adds arrays to King through array types. Array types are the same as in Ada, except that aggregates must be qualified. KILLAR also adds the concept of a half-constrained array:

```
type Something is array (Positive range 1 .. <>, Positive range 1 .. <>)
of Component;
```

KILLAR adds pointers to King through reference types.

```
type A is reference of B;
P : A; -- Initial value is null
P <- new reference of B; -- Default initialized
P <- new reference of B'(Value); -- Initialized to Value
P.all -- What P points to; raises Constraint_Violation if P = null
P.all.Field -- Record component; all is required
P.all (42) -- Indexed component; all is required
P'Free; -- Unchecked deallocation; sets P to null
```

All unreleased allocated memory for a reference type is freed when the type goes out of scope. Reference types are elementary types.

KILLAR can only compile modules (including hidden and macro modules), and those modules must declare array or reference types in their bodies. Array and reference types cannot be declared in normal module specifications, but may be declared in hidden module specifications. Normal modules compiled with KILLAR can be used from King as if they were King modules.

## ***Unconstrained Record Objects***

Ada's unconstrained, varying-size record types have an undefined implementation issue that causes apparent undefined semantics. For an Ada record type such as

```
type V_String (Length : Natural := 0) is record
  Value : String (1 .. Length) := (others => ' ');
end record;

S : V_String;
```

S may be allocated in one of two ways. One way is to allocate enough space for the largest variant. In many cases such an object will not fit on the stack, and the elaboration of S will raise `Storage_Error`. This is the approach used by the GNAT compiler.

The other way is to allocate Length and a pointer on the stack, and allocate Value on the heap, using only enough heap to hold the current size. This is similar to the approach used by the Janus/Ada compiler.

Thus, identical code compiled with two compilers for the same platform might work fine with one compiler but fail with another. King considers this amount of implementation variability unacceptable.

King's requirements that objects be allocated on the heap if there is not enough room for them on the stack mean both approaches will usually work, but there will still be cases in which there will not be enough memory for the largest variant, even though the default variant will fit.

For the kind of systems KILLAR is currently intended for, the side effects of the first approach are simply a nuisance. In the interest of predictability and portability, KILLAR mandates the second approach.

King does not have such types, so this is not a concern for it.

## **Alternatives**

### ***Unreserved Keywords***

Some of the reserved words are only used in limited circumstances (**map**, **reverse**) and might be better considered unreserved keywords that only have a special meaning in those circumstances.

### ***Explicitly Empty Parameter Lists***

In keeping with the philosophy that things that are deliberately empty should be explicitly marked as such with **null** (declarative regions, sequences of statements), perhaps subprogram parameter lists should, too.

```
P : procedure (null);
F : function (null) return T;
V : T is F (null);
```

P (null);

### ***Array and Reference Types***

Have them in King with the same restrictions?

### ***Type Names***

Perhaps add a prefix to all type names: `Type\_Name` ?