

Fourth REST API



API Documentation

Updated 01.2022

Generate Token

To **generate a token**, you'll need to POST your request to the following URL: <https://agent-pos-na1.fourth.com/login>

With the following information:

Header

Content-Type: application/json

JSON Body

```
{ "user_id":"<username>", "password":"","<password>" }
```

Response body:

```
{"permissions":["<permissions>"],"Bearer":"<token>"}
```

The Bearer value is your token which is valid for at least 1 hour – save that! You may use either the Bearer token Authentication, preferred, or you can use the Basic Authentication with your Username and Password provided by HotSchedules.

REST API Service

Introduction

The HotSchedules REST API provides a user-friendly way to obtain HS Data. Please ensure that API access has been enabled for your HotSchedules account. Contact customer service 1-866-753-3853 for access or questions.

The **url path** can look like any of the following, depending on which type is being queried: HTTP Status Codes provide a description of the success or failure of a call: <https://httpstatuses.com>

- `../hotschedules/<concept_id>/<store_id>/<type_method>?`
- `../hotschedules/<concept_id>/<type_method>?`
- `../hotschedules/<type_method>?`

The **base URI** for the HotSchedules REST Service is <https://agent-pos-na1.fourth.com>

Available Methods

FETCHING DATA METHODS

Note: Results are currently cached with a TTL of 60 minutes.

What is TTL? Time to live or hop limit is a mechanism that limits the lifespan or lifetime of data in a computer or network

getConcepts

This method returns a list of concepts for a company.

Example with Username and Password:

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/getConcepts"
```

Example with Token:

```
curl -X GET -H "Authorization: Bearer <token>" -H "Content-Type:application/json" "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/getConcepts"
```

Key	Type	Description
extId	Number	Concept external ID
name	String	Concept Name

getClientCertifications

This method takes in a concept ID and a store ID and returns client certification objects. It is meant to get a list of all certifications for that store.

The inputs of this method are the arguments defined by the following table.

Query parameter	Type	Description
Concept	Int	The identifier for the location's concept. Must be unique within the company. Contact HotSchedules if you're not sure about this value.

Query parameter	Type	Description
storeNum	Int	Numeric (integer) identifier for the store. Must be unique within the concept.

getEmployeeCertifications

This method takes in a concept ID, store ID and employee POS ID and returns an array of employee certificate objects. It is meant to get a list of all employee certification information for an employee for that store.

The inputs of this method are the arguments defined by the following table.

Query parameter	Type	Description
Concept	Int	The identifier for the location's concept. Must be unique within the company. Contact HotSchedules if you're not sure about this value.
storeNum	Int	Numeric (integer) identifier for the store. Must be unique within the concept.
empPOSId	Int	POS numeric employee ID.

getLocations

This method takes in a concept ID and store ID. It returns an array of dataLocation objects, each of which represent one HotSchedules schedule location.

The inputs of this method are the arguments defined by the following table.

Query parameters	Type	Description
concept	int	The identifier for the location's concept/group. Must be unique within the company. Contact HotSchedules if you're not sure about this value.
storeNum	int	Numeric (integer) identifier for the location. Must be unique within the concept.

The outputs of this method are the arguments defined by the following table.

Query parameter	Type	Description
return	dataLocationArray	Array of dataLocation objects.

getDriversByInterval

This method will take a concept ID, store number, start and end dates, volume type, and data type and return a list of total driver amount for each interval in the date range requested for that concept, store and labor type.

Intervals are configured during initial setup for the customer and are typically 30 minutes or 15 minutes.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept
startDate	hsSimpleDate	Start date for the range of data requested
endDate	hsSimpleDate	End date for the range of data requested
volumeType	driverClass	Classification of driver requested. Allowed types would be all of the classifications supported from API, HSC, or FTP integration. "Guests", "Tables", "Entrees", "Deliveries", "Transactions" and "Products"
dataType	driverType	Type of driver requested. Allowed types are "ACTUAL", "ADJ_FORECASTED", and "PRE_ADJ_FORECASTED"

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getDriversByInterval?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016&volume_type=TABLE&data_type=ACTUAL"
```

Key	Type	Description
driverAmount	Number	Quantity of driver for interval expressed in the record
driverClass	String	Description of driver type supplied for the interval expressed in

Key	Type	Description
		the record
intervalStartTime	Object	The hour, minutes, and seconds corresponding to the start of the interval expressed in the record. Interval times are local to the store's time zone
intervalEndTime	Object	The hour, minutes, and seconds corresponding to the end of the interval expressed in the record. Interval times are local to the store's time zone
intervalStartDate	Object	The date corresponding to the start of the interval expressed in the record
intervalEndDate	Object	The date corresponding to the end of the interval expressed in the record
conceptExtRef	Number	The concept ID configured by HotSchedules for the concept of the store owning the data of the record., contact HotSchedules if Concept IDs need to be defined or configured
storeExtRef	Number	The store ID configured within HotSchedules for the store owning the data of the record., contact HotSchedules if Store IDs need to be defined or configured
companyExtRef	Number	The company ID defined by HotSchedules for the store owning the data of the record., contact HotSchedules if the Company ID needs to be defined. This ID cannot be customized or configured
driverType	String	Type of driver requested. Allowed types are: "ACTUAL" - Corresponds to the actual values produced by the store. "ADJ_FORECASTED"- Corresponds to the final forecasted driver amount that the schedules were based off from for the driver. "PRE_ADJ_FORECASTED"- Corresponds to the original forecasted driver amount previous to any forecast adjustments

getEmpAvailabilityV2

This method takes in a concept ID and a store ID and returns an array of wsEmpAvailability objects. It is meant to get a list of all employee availability for that store.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the

Query parameter	Type	Description
		company, contact HotSchedules if you're not sure about this value
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept
active_only	Boolean	Boolean that defines whether or not to include terminated employees in response

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getEmpAvailability?active_only=true"
```

Key	Type	Description
empNum	Number	Employee POS ID
availabilities	Array	Returns an array of availability for an employee
empHrId	Number	Employee HR ID

getEmpInfo

This method takes in a concept ID and a store ID and returns an array of wsEmpInfo objects. It is meant to get a list of all employees for that store.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
active_only	Boolean	Boolean that defines whether or not to include terminated employees in response.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getEmpInfo?active_only=true"
```

Key	Type	Description
-----	------	-------------

Key	Type	Description
lastUpdated	String	Last time the employee record was updated
accountCreated	String	Date/time the account was created
permissionSetName	String	Permission set name assigned to the employee
empNum	Number	Employee POS ID
assignedSchedules	Array	The schedule in which the employee is assigned. Array contains extId, hsId and name
empHrId	Number	Employees HR ID

getEmpJobs

This method takes in a concept ID and a store ID and returns an array of wsEmpJob objects. It is meant to get a list of all jobs assigned to all employees for that store.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getEmpJobs?active_only=true"
```

Key	Type	Description
hsJobId	Number	HotSchedules internal job code ID
clientId	Number	Unique identifier for client provided via HotSchedules
regWage	Number	Regular hourly wage rate for employee
posEmpId	Number	POS numeric ID for employee
hsEmpId	Number	HotSchedules internal employee account ID
storeNum	Number	Unique numeric store ID within HotSchedules, generally set up to mirror the client internal store IDs
ovtWage	Number	Overtime hourly wage rate for employee
posJobId	Number	POS numeric ID for the job code

Key	Type	Description
primary	Boolean	Boolean flag to designate if the job code is the primary job for the employee

getGroups

This method takes in a concept ID and returns group information for the concept.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/getGroups"
```

Key	Type	Description
conceptExtId	Number	Concept external ID
extId	Number	Group external ID
name	String	Group name

getGuestCounts

This method will take a concept ID, store number, start and end dates and return a list of guest counts for the date range requested.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
start	dateTime	Start date for the range of data requested. This is a basic dateTime object.
end	dateTime	End date for the range of data requested. This is a basic dateTime object.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getGuestC"
```

ounts?start_date=2016-04-30T00:00:00&end_date=2016-05-03T00:00:00"

Key	Type	Description
businessDate	String	Business date of transaction
dateTime	String	Date time of the transaction
guestCount	Number	Number of guests for the transaction
rvcExtId	Number	Represents the numeric revenue center ID associated with the guest

getLaborByBusDay

This method will take a concept ID, store number, start and end dates and a labor type and return a list of total labor by job code for each interval in the date range requested for that concept, store and labor type.

Intervals are configured during initial setup for the customer and are typically 30 minutes.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept
start	hsSimpleDate	Start date for the range of data requested
end	hsSimpleDate	End date for the range of data requested
laborType	laborType	Type of labor requested. Allowed types are "optimal", "forecasted" and "scheduled".

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getLaborByBusDay?start_day=30&start_month=1&start_year=2016&end_day=5&end_month=5&end_year=2016&labor_type=optimal"
```

Key	Type	Description
intervalDate	Object	Date expressed in the record
intervalTime	Object	The hour, minutes, and seconds expressed in record

Key	Type	Description
laborType	String	Type of labor requested. Allowed types are “optimal”, “forecasted” and “scheduled”.
volume	String	Number of employees based on demand at that interval

getLaborByJobAndInterval

This method will take a concept ID, store number, start and end dates and a labor type and return a list of total labor by job code for each interval in the date range requested for that concept, store and labor type.

Intervals are configured during initial setup for the customer and are typically 30 minutes.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
start	hsSimpleDate	Start date for the range of data requested
end	hsSimpleDate	End date for the range of data requested
laborType	laborType	Type of labor requested. Allowed types are “optimal”, “forecasted” and “scheduled”.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getLaborByJobAndInterval?start_day=30&start_month=1&start_year=2016&end_day=5&end_month=5&end_year=2016&labor_type=optimal"
```

Key	Type	Description
intervalDate	Object	Date expressed in the record
intervalTime	Object	The hour, minutes, and seconds expressed in record
laborType	String	Type of labor requested. Allowed types are “optimal”, “forecasted” and “scheduled”.
volume	String	Number of employees based on demand at that interval

getSalesItemsV3

This method takes in a concept ID, store ID, start and end dates. It returns an array of sales for that store.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
start	hsSimpleDate	First day of projected sales requested. This is an hsSimpleDate object.
end	hsSimpleDate	Last day of projected sales requested. This is an hsSimpleDate object.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getSalesItemsV3?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016"
```

Key	Type	Description
clientId	Object	Business Date information, Day, Months and Year
empld	Array	Array of the day part total. Start Time and End Time
extId	Number	Optional-Unique transaction ID for the sales item
rvc	Number	Revenue center
rvcName	String	Name for the revenue center associated with the location within the restaurant
salesCat	Number	Sales category
storeNum	Number	Store number
ttl	Number	Total sales for the sales category
businessDate	Object	Business Date information, Day, Months and Year
transDate	Object	Transaction data
transTime	Object	Transaction time

getProjectedSalesV3

This method will take a concept ID, store number, start and end dates. This method uses hsSimpleDate objects for dates and hsSimpleTime objects for times.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
start	hsSimpleDate	First day of projected sales requested. This is an hsSimpleDate object.
end	hsSimpleDate	Last day of projected sales requested. This is an hsSimpleDate object.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getProjectedSalesV3?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016"
```

Key	Type	Description
businessDate	Object	Business Date information, Day, Months and Year
dayPartTotals	Array	Array of the day part total. Start Time and End Time
dateTotal	Number	Total projected sales for the day part

getRCVs

Revenue center information defined for a group.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getRCVs"
```

Key	Type	Description
revenueCenterName	String	Revenue center name
extId	Number	Revenue center ID
groupLevel	Boolean	Indicates if the revenue center was

Key	Type	Description
		created at a group level

getSalesCats

This method takes in a concept ID and a store ID and returns an array of sales categories for that store. Sales categories will typically establish what kind of item was sold: Food, Beverage, Alcohol, Merchandise. Sales categories can be local to a particular store, or defined in HotSchedules as belonging to an entire group (called group-level sales categories).

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getSalesCats"
```

Key	Type	Description
salesCategoryName	String	Name of the sales category
extId	Number	External ID associated with the category
groupLevel	Boolean	Indicates if the revenue center was created at a group level

getScheduleV3

This method takes in a concept ID, store ID, start and end dates. It returns an array of WSScheduleItem3 objects, which represent one scheduled shift each, for import into the POS. This method returns the same data as getSchedule, plus extended scheduled shift data, including location ID, regular pay rate, OT pay rate, scheduled regular minutes, scheduled OT minutes (if any), scheduled special pay (if any) and the unique schedule ID, internal to HS. This method uses hsSimpleDate objects for dates. Note that the date referenced is the calendar date and not the business date.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
start	hsSimpleDate	First day of scheduled shifts you are requesting. This method uses hsSimpleDate objects for dates.
end	hsSimpleDate	Last day of scheduled shifts you are requesting. This method uses hsSimpleDate objects for dates.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getScheduleV3?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016"
```

Key	Type	Description
outDate	Object	Schedules out date
jobHsId	Number	HotSchedules internal job code ID
payRate	Number	Regular hourly pay rate for employee
inDate	Object	Scheduled in date
specialPay	Number	Special Pay amounts
empHsId	Number	HotSchedules internal employee account ID
ovtMinutes	Number	Total Overtime Minutes for employee
inTime	Object	Scheduled in time
outTime	Object	Scheduled out time

getShiftsV3

This method takes in a concept ID, store ID, start and end dates and three flags (isHouse, isScheduled and isPosted). It returns an array of WSScheduleItem3 objects, which represent one scheduled shift each. What shifts are returned depends on the flags set:

- isHouse - includes scheduled or posted shifts that are not assigned to an employee (called 'house shifts' in HotSchedules).
- isScheduled - includes shifts that are in schedules that have been saved in HotSchedules,

but might not have been posted.

- isPosted - includes shifts that are in schedules that have been set to the 'posted' status within HotSchedules.

This method returns extended scheduled shift data, including location ID, regular pay rate, OT pay rate, scheduled regular minutes, scheduled OT minutes (if any), scheduled special pay (if any) and the unique schedule ID, internal to HS.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
Day	Number	Day formatted dd
Month	Number	Month formatted mm
Year	Number	Year formatted yyyy
isHouse	Boolean	Include house shifts? These are shifts which were never assigned to someone on a schedule, or were once assigned but removed from an employee when their status, job, etc. changed.
isScheduled	Boolean	Include scheduled shifts? These are shifts which are on a schedule that has been saved in HotSchedules, but might not have been posted
isPosted	Boolean	These are shifts that are in schedules that have been set to the 'posted' status within HotSchedules.
jobCodes	IntArray	Integer array of job codes to be included in this method's return. if this parameter is null or empty, all jobs will be included.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getShiftsV3?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016&is_house=true&is_scheduled=true&is_posted=true"
```

Key	Type	Description
empHsId	Number	HotSchedules internal employee account ID
empPosId	Number	POS numeric Employee ID

Key	Type	Description
jobHsId	Number	HotSchedules internal job code ID
jobPosId	Number	POS job code ID
inDate	Object	Scheduled in date
outDate	Object	Schedules out date
inTime	Object	Scheduled in time
outTime	Object	Scheduled out time
weekStart	Object	Start date of the work week
weekEnd	Object	End date of the work week
locationId	Number	Location ID
scheduleId	Number	Schedule ID
payRate	Number	Regular hourly pay rate for employee
ovtRate	Number	overtime pay rate
ovtMinutes	Number	Total overtime minutes for employee
regMinutes	Number	total regular minutes for employee
specialPay	Number	Special Pay amounts

getStoreEmployees

Versions 4 and 5 of this method are also available, eg. `getStoreEmployeesV4` and `getStoreEmployeesV5`.

This method takes in a concept ID, store ID, a flag to determine if only active employees are returned, and returns an array of `WSEmployee` objects.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
active_only	Boolean	Boolean that defines whether or not to include terminated employees in response.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getStoreEmployees?active_only=true"
```

Key	Type	Description
zipCode	Number	Zip Code
hireDate	String	Employee Hire Date
address	String	Employee Address line 1
clientId	Number	Unique identifier for client provided via HotSchedules
LName	String	Employee Last Name
address2	String	Employee Address line 2
city	String	City field for Address
mobile	String	Employees Mobile Phone
NName	String	Employee Nickname
altId	Number	Employee HR ID. This must be a unique value across the company. It is used for HotSchedules Shared Employees.
FName	String	Employee First Name
empNum	Number	Employee POS ID
phone	String	Phone Number
hsId	Number	HS unique ID of an employee that is assigned at the time the employee is created in HS. This number is not configurable but automatically assigned. This number can be obtained through the get method and is an option to include in the set. However this is not necessary
dob	String	Date of birth
state	String	State
storeNum	Number	Unique numeric store ID within HotSchedules. Generally set up to mirror the client internal store IDs.
email	String	Employee's email address
status	Number	Active = 1, Inactive = 0, Terminated = -1

getStoreJobs

This method takes in a concept ID and a store ID, and returns an array of all jobs currently defined in HotSchedules for the given concept/store.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getStoreJobs"
```

Key	Type	Description
jobName	String	Name for Job Code
posId	Number	Numeric POS ID for Job Code
clientId	Number	Unique identifier for client provided via HotSchedules
hslId	Number	HS unique ID of an employee that is assigned at the time the employee is created in HS. This number is not configurable but automatically assigned. This number can be obtained through the get method and is an option to include in the set. However this is not necessary
defRate	Number	Default Pay Rate for a Job Code

getStoresV2

Returns information about the stores within a group.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
group_id	Number	Group in which the store is assigned

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/getStoresV2?group_id=0"
```

Key	Type	Description
groupName	String	Name of the group
active	Boolean	Indicates if the store is active
groupExtId	Number	The external ID for the store
storeName	String	The name of the store
storeNum	Number	Unique numeric store ID within HotSchedules. Generally set up to mirror the client internal store IDs.
city	String	City
postalCode	Number	Zip code / postal code
stateProvince	String	State province
streetAddress 1	String	Main street address
streetAddress 2	String	Apartment number, Suite, Unit, etc..
timeZone	String	Store timezone

getTimeCards

This method takes in a concept ID, store ID, start and end dates. It returns an array of wsTimeCard3 objects, which represent one employee time card each. Each time card has information for one employee punch record, including business date, regular and OT minutes and wages, clock in and clock out times. If this store is using HotSchedules' web-based timeclock for employee clock-in, any open punches in the date range are also included in the response.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
Day	Number	Day formatted dd
Month	Number	Month formatted mm
Year	Number	Year formatted yyyy

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getTimeC
```

ards?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016
"

Key	Type	Description
jobName	String	POS job code name
ovtTtl	Number	Optional-Overtime total pay amount
ovtHrs	Number	Optional-Overtime hours in shift
clockOut	String	Clock out timestamp for the shift
regWage	Number	Regular hourly pay rate
clockIn	String	Clock in timestamp for the shift
ovtWage	Number	Optional-Overtime hourly pay rate
breakMinutes	Number	Number of non-paid break minutes in shift
jobId	Number	POS numeric identifier for the job
jobExtId	Number	POS numeric Job Code ID
businessDate	Array	Business Date information, Day, Months and Year
regHrs	Number	Regular hours represented in shift
spcTtl	Number	Optional-Special Pay total pay amount
hsId	Number	Optional-Internal HotSchedules employee Account ID. Not required, will be set by the service.
spcHrs	Number	Optional-Special Pay Hours
ovtMins	Number	Optional-Overtime minutes in shift
storeNum	Number	Unique numeric store identifier. Generally set up to mirror the client internal store ID.
empPosId	Number	POS numeric Employee ID
regTtl	Number	Regular total pay amount
extId	Number	Optional-Unique transaction ID for the time card record

getTimeCardsV2

Same as getTimeCards but additionally provides double time info for each timecard.

getTimeCardsDeclaredTips

This method takes in a concept ID, store ID, start and end dates. It returns an array of wsTimeCard3 objects, which represent one employee time card each. Each time card has information for one employee punch record, including business date, regular and OT minutes

and wages, clock in, clock out times and declared tips. If this store is using HotSchedules' web-based timeclock for employee clock-in, any open punches in the date range are also included in the response.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
Day	Number	Day formatted dd
Month	Number	Month formatted mm
Year	Number	Year formatted yyyy

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getTimeCardsDeclaredTips?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016"
```

Key	Type	Description
jobName	String	POS job code name
ovtTtl	Number	Optional-Overtime total pay amount
ovtHrs	Number	Optional-Overtime hours in shift
clockOut	String	Clock out timestamp for the shift
regWage	Number	Regular hourly pay rate
clockIn	String	Clock in timestamp for the shift
ovtWage	Number	Optional-Overtime hourly pay rate
breakMinutes	Number	Number of non-paid break minutes in shift
jobId	Number	POS numeric identifier for the job
jobExtId	Number	POS numeric Job Code ID
businessDate	Array	Business Date information, Day, Months and Year
regHrs	Number	Regular hours represented in shift
spcTtl	Number	Optional-Special Pay total pay amount
hsId	Number	Optional-Internal HotSchedules employee Account ID. Not required, will be set by the service.

Key	Type	Description
spcHrs	Number	Optional-Special Pay Hours
ovtMins	Number	Optional-Overtime minutes in shift
storeNum	Number	Unique numeric store identifier. Generally set up to mirror the client internal store ID.
empPosId	Number	POS numeric Employee ID
regTtl	Number	Regular total pay amount
extId	Number	Optional-Unique transaction ID for the time card record
declaredTips	Number	Tip amount

getVolumeCounts

This method will take a concept ID, store number, start and end dates and a volume type and return a list of volume counts for the date range requested. Supported Volume Types are: "TABLES", "ENTRÉE", "GUESTS", "DELIVERIES", "PRODUCTS", and "TRANSACTIONS".

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
volumeType	volumeType	Classification of driver requested. Allowed types would be all of the classifications supported from API, HSC, or FTP integration. "Guests", "Tables", "Entrees", "Deliveries", "Transactions" and "Products".
start	hsSimpleDate	Start date for the range of data requested
end	hsSimpleDate	End date for the range of data requested

```
curl -X GET -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/getVolumeCounts?start_date=2015-04-30T00:00:00&end_date=2016-05-03T00:00:00&volume_type=TABLE"
```

Key	Type	Description
dateTime	String	Date of business
volumeAmount	Number	Value of the volume count for the transaction

Key	Type	Description
businessDate	String	Business Date information, Day, Months and Year
volumeType	String	Classification of driver requested. Allowed types would be all of the classifications supported from API, HSC, or FTP integration. "Guests", "Tables", "Entrees", "Deliveries", "Transactions" and "Products".
rvcExtId	Number	Represents the numeric revenue center ID associated with the volume count

WRITING DATA METHODS

setTimeCardsV3

Extends dataTimeCard (includes business date and clock in and clockout date/times).

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
start_day	Number	Day formatted dd
start_month	Number	Month formatted mm
start_year	Number	Year formatted yyyy
end_day	Number	Day formatted dd
end_month	Number	Month formatted mm
end_year	Number	Year formatted yyyy

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setTimeCardsV3?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016" -d "[{ \"jobName\": \"Cook\", \"ovtTtl\": 0, \"ovtHrs\": 0, \"clockOut\": \"2016-07-31T22:05:00-05:00\", \"regWage\": 9, \"clockIn\": \"2016-07-30T15:56:00-05:00\", \"ovtWage\": 13.5, \"breakMinutes\": 0, \"jobId\": 16921407, \"businessDate\": { \"month\": 7, \"year\": 2016, \"day\": 31 }, \"regHrs\": 6.15, \"spcTtl\": 0, \"hsId\": 929931334634, \"spcHrs\": 0, \"ovtMins\": 0, \"storeNum\": 1, \"empPosId\": 1052, \"regTtl\": 55.35 }]"
```

Key	Type	Description
jobName	String	POS job code name
ovtTtl	Number	Optional-Overtime total pay amount
ovtHrs	Number	Optional-Overtime hours in shift
clockOut	String	Clock out timestamp for the shift
regWage	Number	Regular hourly pay rate
clockIn	String	Clock in timestamp for the shift
ovtWage	Number	Optional-Overtime hourly pay rate
breakMinutes	Number	Number of non-paid break minutes in shift
jobId	Number	POS numeric identifier for the job
businessDate	Array	Business Date information, Day, Months and Year
regHrs	Number	Regular hours represented in shift
spcTtl	Number	Optional-Special Pay total pay amount
hsId	Number	Optional-Internal HotSchedules employee Account ID. Not required, will be set by the service.
spcHrs	Number	Optional-Special Pay Hours
ovtMins	Number	Optional-Overtime minutes in shift
storeNum	Number	Unique numeric store identifier. Generally set up to mirror the client internal store ID.
empPosId	Number	POS numeric Employee ID
regTtl	Number	Regular total pay amount
extId	Number	Optional-Unique transaction ID for the time card record

setEmpJobs

This method takes in a concept ID, store ID, and an array of WSEmpJob objects to assign jobs to individual employees. This method returns a WSReturn object.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
Day	Number	Day formatted dd

Query parameter	Type	Description
Month	Number	Month formatted mm
Year	Number	Year formatted yyyy

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setEmpJobs?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016" -d "[{json_object_1}, {json_object_2}, {json_object_3}...]"
```

Key	Type	Description
hsJobId	Number	HotSchedules internal job code ID
clientId	Number	Unique identifier for client provided via HotSchedules
regWage	Number	Regular hourly wage rate for employee
posEmpId	Number	POS numeric ID for employee
hsEmpId	Number	HotSchedules internal employee account ID
storeNum	Number	Unique numeric store ID within HotSchedules. Generally set up to mirror the client internal store IDs.
ovtWage	Number	Overtime hourly wage rate for employee
posJobId	Number	POS numeric ID for the job code
primary	Boolean	Boolean flag to designate if the job code is the primary job for the employee

setEmps

This method takes in a concept ID, store ID and an array of WSEmployee objects. Using the authentication from the username token and the concept and store IDs, the server will resolve which HotSchedules client this sync is for. The array of employees will be parsed on the server side to employees who need to be inserted or updated in the HS database. This method returns a WSReturn object.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique

Query parameter	Type	Description
		within the concept.
emps	wsEmployeeArray	Array of WSEmployee objects. Each object represents an employee at this store.
Day	Number	Day formatted dd
Month	Number	Month formatted mm
Year	Number	Year formatted yyyy

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setEmps?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016" -d "[{json_object_1}, {json_object_2}, {json_object_3}...]"
```

Key	Type	Description
zipCode	Number	Zip Code
hireDate	String	Employee Hire Date
termDate	String	Employee Termination Date
address	String	Employee Address line 1
clientId	Number	Unique identifier for client provided via HotSchedules
LName	String	Employee Last Name
address2	String	Employee Address line 2
city	String	City field for Address
mobile	String	Employees Mobile Phone
NName	String	Employee Nickname
altId	Number	Employee HR ID. This must be a unique value across the company. It is used for HotSchedules Shared Employees.
FName	String	Employee First Name
empNum	Number	Employee POS ID
phone	String	Phone Number
hsId	Number	HS unique ID of an employee that is assigned at the time the employee is created in HS. This number is not configurable but automatically assigned. This number can be obtained through the get method and is an option to include in the set. However this is not necessary

Key	Type	Description
dob	String	Date of birth
state	String	State
storeNum	Number	Unique numeric store ID within HotSchedules. Generally set up to mirror the client internal store IDs.
email	String	Employee's email address
status	Number	Active = 1, Inactive = 0, Terminated = -1

setForecastDriversV2

This method takes in a startdate, enddate, starttime, endtime, volume amount, volume type, and a revenue center for the purpose of submitting forecasted volume drivers to HotSchedules from a third party system or point of sale. Using the authentication from the username token and the concept and store IDs, the server will resolve which HotSchedules client this sync is for. The array contains volume driver counts for a range of dates, corresponding to the start and end dates. The server side logic can handle overlapping data (i.e. if you sync 7 days worth of time cards, every day, 6 days of it will be "overlapping" data) and will insert and update data as needed. If the guest are already in the HS database and do not need to be updated, then nothing will change.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
Day	Number	Day formatted dd
Month	Number	Month formatted mm
Year	Number	Year formatted yyyy

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setForecastDriversV2?start_day=30&start_month=4&start_year=2016" -d "[{json_object_1}, {json_object_2}, {json_object_3}...]"
```

Key	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about

Key	Type	Description
		this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
workweekStartDate	Object	Start date of the work week
driverAmount	Number	Quantity of driver for interval expressed in the record
intervalStartTime	Object	The hour, minutes, and seconds corresponding to the start of the interval expressed in the record. Interval times are local to the store's time zone.
intervalEndTime	Object	The hour, minutes, and seconds corresponding to the end of the interval expressed in the record. Interval times are local to the store's time zone.
intervalStartDate	Object	The date corresponding to the start of the interval expressed in the record
intervalEndDate	Object	The date corresponding to the end of the interval expressed in the record
rvclId	Number	Numeric ID for the revenue center associated with the location within the restaurant
volumeType	String	Classification of driver requested. Allowed types would be all of the classifications supported from API, HSC, or FTP integration. "Guests", "Tables", "Entrees", "Deliveries", "Transactions" and "Products".

setGuestCounts

This method takes in a concept ID, store ID, start and end date, business date, date time, guest count (must be a positive integer) and a revenue center for the purpose of submitting actual guest count drivers to HotSchedules from a third party system or point of sale. Using the authentication from the username token and the concept and store IDs, the server will resolve which HotSchedules client this sync is for. The array contains guest counts for a range of dates, corresponding to the start and end dates. The server-side logic can handle overlapping data (i.e. if you sync 7 days worth of time cards, every day, 6 days of it will be "overlapping" data) and will insert and update data as needed. If the guest are already in the HS database and do not need to be updated, then nothing will change. This method returns a WSReturn object.

Query parameter	Type	Description
-----------------	------	-------------

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
start_day	Number	Day formatted dd
start_month	Number	Month formatted mm
start_year	Number	Year formatted yyyy
end_day	Number	Day formatted dd
end_month	Number	Month formatted mm
end_year	Number	Year formatted yyyy

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setGuestCounts?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016" -d "[{json_object_1}, {json_object_2}, {json_object_3}...]"
```

Key	Type	Description
businessDate	String	Business date of transaction
dateTime	String	Date Time of the transaction
guestCount	Number	Number of guests for the transaction (must be a positive integer)
rvcExtID	Number	Numeric ID for the revenue center associated with the transaction

setRVC

This method takes in a concept ID and a store ID and returns an array of revenue centers for that store.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the

Query parameter	Type	Description
		concept
group	Number	Numeric ID group in which the store is assigned
rvclId	Number	Numeric ID for the revenue center associated with the location within the restaurant
rvcName	String	Name for the revenue center associated with the location within the restaurant. i.e. Bar, Togo etc...
isGroupLevel	Boolean	Indicates if the revenue center is assigned at the group level. i.e. Bar used across all locations

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setRVC?group=1&rvclId=1&rvcName=1&isGroupLevel=true" -d "[{json_object_1}, {json_object_2}, {json_object_3}...]"
```

Key	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
group	Number	Numeric ID group in which the store is assigned
rvclId	Number	Numeric ID for the revenue center associated with the location within the restaurant
rvcName	String	Name for the revenue center associated with the location within the restaurant. i.e. Bar, Togo etc...
isGroupLevel	Boolean	Indicates if the revenue center is assigned at the group level. i.e. Bar used across all locations

setSalesCat

This method allows you to add the sales category associated with menu items. Sales categories will typically establish what kind of item was sold: Food, Beverage, Alcohol, Merchandise. Sales categories can be local to a particular store.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
group	Number	Numeric ID group in which the store is assigned
salesCatId	Number	Numeric ID for the sales category associated with the location within the restaurant
salesCatName	String	Name for the sales category associated with the item sold within the restaurant. i.e. Liquor, Beer, etc..
isGroupLevel	Boolean	Indicates if the sales category is assigned at the group level. i.e. Liquor ID 2 used across all locations

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setSalesCat?group=1&salesCatId=1&salesCatName=1&isGroupLevel=true" -d "[{json_object_1}, {json_object_2}, {json_object_3}...]"
```

Key	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
group	Number	Numeric ID group in which the store is assigned
salesCatId	Number	Numeric ID for the sales category associated with the location within the restaurant
salesCatName	String	Name for the sales category associated with the item sold within the restaurant. i.e. Liquor, Beer, etc..
isGroupLevel	Boolean	Indicates if the sales category is assigned at the group level. i.e. Liquor ID 2 used across all locations

setSalesItemsV4

This method takes in a concept ID, store ID, a start and end date and an array of WSSalesItem objects. Using the authentication from the username token and the concept and store IDs, the server will resolve which HotSchedules client this sync is for. The array contains sales items for a range of dates, corresponding to the start and end dates. The server-side logic can handle overlapping data (i.e. if you sync 7 days worth of sales, every day, 6 days of it will be “overlapping” data) and will insert and update data as needed. If the sales items are already in the HS database and do not need to be updated, then nothing will change. The method returns a WSReturn object. This method uses hsSimpleDate objects for dates.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
Day	Number	Day formatted dd
Month	Number	Month formatted mm
Year	Number	Year formatted yyyy

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setSalesItemsV4?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016" -d "[{json_object_1}, {json_object_2}, {json_object_3}...]"
```

Key	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept
catName	String	Category name
clientId	Number	Unique identifier for client provided via HotSchedules
empld	Number	Employee ID
extId	Number	External ID
rvc	String	Revenue Center
rvcName	String	Name for the revenue center associated with the location within the

Key	Type	Description
		restaurant
salesCat	String	Sales category
ttl	String	Total sales for the sales category
businessDate	Object	Business Date information, Day, Months and Year
transDate	Object	Transaction date
transTime	Object	Transaction time
start	Object	Start date for the range of data requested
end	Object	End date for the range of data requested

setTimeCardsDeclaredTips

This method takes in a concept ID, store ID, a start and end date and an array of WSTimeCardsDeclaredTips objects. Using the authentication from the username token and the concept and store IDs, the server will resolve which HotSchedules client this sync is for. The array contains time cards for a range of dates, corresponding to the start and end dates. The server-side logic can handle overlapping data (i.e. if you sync 7 days worth of time cards, every day, 6 days of it will be “overlapping” data) and will insert and update data as needed. If the time cards are already in the HS database and do not need to be updated, then nothing will change. This method returns a WSReturn object.

Query parameter	Type	Description
concept	Number	The identifier for the location’s concept. Must be unique within the company, contact HotSchedules if you’re not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.
Day	Number	Day formatted dd
Month	Number	Month formatted mm
Year	Number	Year formatted yyyy

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setTimeCardsDeclaredTips?start_day=30&start_month=4&start_year=2016&end_day=5&end_month=5&end_year=2016" -d "[{json_object_1}, {json_object_2}, {json_object_3}...]"
```

Key	Type	Description
-----	------	-------------

Key	Type	Description
jobName	String	POS job code name
ovtTtl	Number	Optional-Overtime total pay amount
ovtHrs	Number	Optional-Overtime hours in shift
clockOut	String	Clock out timestamp for the shift
regWage	Number	Regular hourly pay rate
clockIn	String	Clock in timestamp for the shift
ovtWage	Number	Optional-Overtime hourly pay rate
breakMinutes	Number	Number of non-paid break minutes in shift
jobId	Number	POS numeric identifier for the job
jobExtId	Number	POS numeric Job Code ID
businessDate	Array	Business Date information, Day, Months and Year
regHrs	Number	Regular hours represented in shift
spcTtl	Number	Optional-Special Pay total pay amount
hsId	Number	Optional-Internal HotSchedules employee Account ID. Not required, will be set by the service.
spcHrs	Number	Optional-Special Pay Hours
ovtMins	Number	Optional-Overtime minutes in shift
storeNum	Number	Unique numeric store identifier. Generally set up to mirror the client internal store ID.
empPosId	Number	POS numeric Employee ID
regTtl	Number	Regular total pay amount
extId	Number	Optional-Unique transaction ID for the time card record
declaredTips	Number	Tip amount

setVolumeCountsV2

This method takes in a concept ID, store ID, business date, date time, volume amount, volume type, and a revenue center for the purpose of submitting actual volume drivers to HotSchedules from a third party system or point of sale. Using the authentication from the username token and the concept and store IDs, the server will resolve which HotSchedules client this sync is for. The array contains volume driver counts for a range of dates, corresponding to the start and end dates. The server-side logic can handle overlapping data (i.e. if you sync 7 days worth of time cards, every day, 6 days of it will be “overlapping” data) and will insert and update data as needed. If the guest are already in the HS database and do not need to be updated, then nothing will

change. This method returns a WSReturn object.

Query parameter	Type	Description
concept	Number	The identifier for the location's concept. Must be unique within the company, contact HotSchedules if you're not sure about this value.
storeNum	Number	Numeric (integer) identifier for the store. Must be unique within the concept.

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setVolumeCountsV2" -d "[{json_object_1}, {json_object_2}, {json_object_3}...]"
```

Key	Type	Description
businessDate	String	Business date of transaction
dateTime	String	Date time of transaction
rvcExtId	Number	Represents the numeric revenue center ID associated with the guest
volumeAmount	Number	Value of the volume count for the transaction
volumeType	String	Classification of driver requested. Allowed types would be all of the classifications supported from API, HSC, or FTP integration. "Guests", "Tables", "Entrees", "Deliveries", "Transactions" and "Products".

setLaborForecastByJob

This method takes in a concept ID, store ID, business date, daypart start and end times, labor forecast and jobExtId. Forecasted labor for the site, date, internal and job will be updated for the purpose of labor scheduling and all relevant reports. The call can be sent for a full week or single date. All intervals must be updated. A zero in the interval is an acceptable value. A null or blank is an acceptable value and will be treated as a zero. If sent for a single date only the date provided will be updated. All other dates within the week will not be impacted and any values already in the database will be retained. A full day's data must be sent, updating only one interval within a business date is not permitted and the call will fail.

Query Parameter	Type	Description
concept	int	The identifier for the location's concept/group. Must be unique within the company. Contact HotSchedules

Query Parameter	Type	Description
		if you're not sure about this value.
storeNum	int	Numeric (integer) identifier for the location. Must be unique within the concept.
jobs	wsEmpJobArray	Array of WSEmpJob objects. Each object represents one employee job, so a single employee can have one or more employee jobs (EmpJob) assigned to him/her. Each job that the employee works will be a separate object in this array.
day	int	Formatted dd
month	int	Formatted mm
year	int	Formatted yyyy
dayPartStartTime	dateTime	Day part start time
laborForecastMinutes	int	Minutes value
jobExtRef	int	Job reference id

```
curl -X PUT -H "Content-Type:application/json" -u <username>:<password> "https://agent-pos-na1.fourth.com/<companyID>/controllers/vertx/hotschedules/<concept>/<storeNum>/setLaborForecastByJob"
```