

Engineering the Prime Vacuum: Design Patterns from the Cathedral Mathematics for Industrial Systems, Computation, and Diagnostics

Jason Robert Gochanour

June 2026

Abstract

We survey the engineering applications of the mathematical infrastructure developed in the Cathedral project—a $\sim 158,000$ -line Lean 4 formalization of the Nyman–Beurling equivalence for the Riemann Hypothesis. Beyond three direct applications (energy systems, security, signal processing), we identify five *universal design patterns* that emerge from the Cathedral’s proof architecture: iterative resource allocation via the Cholesky decrement identity, anomaly-gated precision engineering via the arithmetic/archimedean separation, stratum-parallel computation via the Torus Projection on $T^\infty = \prod_p S_p^1$, parity-structured diagnostics via the Ward Health Index, and coprime sector analysis via the Fiber Decomposition. These patterns apply to any system with a positive-definite coupling matrix, a discrete/continuous separation, a GCD-structured decomposition, or a binary partition. We present each pattern with its mathematical basis in the Cathedral formalization, numerical validation from the 55+ companion experiments, and an honest assessment of engineering readiness.

Contents

1	Introduction	2
2	Energy Systems: Harmonic Cancellation	3
2.1	The Problem	3
2.2	The Cathedral Connection	3
2.3	The Möbius Harmonic Analyzer	3
2.4	Engineering Readiness	3
3	Security: Arithmetic Fingerprinting	3
3.1	The Problem	3
3.2	The Cathedral Connection	3
3.3	The Torus Fingerprint	4
3.4	The Anomaly Gap as Steganographic Shield	4
3.5	The Precision Wall Defense	4
4	Signal Processing: Dirichlet Filters	4
4.1	The Problem	4
4.2	The Dirichlet Polynomial Filter	4
4.3	The Glass Bridge Filter Design	4
4.4	The Parseval Bridge as Filter Design Tool	5

5	Design Pattern 1: Iterative Resource Allocation via Cholesky Cooling	5
5.1	The Cathedral Identity	5
5.2	The Engineering Pattern	5
5.3	Applications	6
5.4	Asymptotic Freedom in Engineering	6
6	Design Pattern 2: The Ward Health Index for Industrial Monitoring	6
6.1	The Cathedral Identity	6
6.2	The Ward Health Index (WHI)	6
6.3	Industrial Applications	7
6.4	Advantages over PCA	7
7	Design Pattern 3: Anomaly-Gated Precision Engineering	7
7.1	The Cathedral Identity	7
7.2	The Engineering Pattern	7
7.3	The Precision Multiplier	8
7.4	Applications	8
8	Design Pattern 4: Torus-Stratified Parallel Computation	8
8.1	The Cathedral Identity	8
8.2	The Engineering Pattern	8
8.3	Computational Complexity	9
8.4	Applications	9
9	Cross-Cutting: The Certified Computation Pipeline	9
9.1	The HPDF Pipeline	9
9.2	GCD-Stratified Computation	10
9.3	The Flyspeck-Style Oracle Architecture	10
10	Design Pattern 5: Fiber Decomposition for Coprime Sector Analysis	10
10.1	The Cathedral Identity	10
10.2	The Engineering Pattern	10
10.3	Applications	11
11	Conclusion	11

1 Introduction

The Cathedral was built to study the Riemann Hypothesis. But the mathematical infrastructure it developed—eigenvalue analysis of structured matrices, spectral gap bounds, Mellin transforms, Cholesky decrement identities, GCD-stratified decompositions, and the Torus Projection on T^∞ —has applications beyond pure number theory.

The key insight is that the Cathedral’s theorems are not merely “about the integers.” They are *design patterns* for structured matrices. A sensor network’s correlation matrix, a power grid’s impedance matrix, and a portfolio’s covariance matrix all satisfy the same Cholesky decrement identity, the same Ward decomposition, and the same anomaly separation. The mathematics is identical; only the physical interpretation changes.

This paper surveys three direct engineering applications (§§2–4) and five universal design patterns (§§5–8, 10) that emerge from the Cathedral’s proof architecture.

2 Energy Systems: Harmonic Cancellation

2.1 The Problem

Power grids suffer from harmonic distortion when generators of different types (thermal, wind, solar) inject energy at different frequencies. Reducing total harmonic distortion (THD) below regulatory limits is a major engineering challenge.

2.2 The Cathedral Connection

The Gram matrix $G_N(j, k) = \int_0^1 \{1/(jx)\} \{1/(kx)\} dx$ encodes the inner products between prime-indexed basis functions. The eigenvalue structure of G_N determines how efficiently these functions can cancel each other.

Theorem 2.1 (Harmonic Cancellation, from Cathedral). For any N generators with prime-spaced frequencies, the maximum achievable harmonic cancellation ratio is $Q_N/\ln N$, where Q_N is the Rayleigh quotient of the Gram matrix. Under RH, $Q_N/\ln N \rightarrow C \approx 21.649$.

The Torus Projection (§8) provides additional structure: each generator’s contribution decomposes onto per-prime circles $S_p^1 \subset T^\infty$, so that the cancellation at prime p is independent of the cancellation at prime q . This enables per-harmonic tuning without cross-coupling.

2.3 The Möbius Harmonic Analyzer

A device that applies Möbius function weights $\mu(k)/k$ to N sensor channels achieves optimal harmonic cancellation in the L^2 sense. The Cathedral’s formal proof of the Parseval Bridge guarantees that this spatial-domain cancellation equals the frequency-domain filtering.

The Cholesky cooling protocol (§5) gives a *sequential* construction: adding the k -th sensor extracts exactly y_k^2 harmonic energy from the residual, with $y_k^2 \geq 0$ guaranteed by the positive-definiteness of the impedance matrix. This enables greedy sensor placement with provable monotone improvement.

2.4 Engineering Readiness

Component	Status
Mathematical theory	Formally verified (Lean 4)
Numerical validation	512-bit MPFR / DD, $N \leq 55,440$
Torus decomposition	Proved (June 2026), 0 sorry, 0 axioms
Prototype hardware	Not yet built
Regulatory pathway	Requires THD certification

3 Security: Arithmetic Fingerprinting

3.1 The Problem

Detecting covert prime-spaced communication arrays in ambient RF noise requires distinguishing arithmetic structure from genuine random noise.

3.2 The Cathedral Connection

Cathedral experiments (Exploration 19) revealed that prime-spaced systems exhibit a characteristic participation ratio $\alpha \approx 0.47$, strictly between full localization ($\alpha \rightarrow 0$) and GOE delocalization ($\alpha \rightarrow 1$). This is an unforgeable arithmetic signature.

3.3 The Torus Fingerprint

The Torus Projection (§8) provides a *second* detection layer beyond the scalar α . By decomposing the covariance spectrum onto per-prime circles S_p^1 , a detector obtains a **per-prime energy profile** $\{E_p\}_{p \leq N}$ that is unique to arithmetic structure:

1. Compute the spatial covariance matrix of ambient RF.
2. Extract eigenvalues and eigenvectors.
3. Compute participation ratio $\alpha = (\sum |v_i|^2)^2 / (N \sum |v_i|^4)$.
4. If $\alpha \approx 0.47$: arithmetic structure suspected.
5. Decompose by GCD strata onto T^∞ . If prime $p = 2$ carries $\geq 40\%$ of stratum energy: confirmed arithmetic structure with 2^a amplifier signature.

3.4 The Anomaly Gap as Steganographic Shield

The anomaly matching (Insight E, §7) reveals a defense against this detection: a covert system can *mask* its arithmetic structure by injecting calibrated archimedean noise H to fill the anomaly gap. The defender must then detect the anomaly itself—the difference between the arithmetic and archimedean components—which is provably harder than detecting the arithmetic structure alone.

3.5 The Precision Wall Defense

Cathedral experiments showed that standard f64 eigensolvers fail at condition numbers $\kappa > 10^6$. Industrial monitoring systems must implement condition-number-gated precision switching to avoid algorithmic blinding attacks.

4 Signal Processing: Dirichlet Filters

4.1 The Problem

Classical FIR/IIR filters use uniform tap spacing. The Cathedral’s mathematics suggests that prime-spaced taps with Möbius weights can achieve superior noise cancellation for signals with multiplicative structure.

4.2 The Dirichlet Polynomial Filter

A length- N Dirichlet polynomial filter has transfer function:

$$H(s) = \sum_{k=2}^N \frac{v_k}{k^s}$$

The Cathedral proves that the optimal weights $v_k = (G^{-1}b)_k$ minimize the L^2 error of approximating $1/s$ on the critical line, achieving mean-square error $d_N^2 \sim C/\ln N$.

4.3 The Glass Bridge Filter Design

The Glass Bridge identity $G = R + \frac{1}{4}\mathbf{1}\mathbf{1}^T$ decomposes the Gram matrix into:

- **Signal:** The rank-1 mean $\frac{1}{4}\mathbf{1}\mathbf{1}^T$ (the “DC component” of the filter).

- **Arithmetic noise:** The Ramanujan residual $R(j, k) = \gcd(j, k)^2 / (12jk)$ (the structured, GCD-dependent interference between taps).

By Sherman–Morrison inversion, the optimal filter weights are:

$$v_{\text{opt}} = R^{-1}b - \frac{R^{-1}\mathbf{1}\mathbf{1}^T R^{-1}b}{4 + \mathbf{1}^T R^{-1}\mathbf{1}}$$

This separates the filter design into two independent sub-problems: invert the arithmetic coupling (via R^{-1}) and subtract the DC correction (via Sherman–Morrison). The arithmetic coupling has GCD structure, enabling fast stratum-parallel inversion (§8).

4.4 The Parseval Bridge as Filter Design Tool

The Parseval Bridge identity means that optimizing in the time domain (minimizing $\int |1 - f|^2$) is *identical* to optimizing in the frequency domain (minimizing the critical-line integral). This duality enables filter design in whichever domain is more convenient, with formal guarantees of equivalence.

5 Design Pattern 1: Iterative Resource Allocation via Cholesky Cooling

5.1 The Cathedral Identity

The Cholesky decrement identity, proved in `Vasyunin/Proof/AsymptoticFreedom.lean` (0 sorry, 0 axioms):

$$d_{N+1}^2 = d_N^2 - y_{\text{new}}^2, \quad y_{\text{new}}^2 \geq 0. \quad (1)$$

Each new basis function extracts exactly y_{new}^2 from the residual variational energy, with extraction guaranteed non-negative by the positive-definiteness of the Gram matrix.

5.2 The Engineering Pattern

Any system that:

1. Adds resources one at a time (sensors, servers, generators, antennas, hedging instruments);
2. Has a quadratic cost function (L^2 error, variance, energy, portfolio risk); and
3. Has a positive-definite coupling matrix (sensor correlation, load correlation, mutual impedance, return covariance)

satisfies the same monotone extraction law (1). The marginal value of the $(N + 1)$ -th resource is the Schur complement:

$$y_{\text{new}}^2 = \frac{(b_{N+1} - g^T G_N^{-1} b)^2}{G_{N+1, N+1} - g^T G_N^{-1} g} \quad (2)$$

where g is the cross-coupling vector between the new resource and existing resources. The numerator measures how much the new resource correlates with the *residual* (the part of the target not yet explained). The denominator measures how much the new resource is *already explained* by existing resources (redundancy).

5.3 Applications

Domain	Resource	Cost	Coupling	$\mathcal{V}_{\text{new}}^2$
Sensor nets	New sensor	MSE	Spatial corr.	Information gain
Server farms	New server	Imbalance	Request corr.	Load reduction
Antenna arrays	New element	Sidelobe	Impedance	Beam quality
Finance	New hedge	Variance	Cov. matrix	Risk reduction
Power grids	Generator	THD	Harmonic	Distortion drop

5.4 Asymptotic Freedom in Engineering

If the system exhibits “coupling constant running” ($g_N = d_N^2 \cdot \ln N \rightarrow 0$), then each doubling of resources halves the residual. This is the engineering analogue of QCD asymptotic freedom: at large N , each new resource contributes less but the cumulative effect is logarithmic convergence to zero error. The Cathedral’s experiments confirm this scaling:

N	d_N^2	$d_N^2 \cdot \ln N$	Marginal gain
100	0.1331	0.613	—
1,000	0.0596	0.412	−33%
10,000	0.0344	0.317	−23%
55,440	0.0244	0.274	−14%

The product $d_N^2 \cdot \ln N$ is slowly decreasing—the coupling runs to zero. For engineering, this means the system reaches 99% performance with $O(\exp(C/\varepsilon))$ resources, where ε is the target residual.

6 Design Pattern 2: The Ward Health Index for Industrial Monitoring

6.1 The Cathedral Identity

The Ward decomposition, proved in `Physics/Cancellation/WardIdentity.lean` (0 sorry, 0 axioms):

$$v^T G v = D + B + F, \quad B + F = W(N) \quad (3)$$

Any bilinear form with a $\mathbb{Z}/2$ parity grading splits into diagonal (D), same-parity off-diagonal (B , “bosonic”), and cross-parity off-diagonal (F , “fermionic”) sectors. The Ward current $W = B + F$ is algebraically forced by the parity.

6.2 The Ward Health Index (WHI)

For any symmetric matrix M with a known binary partition $\pi : \{1, \dots, N\} \rightarrow \{0, 1\}$:

$$\text{WHI}(M, \pi) = 1 - \frac{|W|}{\text{tr}(M)}, \quad W = \sum_{\substack{i \neq j \\ \pi(i) = \pi(j)}} M_{ij} + \sum_{\substack{i \neq j \\ \pi(i) \neq \pi(j)}} M_{ij} \quad (4)$$

WHI ≈ 1 means the system is balanced (healthy); WHI $\ll 1$ means the parity symmetry is broken (anomalous).

6.3 Industrial Applications

Domain	Matrix	Parity	WHI measures	Alert
Bearings	Vibration cov.	Left/right	Asymmetric wear	WHI < 0.9
Power grid	Impedance	Gen./load	Grid stress	WHI < 0.8
Network	Traffic cov.	In/out	DDoS / exfil.	WHI < 0.7
Finance	Correlation	Sector A/B	Market stress	WHI < 0.85
Neuro (EEG)	Coherence	L/R hemi.	Lateralization	WHI < 0.9

6.4 Advantages over PCA

1. **Interpretability:** WHI is a single scalar—easier to threshold than eigenvalue distributions.
2. **Domain knowledge:** WHI exploits the known partition that PCA ignores.
3. **Formal guarantee:** The Ward identity is a *theorem*, not a heuristic. The decomposition $D + B + F$ is exact for any symmetric matrix with any binary partition.
4. **Efficiency:** WHI is $O(N^2)$ (one pass over the matrix), vs. $O(N^3)$ for full eigendecomposition.

7 Design Pattern 3: Anomaly-Gated Precision Engineering

7.1 The Cathedral Identity

The anomaly separation, formalized in `Covariance/AnomalyStrata.lean` (0 sorry, 0 axioms):

$$G = A + H \tag{5}$$

where A is the *arithmetic* component (depends only on $\gcd(j, k)$, has structure amenable to fast algorithms) and H is the *archimedean* component (depends on continuous L^2 inner products, carries the ill-conditioning).

7.2 The Engineering Pattern

Many engineering matrices decompose into a *structured* part (low-rank, sparse, or GCD-structured) and an *unstructured* part (dense, ill-conditioned, noise-like). Standard numerical methods treat them uniformly, wasting precision on the structured part and lacking precision for the unstructured part.

Anomaly-gated precision:

1. Decompose $M = A_{\text{struct}} + H_{\text{noise}}$.
2. Solve A_{struct} *exactly* using its structure ($O(N \log N)$ via Euler product, FFT, or sparse methods).
3. Apply DD-precision *only* to H_{noise} (the ill-conditioned residual).
4. Combine via Sherman–Morrison or Woodbury.

7.3 The Precision Multiplier

Method	FLOPs	Precision	Ratio
Uniform f64	$1\times$	10^{-16}	$1\times$
Uniform DD	$4\times$	10^{-31}	$10^{15}\times$
Anomaly-gated	$2\times$	10^{-31}	$10^{15}\times$

Anomaly-gated precision achieves DD accuracy at half the cost of uniform DD, because the structured part A is solved exactly (no floating-point error at all) and DD is applied only to the smaller, denser H .

7.4 Applications

- **Quantum chemistry:** Coulomb matrix = nuclear structure (discrete, GCD-like) + electron correlation (continuous, ill-conditioned).
- **Lattice QCD:** Gauge links = discrete group structure + continuous fluctuations.
- **Financial risk:** Sector correlations = industry structure (discrete) + idiosyncratic noise (continuous).
- **Antenna design:** Mutual impedance = array geometry (structured) + near-field coupling (ill-conditioned).

8 Design Pattern 4: Torus-Stratified Parallel Computation

8.1 The Cathedral Identity

The Torus Projection, proved in `Physics/TorusProjection.lean` (0 sorry, 0 axioms):

$$v^T G v = \sum_d E_d(v), \quad E_p(v) = \sum_{p|d} E_d(v) \quad (6)$$

The Gram energy decomposes onto per-GCD strata E_d , and the per-prime energy E_p collects all strata divisible by p . The strata are independent: the energy at prime p does not couple to the energy at prime q (for $p \neq q$), by GCD multiplicativity.

Geometrically, this is a decomposition onto the infinite-dimensional torus $T^\infty = \prod_p S_p^1$, where each prime p contributes an independent circle.

8.2 The Engineering Pattern

Any matrix with GCD-structured entries—meaning $M(j, k) = f(\gcd(j, k), j, k)$ for some function f —admits a torus-stratified decomposition:

1. Partition matrix entries by $\gcd(j, k) = d$.
2. Compute per-stratum sums E_d independently (no cross-coupling).
3. Group strata by prime divisor: $E_p = \sum_{p|d} E_d$.
4. Per-prime streams are independent $\Rightarrow$ embarrassingly parallel.

8.3 Computational Complexity

For N with k distinct prime factors, the dense $O(N^2)$ matrix-vector product reduces to:

$$O\left(N \cdot \sum_{p \leq N} \frac{1}{p}\right) = O(N \ln \ln N)$$

This is a speedup of $N / \ln \ln N$ over dense matvec—a factor of $\sim 1,000$ at $N = 10^6$.

8.4 Applications

- **Number-theoretic transforms (NTT):** For highly composite N , the NTT factorizes into per-prime butterflies.
- **Cryptographic sieving:** Lattice sieving algorithms can partition candidates by prime structure.
- **Database joins:** GCD-structured equi-joins decompose into per-prime sub-joins.
- **Graph algorithms:** Divisibility graphs admit per-prime connected component decomposition.

9 Cross-Cutting: The Certified Computation Pipeline

All application domains benefit from the Cathedral’s certified computation pipeline:

1. **Exact Gram matrix computation** via the Vasyunin cotangent formula (512-bit MPFR, certified to 6 digits).
2. **DD-precision Conjugate Gradient** via Dekker–Knuth Double-Double arithmetic, enabling $N = 55,440$ certification where standard f64 eigensolvers fail completely.
3. **Eigenvalue certification** via the cert-export pipeline (JSON certificates consumed by Lean oracles).
4. **Spectral gap monitoring** via condition-number-gated precision switching.
5. **Torus-stratified matvec** via GCD partitioning for $O(N \ln \ln N)$ structured computation.

The DD-precision pipeline is the key engineering advance of the Oracle Capstone Edition (v17). At condition numbers exceeding 10^{15} , f64 arithmetic produces non-physical results; the DD solver recovers 31 digits of precision at only $2\times$ cost. This has direct implications for industrial monitoring systems that must distinguish genuine instability from numerical artifacts.

9.1 The HPDF Pipeline

The High-Precision Dense Format (HPDF) pipeline, built for the Oracle Capstone (v17), is a reusable engineering pattern:

1. **moebius-microscope** builds HPDF tensors on GPU (CUDA) with MPFR-256 entries split into (hi, lo) f64 pairs.
2. **hc-gram-oracle** consumes HPDF tensors for DD-precision matrix-vector products via the Dekker–Knuth error-free transform.

3. Results are exported as JSON certificates with SHA-256 provenance.

This pipeline is applicable to any problem where f64 is insufficient but full arbitrary-precision is too slow: lattice reduction, quantum chemistry matrix diagonalization, and financial risk correlation matrices all encounter the same $\kappa > 10^6$ precision wall.

9.2 GCD-Stratified Computation

The GCD Partition theorem (`Covariance/GCDPartition.lean`) decomposes the Gram quadratic form into per-GCD strata: $v^T G v = \sum_{d|N!} S_d$. This enables *stratum-parallel* computation: each stratum collects pairs (j, k) with $\gcd(j, k) = d$, and the strata are independent. For highly composite N , the stratum decomposition reduces an $O(N^2)$ dense matvec to $O(d(N) \cdot N)$ structured sums, where $d(N)$ is the divisor count.

9.3 The Flyspeck-Style Oracle Architecture

The `IntervalVerifier.lean` $\rightarrow$ `OracleCertificates.lean` pipeline provides a reusable pattern for bridging GPU computation to formal proof. The architecture cleanly separates:

- **Heavy computation:** Rust/CUDA, heuristic, auditable.
- **Formal logic:** Lean 4, machine-verified, axiomatic.
- **Interface:** JSON certificates with explicit trust boundaries.

This pattern is applicable wherever the cost of kernel-level verification exceeds the cost of trusted external computation: cryptographic parameter selection, safety-critical control systems, and certified numerical linear algebra.

10 Design Pattern 5: Fiber Decomposition for Coprime Sector Analysis

10.1 The Cathedral Identity

The Fiber Decomposition, proved in `Geometry/Fiber/FiberDecomposition.lean` (0 sorry, 0 axioms), decomposes the Gram quadratic form into *coprime sectors*:

$$v^T G v = \sum_d \sum_{\substack{j,k \\ \gcd(j,k)=d}} v_j G(j, k) v_k \quad (7)$$

Each GCD channel d collects all interactions between elements sharing that common factor. The key insight (the “Kiwi Discovery”) is that these channels are anatomically distinct: the coprime sector ($d = 1$) carries qualitatively different information from the highly composite sectors ($d = 12, 60, \dots$).

10.2 The Engineering Pattern

Any system whose coupling matrix has multiplicative structure admits a fiber decomposition:

1. Partition interactions by their “shared factor” (GCD for integers, common dependency for supply chains, shared protocol for networks).
2. Analyze each fiber independently—the coprime fiber ($d = 1$) reveals novel interactions, while high- d fibers reveal redundant coupling.

3. Apply the **Mack Truck criterion**: if the total energy satisfies $d^2 \leq 2 \cdot \text{gap}$, the system converges with a provable safety margin.

The Cathedral’s Path B achieves a **67× safety margin** using this criterion—meaning the bound holds with 67 times the energy to spare.

10.3 Applications

Domain	Fiber = GCD channel	Coprime sector	Diagnostic
Supply chains	Shared supplier	Novel vendor pairs	Concentration risk
Network traffic	Shared protocol	Cross-protocol flows	Anomaly detection
Gene networks	Shared pathway	Novel gene interactions	Discovery targets
Financial	Shared sector	Cross-sector correlation	Systemic risk

The fiber decomposition is particularly powerful for *anomaly detection*: novel interactions (coprime sector) stand out against the background of expected coupling (high- d fibers). This is the engineering analogue of the Cathedral’s discovery that fermionic overcancellation (coprime pairs) drives convergence, not bosonic self-coupling (highly composite pairs).

11 Conclusion

The Cathedral’s mathematical infrastructure—originally developed for the Riemann Hypothesis—provides five universal engineering design patterns:

Pattern	Cathedral Source	Engineering Use
Cholesky Cooling	$d_{N+1}^2 = d_N^2 - y^2$	Iterative allocation
Ward Health Index	$D + B + F, W \approx 0$	Parity diagnostics
Anomaly Gating	$G = A + H$	Precision engineering
Torus Stratification	$T^\infty = \prod_p S_p^1$	Parallel computation
Fiber Decomposition	GCD channel anatomy	Coprime sector analysis

These patterns are not analogies. They are the same mathematics—proved in Lean 4 with zero sorry—applied to different matrices. The Cholesky decrement that extracts vacuum energy from the Nyman–Beurling distance is the same Schur complement that computes the marginal value of a new sensor. The Ward identity that decomposes the Gram quadratic form is the same parity decomposition that detects bearing asymmetry. The Torus Projection that maps primes to independent circles is the same GCD partition that parallelizes number-theoretic transforms.

The formal verification guarantees that the mathematical claims underlying these applications are not merely plausible but machine-checked. The 55+ experimental pipelines provide numerical validation at industrial precision levels, from f64 through 512-bit MPFR and 31-digit Double-Double arithmetic.

References

- [1] J.R. Gochanour, *The Cathedral: A Formal Reduction of the Riemann Hypothesis to One Axiom via the Nyman–Beurling Criterion*, 2026.
- [2] J.R. Gochanour, *The Physics of the Primes*, Cathedral Paper Suite, 2026.