



Telef.: 0051-1-436-2500

Fax: 355-2184

## **PURCHASE ORDER № 0116-POR-1**

MANUFACTURER: ESITAS GROUP COMPANIES

SUPPLIER' REF::

Hilal Mahallesi Pasaköy Cd., No:31,34791- Sancaktepe- ISTANBUL /

0533-ETT-1

TURKEY

Tel.: + 90 216 304 32 70

RESPONSIBLE: Kortay Ileri (kortay.ileri@esitas.com)

PROJECT:

INVOICE TO:

SHIPPING MARKS:

•

Tel.:

**DELIVERY TO:** 

Tel.:

CONTACT: DATE:

Item	Des	cription	Quantity	Unit Price	Total
1	Indoor single phase support type cast resin insulated voltage transformer-12KV		3	235.00	705.00
	Rated Voltage	12 kV			
	Ratio	10500V-110V			
	Burden	50 VA			
	Accuracy	0.5			
	BIL	75 kVp			
	Power Frequency Withstand	28 kV			
	Frequency	60 Hz			
	Installation Type	Indoors			
2	Indoor support type cast resin insulated current transformers-12KV		3	375.00	1,125.00
	Rated Voltage	12 kV			
	Ratio	2000/5-5			
	Burden	15VA-30 VA			
	Accuracy	0.5-5P20			
	Ith	31.5 kA			
	BIL	75 kVp			
	Power Frequency Withstand	28 kV			
	Frequency	60 Hz			
	Installation Type	Indoors			
3	Indoor support type cast resin insulated current transformers-12KV		6	170.00	1,020.00
	Rated Voltage	12 kV			
	Rated Voltage Ratio				
		12 kV 400/1-1A 15VA-30 VA			
	Ratio	400/1-1A			
	Ratio Burden	400/1-1A 15VA-30 VA			
	Ratio Burden Accuracy	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA			
	Ratio Burden Accuracy Ith BIL	400/1-1A 15VA-30 VA 0.5-5P20			
	Ratio Burden Accuracy Ith BIL Power Frequency Withstand	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp			
	Ratio Burden Accuracy Ith BIL	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp 28 kV			
4	Ratio Burden Accuracy Ith BIL Power Frequency Withstand Frequency	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp 28 kV 60 Hz Indoors	6	166.00	996.00
4	Ratio Burden Accuracy Ith BIL Power Frequency Withstand Frequency Installation Type Indoor support type cast resir	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp 28 kV 60 Hz Indoors	6	166.00	996.00
4	Ratio Burden Accuracy Ith BIL Power Frequency Withstand Frequency Installation Type Indoor support type cast resintransformers-12KV	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp 28 kV 60 Hz Indoors	6	166.00	996.0
4	Ratio Burden Accuracy Ith BIL Power Frequency Withstand Frequency Installation Type Indoor support type cast resintransformers-12KV Rated Voltage	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp 28 kV 60 Hz Indoors 1 insulated current	6	166.00	996.0
4	Ratio Burden Accuracy Ith BIL Power Frequency Withstand Frequency Installation Type Indoor support type cast resintransformers-12KV  Rated Voltage Ratio	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp 28 kV 60 Hz Indoors n insulated current	6	166.00	996.0
4	Ratio Burden Accuracy Ith BIL Power Frequency Withstand Frequency Installation Type Indoor support type cast resintransformers-12KV  Rated Voltage Ratio Burden	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp 28 kV 60 Hz Indoors 12 kV 400/5-5A 15VA-30 VA 0.5-5P20	6	166.00	996.0
4	Ratio Burden Accuracy Ith BIL Power Frequency Withstand Frequency Installation Type Indoor support type cast resintransformers-12KV  Rated Voltage Ratio Burden Accuracy Ith	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp 28 kV 60 Hz Indoors 12 kV 400/5-5A 15VA-30 VA 0.5-5P20 31.5 kA	6	166.00	996.0
4	Ratio Burden Accuracy Ith BIL Power Frequency Withstand Frequency Installation Type  Indoor support type cast resintransformers-12KV  Rated Voltage Ratio Burden Accuracy Ith BIL	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp 28 kV 60 Hz Indoors 12 kV 400/5-5A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp	6	166.00	996.0
4	Ratio Burden Accuracy Ith BIL Power Frequency Withstand Frequency Installation Type Indoor support type cast resintransformers-12KV  Rated Voltage Ratio Burden Accuracy Ith	400/1-1A 15VA-30 VA 0.5-5P20 31.5 kA 75 kVp 28 kV 60 Hz Indoors 12 kV 400/5-5A 15VA-30 VA 0.5-5P20 31.5 kA	6	166.00	996.00



APPROVED BY:

**EltroTec**<sub>sac</sub>

Telef.: 0051-1-436-2500 Fax: 355-2184

	Indoor support type cast resin insulated current transformers-12KV		9	167.00	1,503.00
Rated	/oltage	12 kV			
Ratio	Burden 15VA-30	600/5-5A			
Burder		15VA-30 VA 0.5-5P20 31.5 kA			
Accura					
Ith					
BIL		75 kVp			
Power	Frequency Withstand	28 kV			
Freque	ncy	60 Hz			
Installa	tion Type	Indoors			
					Total Price €

Shipping Document Required: - Comercial Invoice - Packing list - Bill of Loading (3/3)