Systemd Deployment Instructions

Follow these steps to deploy the Home Control services to your remote server.

1. Copy Files to Server

Transfer the service and timer files to the remote server (e.g., using `scp`):

```
scp hc_server.service update_crontab.service update_crontab.timer ubuntu@<remote_host>:/home/ubu
```

2. Install Services

SSH into the remote server and move the files to the systemd directory:

```
ssh ubuntu@<remote_host>
sudo cp /home/ubuntu/home_control/*.service /etc/systemd/system/
sudo cp /home/ubuntu/home_control/*.timer /etc/systemd/system/
```

3. Enable and Start Services

Reload the systemd daemon to recognize the new files:

```
sudo systemctl daemon-reload
```

Home Control Server

Enable and start the main server:

```
sudo systemctl enable hc_server.service
sudo systemctl start hc_server.service
```

Check status:

```
sudo systemctl status hc_server.service
```

Update Crontab (Schedule)

Enable and start the timer (this will run the service daily):

```
sudo systemctl enable update_crontab.timer
sudo systemctl start update_crontab.timer
```

To run the update immediately (without waiting for the timer):

```
sudo systemctl start update_crontab.service
```

Check timer status:

```
sudo systemctl list-timers --all | grep update_crontab
```

4. Troubleshooting

View logs for the services:

```
# For the web server
sudo journalctl -u hc_server.service -f

# For the schedule updater
sudo journalctl -u update_crontab.service -f
```